sas innovate

SAS Viya Overview

The Data & AI Life Cycle

Allison Saito
Sr Technical Training Consultant

#SASinnovate

Contents

Abstract **2**

Setup **3**

Sign In and Create Data *3*

SAS Information Catalog **4**

General Layout *4*

Analyze Tables *4*

Examine HOMEEQUITY Table Analysis *4*

SAS Data Explorer **6**

Explore Existing Data Sources *6*

Import from Local Machine *6*

SAS Visual Analytics **8**

Access Data *8*

Prepare Data *8*

Explore Data *9*

Save and View the Report *10*

SAS Studio **12**

Make a New SAS Program *12*

Run an Existing SAS Program *12*

Make and Run a Python Program *13*

Explore More Features of SAS Studio *13*

Interactive Table Viewer 13

Drag and Drop Column Names into a Program 13

Schedule a Job 14

Point-and-Click to Make a Library as Startup, and Autoexec File 14

SAS Model Studio **15**

Begin a Project with a Template *15*

Automatically Generated Pipeline *16*

Integrate an Open Source Model *16*

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

Abstract

Get hands on experience with some of Viya®'s most popular features in this condensed version of our popular "SAS® Viya® Overview" course. We'll introduce SAS® Information Catalog, SAS® Data Explorer, SAS® Visual Analytics, SAS® Model Studio, and SAS® Studio as we explore a data set.

This presentation is a condensed version of the *SAS Viya Overview* course (version 2025.09) that is available online through https://www.sas.com/en_us/training/offers/free-training.html

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

Setup

Sign In and Create Data

During SAS Innovate 2026, the hands on workshop labs will be configured for these instructions. If accessing at another time, the files are available through https://github.com/sassoftware/sas-viya-quick-start .

1. Open Google Chrome and select the **SASStudio** bookmark
2. If necessary, sign in to SAS Viya using the username *student* and the password *Metadata0*
   - **Note**: If you were already signed in to SAS Viya, make sure that you are signed in to the Student account. You can check the account by going to the top right of SAS Studio and clicking the circle icon, then view the account name. If the account isn't Student, log out and log back in using the required information.



3. When prompted to opt in to all of your assumable groups, select **Yes**
4. In SAS Studio, select **SAS Server** on the left side menu. Navigate to **Files** > **Home** > **workshop** > **ViyaOverview**
5. From the **ViyaOverview** folder, open and run **_Load_Quick_Start_Data.sas.** If it runs correctly, the results tab will contain two grids of information, and the output table work.homeEquity will be created with 5,960 rows.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

SAS Information Catalog

SAS Information Catalog lets you create and maintain an inventory for your information assets. This catalog gives you the ability to ingest, integrate, and enrich metadata from the assets that are distributed across your enterprise. You can then use this metadata to find and explore the relevant assets that you need. It also enables data administrators to review data usage from a single point of access.

General Layout

1. To open SAS Information Catalog, click the **Applications menu** (top left, looks like nine dots arranged in a grid pattern) and select **Discover Information Assets**. Be sure to expand the left panel to view labels for each of the icons.

2. Below the search field, the number and type of each cataloged asset is shown. Resources include data sets, files, and lookup tables. Information Catalog also curates SAS assets, such as reports, SAS Studio flows, and models.

3. As objects are created on the SAS Viya platform, SAS Information Catalog collects basic metadata. The administrator can also run a process called a *discovery agent* on a SAS library or caslib to produce additional metrics and metadata for the tables in those libraries.

Analyze Tables

1. Search for the keyword *Home*. We will examine the **HOMEEQUITY** table in the **CASUSER** caslib more closely. This table will be the focus of our journey though the SAS Viya applications. Click the **HOMEEQUITY** table name to open its details.

2. Because the **HOMEEQUITY** table was created in SAS Viya, SAS Information Catalog knows it exists, but there are no metrics because the table hasn't been analyzed yet. Your administrator can analyze entire libraries or caslibs on a scheduled basis, but you can analyze individual tables as necessary.

   Click **Analyze data**. A warning appears, saying that the analysis will happen in the background but could take a while. Click **Submit request**.

3. When the analysis is complete, the text at the top of the screen will change to "*A new analysis is now available for this asset.*"

Examine HOMEEQUITY Table Analysis

1. Return to the **HOMEEQUITY** table in the **CASUSER** caslib. If necessary, wait for its analysis to complete.

2. Across the top of the display, we see key table metrics, including Completeness, which represents the percentage of nonmissing values, the number of rows and columns, and file size.

3. Examine the **Overview** tab. The left pane provides high-level information about the table, including the information privacy and time period covered. These analyses are done with algorithms from the SAS Quality Knowledge Base.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

4. In the middle of the screen, look more closely at **Semantic Type**. **Semantic Type** identifies the classification of data that is likely to be contained in the column. Information Catalog uses the SAS Quality Knowledge base to assign an appropriate semantic type, but you can modify the type for each column.

   Scroll down to the description of the **Region** column. It was assigned a semantic type of *State/province*. Select **State/province** > **Remediate** > **Choose other** and then search for *Region* and select it, then click **OK**.

5. Select the **Column Analysis** tab. All the columns in the table have three subtabs that display different sets of metrics. In the **Descriptive Measures** tab, you can see standard numeric metrics like mean, median, and standard deviation.

6. The first row in the table contains metrics for the **BAD** column. This column contains two distinct values, 0 and 1. 0 represents a loan in good standing, and 1 represents a defaulted loan. Expand the right panel and view the Properties. The Frequency Distribution chart indicates how many 0 and 1 values occur in the data. Our ultimate goal is to build a predictive model to anticipate loan status based on the other columns in the table.

7. To select the **MORTDUE** row, single click on one of its statistics. Examine the distribution visualization and metrics that are provided in the Properties pane. If you double click the statistics or single click the column name, several additional graphs are displayed. To return to the table summary, click **Descriptive View** (top left of the tab).

8. To examine the next subtab of **Column Analysis**, click **Metadata Measures**. Here you can examine column length, type, and label and additional helpful information such as Primary Key Candidate and Information Privacy.

9. For the next subtab of **Column Analysis**, click **Data Quality Measures**. You can view other data quality metrics, like pattern count, uniqueness, and completeness

10. Scroll down to review the most common and least common values for **CITY**. It looks like the city names might be in all lowercase, which won't look good in a report.

11. This is a table that we will frequently reference, so click the star (**Add to favorites**) in upper right corner. To confirm it is saved to favorites, select **Catalog Home** at the top left. In the **Relevant to Me** section, bring **Favorites** to the foreground.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

SAS Data Explorer

SAS Data Explorer is a tool in the SAS Viya platform that enables you to access, manage, and explore data on a SAS Cloud Analytic Services (CAS) server. It provides an easy-to-use interface for loading data from various sources, including on-premises systems and cloud-based platforms.

Explore Existing Data Sources

1. To open SAS Data Explorer, click the **Applications menu** in the upper left corner and select **Manage Data**.
2. The Sources tab allows you to view and manage your data sources. First, click **In-memory data (available)** to view all existing in-memory tables. If you select a row representing a table, the toolbar provides options to view the data, load or unload from memory, or import to a different location. You can also select **Actions** to open the data in another Viya application.
3. Click the **HOMEEQUITY** table and view the **Details** tab with column metadata, and the **Sample data** tab. In the **Sample data** tab, column names are displayed by default, but you can select **More Options** (top right of the tab, looks like three dots stacked snowman style) and click **Show Labels** to view the more descriptive column headers. Click the **X** in the upper-right corner to close the data preview.
4. In the **Sources** pane, expand **cas-shared-default** to view the caslibs defined in your environment and that you are authorized to access. Select **CASUSER** to view the data files and in-memory tables associated with this caslib. Click **Connection properties** (far right column, looks like a box with a bunch of dots in it) to view the attributes of the caslib. Notice CASUSER is a path-based caslib.
5. The **CUSTOMER** and **HOMEEQUITY** tables are loaded into memory, indicated by the table icon with a lightning bolt. Right-click either table to view available options, such as **View data**, **Unload from memory**, or **Download table**.
6. The CASUSER caslib also includes additional data sources, such as **countrylookup.csv**, **customer.parquet**, and **homeequity.sashdat**. Each of these files are saved on disk and can be loaded into memory for further analysis in CAS. Right-click **countrylookup.csv**, then select **Load into memory**.

Import from Local Machine

1. What if you have files on your local machine that you would like to analyze in SAS Viya? Select the **Import** tab to copy files to existing caslibs. Select **Local Files**, then navigate to **This PC** > **Local Disk (C:)** > **Users** > **student** > **Documents**. Select **mortgagerates.xlsx** and click **Open**
2. Expand Step 2 to set the following import options:
    a. Next to the Location (library) field, click **Choose a target location** (looks like a cloud). Expand **cas-shared-default** and select **CASUSER** > **OK**.
    b. The Label field is optional. Do not type anything in this field.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

   c. The **Format** selector defines the type of the imported file that will be saved on disk. Confirm the format is *sashdat*.

   d. Change **If table name exists** to *Replace file*.

3. Click **Import item** in the upper-right corner. Once the table has been successfully imported, click the **Sources** tab and the **CASUSER** caslib. Confirm the **MORTGAGERATES** in-memory table and **MORTGAGERATES.sashdat** file are available. You can click on the link to either file to examine the imported file in the Sample data tab.

   These new data sources and caslibs will now be available to use in other applications, such as SAS Visual Analytics or SAS Studio.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

SAS Visual Analytics

Access Data

1. To open Visual Analytics, click the **Applications** menu in the upper left corner and select **Explore and Visualize**.

2. From the welcome window, you can open an existing report or create a new report. Select **New report**.

3. Visual Analytics consists of three main areas: the left pane with icons for working with the overall report, a canvas where you build the report, and a right pane with icons for working with specific objects. The canvas displays one or more page tabs across the top of the report.

   Note: Expand the left and right panels to view descriptive labels for each of the icons.

4. Reports use data that is loaded into memory. In the **Data** pane (on the left side menu), there are options to either add data or import data.

5. Click **Add data** to select from tables that have been loaded into memory. Select the **HOMEEQUITY** table from the **CASUSER** caslib, then click **Add**.

6. The Data pane displays all the columns, or data items, in the **HOMEEQUITY** table. Data items are organized by type. Character columns and date formatted numeric columns appear as categories. Distinct counts appear next to each category. Numeric variables appear as measures.

Prepare Data

1. Change name and classification of **Loan Status**

   1. The **Data** pane is used to modify or create new data items. In this data, in the **Loan Status** column, the value *0* represents a loan in good standing, and *1* is a loan that has defaulted. The values of **Loan Status** represent a binary response rather than a measure.

   2. Hover over **Loan Status** in the Data pane. Click its **Edit Properties** (looks like arrows pointed downward)

   3. Change **Name** to *Loan Status Code*

   4. Change **Classification** to *Category*. This data item now appears in the **Category** group and includes two distinct values.

2. Create a custom category

   1. A consumer of this report might not know what the *0* and *1* values represent. We can create a new data item that assigns more descriptive labels to the raw loan status codes.

   2. Right-click **Loan Status Code** and select **New Custom Category**.

   3. Enter *Loan Status* in the **Name** field. The first group name will be *Paid*. In the **Values** field, enter *0* and press the Enter key.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

    4. Click **Add group** and enter *Defaulted* in the **Name** field. Set its **Value** to *1*.
    5. Expand **Remaining Values** and select **Show as missing**, and then click **OK**.

3. Change the format on a data item
    1. In the **Data** pane, expand the properties of **Loan Application Date** and click **Edit** next to the **Format** field.
    2. Select the **MMMYYYY** format so that the displayed values are the three-letter month and four-digit year. Click **OK**.

4. Change aggregation method for measures
    1. Finally, hover the cursor over each of the data items in the **Measure** classification. Notice that the default aggregation for all measures, with the exception of Frequency, is SUM. This means that as we build visualizations that include these measures, the summarized values will be totals. Because each row in the data is a separate loan, it makes more sense to look at the average for all measures.
    2. To change the aggregation method, select at least one measure data item and select the **More** menu to the right of the **New data item** button (towards the top of the pane). Choose **Select** > **Select measures with same aggregation**.
    3. Right-click over the selected data items and change **Aggregation** to **Average**.

5. Save data changes into a **Data view**
    1. The modifications made to the data items from the **HOMEEQUITY** table are saved as part of this report and do not change the underlying data. However, we could create a reusable and shareable template for the data source that can be applied in other reports.
    2. Next to the name of the table in the **Data** pane, click the **Data source menu** and select **Save data view**.
    3. Name the view *HomeEquity Innovate 2026*, and click **Save**.
    4. Saved views can be applied by selecting **Data source menu** and **Manage data views**. At this time, we will not apply a new view, so click **Cancel**.

Explore Data

1. Make a **List Table**
    1. To begin by examining the raw data, select the Objects pane on the left side and then drag **List Table** onto the canvas.
    2. On the right side of the canvas, select the **Roles** pane. Select **Add** next to **Columns** and then choose **Select all** > **Apply**.
    3. Drag **Loan Status** to the top of the list so that it's the first column.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

    4. You can scroll to view the different columns and values.
    5. Click on the **Division** column to sort the table..

2. Double-click **Page1** at the top of the report and type *Home Equity Data* to name the report page.
3. At the top of the canvas, click the plus sign to create a new page. Name it *Loan Exploration*.
4. Use the autochart feature, and adjust the output
    1. From the **Data** pane, drag **Loan Status** to the canvas. An autochart is generated, which means that Visual Analytics selects an appropriate graph based on the data type and values. In this example, the autochart is a bar chart.
    2. The autochart can be changed to another visualization. Select **Object menu** (upper right corner of the object, looks like three dots stacked snowman style) in the upper right corner of the bar chart and select **Change bar chart to** > **Pie chart**.
    3. On the right side of the canvas, expand the **Options** pane. Expand the Pie section.
    4. Under the Data Labels section, select **Percent of total values** and increase the **Text style** size to **12**. The chart indicates that approximately 20% of the loans default.
    5. In the Data pane, select **Amount of Loan Request** and drag it to the right side of the canvas. Move the cursor until half the screen is highlighted, then release the data item. The autochart is a histogram, which is a great way to view the distribution of the values.
    6. Next, drag **Loan Application Date** below the histogram. Move the cursor until the bottom half of the area of the histogram object is highlighted, then release the data item. This time, the autochart is a line plot that tracks the frequency of loan applications over time. This downward trend is expected because homeowners were more likely to refinance rather than apply for home equity loans during these years of declining interest rates.
5. Add a page control
    1. These static images are informative, but it would be helpful to see how they differ by region.
    2. In the **Data** pane, right-click **Region** and select **Add as a page control**. Now you can click each Region button to see how the graphs change.

Save and View the Report

1. Click **Save** and select **My Folder**. Name the report **Home Equity Report** and click **Save**.
2. The report is currently in Edit mode, so click the **View report** button in the upper left corner. Select the **Loan Exploration** page and confirm that all the charts update as you select each region.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

3. In the upper right corner of Visual Analytics, select **Opened reports (x)** and click **Close all reports**. In **Open reports (x)**, x represents the number of reports that are currently open in Visual Analytics.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

SAS Studio

Make a New SAS Program

1. Open SAS Studio from the applications menu (top left, looks like nine dots arranged in a grid) by selecting **Develop Code and Flows**.

2. The navigation pane on the left provides access to our SAS resources, including data, programs, and other items. The workspace area contains tabs that enable you to build programs and flows. Next to the right-most tab, select **New tab**, then **SAS program**.

3. Enter the following program in the editor. This program creates a new table named **CLASS_NEW**, reads **SASHELP.CLASS**, computes a new column named **Ratio**, and summarizes the numeric columns of the new table.

```
data class_new;
    set sashelp.class;
    Ratio = height / weight;
run;

proc means data=class_new;
run;
```

4. Click **Run**. Additional tabs are available to view the log, results, and output data. Select the **More Options** menu (top right of tab, looks like three dots arranged snowman style) and select **Apply detail layout** to choose other tab arrangements. Select **Standard** to view one tab at a time.

   Note: To change the default tab layout, select your SAS Profile icon in the upper-right corner, then select **Settings** > **Code and Log** > **Detail tab layout** = *Standard*.

5. If you have experience with SAS code, notice there is nothing new or different about the syntax. Most code that was developed for a previous version of SAS will run on the SAS Viya platform on the SAS Compute Server.

Run an Existing SAS Program

1. Existing SAS programs and other files can be saved and accessed in either the **SAS Server** pane or **SAS Content** pane.

   The SAS Server pane provides a direct view of the server's file system, which is where your SAS programming session is running. You can view, upload, and download files in your home directory or other areas you have permission to access. For example, if you want to upload data to process in a SAS program, it is best to load it to a location under SAS Server. Select a folder in SAS Server, then click **Upload** and select one or more files from your local machine.

   The SAS Content pane is the content storage area used by SAS applications (like SAS Visual Analytics, Model Studio, etc.) to organize and access shared resources. SAS Content is typically

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

used to store SAS-specific assets, such as reports, models, or jobs.

SAS programs can be saved in either storage location. The program used in this demonstration is available in SAS Server. Expand **Files** > **Home** > **workshop** > **ViyaOverview**, then double-click **Import_HOMEEQUITY.sas**.

2. The **Import_HOMEEQUITY.sas** program reads a csv from the SAS website and generates a table with the same name in the **WORK** library. The import does not use CAS and could run in SAS 9 too. Click **Run** to submit the program and then view the log to confirm that the table was created.

Make and Run a Python Program

1. SAS Studio also enables you to execute Python code. Click **New** > **Python program**, and a new editor opens where you can type and submit Python code.
2. You can also open an existing .py program from the Explorer. From the **ViyaOverview** folder, double-click **Python_Editor.py**. This program also reads a csv from the SAS website and creates a temporary SAS table. Click **Run** and confirm in the Library Connections pane that **HomeEquity_py** is in the **WORK** library.
3. **Python_Editor.py** also loaded a copy of the table into memory in the **CASUSER** caslib. Confirm **HomeEquity_py** is also in the **CASUSER** caslib.

Explore More Features of SAS Studio

Interactive Table Viewer

1. Expand the **WORK** library and double-click **CLASS_NEW** to open the interactive table viewer.
2. Right-click the header of the **Age** column and several options are available to view, sort, or filter. Select **Sort** > **Ascending**.
3. Type *Age > 13* in the Expression field and press Enter. Close the WORK.CLASS_NEW tab.

Drag and Drop Column Names into a Program

4. Another convenient shortcut in the **Library Connections** pane is the ability to select a table name or columns and insert them into a program. On the **SAS Program.sas** tab, add a VAR statement in the PROC MEANS step. Rather than typing multiple column names, expand **WORK**, then expand **CLASS_NEW** in the **Library Connections** pane. Hold down the Ctrl key and select **Age** and **Ratio** and then drag them into the program. Complete the statement with a semicolon.

```
proc means data=class_new;
   var Age Ratio;
run;
```

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

Schedule a Job

5. Select the **SAS Server** pane. Right-click **Import_HOMEEQUITY.sas** and and select **Schedule as a job.** Specify that the job should run every hour, with an **Offset** of 00:02 (two minutes after each hour; 1:02, 2:02, etc), and save the changes.

Point-and-Click to Make a Library as Startup, and Autoexec File

6. You can interactively create a SAS library as well. Right-click the **ViyaOverview** folder and select **Create library**.

7. Enter *ViyaOvVw* in the **Name** field and select the **Assign and connect to data sources at startup** check box. Click **OK**. Confirm that the **ViyaOvVw** library is available in the **Library Connections** pane.

8. Select **Options** > **Autoexec file**. Any code placed in this file will be executed at the beginning of every SAS session the current user starts in SAS Studio. Because **Assign and connect to data sources at startup** was selected, the code to create **ViyaOvVw** is included in the autoexec file. Click **Cancel**.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

SAS Model Studio

NOTE: Several steps in this demonstration may take several minutes to run. During SAS Innovate 2026, only run a pipeline if instructed by the presenter. To view the run pipelines, open **Home Equity Analysis (Final)Home**

Begin a Project with a Template

1. To start using SAS Model Studio, select **Build Models** from the **Applications menu**. The Projects page appears with a tile view of projects that have been created already.
2. Click **New Project**. In the **New Project** window, set
    1. **Name** = *Home Equity Analysis*
    2. **Type** = *Data Mining and Machine Learning*
    3. **Template** = *Advanced template for class* target
    4. **Data** = **HOMEEQUITY** table from the **CASUSER** caslib
        1. If selecting **Browse** does not bring up the data options within a few seconds, log out of Viya and back in again.
    5. Click **Advanced** to view some of the advanced pipeline settings. Select **Partition Data**. Notice that by default, the data is divided into training, validation, and test partitions.
    6. Click **Save** > **Save**.
3. The project opens on the **Data** tab. Next, set up the modeling properties of your data. Examine the attributes of the variable named **BAD**. Model Studio detected that it is a binary variable and was assigned a role of **Input**. However, **BAD** represents the outcome of each loan, and should be the target variable for the model. Select the row for the BAD variable. In the **Properties** pane (right side of the screen), change the **Role** to *Target*.
4. You can also select variables to assess for bias in your models. Select **Job** and select the **Assess this variable for bias** check box in the **Properties** pane. Change the **Role** value to *Rejected* to prevent it from being used as a predictor in the models.
5. Select the **Pipelines** tab to view the template pipeline that has been generated for our data. After some pre-processing, the data is trained and validated on six models. An ensemble of the six models is also trained, and all seven resulting models are compared. You can change settings on any of the nodes in the pipeline or add new nodes to it. If you want to run the pipeline (and have a few minutes for it to run), click **Run pipeline**. Alternatively, view the pre-run results in **Home Equity Analysis (Final)**.
6. When the pipeline finishes running, green check marks will appear on each node. Right-click the **Model Comparison** node and select **Results**. You can see which model has the best performance. Based on the value of the KS statistic, the champion is the gradient boosting model.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

Automatically Generated Pipeline

Note: Steps 7 and 8 require approximately 10 minutes to execute in the training virtual lab. You may choose to skip these steps. Alternatively, view the pre-run results in **Home Equity Analysis (Final)**

7. Select the plus symbol next to the **Pipeline 1** tab to add a new pipeline. This time, we'll let SAS automate the training and selection. Select **Automatically generate the pipeline**, set a time limit of 20 minutes, then click **Save**.

8. Once the pipeline is built, you can run it as-is, or you can unlock the pipeline to make additional changes. Click **Run pipeline**. When the pipeline finishes running, right-click the **Model Comparison** node and select **Results** to identify the champion model. The champion is another Gradient Boosting model. Click **Close**.

Integrate an Open Source Model

9. Finally, we can include pipelines that use models from open source. Click the plus sign to add a new pipeline tab. To select a pipeline template, click **Browse** and select **Basic template for class target** > **OK** > **Save**. The basic pipeline includes Data, Imputation, Logistic Regression, and Model Comparison nodes.

10. Select **Nodes** in the left panel (not the panel with Projects, The Exchange, and Global Metadata; **Nodes** is in the smaller panel just to the right of the big one). Expand **Miscellaneous**, then drag the **Open Source Code** node on top of the **Imputation** node. Right-click the **Open Source Code** node and select **Open**.

11. The model scoring code is provided on our sassoftware GitHub site. Open a new tab in your browser select the GitHub bookmark to go to https://github.com/sassoftware/sas-viya-quick-start. Click **Train_HOMEEQUITY.txt** to open the file. Copy the code, then return to Model Studio and paste it in the Training Code window.

12. Back in GitHub, select **Score_HOMEEQUITY.txt** from the repository file list. Copy the code in the text file. Return to Model Studio and paste it in the Scoring Code window. Click **Save** > **Close**.

13. Once the model training and scoring code have been added, you can update any settings in the Open Source Code pane. In some cases, it might be necessary to disable SAS formats when processing data with Python code. In the **Open Source Code** pane (on the right), expand **Data Sample** and clear the **Include SAS Formats** check box.

14. Finally, right-click the **Open Source Code** node and select **Move** > **Supervised Learning**. The node will connect to the Model Comparison node. Click **Run pipeline**. The Python code runs and is included in the model comparison.

15. Click the **Pipeline Comparison** tab. The models that are winners from each pipeline are compared against one another, using the KS statistic by default. You can change this selection statistic. The gradient boosting model from the SAS-generated pipeline is the champion for the project.

16. Select the **Insights** tab to generate a natural language summary to interpret the results of the pipeline comparison and examine a host of useful assessment graphs. You can also generate a

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.

PDF of your project results by clicking **Export to PDF** (top right, looks like the Adobe Acrobat logo). Then, customize the contents of the report, and click **Export**. The PDF file will be downloaded through your browser.

Copyright © 2026, SAS Institute Inc., Cary, North Carolina, USA. ALL RIGHTS RESERVED.