ENGINE FAILURE DURING GROUND ROLL

1. Throttles ..... CLOSED
2. Braking ..... MAXIMUM
3. Fuel Selectors ..... OFF
4. Battery, Alternator, and Magneto/Start Switches ..... OFF

NOTE

Braking effectiveness is improved if the brakes are not locked.

ENGINE FAILURE AFTER LIFT-OFF AND IN FLIGHT

An immediate landing is advisable regardless of takeoff weight. Continued flight requires immediate pilot response to the following procedures.

1. Landing Gear and Flaps ..... UP
2. Throttle (inoperative engine) ..... CLOSED
3. Propeller (inoperative engine) ..... FEATHER
4. Power (operative engine) ..... AS REQUIRED
5. Airspee MAINTAIN 100kts MAX UNTIL OBSTACLES ARE CLEARED

After positive control of the airplane is established:

6. Inoperative engine ..... SECURE

a. Mixture Control - IDLE CUT-OFF

b. Fuel Selector - OFF

c. Fuel Boost Pump - OFF

d. Magneto/Start Switch - OFF

e. Alternator Switch - OFF

f. Cowl Flaps - CLOSED

7. Electrical Load ..... MONITOR

Maximum load of 60 amps on remaining engine. Reduce electrical loar if voltmeter indicates less than 28 volts.

NOTE

The most important aspect of engine failure is the necessity to maintain lateral and directional control. If airspeed is below 84 kts, reduce power on the operative engine as required to maintain

AIR START

CAUTION

The pilot should determine the reason for engine failure before attempting an airstart

1. Fuel Selector Valve ..... ON
2. Throttle ..... SET approximately 1/4 travel
3. Mixture Control ..... FULL RICH
4. Fuel Boost Pump ..... LOW
5. Magnetos ..... CHECK ON
6. Propeller ..... MOVE CONTROL TO REACH 600 RPM
7. Wher ADJUST THROTTLE, PROPELLER and MIXTURE CONTROLS
8. Fuel Pump ..... OFF
9. Oil Pressure ..... CHECK
10. Alternator Switch ..... ON
11. Warm Up ..... EXECUTE (1500 RPM and 15 inch Hg)

EMERGENCY DESCENT

1. Throttles ..... CLOSED
2. Propellers ..... 2700 RPM
3. Airspeed ..... 152 kts
4. Landing Gear ..... DOWN
5. Flaps ..... APPROACH (15°)

GLIDE

1. Propellers ..... FEATHER
2. Flaps ..... UP (0°)
3. Landing Gear ..... UP
4. Cowl Flaps ..... CLOSED
5. Airspeed ..... 115 kts

The glide ration in this configuration is approximately 2 nautical miles of gliding distance for each 1000 feet of altitude above terrain.

GEAR-UP LANDING

If possible, choose firm sod or foamed runway. When assured of reaching landing site:

1. Cowl Flaps ..... CLOSED
2. Wing Flaps ..... AS DESIRED
3. Throttles ..... CLOSED
4. Fuel Selectors ..... OFF
5. Mixture Controls ..... IDLE CUT-OFF
6. Battery, Alternator and Magneto/Start Switches ..... OFF
7. Wings ..... KEEP LEVEL DURING TOUCHDOWN
8. Airplane ..... CLEAR AS SOON AS POSSIBLE

ONE-ENGINE-INOPERATIVE LANDING

On final approach and when it is certain that the field can be reached:

1. Landing Gear ..... DOWN
2. Flaps ..... APPROACH (15°)
3. Airspeed ..... 95 kts
4. Power ..... AS REQUIRED to maintain 800 ft/min rate of descent

When it is certain there is no possibility of go-around:

5. Flaps ..... DOWN (30°)

ONE-ENGINE-INOPERATIVE GO-AROUND

WARNING

In any event, DO NOT attempt a one-engine-inoperative go-around after flaps have been fully extended.

1. Power ..... MAXIMUM ALLOWABLE
2. Landing Gear ..... UP
3. Flaps ..... UP (0°)
4. Airspeed ..... MAINTAIN 100 KTS MINIMUM)