Module 02: Numerical Methods

Unit 07: Partial Differential Equation: Numerical Stability of IBVP

Anirban Dhar

Department of Civil Engineering Indian Institute of Technology Kharagpur, Kharagpur

National Programme for Technology Enhanced Learning (NPTEL)

Dr. Anirban Dhar NPTEL Computational Hydraulics 1 /

Learning Objective

• To analyze the numerical stability of the discretized PDE.

Dr. Anirban Dhar

Problem Definition

Governing equation

A two-dimensional (in space) IBVP can be written as,

$$\Omega: \quad \Lambda_{\phi} \frac{\partial \phi}{\partial t} = \Gamma_{x} \frac{\partial^{2} \phi}{\partial x^{2}} + \Gamma_{y} \frac{\partial^{2} \phi}{\partial y^{2}} + S_{\phi}(x, y)$$

Problem Definition

subject to

Initial Condition

$$\phi(x, y, 0) = \phi_0(x, y)$$

and

Boundary Condition

$$\Gamma_D^1: \quad \phi(0, y, t) = \phi_1$$

$$\Gamma_D^2: \quad \phi(L_x, y, t) = \phi_2$$

$$\Gamma_N^3: \quad \frac{\partial \phi}{\partial y}\Big|_{(x,0,t)} = 0$$

$$\Gamma_N^4: \quad \frac{\partial \phi}{\partial y}\Big|_{(x,L_y,t)} = 0$$

Errors

Discretization Error (Biswas, 2003)

Discretization Error =

Analytical Solution of PDE - Exact Solution of the Finite Difference Equation (obtained on a hypothetical infinite precision computer)

=Truncation Error + Error due to treatment of boundary conditions

5 / 19

Errors

Discretization Error (Biswas, 2003)

Discretization Error =

Analytical Solution of PDE - Exact Solution of the Finite Difference Equation (obtained on a hypothetical infinite precision computer)

=Truncation Error + Error due to treatment of boundary conditions

Round-off Error

Round-off Error (ϵ) =

Numerical Solution of the Finite Difference Equation (obtained from finite precision computer) - Exact Solution of the Finite Difference Equation (obtained on a hypothetical infinite precision computer)

Dr. Anirban Dhar NPTEL Computational Hydraulics

• Every algorithm requires repeated operations (e.g., \pm , \times). There is an accumulation of round-off error.

- Every algorithm requires repeated operations (e.g., \pm , \times). There is an accumulation of round-off error.
- In time-stepping algorithm, accumulated round-off error may magnify/ reduce with every step.

- Every algorithm requires repeated operations (e.g., \pm , \times). There is an accumulation of round-off error.
- In time-stepping algorithm, accumulated round-off error may magnify/ reduce with every step.
- Error may increase exponentially. It is known as Numerical Instability.

- Every algorithm requires repeated operations (e.g., \pm , \times). There is an accumulation of round-off error.
- In time-stepping algorithm, accumulated round-off error may magnify/ reduce with every step.
- Error may increase exponentially. It is known as Numerical Instability.
- Numerical Stability/ Instability is a property of the algorithm and discretization of PDE+BCs.

- Every algorithm requires repeated operations (e.g., \pm , \times). There is an accumulation of round-off error.
- In time-stepping algorithm, accumulated round-off error may magnify/ reduce with every step.
- Error may increase exponentially. It is known as Numerical Instability.
- Numerical Stability/ Instability is a property of the algorithm and discretization of PDE+BCs.
- It does not depend on the computer used.

In stability analysis of linear PDE, we analyze only one arbitrary Fourier mode (Biswas, 2003).

In stability analysis of linear PDE, we analyze only one arbitrary Fourier mode (Biswas, 2003).

Let us consider that the error can be represented in the form of Fourier Series and single arbitrary term can be written as,

$$\epsilon_{i,j}^n = A^n e^{\sqrt{-1}i\omega_x \Delta x + \sqrt{-1}j\omega_y \Delta y}$$

where

 ω_x and ω_y are wave numbers corresponding to x and y directions respectively.

In stability analysis of linear PDE, we analyze only one arbitrary Fourier mode (Biswas, 2003).

Let us consider that the error can be represented in the form of Fourier Series and single arbitrary term can be written as,

$$\epsilon_{i,j}^n = A^n e^{\sqrt{-1}i\omega_x \Delta x + \sqrt{-1}j\omega_y \Delta y}$$

where

 ω_x and ω_y are wave numbers corresponding to x and y directions respectively.

Note that, $|\epsilon_{i,j}^n| = |A^n|$.

In stability analysis of linear PDE, we analyze only one arbitrary Fourier mode (Biswas, 2003).

Let us consider that the error can be represented in the form of Fourier Series and single arbitrary term can be written as,

$$\epsilon_{i,j}^n = A^n e^{\sqrt{-1}i\omega_x \Delta x + \sqrt{-1}j\omega_y \Delta y}$$

where

 ω_x and ω_y are wave numbers corresponding to x and y directions respectively.

Note that, $|\epsilon_{i,j}^n| = |A^n|$.

In simplified form, error can be written as,

$$\epsilon_{i,j}^n = A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}j\varphi_y}$$

where

 φ_x and φ_y are phase values corresponding to x and y directions respectively.

Define

$$G = \frac{A^{n+1}}{A^n}$$

where ${\cal G}$ is an amplification factor. It governs the growth of the Fourier component.

Define

$$G = \frac{A^{n+1}}{A^n}$$

where ${\cal G}$ is an amplification factor. It governs the growth of the Fourier component.

The von Neumann Stability Condition is given by $|G| \leq 1$.

Define

$$G = \frac{A^{n+1}}{A^n}$$

where ${\cal G}$ is an amplification factor. It governs the growth of the Fourier component.

The von Neumann Stability Condition is given by $|G| \le 1$.

$$|G| > 1 \Rightarrow$$
 Error grows (Unstable Scheme).

Define

$$G = \frac{A^{n+1}}{A^n}$$

where ${\cal G}$ is an amplification factor. It governs the growth of the Fourier component.

The von Neumann Stability Condition is given by $|G| \leq 1$.

 $|G| > 1 \Rightarrow$ Error grows (Unstable Scheme).

 $|G| < 1 \Rightarrow$ Error reduces (Stable Scheme).

Define

$$G = \frac{A^{n+1}}{A^n}$$

where ${\cal G}$ is an amplification factor. It governs the growth of the Fourier component.

The von Neumann Stability Condition is given by $|G| \leq 1$.

 $|G| > 1 \Rightarrow$ Error grows (Unstable Scheme).

 $|G| < 1 \Rightarrow$ Error reduces (Stable Scheme).

 $|G| = 1 \Rightarrow$ Error remains same (Neutrally Stable Scheme).

The discretized governing equation for IBVP with explicit scheme can be written as,

$$\Lambda_{\phi} \frac{\phi_{i,j}^{n+1} - \phi_{i,j}^{n}}{\Delta t} = \Gamma_{x} \frac{\phi_{i-1,j}^{n} - 2\phi_{i,j}^{n} + \phi_{i+1,j}^{n}}{\Delta x^{2}} + \Gamma_{y} \frac{\phi_{i,j-1}^{n} - 2\phi_{i,j}^{n} + \phi_{i,j+1}^{n}}{\Delta y^{2}} + S_{\phi} \Big|_{i,j}^{n}$$

The discretized governing equation for IBVP with explicit scheme can be written as,

$$\Lambda_{\phi} \frac{\phi_{i,j}^{n+1} - \phi_{i,j}^{n}}{\Delta t} = \Gamma_{x} \frac{\phi_{i-1,j}^{n} - 2\phi_{i,j}^{n} + \phi_{i+1,j}^{n}}{\Delta x^{2}} + \Gamma_{y} \frac{\phi_{i,j-1}^{n} - 2\phi_{i,j}^{n} + \phi_{i,j+1}^{n}}{\Delta y^{2}} + S_{\phi} \Big|_{i,j}^{n}$$

The general variable ϕ can be written as,

$$\phi_{i,j}^n = \hat{\phi}_{i,j}^n + \epsilon_{i,j}^n$$

where

 $\phi^n_{i,j}=$ Numerical solution obtained from finite precision computer $\hat{\phi}^n_{i,j}=$ Exact discrete solution obtained on a hypothetical infinite precision computer

 $\epsilon_{i,j}^n = \text{Accumulated round-off error at time level } n.$

Dr. Anirban Dhar

NPTEL

Computational Hydraulics

The discretized governing equation for IBVP with explicit scheme can be written as,

$$\begin{split} &\Lambda_{\phi} \frac{(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) - (\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n})}{\Delta t} = \\ &\Gamma_{x} \frac{(\hat{\phi}_{i-1,j}^{n} + \epsilon_{i-1,j}^{n}) - 2(\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n}) + (\hat{\phi}_{i+1,j}^{n} + \epsilon_{i+1,j}^{n})}{\Delta x^{2}} + \\ &\Gamma_{y} \frac{(\hat{\phi}_{i,j-1}^{n} + \epsilon_{i,j-1}^{n}) - 2(\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n}) + (\hat{\phi}_{i,j+1}^{n} + \epsilon_{i,j+1}^{n})}{\Delta y^{2}} \\ &+ S_{\phi}|_{i,j}^{n} \end{split}$$

$$(1)$$

The discretized governing equation for IBVP with explicit scheme can be written as,

$$\Lambda_{\phi} \frac{(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) - (\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n})}{\Delta t} = \\
\Gamma_{x} \frac{(\hat{\phi}_{i-1,j}^{n} + \epsilon_{i-1,j}^{n}) - 2(\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n}) + (\hat{\phi}_{i+1,j}^{n} + \epsilon_{i+1,j}^{n})}{\Delta x^{2}} + \\
\Gamma_{y} \frac{(\hat{\phi}_{i,j-1}^{n} + \epsilon_{i,j-1}^{n}) - 2(\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n}) + (\hat{\phi}_{i,j+1}^{n} + \epsilon_{i,j+1}^{n})}{\Delta y^{2}} + S_{\phi} \Big|_{i,j}^{n}$$
(1)

By definition, $\hat{\phi}$ is the exact discrete solution of the finite difference equation. Thus, the discretized finite difference equation can be written as,

$$\Lambda_{\phi} \frac{\hat{\phi}_{i,j}^{n+1} - \hat{\phi}_{i,j}^{n}}{\Delta t} =
\Gamma_{x} \frac{\hat{\phi}_{i-1,j}^{n} - 2\hat{\phi}_{i,j}^{n} + \hat{\phi}_{i+1,j}^{n}}{\Delta x^{2}} + \Gamma_{y} \frac{\hat{\phi}_{i,j-1}^{n} - 2\hat{\phi}_{i,j}^{n} + \hat{\phi}_{i,j+1}^{n}}{\Delta y^{2}} + S_{\phi}|_{i,j}^{n}$$
(2)

By subtracting Equation 2 from Equation 1, we get the error equation

$$\Lambda_{\phi} \frac{\epsilon_{i,j}^{n+1} - \epsilon_{i,j}^{n}}{\Delta t} =$$

$$\Gamma_{x} \frac{\epsilon_{i-1,j}^{n} - 2\epsilon_{i,j}^{n} + \epsilon_{i+1,j}^{n}}{\Delta x^{2}} + \Gamma_{y} \frac{\epsilon_{i,j-1}^{n} - 2\epsilon_{i,j}^{n} + \epsilon_{i,j+1}^{n}}{\Delta y^{2}}$$
(3)

By subtracting Equation 2 from Equation 1, we get the error equation

$$\Lambda_{\phi} \frac{\epsilon_{i,j}^{n+1} - \epsilon_{i,j}^{n}}{\Delta t} =$$

$$\Gamma_{x} \frac{\epsilon_{i-1,j}^{n} - 2\epsilon_{i,j}^{n} + \epsilon_{i+1,j}^{n}}{\Delta x^{2}} + \Gamma_{y} \frac{\epsilon_{i,j-1}^{n} - 2\epsilon_{i,j}^{n} + \epsilon_{i,j+1}^{n}}{\Delta y^{2}}$$
(3)

In simplified form, this can be written as,

$$\epsilon_{i,j}^{n+1} = \alpha_y \epsilon_{i,j-1}^n + \alpha_x \epsilon_{i-1,j}^n + [1 - 2(\alpha_x + \alpha_y)] \epsilon_{i,j}^n + \alpha_x \epsilon_{i+1,j}^n + \alpha_y \epsilon_{i,j+1}^n$$

with
$$\alpha_x = \frac{\Gamma_x \Delta t}{\Lambda_\phi \Delta x^2}$$
 and $\alpha_y = \frac{\Gamma_y \Delta t}{\Lambda_\phi \Delta y^2}$.

With

$$\begin{split} \epsilon_{i,j}^{n+1} &= A^{n+1} e^{\sqrt{-1}i\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i,j}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i-1,j}^n &= A^n e^{\sqrt{-1}(i-1)\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i+1,j}^n &= A^n e^{\sqrt{-1}(i+1)\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i,j-1}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}(j-1)\varphi_y} \\ \epsilon_{i,j+1}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}(j+1)\varphi_y} \end{split}$$

With

$$\begin{split} \epsilon_{i,j}^{n+1} &= A^{n+1} e^{\sqrt{-1}i\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i,j}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i-1,j}^n &= A^n e^{\sqrt{-1}(i-1)\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i+1,j}^n &= A^n e^{\sqrt{-1}(i+1)\varphi_x + \sqrt{-1}j\varphi_y} \\ \epsilon_{i,j-1}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}(j-1)\varphi_y} \\ \epsilon_{i,j+1}^n &= A^n e^{\sqrt{-1}i\varphi_x + \sqrt{-1}(j+1)\varphi_y} \end{split}$$

By substituting all terms in the error equation,

$$\frac{A^{n+1}}{A^n} = \alpha_y e^{-\sqrt{-1}\varphi_y} + \alpha_x e^{-\sqrt{-1}\varphi_x} + \left[1 - 2(\alpha_x + \alpha_y)\right] + \alpha_x e^{\sqrt{-1}\varphi_x} + \alpha_y e^{\sqrt{-1}\varphi_y}$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = 1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)$$

$$G = 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = 1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)$$

$$G = 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})$$

The von Neumann Stability condition

$$|1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})| \le 1$$
$$-1 \le 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2}) \le 1$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = 1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)$$

$$G = 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})$$

The von Neumann Stability condition

$$|1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})| \le 1$$
$$-1 \le 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2}) \le 1$$

Two Cases:

•
$$sin(\frac{\varphi_x}{2}) = 0$$
 and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = 1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)$$

$$G = 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})$$

The von Neumann Stability condition

$$|1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})| \le 1$$
$$-1 \le 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2}) \le 1$$

Two Cases:

- $sin(\frac{\varphi_x}{2}) = 0$ and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$
- $sin(\frac{\varphi_x}{2}) = 1$ and $sin(\frac{\varphi_y}{2}) = 1 \Rightarrow G = 1 4(\alpha_x + \alpha_y) \Rightarrow (\alpha_x + \alpha_y) \leq \frac{1}{2}$

Dr. Anirban Dhar

NPTEL

Computational Hydraulics

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = 1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)$$

$$G = 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})$$

The von Neumann Stability condition

$$|1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2})| \le 1$$
$$-1 \le 1 - 4\alpha_y \sin^2(\frac{\varphi_y}{2}) - 4\alpha_x \sin^2(\frac{\varphi_x}{2}) \le 1$$

Two Cases:

- $sin(\frac{\varphi_x}{2}) = 0$ and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$
- $sin(\frac{\varphi_x}{2}) = 1$ and $sin(\frac{\varphi_y}{2}) = 1 \Rightarrow G = 1 4(\alpha_x + \alpha_y) \Rightarrow (\alpha_x + \alpha_y) \leq \frac{1}{2}$

Explicit scheme is Conditionally Stable.

The discretized governing equation for IBVP with implicit scheme can be written as,

$$\Lambda_{\phi} \frac{(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) - (\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n})}{\Delta t} =
\Gamma_{x} \frac{(\hat{\phi}_{i-1,j}^{n+1} + \epsilon_{i-1,j}^{n+1}) - 2(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) + (\hat{\phi}_{i+1,j}^{n+1} + \epsilon_{i+1,j}^{n+1})}{\Delta x^{2}} +
\Gamma_{y} \frac{(\hat{\phi}_{i,j-1}^{n+1} + \epsilon_{i,j-1}^{n+1}) - 2(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) + (\hat{\phi}_{i,j+1}^{n+1} + \epsilon_{i,j+1}^{n+1})}{\Delta y^{2}} + S_{\phi}|_{i,j}^{n+1}$$

14 / 19

Implicit Scheme

The discretized governing equation for IBVP with implicit scheme can be written as,

$$\begin{split} &\Lambda_{\phi} \frac{(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) - (\hat{\phi}_{i,j}^{n} + \epsilon_{i,j}^{n})}{\Delta t} = \\ &\Gamma_{x} \frac{(\hat{\phi}_{i-1,j}^{n+1} + \epsilon_{i-1,j}^{n+1}) - 2(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) + (\hat{\phi}_{i+1,j}^{n+1} + \epsilon_{i+1,j}^{n+1})}{\Delta x^{2}} + \\ &\Gamma_{y} \frac{(\hat{\phi}_{i,j-1}^{n+1} + \epsilon_{i,j-1}^{n+1}) - 2(\hat{\phi}_{i,j}^{n+1} + \epsilon_{i,j}^{n+1}) + (\hat{\phi}_{i,j+1}^{n+1} + \epsilon_{i,j+1}^{n+1})}{\Delta y^{2}} + S_{\phi}|_{i,j}^{n+1} \end{split}$$

By definition, $\dot{\phi}$ is the exact discrete solution of the finite difference equation. Thus, the discretized finite difference equation can be written as,

$$\Lambda_{\phi} \frac{\hat{\phi}_{i,j}^{n+1} - \hat{\phi}_{i,j}^{n}}{\Delta t} =
\Gamma_{x} \frac{\hat{\phi}_{i-1,j}^{n+1} - 2\hat{\phi}_{i,j}^{n+1} + \hat{\phi}_{i+1,j}^{n+1}}{\Delta x^{2}} + \Gamma_{y} \frac{\hat{\phi}_{i,j-1}^{n+1} - 2\hat{\phi}_{i,j}^{n+1} + \hat{\phi}_{i,j+1}^{n+1}}{\Delta y^{2}} + S_{\phi} \Big|_{i,j}^{n+1}$$
(5)

Dr. Anirban Dhar NPTEL Computational Hydraulics

By subtracting Equation 5 from Equation 4, we get the error equation

$$\Lambda_{\phi} \frac{\epsilon_{i,j}^{n+1} - \epsilon_{i,j}^{n}}{\Delta t} =
\Gamma_{x} \frac{\epsilon_{i-1,j}^{n+1} - 2\epsilon_{i,j}^{n+1} + \epsilon_{i+1,j}^{n+1}}{\Delta x^{2}} + \Gamma_{y} \frac{\epsilon_{i,j-1}^{n+1} - 2\epsilon_{i,j}^{n+1} + \epsilon_{i,j+1}^{n+1}}{\Delta y^{2}}$$
(6)

By subtracting Equation 5 from Equation 4, we get the error equation

$$\Lambda_{\phi} \frac{\epsilon_{i,j}^{n+1} - \epsilon_{i,j}^{n}}{\Delta t} =
\Gamma_{x} \frac{\epsilon_{i-1,j}^{n+1} - 2\epsilon_{i,j}^{n+1} + \epsilon_{i+1,j}^{n+1}}{\Delta x^{2}} + \Gamma_{y} \frac{\epsilon_{i,j-1}^{n+1} - 2\epsilon_{i,j}^{n+1} + \epsilon_{i,j+1}^{n+1}}{\Delta y^{2}}$$
(6)

In simplified form, this can be written as,

$$\begin{split} \alpha_y \epsilon_{i,j-1}^{n+1} + \alpha_x \epsilon_{i-1,j}^{n+1} - \left[1 + 2(\alpha_x + \alpha_y)\right] \epsilon_{i,j}^{n+1} \\ + \alpha_x \epsilon_{i+1,j}^{n+1} + \alpha_y \epsilon_{i,j+1}^{n+1} = -\epsilon_{i,j}^n \end{split}$$
 with $\alpha_x = \frac{\Gamma_x \Delta t}{\Lambda_+ \Delta x^2}$ and $\alpha_y = \frac{\Gamma_y \Delta t}{\Lambda_+ \Delta x^2}$.

Dr. Anirban Dhar

With

$$\begin{split} \epsilon_{i,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i,j}^n &= A^n e^{\sqrt{-1} i \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i-1,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} (i-1) \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i+1,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} (i+1) \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i,j-1}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} (j-1) \varphi_y} \\ \epsilon_{i,j+1}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} (j+1) \varphi_y} \end{split}$$

With

$$\begin{split} \epsilon_{i,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i,j}^n &= A^n e^{\sqrt{-1} i \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i-1,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} (i-1) \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i+1,j}^{n+1} &= A^{n+1} e^{\sqrt{-1} (i+1) \varphi_x + \sqrt{-1} j \varphi_y} \\ \epsilon_{i,j-1}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} (j-1) \varphi_y} \\ \epsilon_{i,j+1}^{n+1} &= A^{n+1} e^{\sqrt{-1} i \varphi_x + \sqrt{-1} (j+1) \varphi_y} \end{split}$$

By substituting all terms in the error equation,

$$\frac{A^{n+1}}{A^n} \left[\alpha_y e^{-\sqrt{-1}\varphi_y} + \alpha_x e^{-\sqrt{-1}\varphi_x} - \left[1 + 2(\alpha_x + \alpha_y) \right] + \alpha_x e^{\sqrt{-1}\varphi_x} + \alpha_y e^{\sqrt{-1}\varphi_y} \right]$$

$$= -1$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

$$G = \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})}$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

$$G = \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})}$$

The von Neumann Stability condition

$$\left|\frac{1}{1+4\alpha_y sin^2(\frac{\varphi_y}{2})+4\alpha_x sin^2(\frac{\varphi_x}{2})}\right| \leq 1$$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

$$G = \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})}$$

The von Neumann Stability condition

$$\left| \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})} \right| \le 1$$

Two Cases:

$$\bullet \ sin(\frac{\varphi_x}{2}) = 0$$
 and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

$$G = \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})}$$

The von Neumann Stability condition

$$\left| \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})} \right| \le 1$$

Two Cases:

- $sin(\frac{\varphi_x}{2}) = 0$ and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$
- $sin(\frac{\varphi_x}{2})=1$ and $sin(\frac{\varphi_y}{2})=1 \Rightarrow G=\frac{1}{1+4\alpha_y+4\alpha_x}<1$

The Growth Factor can be written as,

$$G = \frac{A^{n+1}}{A^n} = \frac{-1}{-1 + 2\alpha_y(\cos\varphi_y - 1) + 2\alpha_x(\cos\varphi_x - 1)}$$

$$G = \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})}$$

The von Neumann Stability condition

$$\left| \frac{1}{1 + 4\alpha_y sin^2(\frac{\varphi_y}{2}) + 4\alpha_x sin^2(\frac{\varphi_x}{2})} \right| \le 1$$

Two Cases:

- $sin(\frac{\varphi_x}{2}) = 0$ and $sin(\frac{\varphi_y}{2}) = 0 \Rightarrow G = 1$
- $sin(\frac{\varphi_x}{2})=1$ and $sin(\frac{\varphi_y}{2})=1 \Rightarrow G=\frac{1}{1+4\alpha_y+4\alpha_x}<1$

Implicit scheme is Unconditionally Stable.

Thank You

References

Biswas, G. (2003). Computational Fluid Flow and Heat Transfer. Narosa Publishing House, New Delhi.