



SUPPORT VECTOR MACHINES IN R

Introduction

Kailash Awati
Instructor



Preliminaries

- **Objective:** gain understanding of how SVMs work; options available in the algorithm and situations in which they work best.
- **Prerequisites:** Intermediate knowledge of R; basic visualization using `ggplot()`.
- **Approach:** Start with 1-dimensional example and gradually move on to more complex examples.

Sugar content of soft drinks

- Soft drink manufacturer has two versions of flagship brand:
 - **Choke** - sugar content 11g/ 100 ml
 - **Choke-R** - sugar content 8 g/ 100 ml
- Actual sugar content varies in practice.
- Given 25 samples chosen randomly, find a decision rule to determine brand.
- First step: visualize data!


Sugar content of soft drinks - visualization code

- Data in `drink_samples` dataframe.

```
#specify dataframe, set plot aesthetics in geom_point (note y=0)
p <- ggplot(data = drink_samples) +
  geom_point(aes(x = drink_samples$sugar_content, y = c(0)))

#label each point with sugar content value, adjust text size and location
p <- p +
  geom_text(aes(x=drink_samples$sugar_content, y=c(0)),
            label=drink_samples$sugar_content,
            size=2.5,
            vjust=2,
            hjust=0.5)

#display plot
p
```



Decision boundaries

- Let's pick two points in the interval as candidate boundaries:
 - 9.1 g/100 ml
 - 9.7 g/100 ml
- Classification (decision) rules:
 - if ($y < 9.1$) then "Choke-R" else "Choke"
 - if ($y < 9.7$) then "Choke-R" else "Choke"
- Let's visualize them on the plot shown on the previous slide.

Decision boundaries - visualization code


- Create a dataframe containing the two decision boundaries.

```
#define data frame containing decision boundaries
d_bounds <- data.frame(sep=c(9.1,9.7))
```

- Add to plot using `geom_point()`

```
#add decision boundaries to previous plot
p <- p +
  geom_point(data=d_bounds,
             aes(x=d_bounds$sep, y=c(0)),
             color="red",
             size=3) +
  geom_text(data=d_bounds,
            aes(x=d_bounds$sep, y=c(0)),
            label=d_bounds$sep,
            size=2.5,
            vjust=2,
            hjust=0.5,
            color="red")

#display plot
p
```




Maximum margin separator

- The best decision boundary is one that maximizes the margin: **maximal margin separator**
- Maximal margin separator lies halfway between the two clusters.
- Visualize the maximal margin separator.

```
#create data frame with maximal margin separator
mm_sep <- data.frame(sep = c((8.8+10)/2))

#add mm boundary to previous plot
p <- p +
  geom_point(data=mm_sep,
             aes(x=mm_sep$sep, y=c(0)),
             color="blue",
             size=4)

#display plot
p
```





SUPPORT VECTOR MACHINES IN R

Time to practice!



SUPPORT VECTOR MACHINES IN R

Generating a linearly separable dataset



Overview of lesson

- Create a dataset that we'll use to illustrate key principles of SVMs.
- Dataset has two variables and a linear decision boundary.



Generating a two-dimensional dataset using runif()

- Generate a two variable dataset with 200 points
- Variables `x1` and `x2` uniformly distributed in (0,1).

```
#Preliminaries...
#set required number of data points
n <- 200
#set seed to ensure reproducibility
set.seed(42)

#Generate dataframe with two predictors x1 and x2 in (0,1)
df <- data.frame(x1 = runif(n),
                 x2 = runif(n))
```



Creating two classes

- Create two classes, separated by the straight line decision boundary $x_1 = x_2$
- Line passes through (0,0) and makes a 45 degree angle with horizontal
- Class variable $y = -1$ for points below line and $y = 1$ for points above it

```
#classify points as -1 or +1
df$y <- factor(ifelse(df$x1-df$x2>0,-1,1),
               levels = c(-1,1))
```


Visualizing dataset using ggplot

- Create 2 dimensional scatter plot with x_1 on the x axis and x_2 on the y-axis
- Distinguish classes by color (below line=red; above line=blue)
- Decision boundary is line $x_1=x_2$: passes through (0,0) and has slope=1

```
#load ggplot2
library(ggplot2)

#build plot
p <- ggplot(data = df, aes(x = x1, y = x2, color = y)) +
  geom_point() +
  scale_color_manual(values = c("-1" = "red", "1" = "blue")) +
  geom_abline(slope = 1, intercept = 0)

#display it
p
```




Introducing a margin

- To create a margin we need to remove points that lie close to the boundary
- Remove points that have x_1 and x_2 values that differ by less than a specified value

```
#create a margin of 0.05 in dataset
delta <- 0.05
# retain only those points that lie outside the margin
df1 <- df[abs(df$x1-df$x2)>delta,]
#check number of data points remaining
nrow(df1)

#replot dataset with margin (code is exactly same as before)
p <- ggplot(data = df1, aes(x = x1, y = x2, color = y)) +
  geom_point() +
  scale_color_manual(values = c("red", "blue")) +
  geom_abline(slope = 1, intercept = 0)


#display plot
p
```



Plotting the margin boundaries

- The margin boundaries are:
 - parallel to the decision boundary (slope = 1).
 - located delta units on either side of it (delta = 0.05).

```
p <- p +  
  geom_abline(slope = 1, intercept = delta, linetype = "dashed") +  
  geom_abline(slope = 1, intercept = -delta, linetype = "dashed")  
  
p
```





SUPPORT VECTOR MACHINES IN R

Time to practice!