

# Exercise 01

Saturday, October 21, 2023

9:50 PM

## Problem 1 to hand in: Hand in

The following pseudocode and Python code contain errors. For each subtask determine the error (i.e., explain what the error is) and write down how it can be repaired.

- a) Given two positive integers  $a$  and  $b$ , the code should return the remainder  $c$  of the integer division  $\lfloor \frac{a}{b} \rfloor$ , i.e.  $c = a - b \cdot \lfloor \frac{a}{b} \rfloor$ .

get\_remainder( $a$ ,  $b$ ):

```
1 while  $a > b$  do
2   |  $a \leftarrow a - b$ 
3 return  $a$ 
```

- b) Given an integer  $n$ , the following pseudocode should return a Boolean value True if and only if  $n$  is divisible by 3.

is\_even( $n$ ):

```
1 if  $n \equiv 0 \bmod 3$  then
2   | result  $\leftarrow$  True
3 result  $\leftarrow$  False
4 return result
```

- c) Given two integers  $m$  and  $n$ , the following Python code should compute the power  $m^n$ .

```
1 def power(m, n):
2     power = 1
3     for index in range(n):
4         power = power * m
5     ← return power
```

range(n)  
0 ~ n-1  
n steps in total

- d) Given a positive integer  $n$ , the following Python code should compute  $\sum_{i=1}^n i^2$ .

```
6 def sum_squares(n):
7     sum = 0
8     for index in range(n):
9         sum = sum + index**2
10    return sum
```

- a) The current pseudocode will return  
an  $a < 0$ , which is clearly not the remainder.

The deduction shall stop as soon as

The deduction shall stop as soon as

$a < b$  (  $a // b = 0$  )

- b) In the code, either the condition is fulfilled or not, the statement at line 3 :

$result \leftarrow False$

will always be executed. This means that the function will always return false, regardless of the input. The declaration of the variable  $result$  shall be positioned before the condition.

Additionally, I believe the function shall not be called  $is-even$  and  $n \bmod 3 \equiv 0$  might be a typo

- c) According to the code and the writing style. The statement  $return$  lies within the  $for$  loop. The algorithm returns  $power (=m)$  in the very first step. Putting the return statement outside the loop will give the correct value.

- d) This refers to a typical Python mistake. The command  $range(n)$  creates an array from 0 to  $n-1$ . To get a correct output, one must use  $range(n+1)$

Since the first index is 0, it does not affect the total sum when the permutation starts from 0.

the total sum when the permutation starts from 0.  
We may leave it as it is.

### Problem 2 for discussion: *Efficiency and Refactoring*

Take a closer look at the code examples in Exercise 1.

- a) What are their running times?
- b) How can they be improved in terms of readability and brevity?

a) The running times vary with computer hardware setup.

• a)  $O(n)$  ,  $n \sim a // b$

• b)  $O(1)$

• c)  $O(n)$

• d)  $O(n)$

b) • a

```
1 # this is Python code
2 a % b
```

• b

```
1 # this is Python code
2 def divisible_by_3 (n):
3     return n % 3 == 0
```

• c

```
1 m ** n
```

• d index to i for readability