Automatic container model crane

Juni 17, 2016

Gruppe 633

Daniel Bähner Andersen
Nicolaj Vinkel Christensen
Ralf Victor Lømand Ravgård Christiansen
Simon Bjerre Krogh
Thomas Holm Pilgaard

Institut for elektroniske systemer
Aalborg Universitet
Danmark

AALBORG UNIVERSITY
DENMARK

Agenda

Introduction

System overview

Force estimation

Improvements

Introduction

- Minimally invasive surgery
- Surgical robots teleoperated by console
- Visual feedback recieved by surgeon

Introduction

- Surgeon has to estimate the force excerted by the tool
- Studies show haptic feedback reduces error rate

Introduction

- Force feedback implementation
- Geomagic Touch
  - 3 actuated degrees of freedom
  - Cartesian force feedback
  - Outputs up to 3 N of force

Introduction

- Communication delays
- Force estimation
- Control

System overview

⇒



Introduction

System overview

Force estimation

Improvements

Force estimation model

- Model approach
- Nonlinearities in the EndoWrist dynamics
  - Hammerstein Wiener Models

Figure: Hammerstein-Wiener model.

Force estimation model
Linear model

- Linear model
  - Choice of inputs affects model quality
  - Inputs: effort, velocity
  - Outputs: force
- Black-box identification
  - Subspace identification
  - Hankel singular value analysis

Include picture with effort force fit here!!

- Input and output nonlinearities
  - Effort
  - Force

Include picture with effort force fit here!!

- Nonlinearities
  - Deadzone nonlinearities
  - Input/Output -saturation

include two pictures here worksheet 4.6, 4.6 or 4.7

State estimation

- Modeling for additional outputs allows correction of the model using an estimator
- A multiple output model that adequatley captures the dynamics of the system could be used in a Kalman filter to create a state estimate
- The state estimates can be used in a state feedback loop to change system dynamics
- Reference following capabilities can be added to the system, despite the nonlinear characteristics of the dynamics

State estimation

- The hypothesis was tested in simulation
- Simulation results show that full reference following is possible despite the input nonlinearities in the system
- While the transient behaviour of the reference value is replicated, offsets and parasitic gains need to be compensated
- Could be implemented with improved model, doesn't improve estimate of current one.