

Automatic container model crane

Juni 17, 2016

Gruppe 633

Daniel Bähner Andersen

Nicolaj Vinkel Christensen

Ralf Victor Lømand Ravgård Christiansen

Simon Bjerre Krogh

Thomas Holm Pilgaard

Institut for elektroniske systemer

Aalborg Universitet

Danmark



AALBORG UNIVERSITY
DENMARK



Agenda

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

Introduction

System overview

Communication

Force estimation

Improvements



Introduction

Automatic container
model crane
Gruppe 633

2

- ▶ Minimally invasive surgery
- ▶ Surgical robots teleoperated by console
- ▶ Visual feedback received by surgeon

Introduction
System overview
Communication
Force estimation
Improvements

15



Introduction

Automatic container
model crane
Gruppe 633

3

- ▶ Surgeon has to estimate the force exerted by the tool
- ▶ Studies show haptic feedback reduces error rate

Introduction

System overview

Communication

Force estimation

Improvements

15



Introduction

Automatic container
model crane
Gruppe 633

4

Introduction

System overview

Communication

Force estimation

Improvements

- ▶ Force feedback implementation
- ▶ Geomagic Touch
 - ▶ 3 actuated degrees of freedom
 - ▶ Cartesian force feedback
 - ▶ Outputs up to 3 N of force

15



Introduction

Automatic container
model crane
Gruppe 633

5

- ▶ Communication delays
- ▶ Force estimation
- ▶ Control

Introduction
System overview
Communication
Force estimation
Improvements

15

System overview

Automatic container
model crane

Gruppe 633

Introduction


System overview

6

Communication

Force estimation

Improvements




Communication

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

7



15



Communication

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

- Requirement for force feedback: 1000 Hz

8

15



Communication

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

- ▶ Requirement for force feedback: 1000 Hz
- ▶ Maximum for the initial system: 100 Hz

8

15



Communication

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

8

- ▶ Requirement for force feedback: 1000 Hz
- ▶ Maximum for the initial system: 100 Hz
- ▶ Our approach:

15



Communication

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

8

- ▶ Requirement for force feedback: 1000 Hz
- ▶ Maximum for the initial system: 100 Hz
- ▶ Our approach:
 - ▶ Reducing the size of exchanged data

15



Communication

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

8

- ▶ Requirement for force feedback: 1000 Hz
- ▶ Maximum for the initial system: 100 Hz
- ▶ Our approach:
 - ▶ Reducing the size of exchanged data
 - ▶ Changing the transport protocol

15



Communication

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

8

- ▶ Requirement for force feedback: 1000 Hz
- ▶ Maximum for the initial system: 100 Hz
- ▶ Our approach:
 - ▶ Reducing the size of exchanged data
 - ▶ Changing the transport protocol
- ▶ Results: maximum of 638 Hz

15



Filip Maric

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

Introduction

System overview

Communication

Force estimation

Improvements

9

15

Force estimation model

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

10

- ▶ Model approach
- ▶ Nonlinearities in the EndoWrist dynamics
 - ▶ Hammerstein Wiener Models



Figure : Hammerstein-Wiener model.

15



Force estimation model

Linear model

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

11

- ▶ Linear model
 - ▶ Choice of inputs affects model quality
 - ▶ Inputs: effort, velocity
 - ▶ Outputs: force
- ▶ Black-box identification
 - ▶ Subspace identification
 - ▶ Hankel singular value analysis

Include picture with effort force fit here!!

15

Force estimation model

Hammerstein Wiener Models

Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

- ▶ Input and output nonlinearities

- ▶ Effort
- ▶ Force

Include picture with effort force fit here!!

12

15



Force estimation model

Hammerstein Wiener Models

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

► Nonlinearities

- Deadzone nonlinearities
- Input/Output -saturation

13

15



Automatic container
model crane
Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

14

15



State estimation

Automatic container
model crane

Gruppe 633

Introduction

System overview

Communication

Force estimation

Improvements

14

- ▶ Modeling for additional outputs allows correction of the model using an estimator
- ▶ A multiple output model that adequately captures the dynamics of the system could be used in a Kalman filter to create a state estimate
- ▶ The state estimates can be used in a state feedback loop to change system dynamics
- ▶ Reference following capabilities can be added to the system, despite the nonlinear characteristics of the dynamics

15



State estimation

Automatic container
model crane
Gruppe 633

Introduction
System overview
Communication
Force estimation
Improvements

15

- ▶ The hypothesis was tested in simulation
- ▶ Simulation results show that full reference following is possible despite the input nonlinearities in the system
- ▶ While the transient behaviour of the reference value is replicated, offsets and parasitic gains need to be compensated
- ▶ Could be implemented with improved model, doesn't improve estimate of current one.

15