

INFT-1205 – Data Communications & Networking II

Capstone Project

Bell Router Configuration

Institution: Durham College

By: Group 1

Suhaan Bhanwer, Anointing Iyawe, Hossein Abdolzahraei

Document Overview

This document serves as brief documentation on the Bell ISP router. It includes an overview of the Bell Router, along with its configuration.

Device Overview

The BellRouter acts as the Bell Canada ISP router. It is the Backup ISP of Datacore Solutions and is linked to the Datacore Router on the 101.1.2.0/30 network. It contains a default static route to the Datacore Router, allowing traffic to return.

Configuration

Building configuration...

Current configuration : 1796 bytes

!

! Last configuration change at 16:35:58 UTC Thu Apr 9 2026

!

version 15.4

service timestamps debug datetime msec

service timestamps log datetime msec

no service password-encryption

!

hostname BellRouter

!

boot-start-marker

boot-end-marker

!

!

! card type command needed for slot/vwic-slot 0/1

!

no aaa new-model

memory-size iomem 15

!

!

!

!

!

!

!

!

!

!

!

!

!

!

ip cef

no ipv6 cef

!

multilink bundle-name authenticated

!

!

!

!

!

!

cts logging verbose

!

!

voice-card 0

!

!

!

!

!

!

!

!

license udi pid CISCO2901/K9 sn FJC2121A0VC

license accept end user agreement

license boot module c2900 technology-package securityk9

license boot module c2900 technology-package uck9

hw-module pvdm 0/0

!

hw-module pvdm 0/1

!

!

!

!

redundancy

!

!

!

!

!

!

!

!

!

!

!

!

!

!

!

interface Embedded-Service-Engine0/0

no ip address

shutdown

!

interface GigabitEthernet0/0

no ip address

shutdown

duplex auto

speed auto

!

interface GigabitEthernet0/1

no ip address

shutdown

duplex auto

speed auto

!

interface Serial0/0/0

ip address 101.1.2.2 255.255.255.252

clock rate 256000

!

interface Serial0/0/1

no ip address

shutdown

!

ip forward-protocol nd

!

no ip http server

no ip http secure-server

!

ip route 0.0.0.0 0.0.0.0 101.1.2.1

!

!

!

!

control-plane

!

!

voice-port 0/2/0

!

voice-port 0/2/1

!

voice-port 0/3/0

!

voice-port 0/3/1

!

!

!

!

!

mgcp behavior rsip-range tgcp-only

mgcp behavior comedia-role none

mgcp behavior comedia-check-media-src disable

mgcp behavior comedia-sdp-force disable

!

mgcp profile default

!

!

!

!

!

!

!

gatekeeper

shutdown

!

!

!

line con 0

line aux 0

line 2

no activation-character

no exec

transport preferred none

transport output pad telnet rlogin lapb-ta mop udptn v120 ssh

stopbits 1

line vty 0 4

login

transport input none

!

scheduler allocate 20000 1000

!

end