

```
CREATE DATABASE SalesDB;
```

```
USE SalesDB;
```

```
CREATE TABLE Sales (  
    SaleID INT PRIMARY KEY,  
    ProductName VARCHAR(50),  
    Quantity INT,  
    Price DECIMAL(10,2)  
);
```

```
DELIMITER //
```

```
CREATE PROCEDURE AddSale(  
    IN p_SaleID INT,  
    IN p_ProductName VARCHAR(50),  
    IN p_Quantity INT,  
    IN p_Price DECIMAL(10,2)  
)  
BEGIN  
    INSERT INTO Sales  
    VALUES(p_SaleID, p_ProductName, p_Quantity, p_Price);  
END //
```

```
DELIMITER ;
```

```
CALL AddSale(1,'Laptop',2,50000);
```

```
CALL AddSale(2,'Mouse',5,500);
```

```
DELIMITER //
```

```
CREATE FUNCTION TotalSales()
```

```
RETURNS DECIMAL(10,2)
```

```
DETERMINISTIC
```

```
BEGIN
```

```
    DECLARE total DECIMAL(10,2);
```

```
    SELECT SUM(Quantity * Price)
```

```
    INTO total
```

```
    FROM Sales;
```

```
    RETURN total;
```

```
END //
```

```
DELIMITER ;
```

```
SELECT * FROM Sales;
```

```
SELECT TotalSales();
```