# Quantifying biological constraints on stream integrity for classification and management priorization

Marcus W. Beck (marcusb@sccwpr.org), Raphael D. Mazor (raphaelm@sccwrp.org), Scott

Johnson (scott@aquaticbioassay.com), Phil Markle (phil@lacsd.org), Peter D. Ode

(peter.ode@wildlife.ca.gov), Ryan Hill (hill.ryan@epa.gov), Eric D. Stein (erics@sccwrp.org)

## 6 Introduction

- Degraded biological condition in streams can occur from individual or multiple stressors acting at different scales (Novotny et al. 2005; Townsend, Uhlmann, and Matthaei 2008; Leps et al. 2015). Identifying and mitigating causes of poor condition requires an understanding of how stressors propogate across space and time. Incomplete knowledge on drivers of change or high level of uncertainty in how biology is linked to drivers can lead to ineffective management actions. Placing bounds on effects of known drivers of change can reduce expenses and increase assurance of outcomes for targeted management (e.g., varying costs and challenges of urban stream restoration (Kenney et al. 2012; Shoredits and Clayton 2013))
  - Effective stream management can depend on identification and prioritization of sites where activities are expected to have desired outcomes. This requires an understanding of how stressors affect biological integrity to place bounds on reasonable expectations for what is likely to be a possible outcome of a management action. This requires identifying biological constraints or limits on the potential range of biological conditions. Identifying an appropriate context for observed conditions can be used to prioritize. Context can be defined by models, expert knowledge, and/or defined value sets.
  - We don't have good constraint tools to develop a context of expectation of what's possible at a site. This can help prioritize locations where management efforts will or will not have the intended outcomes. Biological filters act at different scales (Poff 1997) and we can use this information to describe an expectation for prioritization that is scale-specific. Landscape-level constraints are particularly relevant for macroinvertebrate communities in streams (Sponseller, Benfield, and Valett 2001)
  - The goal of this study is to demonstrate application of a landscape model to classify and prioritize stream monitoring sites using estimated constraints on biological integrity. The model provides an estimate of context for biological condition that provides an expectation of what is likely to be achieved at a given site relative to large-scale drivers of stream health. The model was developed and applied to all stream reaches in California. A case study is used to demonstrate how the model can be used to classify and prioritize using guidance from a regional stakeholder group. Active stakeholder involvement was critical in applying the landscape models to define a framework for decision-making because priorities varied with management objectives.

#### $_{^{14}}$ Methods

## Study area and data sources

- Brief description of CA, stream types and designated uses, PSA regions, management interests (e.g., southern vs. northern CA)
  - Streamcat database used to quantify watershed land use at all sites (Hill et al. 2016)
  - Streamcat data linked to National Hydrography Dataset Plus (NHD) (USGS (US Geological Survey) 2014), reach as individual unit for model output

The California Stream Condition Index (CSCI) (Ode et al. 2016; Mazor et al. 2016) was used as a measure of biological condition to assess site performance relative to reach classification. Benthic macroinvertebrate 42 data used to calculate CSCI scores were collected at nearly 4800 sites between 2000 and 2014. Field data 43 were collected during baseflow conditions typically between May and July following methods in Ode (2007). The CSCI is a predictive index of stream health that compares the observed taxa and metrics at a site to 45 those expected under reference conditions. Expected conditions at a site are based on models that estimate the likely macroinvertebrate community in relation to factors that naturally influence biology, e.g., watershed 47 size, elevation, climate, etc. The CSCI score at a site is based on an observed-to-expected ratio of taxa and a predictive multimetric index (pMMI) composed of six individual metrics that describe the structure and 49 function of the macroinvertebrate community. The index score at a site can vary from 0 to 1.4, with higher values indicating an observed community with less deviation from reference conditions. Because the index 51 was developed to minimize the influence of natural gradients, the index scores have consistent meaning across 52 the state (Reynoldson et al. 1997). A threshold score based on a selected lower percentile of scores (e.g., 53 10%) at all reference sites is used to define nominally low and high scoring sites. 54

## 55 Building and validating landscape models

A prediction model of the CSCI was developed to estimate likely ranges of scores associated with land use gradients. Land use as urban and agricultural was quantified for the catchment of each stream reach in California using the StreamCat database (Hill et al. 2016). CSCI scores were modelled using only the estimates of urban and agricultural land use as the developed portion of the landscape within each stream reach. The model was incomplete by design to describe scores only in relation to large-scale constraints on biological condition that are not easily controlled by management actions or where costs to mitigate are likely to be excessive. The remainder of the variation in scores not related to landscape constraints could be attributed to additional, unmeasured environmental variables that influence stream biointegrity. Deviation of observed scores from the model predictions were considered diagnostic of variation not related to landscape effects.

Models were developed using quantile regression forests to estimate ranges of likely CSCI scores in different landscapes (N. Meinshausen 2006; Nicolai Meinshausen 2017). Quantile models evaluate the conditional 67 response across the range of values that are expected, such as the lower and upper percentiles of the distribution, as compared to only the mean response with conventional models (Cade and Noon 2003). This 69 allows use of model predictions to describe where bioassessment targets are unlikely to be met or where streams are unlikely to be impacted by placing bounds on the range of expectations relative to landscape constraints. 71 Random forest models also provide robust predictions by evaluating different subsets of observations from 72 random splits of the predictor variables. The final predictions are the averaged response across several models. 73 These models have been used extensively in bioassessment applications (Carlisle, Falcone, and Meador 2009; Chen et al. 2014; Mazor et al. 2016) and can produce unbiased estimates that are relatively invariant to noisy 75 relationships or non-normal distributions (Breiman 2001; Hastie, Tibshirani, and Friedman 2009). Quantile 76 regression forests were used to predict CSCI scores in each stream reach from the 5<sup>th</sup> to the 95<sup>th</sup> percentile 77 of expectations at five percent intervals (i.e., 5<sup>th</sup>, 10<sup>th</sup>, etc.). 78

Landscape estimates for the catchments of all NHD stream reaches in California were separated into calibration and validation data.

#### 81 San Gabriel River watershed case study

Stream reach and bioassessment data from the San Gabriel River (SGR) watershed in southern California
were used to develop reach classifications, site performance categories, and management priorities from the
landscape models. A strong land use gradient occurs in the SGR watershed. Headwaters begin in the San
Gabriel mountains where the land is primarily undeveloped or protected for reacreational use, whereas the
lower watershed is in a heavily urbanized region of Los Angeles County. The San Gabriel river is dammed at
four locations for flood control in the upper watershed and is hydrologically connected to the Los Angeles

river to the west through the Whittier Reservoir in the lower watershed. Spreading grounds are present in
the middle of the watershed for groundwater recharge during high flow. Nearly all of the stream reaches in
the lower half of the watershed are channelized with concrete or other reinforcements.

91 Figure SGR watershed

105

106

107

108

110

111

112

113

The SGR watershed contains a diverse group of stakeholders from local municipalities, water districts, water quality regulatory agencies, consulting groups, and non-government organizations. Collectively, the 93 San Gabriel River Regional Monitoring Program (SGRRMP) includes stakeholders from these groups that cooperatively work to increase awareness of issues in the SGR watershed and work to improve coordination of compliance and ambient monitoring efforts. The stakeholder workgroup included individuals from the SGRRMP with interests in water supply, improvements to water quality, habitat protection or creation, 97 and storm water permitting. Individuals were selected for partipation to include a variety of mangement 98 interests and based on willingness to adopt tools developed from the landscape models. The stakeholder 99 workgroup met monthly over a six-month period to discuss model applications and to refine the interpretation 100 of results. Stakeholder involement was critical for developing an assessment framework that met the needs of 101 all engaged parties and ensured that final products were more likely to be incorporated into formal processes 102 of decision-making.

## 104 Reach classification and site prioritization

A framework for identifying site priorities for management actions was developed using a three-step process. First, estimates of the range of expected CSCI scores at each stream reach in relation to land use were used to define reach classifications. Second, the relationship between observed CSCI scores and the reach classifications were then used to assign a relative performance value for each monitoring site. Third, site performance categories in relation to reach classification and bioassessment targets were used to define management priorities. This framework was developed through close interaction with the regional stakeholder group to demonstrate how the landscape model can be used as a management tool given that priorities will vary by interests and location. As such, the results are provided as a guide to facilitate decision-making rather than a prescription of targeted actions to manage stream health.

Identifying site priorities began with defining a classification framework for stream reaches to identify the possible or likely extent of biological constraints. Classifications were developed using the range of CSCI expectations at a reach relative to a chosen threshold for the CSCI to define nominally low or high scores. The reach classification was based solely on the intersection of the CSCI expectations at a reach with chosen CSCI threshold, where expectations could be below, above, or overlapping the threshold. Stream reaches with a range of CSCI score expectations entirely below the thresholds were considered likely constrained, whereas those with expectations entirely above were considered likely unconstrained. Reaches with score expectations that included the CSCI thresholds were considered possibly constrained or possibly unconstrained, where the distinction was based on location of the median expectation of a reach relative to the threshold.

CSCI scores from biomonitoring data were used to define performance of a sample site relative to the stream reach classification. For each of the four reach classifications (likely constrained, possibly constrained, possibly unconstrained, and likely unconstrained), the site performance was defined relative to the bounds of the expected CSCI scores. This provided a definition of site performance that can be used to understand the observed score relative to the biological context of a reach. Sites with observed scores above the upper limit of the reach expectation (e.g., above the 95<sup>th</sup> percentile of expected scores) were considered "overperforming" and sites below the lower limit were "under-performing". Sites with CSCI scores within the range of expectations were as "expected".

131 Figure classification and performance

Site performance categories were further split relative to location to the selected CSCI threshold. This final split was created with the intent that description of site scores relative to a defined threshold (e.g., impairment threshold or restoration target) should also be considered. Specifically, a fourth category of site performance for each reach classification was added to define a site as above or below the threshold. For a

- likely unconstrained reach, underperforming sites below the minimum expected score were additionally defined as being above or below the CSCI threshold. Similarly, overperforming sites above the maximum expected score in a likely constrained reach were additionally defined as being below or above the CSCI threshold. For possibly constrained and possibly unconstrained reaches, sites that were performing as expected were additionally defined as being below or above the CSCI threshold. In total, sixteen site types were defined for the three reach classification and three site performance classifications.
- 142 Table reach classification, site performance types and categories
  - Sensitivity analysis how do classes, performance categories change with thresholds and certainty
- Unclassified reaches
  - Prioritization of types stakeholder involvement

## Results

143

145

148

149

153

160

## 147 State-wide patterns

- Where does the model perform well, how does performance vary with validation and calibration datasets.
  - What is the consistency of patterns? For example, percent stream miles as xyz by PSA.
- 50 Figure Statewide map.

## $_{151}$ Case study

- San Gabriel River Regional Monitoring Program
- Extent, classification, prioritization probabilistic assessment to make broader conclusions.
- Relationships with environmental variables for constrained/unconstrained locations. Maybe apply to hardened/non-hardened reaches in constrained locations.
  - What to do with unclassified streams typical urban, typical ag.
- 157 Tables Priority by type, by perspective

## 158 Discussion

- What do priorities really mean? Depends on your interests, needs, values, etc.
  - Link with engineered channels study.
- Values of stakeholder interactions.

## Supplement

Online application.

## References

- Breiman, L. 2001. "Random Forests." Machine Learning 45: 5–32.
- Cade, B. S., and B. R. Noon. 2003. "A Gentle Introduction to Quantile Regression for Ecologists." Frontiers
   in Ecology and the Environment 1 (8): 412–20.
- <sup>168</sup> Carlisle, D. M., J. Falcone, and M. R. Meador. 2009. "Predicting the Biological Condition of Streams:
- 169 Use of Geospatial Indicators of Natural and Anthropogenic Characteristics of Watersheds." Environmental
- 170 Monitoring and Assessment 151 (1-4): 143-60. doi:10.1007/s10661-008-0256-z.
- <sup>171</sup> Chen, K., R. M. Hughes, S. Xu, J. Zhang, D. Cai, and B. Wang. 2014. "Evaluating Performance of
- <sup>172</sup> Macroinvertebrate-Based Adjusted and Unadjusted Multi-Metric Indices (MMI) Using Multi-Season and
- Multi-Year Samples." Ecological Indicators 36: 142–51. doi:10.1016/j.ecolind.2013.07.006.
- Hastie, T., R. Tibshirani, and J. Friedman. 2009. The Elements of Statistical Learning: Data Mining,
- 175 Inference, and Prediction. 2nd ed. New York: Springer.
- Hill, R. A., M. H. Weber, S. G. Leibowitz, A. R. Olsen, and D. J. Thornbrugh. 2016. "The Stream-Catchment
- 177 (StreamCat) Dataset: A Database of Watershed Metrics for the Conterminous United States." Journal of the
- 178 American Water Resources Assocation 52: 120–28. doi:10.1111/1752-1688.12372.
- Kenney, M. A., P. R. Wilcock, B. F. Hobbs, N. E. Flores, and D. C. Martínez. 2012. "Is Urban Stream Restora-
- tion Worth It?" Journal of the American Water Resources Association 48 (3): 603-15. doi:10.1111/j.1752-
- 181 1688.2011.00635.x.
- Leps, M., J. D. Tonkin, V. Dahm, P. Haase, and A. Sundermann. 2015. "Disentangling Environmental Drivers
- 183 of Benthic Invertebrate Assemblages: The Role of Spatial Scale and Riverscape Heterogeneity in a Multiple
- Stressor Environment." Science of the Total Environment 536: 546-56. doi:10.1016/j.scitotenv.2015.07.083.
- Mazor, R. D., A. C. Rehn, P. R. Ode, M. Engeln, K. C. Schiff, E. D. Stein, D. J. Gillett, D. B. Herbst, and
- 186 C. P. Hawkins. 2016. "Bioassessment in Complex Environments: Designing an Index for Consistent Meaning
- in Different Settings." Freshwater Science 35 (1): 249–71.
- <sup>188</sup> Meinshausen, N. 2006. "Quantile Regression Forests." Journal of Machine Learning Research 7: 983–99.
- Meinshausen, Nicolai. 2017. QuantregForest: Quantile Regression Forests. https://CRAN.R-project.org/package=quantregForest.
- Novotny, V., A. Bartosová, N. O'Reilly, and T. Ehlinger. 2005. "Unlocking the Relationship of
- 192 Biotic Integrity of Impaired Waters to Anthropogenic Stresses." Water Research 39 (1): 184–98.
- doi:10.1016/j.watres.2004.09.002.
- Ode, P. R. 2007. "Standard Operating Procedures for Collecting Benthic Macroinvertebrate Samples and
- Associated Physical and Chemical Data for Ambient Bioassessment in California." Surface Water Ambient
- 196 Monitoring Program. Sacramento, CA.
- 197 Ode, P. R., A. C. Rehn, R. D. Mazor, K. C. Schiff, E. D. Stein, J. T. May, L. R. Brown, et al. 2016.
- <sup>198</sup> "Evaluating the Adequacy of a Reference-Site Pool for Ecological Assessments in Environmentally Complex
- 199 Regions." Freshwater Science 35 (1): 237–48.
- 200 Poff, N. L. 1997. "Landscape Filters and Species Traits: Towards Mechanistic Understanding and Prediction
- in Stream Ecology." Journal of the North American Benthological Society 16 (2): 391-409.
- Reynoldson, T. B., R. H. Norris, V. H. Resh, K. E. Day, and D. M. Rosenberg. 1997. "The Reference
- 203 Condition: A Comparison of Multimetric and Multivariate Approaches to Assess Water-Quality Impairment
- Using Benthic Macroinvertebrates." Journal of the North American Benthological Society 16 (4): 833–52.
- Shoredits, A. S., and J. A. Clayton. 2013. "Assessing the Practice and Challenges of Stream Restoration in
- Urbanized Environments of the USA." Geography Compass 7 (5): 358–72. doi:10.1111/gec3.12039.
- <sup>207</sup> Sponseller, R. A., E. F. Benfield, and H. M. Valett. 2001. "Relationships Between Land Use, Spatial Scale

- and Stream Macroinvertebrate Communities." Freshwater Biology 46 (10): 1409-24. doi:10.1046/j.1365-209 2427.2001.00758.x.
- Townsend, C. R., S. S. Uhlmann, and C. D. Matthaei. 2008. "Individual and Combined Responses of Stream Ecosystems to Multiple Stressors." *Journal of Applied Ecology* 45 (6): 1810–9. doi:10.1111/j.1365-212 2664.2008.01548.x.
- USGS (US Geological Survey). 2014. "National Hydrography Dataset available on the World Wide Web."