

Scores

Range:
[0, 4]

Real:
4.0

Predicted:
4.0

Prompt

Based on the excerpt, describe the obstacles the builders of the Empire State Building faced in attempting to allow dirigibles to dock there. Support your answer with relevant and specific information from the excerpt.

Essay

Throughout the designing and construction stages of the Empire State building's mooring mast, builders and engineers confronted many issues including, the distribution of building stress, fire hazards and the constant shifting caused by winds. During the planning stages of engineers, they confronted an issue, how to alliviate stress on the Empire State Building's frame. According to engineers making the "thousand foot dirigible moored at at the top of the building held by a single cable tether would add stress to the building's frame..." @CAPS1, the building would require "over sixty thousand dollars" in redesigning and modifying the current building's foundation and framework. Secondly, engineers and builders never considered the fire hazards, which they were confronted with after the completion of the mooring mast. The American dirigibles were filled with hydrogen rather than helium, making that gaseous-filled transportation highly flammable." An example of this safety violation occurred with the burning of a dirigible in Lakehurst, New Jersey, causing builders to reflect on the possible severity of this possible accident in the heavily populated area of New York. Thirdly, New York had "violent air currents" which could cause the rear of the dirigibles to swivel and shift. The only possible solution was to way down the back with lead blocks, but this would be "neither practical nor safe." Engineers and builders of the Empire State Building were confronted with many problems and concerns sometimes only addressed by irrational solutions.

Top-10 Higher
Feature Attribution Score

