

Contents lists available at ScienceDirect

# **Information Sciences**

journal homepage: www.elsevier.com/locate/ins



# Multi-view face hallucination using SVD and a mapping model



Muwei Jian a,b,\*, Chaoran Cui a, Xiushan Nie a, Huaxiang Zhang C, Liqiang Nie d, Yilong Yin e

- <sup>a</sup> School of Computer Science and Technology, Shandong University of Finance and Economics, Jinan, China
- <sup>b</sup> School of Creative Technologies, University of Portsmouth, Portsmouth, UK
- <sup>c</sup>School of Information Science and Engineering, Shandong Normal University, Jinan, China
- <sup>d</sup> School of Computer Science and Technology, Shandong University, Qingdao, China
- e School of Software Engineering, Shandong University, Jinan 250101, China

#### ARTICLE INFO

# Article history: Received 9 March 2018 Revised 10 March 2019 Accepted 12 March 2019 Available online 14 March 2019

Keywords: Face hallucination Singular value decomposition Multi-view face Mapping model

#### ABSTRACT

Multi-view face hallucination (MFH) presents a challenge issue in face recognition domain. In this paper, an efficient method based on singular value decomposition (SVD) and a mapping model is proposed for multi-view face hallucination. Based on an approximately same linear mapping relationship across different views, two corresponding matrices obtained from the SVD of the low resolution (LR) image for the high-resolution (HR) multi-view face images can be constructed via the mapping model using global reconstruction. Experiments show that our proposed multi-view face-hallucination scheme is effective and produces promising super-resolved results.

© 2019 Elsevier Inc. All rights reserved.

# 1. Introduction

Face hallucination is a technique to construct a high-resolution (HR) image from a low-resolution (LR) face image [30,33,40], and has become an active issue in computer vision and pattern recognition [9,10,21,24 46,48]. Face-hallucinating technique is especially important for video surveillance, in which LR images are usually captured at a far distance.

The pioneering study on face hallucination was proposed by Baker et al. [4], and has become an important and hot topic in image processing right now. Yang et al. [43] proposed a sparse-coding approach to reconstruct the HR patch, which is produced via using the same combination coefficients as corresponding neighboring HR patches. Wang and Tang [41] designed a holistic face-hallucination scheme which utilizes eigentransformation to represent a LR input face as a linear combination of LR training samples. In [35], Park et al. [35] proposed an example-based super-resolution algorithm based on the eigentransformation-based framework [41]. Liu et al. [26] proposed a hybrid method based on global and local constraints for the task of face hallucination. Li and Chang [25] proposed a novel super-resolution algorithm by aligning coupled manifolds for face hallucination. In [32], a framework using patches at the same position and the optimal weights for the training position-patches are combined for hallucinating HR face. Based on the assumption that two similar face images should have similar local-pixel structures, a novel face-hallucination method was developed in [13]. Akyol and Gokmen [1] utilized both the shape and texture components to hallucinate HR image. Recently, based on similarity constraints, a new

E-mail address: jianmuwei@ouc.edu.cn (M. Jian).

<sup>\*</sup> Corresponding author:

face-hallucination approach was proposed for HR face image reconstruction [27]. Jiang et al. designed a novel face superresolution scheme based on multilayer locality-constrained iterative neighbor embedding algorithm, aiming at preserving the manifold-consistency between the reconstructed HR and the original HR image [19]. In [20], a Locality-induced Support Regression (LiSR) method was proposed for face super-resolution. Tian and Ma introduced a technical review for SR image and video reconstruction approached in [39]. In [7], a deep learning method was proposed for single image super-resolution (SR) via learning an end-to-end mapping between LR-HR images, Based on a residual convolutional neural network. Oktav et al. [34] proposed an image super-resolution (SR) for HR 3D volumes reconstruction. Recently, Yue et al. [45] provided a comprehensive view of SR containing reconstruction algorithms, parameter selection and optimization methods. Recently, generative adversarial networks (GAN)-based methods can be performed to generate photo-realistic natural images and faces [11,44]. During the generation of facial images, the main idea of GAN-based methods is to train two adversarial networks: a generator (G) aims to generate facial images, and a discriminator (D) seeks to distinguish generated (fake) images from real facial images. However, there still exists the model collapse problem when the generator (G) learns to map different inputs to the same point and then GAN-based methods may fail to produce satisfactory facial images. Yu and Porikli [44] designed a discriminative generative network, called ultra-resolution by discriminative generative networks (UR-DGN), to generate HR frontal facial images. Nevertheless, the defect is that generative facial images are sensitive to rotations [6], which is not suitable for the task of multi-view face hallucination (MFH).

Based on boundary equilibrium generative adversarial networks, a single face image super-resolution method propose is designed [12]. In [5], Chen et al. proposed a deep end-to-end trainable Face Super-Resolution Network (FSRNet) for reconstructing very LR face images. Through feature learning into an adversarial network, an end-to-end model is designed to fulfill cross-spectral face hallucination [38]. Zhuang et al. [49] proposed a two-stage face hallucination scheme to reconstruct HR face image from the LR face via integrating locality preserving projection (LPP) and radial basis function (RBF) regression simultaneously. In [2], a Generic Shape-Illumination Manifold (gSIM) framework was designed to hallucinate faces across different poses and scales. Later, an efficient framework for matching linear subspaces in images of different scales was designed [3]. More recently, Farrugia and Guillemot proposed a coupled sparse support (CSS) face-hallucination framework via estimating the local geometrical structure on the high-resolution manifold [8]. Based on the relationship between target patch and training patches in the high-resolution feature space, two regularization models are designed to produce HR facial images [37]. In [22], Jiang et al. proposed a novel context-patch method by thresholding locality-constrained representation with reproducing learning to hallucinate HR faces. Based on locality-constrained linear coding, an effective bi-layer representation face-hallucination method is proposed to super-resolve the HR facial images based on training samples [29].

However, most existing algorithms are only limited to frontal faces. Multi-view face hallucination (MFH) is a more difficult issue and only several schemes have been proposed. Li et al. [28] presented a framework based on Gabor wavelet features to deal with the pose variation issue for face hallucination. Jia et al. [16] proposed a Bayesian framework based on tensor for face hallucination; however, probability model and tensor based MFH methods are generally complicated with high computational complexity. In [31], Ma et al. proposed an efficient MFH in two stages: multi-view LR faces are firstly generated by using face transformation, then resolution enhancement step to combine high-frequency details for the multi-view LR faces. Hui and Lam [14] proposed an effective two-step patch-based MFH method. In [47], Zeng and Huang proposed a super-resolution method by learning a crop of nonlinear mappings in the coherent feature space between non-frontal low resolution (NFL) images of various poses and their related frontal high resolution (FH) images. Recently, a multi-view face hallucination based on sparse representation was proposed [15]. More recently, Jin and Bouganis [23] developed a patchwise prior based method to hallucinate LR facial images in PCA subspace for robust blurring kernel estimation. For multi-view face super-resolution, Deshmukh and Rani [6] proposed a Fractional-Grey Wolf Optimizer-based (FGWO) framework via kernel weighted regression.

For our previous work [17], we only focus on frontal-view face hallucination. In this letter, based on an assumption that there exists an approximately same linear mapping relationship across different views, HR multi-view face images can then be constructed. We proposed a method to combine SVD with a mapping model to fulfill the MFH task, which is effective and produces promising results.

The rest of the paper is organized as follows. In Section 2, we will present Singular Value Decomposition and the mapping model. Section 3 introduces a novel framework of Multi-view face hallucination (MFH) and experimental results are presented in Section 4. The paper closes with a conclusion and discussion in Section 5.

# 2. SVD and mapping model

Suppose that a HR face is denoted as  $I_l$  and the corresponding down-sampled LR face is denoted as  $I_l$ . The HR and LR faces can be decomposed by SVD as follows:

$$I_h = U_h W_h V_h^T \text{ and } I_l = U_l W_l V_l^T$$
 (1)

These two matrices  $U_l$  and  $V_l$  for  $I_l$  can be up-sampled to develop two new matrices  $U'_l$  and  $V'_l$  that have the same size as  $U_h$  and  $V_h$ , respectively. Define two mapping matrices  $P_u$  and  $P_v$ , as follows:

$$U_h = U_l' P_u$$
, and  $V_h = V_l' P_v$ . (2)

Then the matrices  $P_{\mu}$  and  $P_{\nu}$  can be approximately obtained via pseudo-inverse technique as below:

$$\tilde{P}_{u} = (U_{l}^{'T}U_{l}' + \lambda E)^{-1}U_{l}^{'T}U_{h}, \text{ and } \tilde{P}_{\nu} = (V_{l}^{'T}V_{l}' + \lambda E)^{-1}V_{l}^{'T}V_{h},$$
(3)

where  $\lambda$  is a small positive number and E is a unit matrix. Then a reconstruction of  $U_h$  and  $V_h$ , denoted as  $\hat{U}_h$  and  $\hat{V}_h$ , respectively, can be calculated:

$$\hat{U}_h = U_l' \tilde{P}_{ll}$$
, and  $\hat{V}_h = V_l' \tilde{P}_{ll}$ . (4)

For the face-hallucination issue, a HR image can be estimated from a LR face using the matrices  $\hat{U}_h$  and  $\hat{V}_h$ , which can be computed based on a pair of LR-HR training faces.

Assuming that an LR image  $I_l$  will be hallucinated to generate a HR image with a magnification factor of  $\alpha$ . By using the LR input face, an amount of M LR face images resembling  $I_l$ , also with the corresponding HR faces as references, are retrieved from a database with pairs of LR-HR faces. These M pairs of LR-HR training faces, denoted as  $I_l^i$  and  $I_h^i$  (i=1,2,...,M), should have a comparable structural appearance to the LR input image after alignment. Every single of the similar HR faces can be super-resolved using the mapping matrices of its corresponding LR face images, i.e.

$$\hat{U}_b^i = U_l^i \tilde{P}_u^i, \text{ and } \hat{V}_b^i = V_l^i \tilde{P}_v^i, \tag{5}$$

where 1 < i < M.

Then, for face hallucination, the mapping matrices  $\tilde{P}_u$  and  $\tilde{P}_v$  can be calculated using the corresponding mapping matrices  $\tilde{P}_u^i$  and  $\tilde{P}_v^i$ , computed from the M pairs of LR and HR faces. A linear combination of mapping matrices is expressed as below:

$$\tilde{P}_u = \sum_{i=1}^M \beta_i \tilde{P}_u^i, \text{ and } \tilde{P}_v = \sum_{i=1}^M \gamma_i \tilde{P}_v^i,$$
(6)

where  $\beta_i$  and  $\gamma_i$  are the corresponding coefficients for  $\tilde{P}_u$  and  $\tilde{P}_v$ , respectively.

By using SVD, matrices  $U_l$  and  $V_l$  of the LR input face  $I_l$  can also be up-sampled via interpolation to produce two new matrices  $U'_l$  and  $V'_l$ , with the same size as  $U_h$  and  $V_h$  for the reconstructed HR face  $I_h$ , respectively. Now, the approximated matrices  $\hat{U}_h$  and  $\hat{V}_h$  can be calculated as follows:

$$\hat{U}_h = U_l' \tilde{P}_u$$
, and  $\hat{V}_h = V_l' \tilde{P}_v$ . (7)

Since the leading singular values in the diagonal matrix  $\hat{W}_h$  can be obtained from a linear relationship  $s_h \cong \alpha s_l$  [17,18], the HR face  $\hat{l}_h$  can be generated using the computed matrices  $\hat{U}_h$  and  $\hat{V}_h$ , and its diagonal matrix  $\hat{W}_h$ , as below:

$$\hat{l}_h = \hat{U}_h \hat{W}_h \hat{V}_h^T. \tag{8}$$

The following E(i) can be utilized to measure the hallucination error, and the optimal hallucinating weights  $\beta_i$  and  $\gamma_i$  can be solved by minimizing the following convex function [17]:

$$\varsigma = \underset{\beta_{i}, \quad \gamma_{i}}{\operatorname{argmin}} \left\{ E(i) \right\} = \underset{\beta_{i}, \quad \gamma_{i}}{\operatorname{argmin}} \left\{ \sum_{i=1}^{M} \left\| I_{h}^{i} - \hat{I}_{h} \right\|^{2} \right\}, \quad \text{s.t.} \quad \hat{I}_{h} \downarrow \alpha = I_{l}. \tag{9}$$

#### 3. Multi-view face hallucination (MFH) design

Assuming that an input LR face  $I_{z, l}$  at view z; z denotes multi-view face images. MFH aims to hallucinate the desired HR faces from  $I_z$ . These M pairs of HR and LR training faces are represented as  $I_{z, l}^i$  and  $I_{z, h}^i$  (i = 1, ..., M), respectively. The linear combination of the corresponding mapping matrices calculated from the M pairs of HR and LR faces at view z, can be obtained as same as in (6):

$$\tilde{P}_{z,u} = \sum_{i=1}^{M} \beta_{z,i} \tilde{P}_{z,u}^{i}, \text{ and } \tilde{P}_{z,v} = \sum_{i=1}^{M} \gamma_{z,i} \tilde{P}_{z,v}^{i}.$$
(10)

From (10), we can see that HR facel<sub>z, h</sub> at view z can be constructed if the weights  $\beta_{z,i}$  and  $\gamma_{z,i}$  are procured. In practice, they are difficult to be procured precisely [31,47]. Inspired by [31], we assume that there exists approximately same linear mapping relationship across different multiple views. Therefore, the weights obtained at the face view z' (e.g. frontal view) in (6) are used to generate two new matrices, and rewrite (10) as follows:

$$\tilde{P}_{z,u} = \sum_{i=1}^{M} \beta_i \tilde{P}_{z,u}^i$$
, and  $\tilde{P}_{z,v} = \sum_{i=1}^{M} \gamma_i \tilde{P}_{z,v}^i$ . (11)

With the aid of linear combination of training faces at view *z* in Eq. (11), we can then hallucinate LR image from one view to multi-view points. Fig. 1 shows the proposed MFH framework. For clarity, the proposed scheme for multi-view face hallucination scheme is summarized as Algorithm 1.




Fig. 1. The proposed MFH framework based on SVD and a Mapping Model.

#### 4. Experimental results

All facial images were aligned based upon the position of the two eyes, and the LR images were down-sampled and the reconstruction was run from these downgraded images. Each of the testing facial images was assessed using the "leave-one-out" method.

#### 4.1. Experiment 1

To evaluate the validity of our proposed method, five poses at  $-22.5^{\circ}$ ,  $22.5^{\circ}$ ,  $0^{\circ}$  (frontal view),  $-45^{\circ}$ , and  $45^{\circ}$  are utilized to verify the performance of the proposed algorithm. The CMU database contains  $68 \times 5$  images, each of the face images is aligned using the location of the two eyes, and every original HR face is cropped into a size with  $108 \times 124$  pixels. The parameter  $\lambda$  in (3) is experimentally set at 0.001. And the reference number of face examples is set with 3. In the Multi-view face hallucination (MFH) experiments, all the algorithms are tested by hallucinating the HR faces with a magnification factor of  $\alpha = 4$ . Two widely used image quality assessments, PSNR (peak signal-to-noise ratio) and SSIM (structural similarity) [42], are utilized to assess the performance of individual MFH approach.

Fig. 2 shows some samples of the multi-view face hallucination results produced using different MFH approaches. It can be seen from Fig. 2(a) that Jia's method [16] generates blurry results as compared to the ground truth faces in Fig. 2(d). The results of Ma's algorithm [31] in Fig. 2(b) generate a slight better visual quality than Jia's method. Fig. 2(c) gives the hallucinated faces based on Jin's method [23], while Fig. 2(d) shows the results of multi-view face super resolution according to Deshmukh's algorithm [6]. Figs. 2(e) are the results produced by using our proposed method, which can effectively hallucinate the fine individual facial details, and can generate sharp edges and corners (e.g. eye regions).

Table 1 provides the PSNR and SSIM of three different multi-view face hallucination methods. As shown in Table 1, our algorithm outperforms other existing state-of-the-art multi-view face hallucination approaches. In addition, as a commonly known assessment quantity, PSNR is not always well consistent with human visual perception. Therefore we provide a curve of SSIM of each CMU individuals in detail. Fig. 3 illustrates the curve of SSIM across all CMU faces for different MFH algorithms with a magnification factor of 4. According to the curve of SSIM, it can be seen that the proposed algorithm can achieve a better performance statistically.



**Fig. 2.** MFH results hallucinated using different methods with a magnification factor of 4 ( $\alpha$ =4): (a) Jia's method [16], (b) Ma's method [31], (c) Jin's method [23], (d) Deshmukh's method [6], (e) our proposed method, (c) Ground truth image.

**Table 1**The average PSNR and SSIM of different MFH algorithms.

Algorithms		Jia's method	Ma's method	Jin's method	Deshmukh's method	Our method
Left 45° to Frontal	PSNR	21.5601	21.6002	21.6213	21.5918	21.6367
	SSIM	0.5525	0.5543	0.5592	0.5564	0.5614
Left 22.5° to Frontal	PSNR	21.9729	22.2119	22.3419	22.2405	22.4702
	SSIM	0.5577	0.5585	0.5680	0.5576	0.5725
Right 22.5° to Frontal	PSNR	21.9820	21.6705	22.3893	22.0166	22.5822
	SSIM	0.5606	0.5633	0.5687	0.5632	0.5775
Right 45° to Frontal	PSNR	21.4006	21.6292	22.3571	22.0047	22.6726
	SSIM	0.5449	0.5557	0.5635	0.5603	0.5708

#### Algorithm 1 Multi-view face hallucination Using SVD and a mapping mode.

- 1. Input: an LR face  $I_{z,l}$  at view z (z denotes multi-view face images).
- 2. Construct M pairs of LR-HR training faces, denoted as  $I_{z,l}^i$  and  $I_{z,h}^i$  (i = 1, 2, ..., M). M LR face images resembling  $I_{z,l}$ , also with the corresponding HR faces, are retrieved.
- 3. Compute the M mapping matrices of each single LR-HR training pairs, according to Eq. (5).
- 4. With the aid of the face view z' (e.g. frontal view), calculate the linear combination of the mapping matrices according to Eq. (6) and compute the approximated matrices  $\hat{U}_h$  and  $\hat{V}_h$  according to Eq. (7), respectively.
- 5. Use Eqs. (8) and (9) to calculate hallucinating weights  $\beta_i$  and  $\gamma_i$  at the face view z'.
- 6. Update  $\beta_{z,i}$  and  $\gamma_{z,i}$  using  $\beta_i$  and  $\gamma_i$ ; compute the combination of the corresponding mapping matrices of HR and LR faces at view z, according to Eq. (11).
- 7. Hallucinate LR image from one view to multi-view using SVD according to Eq. (8)
- 8. Output: HR face  $I_{z,h}$  at view z.




Fig. 3. SSIM curve across all the CMU faces for different MFH algorithms with a magnification factor of 4.

### 4.2. Experiment 2

In reality, we often confronted with parts of the face including chin, particle ears, hair and facial contour line, and were concurrent with other poses of looking down and looking up, which can be seen as faces rotated along the z-axis in Euclidian space (with yaw degrees). Therefore, our algorithm is still suitable for this situation and valid in this practical application. Note that, compared to the faces rotated along the y-axis in Euclidian space (with tilt degrees), it's a much more challenging issue right now. To our best knowledge, the database specially designed for multi-view faces is not publicly available currently. Therefore, it's hard to provide the related performance. However, in order to further evaluate the effectiveness and robustness of our method, we have included one more widely used face dataset, i.e. the FERET face database [36]. In this experiment, 70 individuals are randomly selected form the FERET face database, i.e. there are  $70 \times 5$  images. Each of the face is also aligned using the location of the two eyes, and all original HR facial images are cropped to a size of  $80 \times 80$ . In detail, for each individual, faces of five poses from the cropped FERET face database with parts of the face including chin, particle ears, hair and facial contour line, are contained and performed. Two typical examples are shown in Fig 4.

Fig. 5 illustrates the curve of SSIM of every testing faces for different MFH methods with a magnification factor of 4, respectively. From Fig. 5 we can see that the proposed method, compared with other typical state-of-the-art approaches, can produce plausible and promising results.



**Fig. 4.** Cropped faces of two different subjects with five poses from the FERET face database. From left to right: assigned as  $-45^{\circ}$ ,  $-22.5^{\circ}$ ,  $0^{\circ}$  (frontal view),  $22.5^{\circ}$ , and  $45^{\circ}$  in the experiment.




Fig. 5. SSIM curve across all the 70 FERET faces for different MFH algorithms with a magnification factor of 4.

#### 5. Conclusion and discussion

In this communication, we have proposed a novel MFH method for the hallucination of LR face images. Based on the assumption that the linear mapping manifold across various facial views is similar, two corresponding matrices generated by SVD of the LR face for the HR multi-view face images can be estimated. Thereby, the proposed scheme can hallucinate the holistic pattern and subtle structure of faces. And contrasted with typical state-of-the-art MFH methods, experimental results have shown that the proposed algorithm can generate HR faces with high-frequency details.

In the future, we will investigate a more challenging MFH issue with larger multi-view angles and sub-region occlusion with the aid of 3D face reconstruction.

#### Acknowledgments

We would like to thank Ph.D Zhuo Hui in the Department of Electrical and Computer Engineering, Carnegie Mellon University (CMU) for providing the cropped database.

This work was supported by National Natural Science Foundation of China (NSFC) (61601427, 61602229, 61771230); Royal Society – K. C. Wong International Fellow; Natural Science Foundation of Shandong Province (ZR2016FM40); Shandong Provincial Key Research and Development Program of China (NO. 2017CXGC0701); Fostering Project of Dominant Discipline and Talent Team of Shandong Province Higher Education Institutions.

#### References

- [1] A. Akyol, M. Gokmen, Super-resolution reconstruction of faces by enhanced global models of shape and texture original, Pattern Recognit. vol. 45 (12) (2012) 4103-4116.
- [2] O. Arandjelović, A manifold approach to face recognition from low quality video across illumination and pose using implicit super-resolution, in: IEEE ICCV, 2007, pp. 1049-1057.
- [3] O. Arandjelović, Hallucinating optimal high-dimensional subspaces, Pattern Recognit. vol. 47 (8) (2014) 2662-2672.
- [4] S. Baker, T. Kanade, Hallucinating faces, in: Proceedings of the IEEE International Conference on AFGR, 2000, pp. 83–88.
- [5] Y. Chen, Y. Tai, X. Liu, C. Shen, J. Yang, FSRNet: end-to-end learning face super-resolution with facial priors, in: IEEE CVPR, 2018, pp. 2492-2501.
- [6] A.B. Deshmukh, U. Rani, Fractional-Grey Wolf optimizer-based kernel weighted regression model for multi-view face video super resolution, Int. J. Mach. Learn. Cybern., pp. 1-19, First Online: 23 December 2017. https://doi.org/10.1007/s13042-017-0765-6.
- C. Dong, C. Loy, K. He, X. Tang, Image super-resolution using deep convolutional networks, IEEE Trans. Pattern Anal. Mach. Intell. vol. 38 (2) (2016) 295-307
- [8] R. Farrugia, C. Guillemot, Face hallucination using linear models of coupled sparse support, IEEE Trans. Image Process. vol. 26 (9) (2017) 4562-4577.
- [9] S.S. Farfade, M.J. Saberian, L. Li, Multi-view face detection using deep convolutional neural networks, in: Proceedings of the 5th ACM on International Conference on Multimedia Retrieval, 2015, pp. 643-650.
- [10] Y. Geng, G. Zhang, W. Li, Y. Gu, R. Liang, G. Liang, J. Wang, Y. Wu, N. Patil, J. Wang, A novel image tag completion method based on convolutional neural transformation, in: International Conference on Artificial Neural Networks, 2017, pp. 539-546, doi:10.1007/978-3-319-68612-7\_61
- [11] I. Goodfellow, J. Pougetabadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, Y. Bengio, Generative adversarial nets, Adv. Neural Inf. Process. Syst. (NIPS 2014), pp. 2672-2680.
- [12] B. Huang, W. Chen, X. Wu, C. Lin, et al., High-quality face image super-resolution using conditional generative adversarial networks, Pattern Recognit. Lett. vol. 111 (2018) 72-79.
- Y. Hu, K.M. Lam, G. Qiu, T. Shen, From local pixel structure to global image super-resolution: a new face hallucination framework, IEEE Trans. Image Process, vol. 20 (2) (2011) 433-445.
- [14] Z. Hui, K.M. Lam, Two-Stage patch-based multi-view face super-resolution, in: Proceedings, Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC'2011), paper Thu-PM.PS1, Xi'an, China, October 2011.
- [15] Z. Hui, K.M. Lam, Multi-view face hallucination based on sparse representation, in: Proceedings, IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP'2013), May 2013, pp. 2202-2206.
- [16] K. Jia, S.G. Gong, Generalized face super-resolution, IEEE Trans, Image Process, vol. 17 (6) (Jun. 2008) 873–886.
- [17] M. Jian, K.M. Lam, J. Dong, A novel face-hallucination scheme based on singular value decomposition, Pattern Recognit. vol. 46 (11) (2013) 3091-3102.
- [18] M. Jian, K.M. Lam, Face-Image Retrieval based on singular values and potential-field representation, Signal Process. vol. 100 (2014) 9-15.
- [19] J. Jiang, R. Hu, Z. Wang, Z. Han, Face super-resolution via multilayer locality-constrained iterative neighbor embedding and intermediate dictionary learning, IEEE Trans. Image Process vol. 23 (10) (2014) 4220–4231.
- [20] J. Jiang, R. Hu, Z. Wang, Z. Han, Face image super-resolution through locality-induced support regression, Signal Process. vol. 103 (2014) 168-183.
- [21] J. Jiang, J. Ma, S. Tang, Y. Yu, K. Aizawa, Face hallucination through differential evolution parameter map learning with facial structure prior, Inf. Sci. vol. 481 (2019) 174-188.
- [22] J. Jiang, Y. Yu, S. Tang, J. Ma, A. Aizawa, K. Aizawa, Context-patch based face hallucination via thresholding locality-constrained representation and reproducing learning, IEEE Trans. Cybern. (2018) 1–14, doi:10.1109/TCYB.2018.2868891.
- Y. Jin, C.S. Bouganis, Robust multi-image based blind face hallucination, in: IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2015, pp. 5252-5260.
- [24] R.S. Kute, V. Vyas, A. Anuse, Component-based face recognition under transfer learning for forensic applications, Inf. Sci. vol. 476 (2019) 176-191.
- [25] B. Li, H. Chang, Aligning coupled manifolds for face hallucination, IEEE Signal Process, Lett. vol. 16 (11) (Nov. 2009) 957–960.
- [26] C. Liu, H.Y. Shum, C.S. Zhang, Face Hallucination: theory and Practice, IJCV vol. 75 (1) (2007) 115–134.
  [27] H. Li, L. Xu, G. Liu, Face Hallucination via Similarity Constraints, IEEE Signal Process. Lett. vol. 20 (1) (2013) 19–22.
- [28] Y. Li, X.Y. Lin, Face hallucination with pose variation, in: Pro. 6th IEEE Int. Conf. on AFGR, 2004, pp. 723–728.
- [29] L. Liu, C.L.P. Chen, S. Li, Y.Y. Tang, L. Chen, Robust Face Hallucination via Locality-Constrained Bi-Layer Representation, IEEE Trans. Cybern. vol. 48 (4) (2018) 1189-1201.
- [30] Y. Long, F. Zhu, L. Shao, J. Han, Face recognition with a small occluded training set using spatial and statistical pooling, Inf. Sci. vol. 430 (2018) 634-644.
- [31] X. Ma, H. Huang, S. Wang, C. Qi, A simple approach to multiview face hallucination, IEEE Signal Process. Lett. vol. 17 (2010) 579-582.
- [32] X. Ma, J. Zhang, C. Qi, Hallucinating face by position-patch, Pattern Recognit. vol. 43 (2010) 2224–2236.
  [33] X. Min, G. Zhai, K. Gu, J. Liu, S. Wang, X. Zhang, X. Yang, Visual attention analysis and prediction on human faces, Inf. Sci. vol. 420 (2017) 417–430.
- [34] O. Oktay, et al., Multi-input Cardiac Image Super-Resolution Using Convolutional Neural Networks, in: International Conference on Medical Image Computing and Computer-Assisted Intervention, 2016, pp. 246-254.
- [35] J.S. Park, S.W. Lee, An example-based face hallucination method for single-frame, low-resolution facial images, IEEE Trans. Image Process. vol. 17 (10) (2008) 1806-1816.
- [36] P.J. Phillips, H. Wechsler, J. Huang, P. Rauss, The FERET database and evaluation procedure for face-recognition algorithms, Image Vision Comput. vol. 16 (1998) 295-306.
- J. Shi, X. Liu, Y. Zong, C. Qi, G. Zhao, Hallucinating Face Image by Regularization Models in High-Resolution Feature Space, IEEE Trans. Image Process. vol. 27 (6) (2018) 2980-2995
- [38] L. Song, M. Zhang, X. Wu, R. He. Adversarial Discriminative Heterogeneous Face Recognition, AAAI-2018. https://arxiv.org/pdf/1709.03675.
- [39] J. Tian, K. Ma, A survey on super-resolution imaging, Signal, Image Video Process. vol. 5 (3) (2011) 329-342.
- [40] D. Vo, S. Lee, Robust face recognition via hierarchical collaborative representation, Inf. Sci. vol. 432 (2018) 332-346.
- [41] X. Wang, X. Tang, Hallucinating face by eigentransformation, IEEE Trans. Syst., Man, Cybern. C, Appl. Rev vol. 35 (3) (2005) 425-434.
- [42] Z. Wang, et al. Image quality assessment: from error measurement to structural similarity, IEEE Trans. Image Process., 13, (4), 2004
- [43] J. Yang, J. Wright, T. Huang, Y. Ma, Image super-resolution via sparse representation, IEEE Trans. Image Process. vol. 19 (11) (2010) 2861–2873.
- [44] X. Yu, F.M. Porikli, Ultra-Resolving Face Images by Discriminative Generative Networks, in: European Conference on Computer Vision, 2016, pp. 318-333.
- [45] L. Yue, H. Shen, J. Li, O. Yuan, H. Zhang, L. Zhang, Image super-resolution: the techniques, applications, and future, Signal Process, vol. 128 (2016) 389-408.
- [46] G. Zhang, G. Liang, W. Li, J. Fang, J. Wang, Y. Geng, J. Wang, Learning Convolutional Ranking-Score Function by Query Preference Regularization, in: International Conference on Intelligent Data Engineering and Automated Learning, 2017, pp. 1-8, doi:10.1007/978-3-319-68935-7\_1.
- [47] X. Zeng, H. Huang, Super-resolution Method For Multi-view Face Recognition From a Single Image Per Person Using Nonlinear Mappings on Coherent Features, IEEE Signal Process. Lett. vol. 19 (4) (2012) 195-198.
- [48] Z. Zhu, et al., Multi-view perceptron: a deep model for learning face identity and view representations, Adv. Neural Inf. Process. Syst. vol. 1 (2014) 217 - 225.
- [49] Y. Zhuang, J. Zhang, F. Wu, Hallucinating faces: LPH super-resolution and neighbor reconstruction for residue compensation, Pattern Recognit. vol. 40 (11) (2007) 3178-3194.



Muwei Jian received the PhD degree from the Department of Electronic and Information Engineering, The Hong Kong Polytechnic University, in October 2014. He was a Lecturer with the Department of Computer Science and Technology, Ocean University of China, from 2015 to 2017. Currently, Dr. Jian is a Professor and Ph.D Supervisor at the School of Computer Science and Technology, Shandong University of Finance and Economics. His current research interests include human face recognition, image and video processing, machine learning and computer vision. Prof. Jian was actively involved in professional activities. He has been a member of the Program Committee and Special Session Chair of several international conferences, such as SNPD 2007, ICIS 2008, APSIPA 2015, EEECS 2016, ICTAl2016, ICGIP 2016 and ICTAl 2017. Dr. Jian has also served as a reviewer for several international SCI-indexed journals, including IEEE Trans., Pattern Recognition, Information Sciences, Computers in Industry, Machine Vision and Applications, Machine Learning and Cybernetics, The Imaging Science Journal, and Multimedia Tools and Applications. Prof. Jian holds 3 granted national patents and has published over 40 papers in refereed international leading journals/conferences such as IEEE Trans. on Cybernetics, IEEE Trans. on Circuits and Systems for Video Technology, Pattern Recognition, Information Sciences, Signal Processing, ISCAS, ICME and ICIP.



**Chaoran Cui** received the B.S. degree in Software Engineering in 2010 and the Ph.D. degree in Computer Science and Technology in 2015, both from Shandong University, Jinan, China. During 2015–2016, he was a research fellow at Singapore Management University. He is now a Professor in School of Computer Science and Technology at Shandong University of Finance and Economics. His research interests include information retrieval, analysis and understanding on multimedia information, and computer vision.



**Xiushan Nie** received the Ph.D. degree from Shandong University, Shandong, China, in 2011. He is currently a Professor with Shandong University of Finance and Economics, Shandong, China. From 2013 to 2014, he was a Visiting Scholar with the University of Missouri-Columbia, Columbia, MO,USA. His research interests include multimedia retrieval and indexing, multimedia security, and computer vision.



**Huaxiang Zhang** is currently a professor with the School of Information Science and Engineering & the Institute of Data Science and Technology, Shandong Normal University, China. He received his Ph.D. from Shanghai Jiaotong University in 2004, and worked as an associated professor with the Department of Computer Science, Shandong Normal University from 2004 to 2005. He has authored over 180 journal and conference papers and holds13 granted national patents. His current research interests include machine learning, pattern recognition, evolutionary computation, cross-media retrieval, web information processing, big data analysis, etc.



**Liqiang Nie** is currently a professor with the School of Computer Science and Technology, Shandong University. He received his B.Eng. and Ph.D. degree from Xi'an Jiaotong University in July 2009 and National University of Singapore (NUS) in 2013, respectively. After PhD, Dr. Nie continued his research in NUS as a research follow for more than three years. His research interests lie primarily in information retrieval, multimedia computing and their applications in the field of healthcare. Dr. Nie has co-authored around 100 papers. Thereinto, 70 papers are in the CCF-A venues or IEEE/ACM Trans series including SIGIR, ACM MM, TOIS and TMM. He is an Associate Editor of Information Sciences, an area chair of ACM MM 2018, and a PC chair of ICIMCS 2017. Meanwhile, he is supported by the program of "Thousand Youth Talents Plan 2016".



Yilong Yin received the Ph.D. degree from Jilin University, Changchun, China, in 2000. From 2000 to 2002, he was a Post-Doctoral Fellow with the Department of Electronics Science and Engineering, Nanjing University, Nanjing, China. He is currently the Director of the Data Mining, Machine Learning, and their Applications Group and a Professor of the School of Software Engineering, Shandong University, Jinan, China. His research interests include machine learning, data mining, and computational medicine.