

streamout

Generated by Doxygen 1.9.3

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	1
2.1 Class List	1
3 File Index	2
3.1 File List	2
4 Class Documentation	4
4.1 Buffer Class Reference	4
4.1.1 Detailed Description	4
4.1.2 Constructor & Destructor Documentation	4
4.1.3 Member Function Documentation	5
4.2 BufferLooper< SOURCE, DESTINATION > Class Template Reference	7
4.2.1 Detailed Description	7
4.2.2 Constructor & Destructor Documentation	7
4.2.3 Member Function Documentation	8
4.3 BufferLooperCounter Struct Reference	11
4.3.1 Detailed Description	11
4.3.2 Member Function Documentation	11
4.3.3 Member Data Documentation	12
4.4 DIF Class Reference	13
4.4.1 Detailed Description	14
4.4.2 Member Function Documentation	14
4.5 DIFPtr Class Reference	16
4.5.1 Detailed Description	17
4.6 DIFSlowControl Class Reference	19
4.6.1 Detailed Description	20
4.6.2 Constructor & Destructor Documentation	20
4.6.3 Member Function Documentation	20
4.7 Event Class Reference	22
4.7.1 Detailed Description	22
4.7.2 Member Function Documentation	22
4.8 Exception Class Reference	23
4.8.1 Detailed Description	23
4.8.2 Constructor & Destructor Documentation	23
4.8.3 Member Function Documentation	24
4.9 Hit Class Reference	24
4.9.1 Detailed Description	25
4.9.2 Member Function Documentation	25
4.10 Interface Class Reference	28
4.10.1 Detailed Description	29

4.10.2 Constructor & Destructor Documentation	29
4.10.3 Member Function Documentation	29
4.11 InterfaceReader Class Reference	31
4.11.1 Detailed Description	32
4.11.2 Constructor & Destructor Documentation	32
4.11.3 Member Data Documentation	32
4.12 InterfaceWriter Class Reference	33
4.12.1 Detailed Description	33
4.12.2 Constructor & Destructor Documentation	33
4.12.3 Member Function Documentation	33
4.13 PayloadParser Class Reference	34
4.13.1 Detailed Description	35
4.13.2 Constructor & Destructor Documentation	35
4.13.3 Member Function Documentation	35
4.14 RawBufferNavigator Class Reference	40
4.14.1 Detailed Description	40
4.14.2 Constructor & Destructor Documentation	41
4.14.3 Member Function Documentation	41
4.15 RawdataReader Class Reference	42
4.15.1 Detailed Description	43
4.15.2 Constructor & Destructor Documentation	43
4.15.3 Member Function Documentation	43
4.16 ROOTWriter Class Reference	46
4.16.1 Detailed Description	46
4.16.2 Constructor & Destructor Documentation	46
4.16.3 Member Function Documentation	46
4.17 textDump Class Reference	50
4.17.1 Detailed Description	50
4.17.2 Constructor & Destructor Documentation	50
4.17.3 Member Function Documentation	50
4.18 Timer Class Reference	52
4.18.1 Detailed Description	52
4.18.2 Member Function Documentation	52
4.19 Version Class Reference	53
4.19.1 Detailed Description	53
4.19.2 Constructor & Destructor Documentation	53
4.19.3 Member Function Documentation	54
5 File Documentation	55
5.1 libs/core/include/Bits.h File Reference	55
5.1.1 Detailed Description	55
5.1.2 Typedef Documentation	55

5.1.3 Function Documentation	56
5.2 Bits.h	56
5.3 libs/core/include/Buffer.h File Reference	56
5.3.1 Detailed Description	57
5.4 Buffer.h	57
5.5 libs/core/include/BufferLooper.h File Reference	58
5.5.1 Detailed Description	58
5.6 BufferLooper.h	58
5.7 libs/core/include/BufferLooperCounter.h File Reference	61
5.7.1 Detailed Description	62
5.8 BufferLooperCounter.h	62
5.9 libs/core/include/DetectorId.h File Reference	62
5.9.1 Detailed Description	62
5.9.2 Enumeration Type Documentation	62
5.10 DetectorId.h	63
5.11 libs/core/include/DIFSlowControl.h File Reference	63
5.11.1 Detailed Description	63
5.11.2 Function Documentation	64
5.12 DIFSlowControl.h	64
5.13 libs/core/include/Exception.h File Reference	65
5.13.1 Detailed Description	65
5.14 Exception.h	65
5.15 libs/core/include/FileSystem.h File Reference	66
5.15.1 Detailed Description	66
5.15.2 Function Documentation	66
5.16 FileSystem.h	67
5.17 libs/core/include/Formatters.h File Reference	67
5.17.1 Detailed Description	67
5.17.2 Function Documentation	67
5.18 Formatters.h	71
5.19 libs/core/include/Interface.h File Reference	71
5.19.1 Detailed Description	72
5.19.2 Enumeration Type Documentation	72
5.20 Interface.h	73
5.21 libs/core/include/PayloadParser.h File Reference	74
5.21.1 Detailed Description	74
5.22 PayloadParser.h	74
5.23 libs/core/include/RawBufferNavigator.h File Reference	78
5.23.1 Detailed Description	78
5.24 RawBufferNavigator.h	78
5.25 libs/core/include/Timer.h File Reference	79
5.25.1 Detailed Description	79

5.26 Timer.h	79
5.27 libs/core/include/Utilities.h File Reference	79
5.27.1 Detailed Description	79
5.27.2 Function Documentation	80
5.28 Utilities.h	80
5.29 libs/core/include/Version.h File Reference	80
5.29.1 Detailed Description	80
5.30 Version.h	81
5.31 libs/core/include/Words.h File Reference	81
5.31.1 Detailed Description	81
5.31.2 Enumeration Type Documentation	82
5.32 Words.h	84
5.33 libs/core/src/Bits.cc File Reference	85
5.33.1 Detailed Description	85
5.33.2 Function Documentation	85
5.34 Bits.cc	85
5.35 libs/core/src/BufferLooperCounter.cc File Reference	85
5.36 BufferLooperCounter.cc	86
5.37 libs/core/src/DIFSlowControl.cc File Reference	86
5.37.1 Detailed Description	86
5.37.2 Function Documentation	87
5.38 DIFSlowControl.cc	87
5.39 libs/core/src/FileSystem.cc File Reference	90
5.39.1 Detailed Description	90
5.39.2 Function Documentation	90
5.40 FileSystem.cc	91
5.41 libs/core/src/Formatters.cc File Reference	91
5.41.1 Detailed Description	92
5.41.2 Function Documentation	92
5.42 Formatters.cc	96
5.43 libs/core/src/RawBufferNavigator.cc File Reference	97
5.43.1 Detailed Description	97
5.44 RawBufferNavigator.cc	97
5.45 libs/core/src/Version.cc File Reference	98
5.45.1 Detailed Description	98
5.46 Version.cc	98
5.47 libs/interface/Dump/include/textDump.h File Reference	99
5.47.1 Detailed Description	99
5.48 textDump.h	99
5.49 libs/interface/Dump/src/textDump.cc File Reference	100
5.49.1 Detailed Description	100
5.50 textDump.cc	100

5.51	libs/interface/LCIO/include/LCIOWriter.h File Reference	100
5.51.1	Detailed Description	100
5.52	LCIOWriter.h	101
5.53	libs/interface/LCIO/src/LCIOWriter.cc File Reference	101
5.53.1	Detailed Description	101
5.54	LCIOWriter.cc	101
5.55	libs/interface/RawDataReader/include/RawdataReader.h File Reference	101
5.55.1	Detailed Description	101
5.56	RawdataReader.h	102
5.57	libs/interface/RawDataReader/src/RawdataReader.cc File Reference	102
5.57.1	Detailed Description	102
5.58	RawdataReader.cc	103
5.59	libs/interface/ROOT/include/DIF.h File Reference	104
5.59.1	Detailed Description	104
5.59.2	Typedef Documentation	105
5.60	DIF.h	105
5.61	libs/interface/ROOT/include/DIFLinkDef.h File Reference	105
5.61.1	Detailed Description	105
5.62	DIFLinkDef.h	106
5.63	libs/interface/ROOT/include/Event.h File Reference	106
5.63.1	Detailed Description	106
5.63.2	Typedef Documentation	106
5.64	Event.h	107
5.65	libs/interface/ROOT/include/EventLinkDef.h File Reference	107
5.65.1	Detailed Description	107
5.66	EventLinkDef.h	107
5.67	libs/interface/ROOT/include/Hit.h File Reference	107
5.67.1	Detailed Description	108
5.68	Hit.h	108
5.69	libs/interface/ROOT/include/HitLinkDef.h File Reference	108
5.69.1	Detailed Description	108
5.70	HitLinkDef.h	109
5.71	libs/interface/ROOT/include/ROOTWriter.h File Reference	109
5.72	ROOTWriter.h	109
5.73	libs/interface/ROOT/src/DIF.cc File Reference	110
5.73.1	Detailed Description	110
5.74	DIF.cc	110
5.75	libs/interface/ROOT/src/Event.cc File Reference	110
5.75.1	Detailed Description	110
5.76	Event.cc	111
5.77	libs/interface/ROOT/src/Hit.cc File Reference	111
5.77.1	Detailed Description	111

5.78 Hit.cc	111
5.79 libs/interface/ROOT/src/ROOTWriter.cc File Reference	112
5.79.1 Detailed Description	112
5.80 ROOTWriter.cc	112

1 Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Buffer	4
PayloadParser	34
BufferLooper< SOURCE, DESTINATION >	7
BufferLooperCounter	11
DIFPtr	16
DIFSlowControl	19
Exception	23
Interface	28
InterfaceReader	31
RawdataReader	42
InterfaceWriter	33
ROOTWriter	46
textDump	50
RawBufferNavigator	40
Timer	52
TObject	
DIF	13
Event	22
Hit	24
semver::version	
Version	53

2 Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Buffer	4
BufferLooper< SOURCE, DESTINATION >	7
BufferLooperCounter	11
DIF	13
DIFPtr	
M3 MICROROC and HARDROC2 dataformat	16
DIFSlowControl	19
Event	22
Exception	23
Hit	24
Interface	28
InterfaceReader	31
InterfaceWriter	33
PayloadParser	34
RawBufferNavigator	
Class to navigate in the raw data buffer parse the header and send the payload as Buffer	40
RawdataReader	42
ROOTWriter	46
textDump	50
Timer	52
Version	53

3 File Index

3.1 File List

Here is a list of all files with brief descriptions:

libs/core/include/Bits.h	55
libs/core/include/Buffer.h	56
libs/core/include/BufferLooper.h	58
libs/core/include/BufferLooperCounter.h	61
libs/core/include/DetectorId.h	62
libs/core/include/DIFSlowControl.h	63
libs/core/include/Exception.h	65


libs/core/include/FileSystem.h	66
libs/core/include/Formatters.h	67
libs/core/include/Interface.h	71
libs/core/include/PayloadParser.h	74
libs/core/include/RawBufferNavigator.h	78
libs/core/include/Timer.h	79
libs/core/include/Utilities.h	79
libs/core/include/Version.h	80
libs/core/include/Words.h	81
libs/core/src/Bits.cc	85
libs/core/src/BufferLooperCounter.cc	85
libs/core/src/DIFSlowControl.cc	86
libs/core/src/FileSystem.cc	90
libs/core/src/Formatters.cc	91
libs/core/src/RawBufferNavigator.cc	97
libs/core/src/Version.cc	98
libs/interface/Dump/include/textDump.h	99
libs/interface/Dump/src/textDump.cc	100
libs/interface/LCIO/include/LCIOWriter.h	100
libs/interface/LCIO/src/LCIOWriter.cc	101
libs/interface/RawDataReader/include/RawdataReader.h	101
libs/interface/RawDataReader/src/RawdataReader.cc	102
libs/interface/ROOT/include/DIF.h	104
libs/interface/ROOT/include/DIFLinkDef.h	105
libs/interface/ROOT/include/Event.h	106
libs/interface/ROOT/include/EventLinkDef.h	107
libs/interface/ROOT/include/Hit.h	107
libs/interface/ROOT/include/HitLinkDef.h	108
libs/interface/ROOT/include/ROOTWriter.h	109
libs/interface/ROOT/src/DIF.cc	110
libs/interface/ROOT/src/Event.cc	110
libs/interface/ROOT/src/Hit.cc	111

4 Class Documentation

4.1 Buffer Class Reference

```
#include <libs/core/include/Buffer.h>
```

Inheritance diagram for Buffer:



Public Member Functions

- [Buffer](#) ()
- virtual [~Buffer](#) ()
- [Buffer](#) (const [bit8_t](#) b[], const std::size_t &i)
- [Buffer](#) (const char b[], const std::size_t &i)
- template<typename T >
 [Buffer](#) (const std::vector< T > &rawdata)
- template<typename T, std::size_t N>
 [Buffer](#) (const std::array< T, N > &rawdata)
- std::size_t [size](#) () const
- std::size_t [capacity](#) () const
- bool [empty](#) ()
- void [set](#) (unsigned char *b)
- void [set](#) (const [Buffer](#) &buffer)
- [bit8_t](#) * [begin](#) () const
- [bit8_t](#) * [end](#) () const
- [bit8_t](#) & [operator\[\]](#) (const std::size_t &pos)
- [bit8_t](#) & [operator\[\]](#) (const std::size_t &pos) const
- void [setSize](#) (const std::size_t &size)

4.1.1 Detailed Description

Definition at line 14 of file [Buffer.h](#).

4.1.2 Constructor & Destructor Documentation

4.1.2.1 Buffer() [1/5] `Buffer::Buffer () [inline]`Definition at line 17 of file [Buffer.h](#).00017 : `m_Buffer(nullptr), m_Size(0), m_Capacity(0) {}`**4.1.2.2 ~Buffer()** `virtual Buffer::~~Buffer () [inline], [virtual]`Definition at line 18 of file [Buffer.h](#).

00018 {}

4.1.2.3 Buffer() [2/5] `Buffer::Buffer (`
`const bit8_t b[],`
`const std::size_t & i) [inline]`Definition at line 19 of file [Buffer.h](#).00019 : `m_Buffer(const_cast<bit8_t*>(&b[0])), m_Size(i), m_Capacity(i) {}`**4.1.2.4 Buffer()** [3/5] `Buffer::Buffer (`
`const char b[],`
`const std::size_t & i) [inline]`Definition at line 20 of file [Buffer.h](#).00020 : `m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const bit8_t*>(&b[0])), m_Size(i * sizeof(char)),`
`m_Capacity(i * sizeof(char)) {}`**4.1.2.5 Buffer()** [4/5] `template<typename T >`
`Buffer::Buffer (`
`const std::vector< T > & rawdata) [inline]`Definition at line 21 of file [Buffer.h](#).00021 : `m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const bit8_t*>(rawdata.data()))),`
`m_Size(rawdata.size() * sizeof(T)), m_Capacity(rawdata.capacity() * sizeof(T)) {}`**4.1.2.6 Buffer()** [5/5] `template<typename T , std::size_t N>`
`Buffer::Buffer (`
`const std::array< T, N > & rawdata) [inline]`Definition at line 22 of file [Buffer.h](#).00022 : `m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const bit8_t*>(rawdata.data()))),`
`m_Size(rawdata.size() * sizeof(T)), m_Capacity(rawdata.size() * sizeof(T)) {}`**4.1.3 Member Function Documentation**

4.1.3.1 `begin()` `bit8_t * Buffer::begin () const [inline]`

Definition at line 35 of file [Buffer.h](#).

```
00035 { return m_Buffer; }
```

4.1.3.2 `capacity()` `std::size_t Buffer::capacity () const [inline]`

Definition at line 25 of file [Buffer.h](#).

```
00025 { return m_Capacity; }
```

4.1.3.3 `empty()` `bool Buffer::empty () [inline]`

Definition at line 27 of file [Buffer.h](#).

```
00027 { return m_Size == 0; }
```

4.1.3.4 `end()` `bit8_t * Buffer::end () const [inline]`

Definition at line 36 of file [Buffer.h](#).

```
00036 { return m_Buffer + m_Size; }
```

4.1.3.5 `operator[]()` [1/2] `bit8_t & Buffer::operator[] (const std::size_t & pos) [inline]`

Definition at line 37 of file [Buffer.h](#).

```
00037 { return m_Buffer[pos]; }
```

4.1.3.6 `operator[]()` [2/2] `bit8_t & Buffer::operator[] (const std::size_t & pos) const [inline]`

Definition at line 38 of file [Buffer.h](#).

```
00038 { return m_Buffer[pos]; }
```

4.1.3.7 `set()` [1/2] `void Buffer::set (const Buffer & buffer) [inline]`

Definition at line 29 of file [Buffer.h](#).

```
00030 {  
00031     m_Buffer = buffer.begin();  
00032     m_Size   = buffer.size();  
00033     m_Capacity = buffer.capacity();  
00034 }
```

4.1.3.8 set() [2/2] void Buffer::set (
 unsigned char * b) [inline]

Definition at line 28 of file [Buffer.h](#).

```
00028 { m_Buffer = b; }
```

4.1.3.9 setSize() void Buffer::setSize (
 const std::size_t & size) [inline]

Definition at line 40 of file [Buffer.h](#).

```
00040 { m_Size = size; }
```

4.1.3.10 size() std::size_t Buffer::size () const [inline]

Definition at line 24 of file [Buffer.h](#).

```
00024 { return m_Size; }
```

The documentation for this class was generated from the following file:

- [libs/core/include/Buffer.h](#)

4.2 BufferLooper< SOURCE, DESTINATION > Class Template Reference

```
#include <libs/core/include/BufferLooper.h>
```

Public Member Functions

- [BufferLooper](#) (SOURCE &source, DESTINATION &dest, bool debug=false)
- void [addSink](#) (const spdlog::sink_ptr &sink, const spdlog::level::level_enum &level=spdlog::get_level())
- void [loop](#) (const std::uint32_t &m_NbrEventsToProcess=0)
- void [printAllCounters](#) ()
- std::shared_ptr< spdlog::logger > [log](#) ()
- void [setDetectorIDs](#) (const std::vector< [DetectorID](#) > &detectorIDs)

4.2.1 Detailed Description

```
template<typename SOURCE, typename DESTINATION>
class BufferLooper< SOURCE, DESTINATION >
```

Definition at line 28 of file [BufferLooper.h](#).

4.2.2 Constructor & Destructor Documentation

4.2.2.1 BufferLooper() `template<typename SOURCE , typename DESTINATION >`

```
BufferLooper< SOURCE, DESTINATION >::BufferLooper (
    SOURCE & source,
    DESTINATION & dest,
    bool debug = false ) [inline]
```

Definition at line 31 of file [BufferLooper.h](#).

```
00031                                     : m_Source(source),
    m_Destination(dest), m_Debug(debug)
00032 {
00033     m_Logger = spdlog::create<spdlog::sinks::null_sink_mt>("streamout");
00034     if(!spdlog::get("streamout")) { spdlog::register_logger(m_Logger); }
00035     m_Source.setLogger(m_Logger);
00036     m_Destination.setLogger(m_Logger);
00037 }
```

4.2.3 Member Function Documentation

4.2.3.1 addSink() `template<typename SOURCE , typename DESTINATION >`

```
void BufferLooper< SOURCE, DESTINATION >::addSink (
    const spdlog::sink_ptr & sink,
    const spdlog::level::level_enum & level = spdlog::get_level() ) [inline]
```

Definition at line 39 of file [BufferLooper.h](#).

```
00040 {
00041     sink->set_level(level);
00042     m_Sinks.push_back(sink);
00043     m_Logger = std::make_shared<spdlog::logger>("streamout", begin(m_Sinks), end(m_Sinks));
00044     m_Source.setLogger(m_Logger);
00045     m_Destination.setLogger(m_Logger);
00046 }
```

4.2.3.2 log() `template<typename SOURCE , typename DESTINATION >`

```
std::shared_ptr< spdlog::logger > BufferLooper< SOURCE, DESTINATION >::log ( ) [inline]
```

Definition at line 232 of file [BufferLooper.h](#).

```
00232 { return m_Logger; }
```

4.2.3.3 loop() `template<typename SOURCE , typename DESTINATION >`

```
void BufferLooper< SOURCE, DESTINATION >::loop (
    const std::uint32_t & m_NbrEventsToProcess = 0 ) [inline]
```

Definition at line 48 of file [BufferLooper.h](#).

```
00049 {
00050     // clang-format off
00051     fmt::print(fg(fmt::color::medium_orchid) | fmt::emphasis::bold,
00052         "\n"
00053         " SSSSSSSSSSSSSSS      tttt
00054         tttt\n"
00055         "SS:::::::::::::S  ttt::t
00056         ttt::t\n"
00057         "S::::SSSSS:::::S  t::::t
00058         t::::t\n"
00059         "S::::S      SSSSSS  t::::t
00060         t::::t\n"
00061         "S::::S      tttttt:::::tttttt  rrrrr  rrrrrrrrr  eeeeeeeeeee  aaaaaaaaaaaa
00062         mmmmmmm  mmmmmmm  oooooooooo  uuuuuu  uuuuuutttttt:::::tttttt\n"
```

```
00058 "S:::::S t:::::t r:::::r ee:::::ee a:::::a
mm:::::m m:::::mm oo:::::oo u::::u u::::ut:::::t\n"
00059 " S::::SSSS t:::::t r:::::r e:::::e eaaaaa:::::a
m:::::mm:::::mo:::::ou::::u u::::ut:::::t\n"
00060 " SS:::::SSSSStttttt:::::ttttt rr:::::rrrrr:::::re:::::e e:::::e a:::::a
m:::::t:::::mo:::::oo:::::ou::::u u::::utttttt:::::ttttt\n"
00061 " SSS:::::SS t:::::t r:::::r r:::::re:::::e eaaaaa:::::a
m:::::mmm:::::mm:::::mo:::::o o:::::ou::::u u::::u t:::::t\n"
00062 " SSSSS:::S t:::::t r:::::r rrrrrrre:::::e aa:::::a m:::::m
m:::::m m:::::mo:::::o o:::::ou::::u u::::u t:::::t\n"
00063 " S:::::S t:::::t r:::::r e:::::e eeeeeee a:::::aaaa:::::a m:::::m
m:::::m m:::::mo:::::o o:::::ou::::u u::::u t:::::t\n"
00064 " S:::::S t:::::t ttttttr:::::r e:::::e a:::::a a:::::a m:::::m
m:::::m m:::::mo:::::o o:::::ou:::::uuu::::u t:::::t tttttt\n"
00065 "SSSSSSS S:::::S t:::::ttttttr:::::r e:::::e a:::::a a:::::a m:::::m
m:::::m m:::::mo:::::oo:::::ou:::::uu t:::::ttttt:::::t\n"
00066 "S:::::SSSSS:::S tt:::::tr:::::r e:::::e eeeeeee a:::::aaaa:::::a m:::::m
m:::::m m:::::mo:::::o u:::::u tt:::::t\n"
00067 "S:::::SS tt:::::tr:::::r ee:::::e a:::::aa:::am:::::m
m:::::m m:::::mo oo:::::oo uu:::::uu t:::::t\n"
00068 " SSSSSSSSSSSS tttttttt rrrrrr eeeeeee aaaaaa aaaammmmm
mmmmmm mmmmmmm oooooooooo uuuuuuuu uuuu tttttttttt {} \n"
00069 "\n",
00070 fmt::format(fg(fmt::color::red) | fmt::emphasis::bold, "v{}", streamout_version.to_string());
00071 // clang-format on
00072 log()->info("*****");
00073 log()->info("Streamout Version: {}", streamout_version.to_string());
00074 log()->info("Using InterfaceReader {} version {}", m_Source.getName(),
m_Source.getVersion().to_string());
00075 log()->info("Using InterfaceWriter {} version {}", m_Destination.getName(),
m_Destination.getVersion().to_string());
00076
00077 if(!m_Destination.checkCompatibility(m_Source.getName(), m_Source.getVersion().to_string()))
00078 {
00079 log()->critical("{} version {} is not compatible with {} version {} ! ", m_Source.getName(),
m_Source.getVersion().to_string(), m_Destination.getName(), m_Destination.getVersion().to_string());
00080 log()->info("Compatible Interfaces for {} are", m_Destination.getName());
00081 for(std::map<std::string, std::string>::iterator it = m_Destination.getCompatibility().begin();
it != m_Destination.getCompatibility().end(); ++it) { log()->info("{} version {}", it->first,
it->second); }
00082 std::exit(-1);
00083 }
00084 if(!m_DetectorIDs.empty())
00085 {
00086 std::string ids;
00087 for(std::vector<DetectorID>::const_iterator it = m_DetectorIDs.cbegin(); it !=
m_DetectorIDs.cend(); ++it) ids += std::to_string(static_cast<std::uint16_t>(*it)) + ";";
00088 log()->info("Detector ID(s) other than {} will be ignored", ids);
00089 }
00090 log()->info("*****");
00091 RawBufferNavigator bufferNavigator;
00092 Timer timer;
00093 timer.start();
00094 m_Source.start();
00095 m_Destination.start();
00096 while(m_Source.nextEvent() && m_NbrEventsToProcess >= m_NbrEvents)
00097 {
00098 /*****/
00099 /*** START EVENT ***/
00100 m_Source.startEvent();
00101 m_Destination.startEvent();
00102 /*****/
00103
00104 m_Logger->warn("==== Event {} *****", m_NbrEvents);
00105 while(m_Source.nextDIFbuffer())
00106 {
00107 const Buffer& buffer = m_Source.getBuffer();
00108
00109 bufferNavigator.setBuffer(buffer);
00110 if(std::find(m_DetectorIDs.begin(), m_DetectorIDs.end(),
static_cast<DetectorID>(bufferNavigator.getDetectorID())) == m_DetectorIDs.end())
00111 {
00112 m_Logger->debug("Ignoring detector ID : {}", bufferNavigator.getDetectorID());
00113 continue;
00114 }
00115
00116 std::int32_t idstart = bufferNavigator.getStartOfPayload();
00117 if(m_Debug && idstart == -1) m_Logger->info(to_hex(buffer));
00118 c.DIFStarter[idstart]++;
00119 if(!bufferNavigator.validPayload())
00120 {
00121 m_Logger->error("!bufferNavigator.validBuffer()");
00122 continue;
00123 }
00124
00125 /*****/
00126 /*** START DIF ***/
```

```

00127         m_Source.startDIF();
00128         m_Destination.startDIF();
00129         /***** */
00130         PayloadParser d;
00131         // This is really a big error so skip DIF entirely if exception occurs
00132         try
00133         {
00134             d.setBuffer(bufferNavigator.getPayload());
00135         }
00136         catch(const Exception& e)
00137         {
00138             m_Logger->error("{} ", e.what());
00139             continue;
00140         }
00141
00142         if(buffer.end() != d.end()) m_Logger->error("DIF BUFFER END {} {} ", fmt::ptr(buffer.end()),
fmt::ptr(d.end()));
00143         assert(buffer.end() == d.end());
00144
00145         m_Logger->error("CRC : {} ", d.getDIF_CRC());
00146         c.DIFPtrValueAtReturnedPos[d.begin() [d.getEndOfDIFData()-3]]++;
00147         assert(d.begin() [d.getEndOfDIFData()-3] == 0xa0);
00148
00149
00150         c.SizeAfterDIFPtr[d.getSizeAfterDIFPtr()]++;
00151         m_Destination.processDIF(d);
00152         for(std::size_t i = 0; i < d.getNumberOfFrames(); ++i)
00153         {
00154             /***** */
00155             /*** START FRAME ***/
00156             m_Source.startFrame();
00157             m_Destination.startFrame();
00158             /***** */
00159             m_Destination.processFrame(d, i);
00160             for(std::size_t j = 0; j < static_cast<std::size_t>(Hardware::NUMBER_PAD); ++j)
00161             {
00162                 if(d.getThresholdStatus(i, j) != 0)
00163                 {
00164                     m_Source.startPad();
00165                     m_Destination.startPad();
00166                     m_Destination.processPadInFrame(d, i, j);
00167                     m_Source.endPad();
00168                     m_Destination.endPad();
00169                 }
00170             }
00171             /***** */
00172             /*** END FRAME ***/
00173             m_Source.endFrame();
00174             m_Destination.endFrame();
00175             /***** */
00176         }
00177         // If I want SlowControl I need to check for it first, If there is an error then it's not a
big deal just continue and say is bad SlowControl
00178         / * try
00179         {
00180             d.setSCBuffer();
00181         }
00182         catch(const Exception& e)
00183         {
00184             m_Logger->error("{} ", e.what());
00185         }
00186
00187         bool processSC = false;
00188         if(d.hasSlowControl())
00189         {
00190             c.hasSlowControl++;
00191             processSC = true;
00192         }
00193         if(d.badSCData())
00194         {
00195             c.hasBadSlowControl++;
00196             processSC = false;
00197         }
00198         if(processSC) { m_Destination.processSlowControl(d.getSCBuffer()); } */
00199
00200         //Buffer eod = d.getEndOfAllData();
00201         //c.SizeAfterAllData[eod.size()]++;
00202         // bit8_t* debug_variable_3 = eod.end();
00203         // if(buffer.end() != debug_variable_3) m_Logger->info("END DATA BUFFER END {} {} ",
fmt::ptr(buffer.end()), fmt::ptr(debug_variable_3));
00204         // assert(buffer.end() == debug_variable_3);
00205         //if(eod.size() != 0) m_Logger->info("End of Data remaining stuff : {} ", to_hex(eod)); */
00206
00207         /*int nonzeroCount = 0;
00208         for(bit8_t* it = eod.begin(); it != eod.end(); it++)
00209             if(static_cast<int>(*it) != 0) nonzeroCount++;
00210         c.NonZeroValusAtEndOfData[nonzeroCount]++; */

```



```

00211
00212 /*****/
00213 /*** END DIF ***/
00214     m_Source.endDIF();
00215     m_Destination.endDIF();
00216 /*****/
00217 } // end of DIF while loop
00218 m_Logger->warn("==== Event {} =====", m_NbrEvents);
00219 m_NbrEvents++;
00220 /*****/
00221 /*** END EVENT ***/
00222     m_Source.endEvent();
00223     m_Destination.endEvent();
00224 /*****/
00225 } // end of event while loop
00226 m_Destination.end();
00227 m_Source.end();
00228 timer.stop();
00229 fmt::print(fg(fmt::color::green) | fmt::emphasis::bold, "=== elapsed time {}ms ({}ms/event)
===\n", timer.getElapsedTime() / 1000, timer.getElapsedTime() / (1000 * m_NbrEvents));
00230 }

```

4.2.3.4 printAllCounters() `template<typename SOURCE , typename DESTINATION >`

```
void BufferLooper< SOURCE, DESTINATION >::printAllCounters ( ) [inline]
```

Definition at line 231 of file [BufferLooper.h](#).

```
00231 { c.printAllCounters(); }
```

4.2.3.5 setDetectorIDs() `template<typename SOURCE , typename DESTINATION >`

```
void BufferLooper< SOURCE, DESTINATION >::setDetectorIDs (
    const std::vector< DetectorID > & detectorIDs ) [inline]
```

Definition at line 234 of file [BufferLooper.h](#).

```
00234 { m_DetectorIDs = detectorIDs; }
```

The documentation for this class was generated from the following file:

- `libs/core/include/BufferLooper.h`

4.3 BufferLooperCounter Struct Reference

```
#include <libs/core/include/BufferLooperCounter.h>
```

Public Member Functions

- void [printCounter](#) (const std::string &description, const std::map< int, int > &m, const std::ios_base::fmtflags &base=std::ios_base::dec)
- void [printAllCounters](#) ()

Public Attributes

- int [hasSlowControl](#) = 0
- int [hasBadSlowControl](#) = 0
- std::map< int, int > [DIFStarter](#)
- std::map< int, int > [DIFPtrValueAtReturnedPos](#)
- std::map< int, int > [SizeAfterDIFPtr](#)
- std::map< int, int > [SizeAfterAllData](#)
- std::map< int, int > [NonZeroValueAtEndOfData](#)

4.3.1 Detailed Description

Definition at line 12 of file [BufferLooperCounter.h](#).

4.3.2 Member Function Documentation

4.3.2.1 printAllCounters() void BufferLooperCounter::printAllCounters ()

Definition at line 10 of file [BufferLooperCounter.cc](#).

```
00011 {
00012     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, "BUFFER LOOP FINAL STATISTICS : \n");
00013     printCounter("Start of DIF header", DIFStarter);
00014     printCounter("Value after DIF data are processed", DIFPtrValueAtReturnedPos, std::ios_base::hex);
00015     printCounter("Size remaining in buffer after end of DIF data", SizeAfterDIFPtr);
00016     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, "Number of Slow Control found {} out of
which {} are bad\n", hasSlowControl, hasBadSlowControl);
00017     printCounter("Size remaining after all of data have been processed", SizeAfterAllData);
00018     printCounter("Number on non zero values in end of data buffer", NonZeroValusAtEndOfData);
00019 }
```

4.3.2.2 printCounter() void BufferLooperCounter::printCounter (const std::string & description, const std::map< int, int > & m, const std::ios_base::fmtflags & base = std::ios_base::dec)

Definition at line 21 of file [BufferLooperCounter.cc](#).

```
00022 {
00023     std::string out{"statistics for " + description + " : \n"};
00024     for(std::map<int, int>::const_iterator it = m.begin(); it != m.end(); it++)
00025     {
00026         if(it != m.begin()) out += ", ";
00027         out += " [";
00028         switch(base)
00029         {
00030             case std::ios_base::dec:
00031                 out += to_dec(static_cast<std::uint32_t>(it->first));
00032                 break;
00033             case std::ios_base::hex:
00034                 out += to_hex(static_cast<std::uint32_t>(it->first));
00035                 break;
00036             case std::ios_base::oct:
00037                 out += to_oct(static_cast<std::uint32_t>(it->first));
00038                 break;
00039             default:
00040                 out += to_dec(static_cast<std::uint32_t>(it->first));
00041                 break;
00042         }
00043         out += "]=" + std::to_string(it->second);
00044     }
00045     out += "\n";
00046     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, out);
00047 }
```

4.3.3 Member Data Documentation

4.3.3.1 DIFPtrValueAtReturnedPos `std::map<int, int> BufferLooperCounter::DIFPtrValueAt↵
ReturnedPos`

Definition at line 18 of file [BufferLooperCounter.h](#).

4.3.3.2 DIFStarter `std::map<int, int> BufferLooperCounter::DIFStarter`

Definition at line 17 of file [BufferLooperCounter.h](#).

4.3.3.3 hasBadSlowControl `int BufferLooperCounter::hasBadSlowControl = 0`

Definition at line 16 of file [BufferLooperCounter.h](#).

4.3.3.4 hasSlowControl `int BufferLooperCounter::hasSlowControl = 0`

Definition at line 15 of file [BufferLooperCounter.h](#).

4.3.3.5 NonZeroValusAtEndOfData `std::map<int, int> BufferLooperCounter::NonZeroValusAtEnd↵
OfData`

Definition at line 21 of file [BufferLooperCounter.h](#).

4.3.3.6 SizeAfterAllData `std::map<int, int> BufferLooperCounter::SizeAfterAllData`

Definition at line 20 of file [BufferLooperCounter.h](#).

4.3.3.7 SizeAfterDIFPtr `std::map<int, int> BufferLooperCounter::SizeAfterDIFPtr`

Definition at line 19 of file [BufferLooperCounter.h](#).


The documentation for this struct was generated from the following files:

- [libs/core/include/BufferLooperCounter.h](#)
- [libs/core/src/BufferLooperCounter.cc](#)

4.4 DIF Class Reference

```
#include <libs/interface/ROOT/include/DIF.h>
```

Inheritance diagram for DIF:



Public Member Functions

- void `clear` ()
- void `addHit` (const `Hit` &)
- void `setId` (const std::uint8_t &)
- std::uint8_t `getId` () const
- void `setDTC` (const std::uint32_t &)
- std::uint32_t `getDTC` () const
- void `setGTC` (const std::uint32_t &)
- std::uint32_t `getGTC` () const
- void `setDIFBCID` (const std::uint32_t &)
- std::uint32_t `getDIFBCID` () const
- void `setAbsoluteBCID` (const std::uint64_t &)
- std::uint64_t `getAbsoluteBCID` () const
- std::vector< `Hit` >::const_iterator `cbegin` () const
- std::vector< `Hit` >::const_iterator `cend` () const

4.4.1 Detailed Description

Definition at line 16 of file `DIF.h`.

4.4.2 Member Function Documentation

4.4.2.1 `addHit()` void `DIF::addHit` (
const `Hit` & *hit*)

Definition at line 10 of file `DIF.cc`.

```
00010 { m_Hits.push_back(hit); }
```

4.4.2.2 `cbegin()` std::vector< `Hit` >::const_iterator `DIF::cbegin` () const

Definition at line 32 of file `DIF.cc`.

```
00032 { return m_Hits.cbegin(); }
```

4.4.2.3 cend() `std::vector< Hit >::const_iterator DIF::cend () const`

Definition at line 34 of file [DIF.cc](#).

```
00034 { return m_Hits.cend(); }
```

4.4.2.4 clear() `void DIF::clear ()`

Definition at line 36 of file [DIF.cc](#).

```
00036 { m_Hits.clear(); }
```

4.4.2.5 getAbsoluteBCID() `std::uint64_t DIF::getAbsoluteBCID () const`

Definition at line 30 of file [DIF.cc](#).

```
00030 { return m_AbsoluteBCID; }
```

4.4.2.6 getDIFBCID() `std::uint32_t DIF::getDIFBCID () const`

Definition at line 26 of file [DIF.cc](#).

```
00026 { return m_DIFBCID; }
```

4.4.2.7 getDTC() `std::uint32_t DIF::getDTC () const`

Definition at line 18 of file [DIF.cc](#).

```
00018 { return m_DTC; }
```

4.4.2.8 getGTC() `std::uint32_t DIF::getGTC () const`

Definition at line 22 of file [DIF.cc](#).

```
00022 { return m_GTC; }
```

4.4.2.9 getID() `std::uint8_t DIF::getID () const`

Definition at line 14 of file [DIF.cc](#).

```
00014 { return m_ID; }
```

4.4.2.10 setAbsoluteBCID() `void DIF::setAbsoluteBCID (`
`const std::uint64_t & absolutebcid)`

Definition at line 28 of file [DIF.cc](#).

```
00028 { m_AbsoluteBCID = absolutebcid; }
```

4.4.2.11 setDIFBCID() `void DIF::setDIFBCID (`
`const std::uint32_t & difbcid)`

Definition at line 24 of file [DIF.cc](#).

```
00024 { m_DIFBCID = difbcid; }
```

4.4.2.12 setDTC() `void DIF::setDTC (`
`const std::uint32_t & dtc)`

Definition at line 16 of file [DIF.cc](#).

```
00016 { m_DTC = dtc; }
```

4.4.2.13 setGTC() `void DIF::setGTC (`
`const std::uint32_t & gtc)`

Definition at line 20 of file [DIF.cc](#).

```
00020 { m_GTC = gtc; }
```

4.4.2.14 setID() `void DIF::setID (`
`const std::uint8_t & id)`

Definition at line 12 of file [DIF.cc](#).

```
00012 { m_ID = id; }
```

The documentation for this class was generated from the following files:

- [libs/interface/ROOT/include/DIF.h](#)
- [libs/interface/ROOT/src/DIF.cc](#)

4.5 DIFPtr Class Reference

M3 MICROROC and HARDROC2 dataformat.

```
#include <libs/core/include/PayloadParser.h>
```

4.5.1 Detailed Description

M3 MICROROC and HARDROC2 dataformat.

Data from the DAQ (once at the beginning of the file) :

(1 fois par fichier) [Données venant de la DAQ]

data format version (8 bits)

daq software version (16 bits)

SDCC firmware version (16 bits)

DIF firmware version (16 bits)

timestamp (32bits) (secondes depuis le 01/01/1970)

timestamp (32bits) (milliseconde)



Explication :

- **data format version** = la version du format de données utilisée, c'est la version 13
- **daq software version** = la version du soft d'acquisition labview ou Xdaq
- **SDCC firmware version** = la version du code VHDL de la carte SDCC
- **DIF firmware version** = la version du code VHDL de la carte DIF
- **timestamp** = secondes et milliseconde depuis le 01/01/1970

Figure 1 Data from the DAQ (once at the beginning of the file)

Data from the **DIF** analog or/and digital (loop) :




Figure 2 Data from the DIF analog or/and digital

Data from the DAQ (slowcontrol) :

(1 fois par slow control, c'est à dire 1 fois par fichier par DIF) [Données venant de la DAQ]

SC Header (0xB1)

DIF ID (8 bits)

ASIC Header (8 bits)

Size SC ASIC

[74 ou 109 selon le chip]

SC ASIC (n x 8bits)

[n= 74 ou 109 selon le chip]

DIF ID (8 bits)

ASIC Header (8 bits)

Size SC ASIC

[74 ou 109 selon le chip]

SC ASIC (n x 8bits)

[n= 74 ou 109 selon le chip]

...

SC Trailer (0xA1)

Explication :

- **SC Header (0xB1) / SC Trailer (0xA1)** = balise pour repérer les infos sur le Slow Control
- **DIF ID** = identité de la DIF qui envoient les data
- **Size SC ASIC** = taille de la trame SC d'un CHIP (MR=74 byte, HR = 109 byte)
- **ASIC header (8 bits)** : header dans le SC
- **SC ASIC (n x 8bits)** : de 1 a 48 par DIF moins ceux qui sont bypassés

Figure 3 Data from the DAQ (slowcontrol)

The documentation for this class was generated from the following file:

- `libs/core/include/PayloadParser.h`

4.6 DIFSlowControl Class Reference

```
#include <libs/core/include/DIFSlowControl.h>
```

Public Member Functions

- **DIFSlowControl** (const std::uint8_t &version, const std::uint8_t &DIFid, unsigned char *buf)
Constructor.
- std::uint8_t **getDIFid** ()
get DIF id
- std::map< int, std::map< std::string, int > > **getChipsMap** ()
Get chips map.
- std::map< std::string, int > **getChipSlowControl** (const int &asicid)
Get one chip map.
- int **getChipSlowControl** (const std::int8_t &asicid, const std::string ¶m)
Get one Chip value.
- std::map< int, std::map< std::string, int > >::const_iterator **cbegin** () const
- std::map< int, std::map< std::string, int > >::const_iterator **cend** () const

4.6.1 Detailed Description

Definition at line 13 of file [DIFSlowControl.h](#).

4.6.2 Constructor & Destructor Documentation

4.6.2.1 DIFSlowControl() `DIFSlowControl::DIFSlowControl (`
`const std::uint8_t & version,`
`const std::uint8_t & DIFid,`
`unsigned char * buf)`

Constructor.

Parameters

<i>version</i>	Data format version
<i>DIFid</i>	DIF id
<i>buf</i>	Pointer to the Raw data buffer

Definition at line 7 of file [DIFSlowControl.cc](#).

```
00007 : m_Version(version), m_DIFid(DifId), m_AsicType(2)
00008 {
00009     if(cbuf[0] != 0xb1) return;
00010     int header_shift{6};
00011     if(m_Version < 8) m_NbrAsic = cbuf[5];
00012     else
00013     {
00014         m_DIFid      = cbuf[1];
00015         m_NbrAsic     = cbuf[2];
00016         header_shift = 3;
00017     }
00018     int size_hardroc1 = m_NbrAsic * 72 + header_shift + 1;
00019     if(cbuf[size_hardroc1 - 1] != 0xal) size_hardroc1 = 0;
00020
00021     int size_hardroc2 = m_NbrAsic * 109 + header_shift + 1;
00022     if(cbuf[size_hardroc2 - 1] != 0xal) size_hardroc2 = 0;
00023     if(size_hardroc1 != 0)
00024     {
00025         FillHR1(header_shift, cbuf);
00026         m_AsicType = 1;
00027     }
00028     else if(size_hardroc2 != 0)
00029         FillHR2(header_shift, cbuf);
00030     else
00031         return;
00032 }
```

4.6.3 Member Function Documentation

4.6.3.1 cbegin() `std::map< int, std::map< std::string, int > >::const_iterator DIFSlowControl::cbegin () const [inline]`

Definition at line 47 of file [DIFSlowControl.h](#).

```
00047 { return m_MapSC.cbegin(); }
```

4.6.3.2 cend() `std::map< int, std::map< std::string, int > >::const_iterator DIFSlowControl↵
::cend () const [inline]`

Definition at line 49 of file [DIFSlowControl.h](#).

```
00049 { return m_MapSC.cend(); }
```

4.6.3.3 getChipSlowControl() [1/2] `std::map< std::string, int > DIFSlowControl::getChipSlow↵
Control (
const int & asicid) [inline]`

Get one chip map.

Parameters

<i>asicid</i>	ASIC ID
---------------	---------

Returns

a map of <string (parameter name),int (parameter value) >

Definition at line 38 of file [DIFSlowControl.cc](#).

```
00038 { return m_MapSC[asicid]; }
```

4.6.3.4 getChipSlowControl() [2/2] `int DIFSlowControl::getChipSlowControl (
const std::int8_t & asicid,
const std::string & param) [inline]`

Get one Chip value.

Parameters

<i>asicid</i>	ASic ID
<i>param</i>	Parameter name

Definition at line 40 of file [DIFSlowControl.cc](#).

```
00040 { return getChipSlowControl(asicid)[param]; }
```

4.6.3.5 getChipsMap() `std::map< int, std::map< std::string, int > > DIFSlowControl::get↵
ChipsMap () [inline]`

Get chips map.

Returns

a map of < Asic Id, map of <string (parameter name),int (parameter value) >

Definition at line 36 of file [DIFSlowControl.cc](#).

```
00036 { return m_MapSC; }
```

4.6.3.6 getDIFId() `std::uint8_t DIFSlowControl::getDIFId () [inline]`

get DIF id

Definition at line 34 of file [DIFSlowControl.cc](#).

```
00034 { return m_DIFId; }
```


The documentation for this class was generated from the following files:

- [libs/core/include/DIFSlowControl.h](#)
- [libs/core/src/DIFSlowControl.cc](#)

4.7 Event Class Reference

```
#include <libs/interface/ROOT/include/Event.h>
```

Inheritance diagram for Event:



Public Member Functions

- void [clear](#) ()
- void [addDIF](#) (const [DIF](#) &dif)
- `std::map< std::uint8_t, DIF >::const_iterator cbegin () const`
- `std::map< std::uint8_t, DIF >::const_iterator cend () const`

4.7.1 Detailed Description

Definition at line 15 of file [Event.h](#).

4.7.2 Member Function Documentation

4.7.2.1 addDIF() `void Event::addDIF (const DIF & dif)`

Definition at line 10 of file [Event.cc](#).

```
00010 { DIFs[dif.getID()] = dif; }
```

4.7.2.2 cbegin() `std::map< std::uint8_t, DIF >::const_iterator Event::cbegin () const`

Definition at line 12 of file [Event.cc](#).

```
00012 { return DIFs.cbegin(); }
```

4.7.2.3 cend() `std::map< std::uint8_t, DIF >::const_iterator Event::cend () const`

Definition at line 14 of file [Event.cc](#).

```
00014 { return DIFs.cend(); }
```

4.7.2.4 clear() `void Event::clear ()`

Definition at line 8 of file [Event.cc](#).

```
00008 { DIFs.clear(); }
```

The documentation for this class was generated from the following files:

- [libs/interface/ROOT/include/Event.h](#)
- [libs/interface/ROOT/src/Event.cc](#)

4.8 Exception Class Reference

```
#include <libs/core/include/Exception.h>
```

Public Member Functions

- virtual const char * [what](#) () const noexcept
- [Exception](#) (const std::string &[message](#))
- [Exception](#) (const std::int32_t &[error](#), const std::string &[message](#))
- std::int32_t [error](#) ()
- std::string [message](#) ()

4.8.1 Detailed Description

Definition at line 11 of file [Exception.h](#).

4.8.2 Constructor & Destructor Documentation

4.8.2.1 Exception() [1/2] `Exception::Exception (const std::string & message) [inline], [explicit]`

Definition at line 15 of file [Exception.h](#).

```
00015 : m_Message(message) { constructWhat(); }
```

4.8.2.2 Exception() [2/2] `Exception::Exception (`
 `const std::int32_t & error,`
 `const std::string & message) [inline]`

Definition at line 16 of file [Exception.h](#).

```
00016 : m_Error(error), m_Message(message) { constructWhat(); }
```

4.8.3 Member Function Documentation

4.8.3.1 error() `std::int32_t Exception::error () [inline]`

Definition at line 17 of file [Exception.h](#).

```
00017 { return m_Error; }
```

4.8.3.2 message() `std::string Exception::message () [inline]`

Definition at line 18 of file [Exception.h](#).

```
00018 { return m_Message; }
```

4.8.3.3 what() `virtual const char * Exception::what () const [inline], [virtual], [noexcept]`

Definition at line 14 of file [Exception.h](#).

```
00014 { return m_What.c_str(); }
```


The documentation for this class was generated from the following file:

- [libs/core/include/Exception.h](#)

4.9 Hit Class Reference

```
#include <libs/interface/ROOT/include/Hit.h>
```

Inheritance diagram for Hit:



Public Member Functions

- void [clear](#) ()
- void [setDIF](#) (const std::uint8_t &)
- void [setASIC](#) (const std::uint8_t &)
- void [setChannel](#) (const std::uint8_t &)
- void [setThreshold](#) (const std::uint8_t &)
- void [setDTC](#) (const std::uint32_t &)
- void [setGTC](#) (const std::uint32_t &)
- void [setDIFBCID](#) (const std::uint32_t &)
- void [setFrameBCID](#) (const std::uint32_t &)
- void [setTimestamp](#) (const std::uint32_t &)
- void [setAbsoluteBCID](#) (const std::uint64_t &)
- std::uint8_t [getDIFid](#) () const
- std::uint8_t [getASICid](#) () const
- std::uint8_t [getChannel](#) () const
- std::uint8_t [getThreshold](#) () const
- std::uint32_t [getDTC](#) () const
- std::uint32_t [getGTC](#) () const
- std::uint32_t [getDIFBCID](#) () const
- std::uint32_t [getFrameBCID](#) () const
- std::uint32_t [getTimestamp](#) () const
- std::uint64_t [getAbsoluteBCID](#) () const

4.9.1 Detailed Description

Definition at line 10 of file [Hit.h](#).

4.9.2 Member Function Documentation

4.9.2.1 [clear\(\)](#) void Hit::clear ()

Definition at line 7 of file [Hit.cc](#).

```
00008 {
00009     m_DIF          = 0;
00010     m_ASIC         = 0;
00011     m_Channel      = 0;
00012     m_Threshold    = 0;
00013     m_DTC          = 0;
00014     m_GTC          = 0;
00015     m_DIFBCID      = 0;
00016     m_FrameBCID    = 0;
00017     m_Timestamp     = 0;
00018     m_AbsoluteBCID = 0;
00019 }
```

4.9.2.2 [getAbsoluteBCID\(\)](#) std::uint64_t Hit::getAbsoluteBCID () const

Definition at line 59 of file [Hit.cc](#).

```
00059 { return m_AbsoluteBCID; }
```

4.9.2.3 getASICid() `std::uint8_t Hit::getASICid () const`

Definition at line 43 of file [Hit.cc](#).

```
00043 { return m_ASIC; }
```

4.9.2.4 getChannel() `std::uint8_t Hit::getChannel () const`

Definition at line 45 of file [Hit.cc](#).

```
00045 { return m_Channel; }
```

4.9.2.5 getDIFBCID() `std::uint32_t Hit::getDIFBCID () const`

Definition at line 53 of file [Hit.cc](#).

```
00053 { return m_DIFBCID; }
```

4.9.2.6 getDIFid() `std::uint8_t Hit::getDIFid () const`

Definition at line 41 of file [Hit.cc](#).

```
00041 { return m_DIF; }
```

4.9.2.7 getDTC() `std::uint32_t Hit::getDTC () const`

Definition at line 49 of file [Hit.cc](#).

```
00049 { return m_DTC; }
```

4.9.2.8 getFrameBCID() `std::uint32_t Hit::getFrameBCID () const`

Definition at line 55 of file [Hit.cc](#).

```
00055 { return m_FrameBCID; }
```

4.9.2.9 getGTC() `std::uint32_t Hit::getGTC () const`

Definition at line 51 of file [Hit.cc](#).

```
00051 { return m_GTC; }
```


4.9.2.10 getThreshold() `std::uint8_t Hit::getThreshold () const`

Definition at line 47 of file [Hit.cc](#).

```
00047 { return m_Threshold; }
```

4.9.2.11 getTimestamp() `std::uint32_t Hit::getTimestamp () const`

Definition at line 57 of file [Hit.cc](#).

```
00057 { return m_Timestamp; }
```

4.9.2.12 setAbsoluteBCID() `void Hit::setAbsoluteBCID (const std::uint64_t & absolutebcid)`

Definition at line 39 of file [Hit.cc](#).

```
00039 { m_AbsoluteBCID = absolutebcid; }
```

4.9.2.13 setASIC() `void Hit::setASIC (const std::uint8_t & asic)`

Definition at line 23 of file [Hit.cc](#).

```
00023 { m_ASIC = asic; }
```

4.9.2.14 setChannel() `void Hit::setChannel (const std::uint8_t & channel)`

Definition at line 25 of file [Hit.cc](#).

```
00025 { m_Channel = channel; }
```

4.9.2.15 setDIF() `void Hit::setDIF (const std::uint8_t & dif)`

Definition at line 21 of file [Hit.cc](#).

```
00021 { m_DIF = dif; }
```

4.9.2.16 setDIFBCID() `void Hit::setDIFBCID (const std::uint32_t & difbcid)`

Definition at line 33 of file [Hit.cc](#).

```
00033 { m_DIFBCID = difbcid; }
```

4.9.2.17 setDTC() `void Hit::setDTC (`
`const std::uint32_t & dtc)`

Definition at line 29 of file [Hit.cc](#).

```
00029 { m_DTC = dtc; }
```

4.9.2.18 setFrameBCID() `void Hit::setFrameBCID (`
`const std::uint32_t & framebcid)`

Definition at line 35 of file [Hit.cc](#).

```
00035 { m_FrameBCID = framebcid; }
```

4.9.2.19 setGTC() `void Hit::setGTC (`
`const std::uint32_t & gtc)`

Definition at line 31 of file [Hit.cc](#).

```
00031 { m_GTC = gtc; }
```

4.9.2.20 setThreshold() `void Hit::setThreshold (`
`const std::uint8_t & threshold)`

Definition at line 27 of file [Hit.cc](#).

```
00027 { m_Threshold = threshold; }
```

4.9.2.21 setTimestamp() `void Hit::setTimestamp (`
`const std::uint32_t & timestamp)`

Definition at line 37 of file [Hit.cc](#).

```
00037 { m_Timestamp = timestamp; }
```


The documentation for this class was generated from the following files:

- [libs/interface/ROOT/include/Hit.h](#)
- [libs/interface/ROOT/src/Hit.cc](#)

4.10 Interface Class Reference

```
#include <libs/core/include/Interface.h>
```

Inheritance diagram for Interface:



Public Member Functions

- [Interface](#) (const std::string &name, const std::string &version, const [InterfaceType](#) &type)
- virtual [~Interface](#) ()=default
- virtual void [startEvent](#) ()
- virtual void [endEvent](#) ()
- virtual void [startDIF](#) ()
- virtual void [endDIF](#) ()
- virtual void [startFrame](#) ()
- virtual void [endFrame](#) ()
- virtual void [startPad](#) ()
- virtual void [endPad](#) ()
- std::shared_ptr< spdlog::logger > & [log](#) ()
- void [setLogger](#) (const std::shared_ptr< spdlog::logger > &logger)
- std::string [getName](#) ()
- [Version](#) [getVersion](#) ()

4.10.1 Detailed Description

Definition at line 38 of file [Interface.h](#).

4.10.2 Constructor & Destructor Documentation

4.10.2.1 Interface() `Interface::Interface (const std::string & name, const std::string & version, const InterfaceType & type) [inline]`

Definition at line 41 of file [Interface.h](#).

```
00041 :   m_Name(name), m_Version(version) {}
```

4.10.2.2 ~Interface() `virtual Interface::~~Interface () [virtual], [default]`

4.10.3 Member Function Documentation

4.10.3.1 endDIF() `virtual void Interface::endDIF () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 46 of file [Interface.h](#).

```
00046 {}
```

4.10.3.2 endEvent() `virtual void Interface::endEvent () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 44 of file [Interface.h](#).

```
00044 {}
```

4.10.3.3 endFrame() `virtual void Interface::endFrame () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 48 of file [Interface.h](#).

```
00048 {}
```

4.10.3.4 endPad() `virtual void Interface::endPad () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 50 of file [Interface.h](#).

```
00050 {}
```

4.10.3.5 getName() `std::string Interface::getName () [inline]`

Definition at line 53 of file [Interface.h](#).

```
00053 { return m_Name; }
```

4.10.3.6 getVersion() `Version Interface::getVersion () [inline]`

Definition at line 54 of file [Interface.h](#).

```
00054 { return m_Version; }
```

4.10.3.7 log() `std::shared_ptr< spdlog::logger > & Interface::log () [inline]`

Definition at line 51 of file [Interface.h](#).

```
00051 { return m_Logger; }
```

4.10.3.8 setLogger() `void Interface::setLogger (
const std::shared_ptr< spdlog::logger > & logger) [inline]`

Definition at line 52 of file [Interface.h](#).

```
00052 { m_Logger = logger; }
```

4.10.3.9 startDIF() `virtual void Interface::startDIF () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 45 of file [Interface.h](#).
00045 {}

4.10.3.10 startEvent() `virtual void Interface::startEvent () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 43 of file [Interface.h](#).
00043 {}

4.10.3.11 startFrame() `virtual void Interface::startFrame () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 47 of file [Interface.h](#).
00047 {}

4.10.3.12 startPad() `virtual void Interface::startPad () [inline], [virtual]`

Reimplemented in [ROOTWriter](#).

Definition at line 49 of file [Interface.h](#).
00049 {}


The documentation for this class was generated from the following file:

- [libs/core/include/Interface.h](#)

4.11 InterfaceReader Class Reference

```
#include <libs/core/include/Interface.h>
```

Inheritance diagram for InterfaceReader:



Public Member Functions

- [InterfaceReader](#) (const std::string &name, const std::string &version)
- virtual [~InterfaceReader](#) ()=default

Protected Attributes

- [Buffer](#) [m_Buffer](#)

4.11.1 Detailed Description

Definition at line 63 of file [Interface.h](#).

4.11.2 Constructor & Destructor Documentation

4.11.2.1 InterfaceReader() `InterfaceReader::InterfaceReader (`
 `const std::string & name,`
 `const std::string & version) [inline]`

Definition at line 66 of file [Interface.h](#).

```
00066 : Interface(name, version, InterfaceType::Reader) {}
```

4.11.2.2 ~InterfaceReader() `virtual InterfaceReader::~~InterfaceReader () [virtual], [default]`

4.11.3 Member Data Documentation

4.11.3.1 m_Buffer [Buffer](#) `InterfaceReader::m_Buffer [protected]`

Definition at line 70 of file [Interface.h](#).


The documentation for this class was generated from the following file:

- `libs/core/include/Interface.h`

4.12 InterfaceWriter Class Reference

```
#include <libs/core/include/Interface.h>
```

Inheritance diagram for InterfaceWriter:



Public Member Functions

- [InterfaceWriter](#) (const std::string &name, const std::string &version)
- void [addCompatibility](#) (const std::string &name, const std::string &version)
- std::map< std::string, std::string > [getCompatibility](#) ()
- bool [checkCompatibility](#) (const std::string &name, const std::string &version)
- virtual [~InterfaceWriter](#) ()=default

4.12.1 Detailed Description

Definition at line 73 of file [Interface.h](#).

4.12.2 Constructor & Destructor Documentation

4.12.2.1 InterfaceWriter() `InterfaceWriter::InterfaceWriter (const std::string & name, const std::string & version) [inline]`

Definition at line 76 of file [Interface.h](#).

```
00076 : Interface(name, version, InterfaceType::Writer) {}
```

4.12.2.2 ~InterfaceWriter() `virtual InterfaceWriter::~~InterfaceWriter () [virtual], [default]`

4.12.3 Member Function Documentation

4.12.3.1 addCompatibility() void InterfaceWriter::addCompatibility (
const std::string & name,
const std::string & version) [inline]

Definition at line 78 of file [Interface.h](#).

```
00078 { m_Compatible[name] = version; }
```

4.12.3.2 checkCompatibility() bool InterfaceWriter::checkCompatibility (
const std::string & name,
const std::string & version) [inline]

Definition at line 82 of file [Interface.h](#).

```
00083 {
00084     if(m_Compatible.find(name) != m_Compatible.end())
00085     {
00086         auto ran = semver::range::detail::range(m_Compatible[name]);
00087         semver::version ver = semver::version(version);
00088         if(ran.satisfies(ver, false)) return true;
00089     }
00090     return false;
00091 }
00092 else
00093     return false;
00094 }
```

4.12.3.3 getCompatibility() std::map< std::string, std::string > InterfaceWriter::getCompatibility
() [inline]

Definition at line 80 of file [Interface.h](#).

```
00080 { return m_Compatible; }
```


The documentation for this class was generated from the following file:

- [libs/core/include/Interface.h](#)

4.13 PayloadParser Class Reference

```
#include <libs/core/include/PayloadParser.h>
```

Inheritance diagram for PayloadParser:



Public Member Functions

- [PayloadParser](#) ()=default
- void [setBuffer](#) (const [Buffer](#) &buffer)
- bool [hasTemperature](#) () const
- bool [hasAnalogReadout](#) () const
- bool [hasSlowControl](#) () const
- float [getTemperatureDIF](#) () const
- float [getTemperatureASU1](#) () const
- float [getTemperatureASU2](#) () const
- [Buffer](#) [getSlowControl](#) () const
- std::vector< [bit8_t](#) * > [getFramesVector](#) () const
- std::vector< [bit8_t](#) * > [getLinesVector](#) () const
- std::uint32_t [getSizeAfterDIFPtr](#) () const
- std::uint32_t [getEndOfDIFData](#) () const
- std::uint32_t [getDTC](#) () const
- std::uint32_t [getGTC](#) () const
- std::uint64_t [getAbsoluteBCID](#) () const
- std::uint32_t [getBCID](#) () const
- bool [hasLine](#) (const std::uint32_t &) const
- std::uint32_t [getNumberOfFrames](#) () const
- [bit8_t](#) * [getFramePtr](#) (const std::uint32_t &) const
- std::uint32_t [getFrameBCID](#) (const std::uint32_t &) const
- std::uint32_t [getFrameTimeToTrigger](#) (const std::uint32_t &) const
- bool [getFrameLevel](#) (const std::uint32_t &, const std::uint32_t &, const std::uint32_t &) const
- std::uint32_t [getDIFid](#) () const
- std::uint32_t [getASICid](#) (const std::uint32_t &) const
- std::uint32_t [getThresholdStatus](#) (const std::uint32_t &, const std::uint32_t &) const
- std::uint32_t [getDIF_CRC](#) () const

4.13.1 Detailed Description

Definition at line 36 of file [PayloadParser.h](#).

4.13.2 Constructor & Destructor Documentation

4.13.2.1 [PayloadParser](#)() `PayloadParser::PayloadParser () [default]`

4.13.3 Member Function Documentation

4.13.3.1 getAbsoluteBCID() `std::uint64_t PayloadParser::getAbsoluteBCID () const [inline]`

Definition at line 238 of file [PayloadParser.h](#).

```
00239 {
00240     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
        Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER};
00241     std::uint64_t LBC = ((begin()[shift] << 16) | (begin()[shift + 1] << 8) | (begin()[shift + 2])) *
        16777216ULL /* to shift the value from the 24 first bits*/
00242         + ((begin()[shift + 3] << 16) | (begin()[shift + 4] << 8) | (begin()[shift + 5]));
00243     return LBC;
00244 }
```

4.13.3.2 getASICid() `std::uint32_t PayloadParser::getASICid (const std::uint32_t & i) const [inline]`

Definition at line 282 of file [PayloadParser.h](#).

```
00282 { return m_Frames[i][0] & 0xFF; }
```

4.13.3.3 getBCID() `std::uint32_t PayloadParser::getBCID () const [inline]`

Definition at line 246 of file [PayloadParser.h](#).

```
00247 {
00248     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
        Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID};
00249     return (begin()[shift] << 16) + (begin()[shift + 1] << 8) + begin()[shift + 2];
00250 }
```

4.13.3.4 getDIF_CRC() `std::uint32_t PayloadParser::getDIF_CRC () const [inline]`

Definition at line 286 of file [PayloadParser.h](#).

```
00287 {
00288     std::uint32_t shift{getEndOfDIFData() - (Size::CRC_MSB + Size::CRC_LSB)};
00289     return (begin()[shift] << 8) + begin()[shift + 1];
00290 }
```

4.13.3.5 getDIFid() `std::uint32_t PayloadParser::getDIFid () const [inline]`

Definition at line 276 of file [PayloadParser.h](#).

```
00277 {
00278     std::uint32_t shift{+Size::GLOBAL_HEADER};
00279     return begin()[shift] & 0xFF;
00280 }
```

4.13.3.6 getDTC() `std::uint32_t PayloadParser::getDTC () const [inline]`

Definition at line 226 of file [PayloadParser.h](#).

```
00227 {
00228     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF};
00229     return (begin()[shift] << 24) + (begin()[shift + 1] << 16) + (begin()[shift + 2] << 8) + begin()[shift
        + 3];
00230 }
```

4.13.3.7 getEndOfDIFData() `std::uint32_t PayloadParser::getEndOfDIFData () const [inline]`

Definition at line 294 of file [PayloadParser.h](#).

```
00294 { return theGetFramePtrReturn_; }
```

4.13.3.8 getFrameBCID() `std::uint32_t PayloadParser::getFrameBCID (const std::uint32_t & i) const [inline]`

Definition at line 262 of file [PayloadParser.h](#).

```
00263 {
00264     std::uint32_t shift{+Size::MICROROC_HEADER};
00265     return GrayToBin((m_Frames[i][shift] << 16) + (m_Frames[i][shift + 1] << 8) + m_Frames[i][shift + 2]);
00266 }
```

4.13.3.9 getFrameLevel() `bool PayloadParser::getFrameLevel (const std::uint32_t & i, const std::uint32_t & ipad, const std::uint32_t & ilevel) const [inline]`

Definition at line 270 of file [PayloadParser.h](#).

```
00271 {
00272     std::uint32_t shift{Size::MICROROC_HEADER + Size::BCID};
00273     return ((m_Frames[i][shift + ((3 - ipad / 16) * 4 + (ipad % 16) / 4)] >> (7 - (((ipad % 16) % 4) * 2 + ilevel))) & 0x1);
00274 }
```

4.13.3.10 getFramePtr() `bit8_t * PayloadParser::getFramePtr (const std::uint32_t & i) const [inline]`

Definition at line 260 of file [PayloadParser.h](#).

```
00260 { return m_Frames[i]; }
```

4.13.3.11 getFramesVector() `std::vector< bit8_t * > PayloadParser::getFramesVector () const [inline]`

Definition at line 216 of file [PayloadParser.h](#).

```
00217 {
00218     return m_Frames;
00219 }
```

4.13.3.12 getFrameTimeToTrigger() `std::uint32_t PayloadParser::getFrameTimeToTrigger (const std::uint32_t & i) const [inline]`

Definition at line 268 of file [PayloadParser.h](#).

```
00268 { return getBCID() - getFrameBCID(i); }
```

4.13.3.13 `getGTC()` `std::uint32_t PayloadParser::getGTC () const [inline]`

Definition at line 232 of file [PayloadParser.h](#).

```
00233 {
00234     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
        Size::INFORMATION_COUNTER};
00235     return (begin()[shift] << 24) + (begin()[shift + 1] << 16) + (begin()[shift + 2] << 8) + begin()[shift
        + 3];
00236 }
```

4.13.3.14 `getLinesVector()` `std::vector< bit8_t * > PayloadParser::getLinesVector () const [inline]`

Definition at line 221 of file [PayloadParser.h](#).

```
00222 {
00223     return m_Lines;
00224 }
```

4.13.3.15 `getNumberOfFrames()` `std::uint32_t PayloadParser::getNumberOfFrames () const [inline]`

Definition at line 258 of file [PayloadParser.h](#).

```
00258 { return m_Frames.size(); }
```

4.13.3.16 `getSizeAfterDIFPtr()` `std::uint32_t PayloadParser::getSizeAfterDIFPtr () const [inline]`

Definition at line 292 of file [PayloadParser.h](#).

```
00292 { return size() - theGetFramePtrReturn_; }
```

4.13.3.17 `getSlowControl()` `Buffer PayloadParser::getSlowControl () const [inline]`

Definition at line 209 of file [PayloadParser.h](#).

```
00210 {
00211     if(hasSlowControl()) return Buffer(&begin()[getEndOfDIFData()], size() - getEndOfDIFData());
00212     else
00213         return Buffer();
00214 }
```

4.13.3.18 `getTemperatureASU1()` `float PayloadParser::getTemperatureASU1 () const [inline]`

Definition at line 197 of file [PayloadParser.h](#).

```
00198 {
00199     if(!hasTemperature()) throw Exception("Don't have TemperatureASU1 information");
00200     return (getTASU1() >> 3) * 0.0625;
00201 }
```

4.13.3.19 `getTemperatureASU2()` `float PayloadParser::getTemperatureASU2 () const [inline]`

Definition at line 203 of file [PayloadParser.h](#).

```
00204 {
00205     if(!hasTemperature()) throw Exception("Don't have TemperatureASU2 information");
00206     return (getTASU2() » 3) * 0.0625;
00207 }
```

4.13.3.20 `getTemperatureDIF()` `float PayloadParser::getTemperatureDIF () const [inline]`

Definition at line 191 of file [PayloadParser.h](#).

```
00192 {
00193     if(!hasTemperature()) throw Exception("Don't have TemperatureDIF information");
00194     return 0.508 * getTDIF() - 9.659;
00195 }
```

4.13.3.21 `getThresholdStatus()` `std::uint32_t PayloadParser::getThresholdStatus (`
`const std::uint32_t & i,`
`const std::uint32_t & ipad) const [inline]`

Definition at line 284 of file [PayloadParser.h](#).

```
00284 { return ((std::uint32_t)getFrameLevel(i, ipad, 1)) « 1 | ((std::uint32_t)getFrameLevel(i, ipad,
0)); }
```

4.13.3.22 `hasAnalogReadout()` `bool PayloadParser::hasAnalogReadout () const [inline]`

Definition at line 143 of file [PayloadParser.h](#).

```
00143 { return getNumberLines() != 0; }
```

4.13.3.23 `hasLine()` `bool PayloadParser::hasLine (`
`const std::uint32_t & line) const [inline]`

Definition at line 252 of file [PayloadParser.h](#).

```
00253 {
00254     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
        Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF};
00255     return ((begin())[shift] » line) & 0x1;
00256 }
```

4.13.3.24 `hasSlowControl()` `bool PayloadParser::hasSlowControl () const [inline]`

Definition at line 171 of file [PayloadParser.h](#).

```
00171 { return theGetFramePtrReturn_ != size(); }
```

4.13.3.25 hasTemperature() `bool PayloadParser::hasTemperature () const [inline]`

Definition at line 141 of file [PayloadParser.h](#).

```
00141 { return (static_cast<std::uint8_t>(begin()[0]) ==
        static_cast<std::uint8_t>(Value::GLOBAL_HEADER_TEMP)); }
```

4.13.3.26 setBuffer() `void PayloadParser::setBuffer (const Buffer & buffer) [inline]`

Definition at line 91 of file [PayloadParser.h](#).

```
00092 {
00093     set(buffer);
00094     m_Frames.clear();
00095     m_Lines.clear();
00096     theGetFramePtrReturn_ = parsePayload();
00097 }
```

The documentation for this class was generated from the following file:

- [libs/core/include/PayloadParser.h](#)

4.14 RawBufferNavigator Class Reference

class to navigate in the raw data buffer parse the header and send the payload as [Buffer](#)

```
#include <libs/core/include/RawBufferNavigator.h>
```

Public Member Functions

- [RawBufferNavigator \(\)](#)
- [~RawBufferNavigator \(\)=default](#)
- void [setBuffer](#) (const [Buffer](#) &)
- std::uint8_t [getDetectorID](#) ()
- bool [findStartOfPayload](#) ()
- std::int32_t [getStartOfPayload](#) ()
- bool [validPayload](#) ()
- [Buffer](#) [getPayload](#) ()

Static Public Member Functions

- static void [StartAt](#) (const int &start)

4.14.1 Detailed Description

class to navigate in the raw data buffer parse the header and send the payload as [Buffer](#)

Definition at line 13 of file [RawBufferNavigator.h](#).

4.14.2 Constructor & Destructor Documentation

4.14.2.1 RawBufferNavigator() RawBufferNavigator::RawBufferNavigator ()

Definition at line 16 of file [RawBufferNavigator.cc](#).

```
00016 {}
```

4.14.2.2 ~RawBufferNavigator() RawBufferNavigator::~~RawBufferNavigator () [default]

4.14.3 Member Function Documentation

4.14.3.1 findStartOfPayload() bool RawBufferNavigator::findStartOfPayload ()

Definition at line 27 of file [RawBufferNavigator.cc](#).

```
00028 {
00029     if(m_StartPayloadDone == true)
00030     {
00031         if(m_StartPayload == -1) return false;
00032         else
00033             return true;
00034     }
00035     else
00036     {
00037         m_StartPayloadDone = true;
00038         for(std::size_t i = m_Start; i < m_Buffer.size(); i++)
00039         {
00040             if(static_cast<std::uint8_t>(m_Buffer[i]) == static_cast<std::uint8_t>(Value::GLOBAL_HEADER) ||
static_cast<std::uint8_t>(m_Buffer[i]) == static_cast<std::uint8_t>(Value::GLOBAL_HEADER_TEMP))
00041             {
00042                 m_StartPayload = i;
00043                 return true;
00044             }
00045         }
00046         m_StartPayload = -1;
00047         return false;
00048     }
00049 }
```

4.14.3.2 getDetectorID() std::uint8_t RawBufferNavigator::getDetectorID ()

Definition at line 25 of file [RawBufferNavigator.cc](#).

```
00025 { return m_Buffer[0]; }
```

4.14.3.3 getPayload() Buffer RawBufferNavigator::getPayload ()

Definition at line 59 of file [RawBufferNavigator.cc](#).

```
00059 { return Buffer(&(m_Buffer.begin()[m_StartPayload]), m_Buffer.size() - m_StartPayload); }
```

4.14.3.4 `getStartOfPayload()` `std::int32_t RawBufferNavigator::getStartOfPayload ()`

Definition at line 51 of file [RawBufferNavigator.cc](#).

```
00052 {
00053     findStartOfPayload();
00054     return m_StartPayload;
00055 }
```

4.14.3.5 `setBuffer()` `void RawBufferNavigator::setBuffer (const Buffer & b)`

Definition at line 18 of file [RawBufferNavigator.cc](#).

```
00019 {
00020     m_Buffer          = b;
00021     m_StartPayload    = -1;
00022     m_StartPayloadDone = false;
00023 }
```

4.14.3.6 `StartAt()` `void RawBufferNavigator::StartAt (const int & start) [static]`

Definition at line 11 of file [RawBufferNavigator.cc](#).

```
00012 {
00013     if(start >= 0) m_Start = start;
00014 }
```

4.14.3.7 `validPayload()` `bool RawBufferNavigator::validPayload ()`

Definition at line 57 of file [RawBufferNavigator.cc](#).

```
00057 { return m_StartPayload != -1; }
```


The documentation for this class was generated from the following files:

- [libs/core/include/RawBufferNavigator.h](#)
- [libs/core/src/RawBufferNavigator.cc](#)

4.15 RawdataReader Class Reference

```
#include <libs/interface/RawDataReader/include/RawdataReader.h>
```

Inheritance diagram for RawdataReader:



Public Member Functions

- [RawdataReader](#) (const char *fileName)
- void [start](#) ()
- void [end](#) ()
- float [getFileSize](#) ()
- void [openFile](#) (const std::string &fileName)
- void [closeFile](#) ()
- bool [nextEvent](#) ()
- bool [nextDIFbuffer](#) ()
- const [Buffer](#) & [getBuffer](#) ()
- virtual [~RawdataReader](#) ()

Static Public Member Functions

- static void [setDefaultBufferSize](#) (const std::size_t &size)

Additional Inherited Members

4.15.1 Detailed Description

Definition at line 17 of file [RawdataReader.h](#).

4.15.2 Constructor & Destructor Documentation

4.15.2.1 RawdataReader() `RawdataReader::RawdataReader (const char * fileName) [explicit]`

Definition at line 18 of file [RawdataReader.cc](#).

```
00018                                     : InterfaceReader("RawdataReader", "1.0.0")
00019 {
00020     m_buf.reserve(m_BufferSize);
00021     m_Filename = fileName;
00022 }
```

4.15.2.2 ~RawdataReader() `virtual RawdataReader::~~RawdataReader () [inline], [virtual]`

Definition at line 29 of file [RawdataReader.h](#).

```
00029 { closeFile(); }
```

4.15.3 Member Function Documentation

4.15.3.1 closeFile() void RawdataReader::closeFile ()Definition at line 47 of file [RawdataReader.cc](#).

```
00048 {
00049     try
00050     {
00051         if(m_FileStream.is_open()) m_FileStream.close();
00052     }
00053     catch(const std::ios_base::failure& e)
00054     {
00055         log()->error("Caught an ios_base::failure in closeFile : {} {}", e.what(), e.code().value());
00056         throw;
00057     }
00058 }
```

4.15.3.2 end() void RawdataReader::end ()Definition at line 26 of file [RawdataReader.cc](#).

```
00026 { closeFile(); }
```

4.15.3.3 getBuffer() const Buffer & RawdataReader::getBuffer ()Definition at line 122 of file [RawdataReader.cc](#).

```
00123 {
00124     uncompress();
00125     return m_Buffer;
00126 }
```

4.15.3.4 getFileSize() float RawdataReader::getFileSize ()Definition at line 130 of file [RawdataReader.cc](#).

```
00130 { return m_FileSize; }
```

4.15.3.5 nextDIFbuffer() bool RawdataReader::nextDIFbuffer ()Definition at line 95 of file [RawdataReader.cc](#).

```
00096 {
00097     try
00098     {
00099         static int DIF_processed{0};
00100         if(DIF_processed >= m_NumberOfDIF)
00101         {
00102             DIF_processed = 0;
00103             return false;
00104         }
00105         else
00106         {
00107             DIF_processed++;
00108             std::uint32_t bsize{0};
00109             m_FileStream.read(reinterpret_cast<char*>(&bsize), sizeof(std::uint32_t));
00110             m_FileStream.read(reinterpret_cast<char*>(&m_buf[0]), bsize);
00111             m_Buffer = Buffer(m_buf);
00112         }
00113     }
00114     catch(const std::ios_base::failure& e)
00115     {
00116         log()->error("Caught an ios_base::failure in openFile : {}", e.what());
00117         return false;
00118     }
00119     return true;
00120 }
```

4.15.3.6 nextEvent() `bool RawdataReader::nextEvent ()`

Definition at line 81 of file [RawdataReader.cc](#).

```
00082 {
00083     try
00084     {
00085         m_FileStream.read(reinterpret_cast<char*>(&m_EventNumber), sizeof(std::uint32_t));
00086         m_FileStream.read(reinterpret_cast<char*>(&m_NumberOfDIF), sizeof(std::uint32_t));
00087     }
00088     catch(const std::ios_base::failure& e)
00089     {
00090         return false;
00091     }
00092     return true;
00093 }
```

4.15.3.7 openFile() `void RawdataReader::openFile (const std::string & fileName)`

Definition at line 60 of file [RawdataReader.cc](#).

```
00061 {
00062     try
00063     {
00064         m_FileStream.rdbuf()->pubsetbuf(0, 0);
00065         m_FileStream.exceptions(std::ifstream::failbit | std::ifstream::badbit);
00066         m_FileStream.open(fileName.c_str(), std::ios::in | std::ios::binary | std::ios::ate); // Start at
the end to directly calculate the size of the file then come back to beginning
00067         m_FileStream.rdbuf()->pubsetbuf(0, 0);
00068         if(m_FileStream.is_open())
00069         {
00070             setFileSize(m_FileStream.tellg());
00071             m_FileStream.seekg(0, std::ios::beg);
00072         }
00073     }
00074     catch(const std::ios_base::failure& e)
00075     {
00076         log()->error("Caught an ios_base::failure in openFile : {}", e.what());
00077         throw;
00078     }
00079 }
```

4.15.3.8 setDefaultBufferSize() `void RawdataReader::setDefaultBufferSize (const std::size_t & size) [static]`

Definition at line 16 of file [RawdataReader.cc](#).

```
00016 { m_BufferSize = size; }
```

4.15.3.9 start() `void RawdataReader::start ()`

Definition at line 24 of file [RawdataReader.cc](#).

```
00024 { openFile(m_Filename); }
```


The documentation for this class was generated from the following files:

- `libs/interface/RawDataReader/include/RawdataReader.h`
- `libs/interface/RawDataReader/src/RawdataReader.cc`

4.16 ROOTWriter Class Reference

```
#include <libs/interface/ROOT/include/ROOTWriter.h>
```

Inheritance diagram for ROOTWriter:



Public Member Functions

- [ROOTWriter](#) ()
- void [setFilename](#) (const std::string &)
- void [start](#) ()
- void [processDIF](#) (const [PayloadParser](#) &)
- void [processFrame](#) (const [PayloadParser](#) &, const std::uint32_t &frameIndex)
- void [processPadInFrame](#) (const [PayloadParser](#) &, const std::uint32_t &frameIndex, const std::uint32_t &channelIndex)
- void [processSlowControl](#) (const [Buffer](#) &)
- void [end](#) ()
- virtual void [startEvent](#) ()
- virtual void [endEvent](#) ()
- virtual void [startDIF](#) ()
- virtual void [endDIF](#) ()
- virtual void [startFrame](#) ()
- virtual void [endFrame](#) ()
- virtual void [startPad](#) ()
- virtual void [endPad](#) ()

4.16.1 Detailed Description

Definition at line 18 of file [ROOTWriter.h](#).

4.16.2 Constructor & Destructor Documentation

4.16.2.1 ROOTWriter() `ROOTWriter::ROOTWriter ()`

Definition at line 10 of file [ROOTWriter.cc](#).

```
00010 : InterfaceWriter("ROOTWriter", "1.0.0") { addCompatibility("RawdataReader", ">=1.0.0"); }
```

4.16.3 Member Function Documentation

4.16.3.1 end() void ROOTWriter::end ()

Definition at line 19 of file [ROOTWriter.cc](#).

```
00020 {  
00021     if(m_Tree) m_Tree->Write();  
00022     if(m_File)  
00023     {  
00024         m_File->Write();  
00025         m_File->Close();  
00026     }  
00027     if(m_File) delete m_File;  
00028 }
```

4.16.3.2 endDIF() void ROOTWriter::endDIF () [virtual]

Reimplemented from [Interface](#).

Definition at line 75 of file [ROOTWriter.cc](#).

```
00076 {  
00077     m_Event->addDIF(*m_DIF);  
00078     delete m_DIF;  
00079 }
```

4.16.3.3 endEvent() void ROOTWriter::endEvent () [virtual]

Reimplemented from [Interface](#).

Definition at line 63 of file [ROOTWriter.cc](#).

```
00064 {  
00065     m_Tree->Fill();  
00066     if(m_Event) delete m_Event;  
00067 }
```

4.16.3.4 endFrame() void ROOTWriter::endFrame () [virtual]

Reimplemented from [Interface](#).

Definition at line 87 of file [ROOTWriter.cc](#).

```
00088 {  
00089     m_DIF->addHit(*m_Hit);  
00090     delete m_Hit;  
00091 }
```

4.16.3.5 endPad() void ROOTWriter::endPad () [virtual]

Reimplemented from [Interface](#).

Definition at line 95 of file [ROOTWriter.cc](#).

```
00095 {}
```

4.16.3.6 processDIF() void ROOTWriter::processDIF (
const PayloadParser & d)

Definition at line 30 of file ROOTWriter.cc.

```
00031 {
00032     m_DIF->setID(d.getDIFid());
00033     m_DIF->setDTC(d.getDTC());
00034     m_DIF->setGTC(d.getGTC());
00035     m_DIF->setDIFBCID(d.getBCID());
00036     m_DIF->setAbsoluteBCID(d.getAbsoluteBCID());
00037 }
```

4.16.3.7 processFrame() void ROOTWriter::processFrame (
const PayloadParser & d,
const std::uint32_t & frameIndex)

Definition at line 39 of file ROOTWriter.cc.

```
00040 {
00041     m_Hit->setDIF(d.getDIFid());
00042     m_Hit->setASIC(d.getASICid(frameIndex));
00043     m_Hit->setDTC(d.getDTC());
00044     m_Hit->setGTC(d.getGTC());
00045     m_Hit->setDIFBCID(d.getBCID());
00046     m_Hit->setAbsoluteBCID(d.getAbsoluteBCID());
00047     m_Hit->setFrameBCID(d.getFrameBCID(frameIndex));
00048     m_Hit->setTimestamp(d.getFrameTimeToTrigger(frameIndex));
00049 }
```

4.16.3.8 processPadInFrame() void ROOTWriter::processPadInFrame (
const PayloadParser & d,
const std::uint32_t & frameIndex,
const std::uint32_t & channelIndex)

Definition at line 51 of file ROOTWriter.cc.

```
00052 {
00053     m_Hit->setChannel(channelIndex);
00054     m_Hit->setThreshold(static_cast<std::uint8_t>(d.getThresholdStatus(frameIndex, channelIndex)));
00055 }
```

4.16.3.9 processSlowControl() void ROOTWriter::processSlowControl (
const Buffer &) [inline]

Definition at line 29 of file ROOTWriter.h.

```
00029 { ; }
```

4.16.3.10 setFilename() void ROOTWriter::setFilename (
const std::string & filename)

Definition at line 8 of file ROOTWriter.cc.

```
00008 { m_Filename = filename; }
```

4.16.3.11 start() void ROOTWriter::start ()

Definition at line 12 of file [ROOTWriter.cc](#).

```
00013 {  
00014     m_File = TFile::Open(m_Filename.c_str(), "RECREATE", m_Filename.c_str(),  
        ROOT::CompressionSettings(ROOT::kZLIB, 5));  
00015     m_Tree = new TTree("RawData", "Raw SDHCAL data tree");  
00016     m_Tree->Branch("Events", &m_Event, 512000, 99);  
00017 }
```

4.16.3.12 startDIF() void ROOTWriter::startDIF () [virtual]

Reimplemented from [Interface](#).

Definition at line 69 of file [ROOTWriter.cc](#).

```
00070 {  
00071     m_DIF = new DIF();  
00072     // m_DIF->clear();  
00073 }
```

4.16.3.13 startEvent() void ROOTWriter::startEvent () [virtual]

Reimplemented from [Interface](#).

Definition at line 57 of file [ROOTWriter.cc](#).

```
00058 {  
00059     m_Event = new Event();  
00060     // m_Event->clear();  
00061 }
```

4.16.3.14 startFrame() void ROOTWriter::startFrame () [virtual]

Reimplemented from [Interface](#).

Definition at line 81 of file [ROOTWriter.cc](#).

```
00082 {  
00083     m_Hit = new Hit();  
00084     // m_Hit->clear();  
00085 }
```

4.16.3.15 startPad() void ROOTWriter::startPad () [virtual]

Reimplemented from [Interface](#).

Definition at line 93 of file [ROOTWriter.cc](#).

```
00093 {}
```


The documentation for this class was generated from the following files:

- [libs/interface/ROOT/include/ROOTWriter.h](#)
- [libs/interface/ROOT/src/ROOTWriter.cc](#)

4.17 textDump Class Reference

```
#include <libs/interface/Dump/include/textDump.h>
```

Inheritance diagram for textDump:



Public Member Functions

- [textDump](#) ()
- void [start](#) ()
- void [processDIF](#) (const [PayloadParser](#) &)
- void [processFrame](#) (const [PayloadParser](#) &, uint32_t frameIndex)
- void [processPadInFrame](#) (const [PayloadParser](#) &, uint32_t frameIndex, uint32_t channelIndex)
- void [processSlowControl](#) (Buffer)
- void [end](#) ()
- std::shared_ptr< spdlog::logger > & [print](#) ()
- void [setLevel](#) (const spdlog::level::level_enum &level)

4.17.1 Detailed Description

Definition at line 14 of file [textDump.h](#).

4.17.2 Constructor & Destructor Documentation

4.17.2.1 textDump() `textDump::textDump ()`

Definition at line 9 of file [textDump.cc](#).

```

00009             : InterfaceWriter("textDump", "1.0.0")
00010 {
00011     m_InternalLogger = std::make_shared<spdlog::logger>("textDump",
std::make_shared<spdlog::sinks::stdout_color_sink_mt>());
00012     m_InternalLogger->set_level(spdlog::level::trace);
00013     addCompatibility("RawdataReader", ">=1.0.0");
00014     addCompatibility("DIFdataExample", ">=1.0.0");
00015 }
```

4.17.3 Member Function Documentation

4.17.3.1 end() void textDump::end ()

Definition at line 33 of file [textDump.cc](#).

```
00033 { print()->info("textDump end of report"); }
```

4.17.3.2 print() std::shared_ptr< spdlog::logger > & textDump::print () [inline]

Definition at line 24 of file [textDump.h](#).

```
00024 { return m_InternalLogger; }
```

4.17.3.3 processDIF() void textDump::processDIF (const PayloadParser & d)

Definition at line 19 of file [textDump.cc](#).

```
00019 { print()->info("DIF_ID : {}, DTC : {}, GTC : {}, DIF BCID {}, Absolute BCID : {}, Nbr frames {}",
    d.getDIFid(), d.getDTC(), d.getGTC(), d.getBCID(), d.getAbsoluteBCID(), d.getNumberOfFrames()); }
```

4.17.3.4 processFrame() void textDump::processFrame (const PayloadParser & d, uint32_t frameIndex)

Definition at line 21 of file [textDump.cc](#).

```
00022 {
00023   print()->info("\tDisplaying frame number {} : ASIC ID {}, Frame BCID {}, Frame Time To Trigger
    (a.k.a timestamp) is {}", frameIndex, d.getASICid(frameIndex), d.getFrameBCID(frameIndex),
    d.getFrameTimeToTrigger(frameIndex));
00024 }
```

4.17.3.5 processPadInFrame() void textDump::processPadInFrame (const PayloadParser & d, uint32_t frameIndex, uint32_t channelIndex)

Definition at line 26 of file [textDump.cc](#).

```
00027 {
00028   if(d.getThresholdStatus(frameIndex, channelIndex) > 0) { print()->info("\t\tChannel {}, Threshold
    {} ", channelIndex, d.getThresholdStatus(frameIndex, channelIndex)); }
00029 }
```

4.17.3.6 processSlowControl() void textDump::processSlowControl (Buffer)

Definition at line 31 of file [textDump.cc](#).

```
00031 { print()->error("textDump::processSlowControl not implemented yet."); }
```

4.17.3.7 setLevel() `void textDump::setLevel (`
`const spdlog::level::level_enum & level) [inline]`

Definition at line 25 of file [textDump.h](#).

```
00025 { m_InternalLogger->set_level(level); }
```

4.17.3.8 start() `void textDump::start ()`

Definition at line 17 of file [textDump.cc](#).

```
00017 { print()->info("Will dump bunch of DIF data"); }
```

The documentation for this class was generated from the following files:

- [libs/interface/Dump/include/textDump.h](#)
- [libs/interface/Dump/src/textDump.cc](#)

4.18 Timer Class Reference

```
#include <libs/core/include/Timer.h>
```

Public Member Functions

- void [start](#) ()
- void [stop](#) ()
- float [getElapsedTime](#) ()

4.18.1 Detailed Description

Definition at line 9 of file [Timer.h](#).

4.18.2 Member Function Documentation

4.18.2.1 getElapsedTime() `float Timer::getElapsedTime () [inline]`

Definition at line 14 of file [Timer.h](#).

```
00014 { return std::chrono::duration_cast<std::chrono::microseconds>(m_StopTime - m_StartTime).count(); }
```

4.18.2.2 start() `void Timer::start () [inline]`

Definition at line 12 of file [Timer.h](#).

```
00012 { m_StartTime = std::chrono::high_resolution_clock::now(); }
```

4.18.2.3 stop() void Timer::stop () [inline]

Definition at line 13 of file [Timer.h](#).

```
00013 { m_StopTime = std::chrono::high_resolution_clock::now(); }
```


The documentation for this class was generated from the following file:

- [libs/core/include/Timer.h](#)

4.19 Version Class Reference

```
#include <libs/core/include/Version.h>
```

Inheritance diagram for Version:



Public Member Functions

- [Version](#) (const std::uint8_t &mj, const std::uint8_t &mn, const std::uint8_t &pt, const semver::prerelease &ppt=semver::prerelease::none, const std::uint8_t &prn=0) noexcept
- [Version](#) (const std::string_view &str)
- [Version](#) ()=default
- std::uint8_t [getMajor](#) ()
- std::uint8_t [getMinor](#) ()
- std::uint8_t [getPatch](#) ()
- std::string [getPreRelease](#) ()
- std::uint8_t [getPreReleaseNumber](#) ()

4.19.1 Detailed Description

Definition at line 11 of file [Version.h](#).

4.19.2 Constructor & Destructor Documentation

4.19.2.1 Version() [1/3] Version::Version (

```

    const std::uint8_t & mj,
    const std::uint8_t & mn,
    const std::uint8_t & pt,
    const semver::prerelease & prt = semver::prerelease::none,
    const std::uint8_t & prn = 0 ) [inline], [noexcept]
```

Definition at line 14 of file [Version.h](#).

```
00014 : semver::version(mj, mn, pt, prt, prn) {}
```

4.19.2.2 Version() [2/3] `Version::Version (`
`const std::string_view & str) [inline], [explicit]`

Definition at line 15 of file [Version.h](#).

```
00015 : semver::version(str) {}
```

4.19.2.3 Version() [3/3] `Version::Version () [default]`

4.19.3 Member Function Documentation

4.19.3.1 getMajor() `std::uint8_t Version::getMajor ()`

Definition at line 9 of file [Version.cc](#).

```
00009 { return major; }
```

4.19.3.2 getMinor() `std::uint8_t Version::getMinor ()`

Definition at line 11 of file [Version.cc](#).

```
00011 { return minor; }
```

4.19.3.3 getPatch() `std::uint8_t Version::getPatch ()`

Definition at line 13 of file [Version.cc](#).

```
00013 { return patch; }
```

4.19.3.4 getPreRelease() `std::string Version::getPreRelease ()`

Definition at line 15 of file [Version.cc](#).

```
00016 {  
00017     switch(prerelease_type)  
00018     {  
00019         case semver::prerelease::alpha: return "alpha";  
00020         case semver::prerelease::beta: return "beta";  
00021         case semver::prerelease::rc: return "rc";  
00022         case semver::prerelease::none: return "";  
00023         default: return "";  
00024     }  
00025 }
```

4.19.3.5 `getPreReleaseNumber()` `std::uint8_t Version::getPreReleaseNumber ()`

Definition at line 27 of file [Version.cc](#).

```
00027 { return prerelease_number; }
```

The documentation for this class was generated from the following files:

- [libs/core/include/Version.h](#)
- [libs/core/src/Version.cc](#)

5 File Documentation

5.1 [libs/core/include/Bits.h](#) File Reference

```
#include <cstdint>
#include <iosfwd>
```

Typedefs

- using [bit8_t](#) = `std::uint8_t`
- using [bit16_t](#) = `std::uint16_t`
- using [bit32_t](#) = `std::uint32_t`
- using [bit64_t](#) = `std::uint64_t`

Functions

- `std::ostream & operator<< (std::ostream &os, const bit8_t &c)`
Stream operator to print [bit8_t](#) aka `std::uint8_t` and not char or unsigned char.

5.1.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Bits.h](#).

5.1.2 Typedef Documentation

5.1.2.1 [bit16_t](#) using [bit16_t](#) = `std::uint16_t`

Definition at line 11 of file [Bits.h](#).

5.1.2.2 `bit32_t` using `bit32_t` = `std::uint32_t`

Definition at line 12 of file [Bits.h](#).

5.1.2.3 `bit64_t` using `bit64_t` = `std::uint64_t`

Definition at line 13 of file [Bits.h](#).

5.1.2.4 `bit8_t` using `bit8_t` = `std::uint8_t`

Definition at line 10 of file [Bits.h](#).

5.1.3 Function Documentation

5.1.3.1 `operator<<()` `std::ostream & operator<< (` `std::ostream & os,` `const bit8_t & c)`

Stream operator to print `bit8_t` aka `std::uint8_t` and not char or unsigned char.

Definition at line 8 of file [Bits.cc](#).

```
00008 { return os << c + 0; }
```

5.2 Bits.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <cstdint>
00008 #include <iosfwd>
00009
00010 using bit8_t = std::uint8_t; /*<! type to represent 8bits words (1 byte) */
00011 using bit16_t = std::uint16_t; /*<! type to represent 16bits words (2 bytes) */
00012 using bit32_t = std::uint32_t; /*<! type to represent 32bits words (4 bytes) */
00013 using bit64_t = std::uint64_t; /*<! type to represent 64bits words (8 bytes) */
00014
00016 std::ostream& operator<<(std::ostream& os, const bit8_t& c);
```

5.3 libs/core/include/Buffer.h File Reference

```
#include "Bits.h"
#include <array>
#include <string>
#include <vector>
```

Classes

- class [Buffer](#)

5.3.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde A.Pingault L.Mirabito

See also

<https://github.com/apingault/Trivent4HEP>

Definition in file [Buffer.h](#).

5.4 Buffer.h

[Go to the documentation of this file.](#)

```

00001
00006 #pragma once
00007
00008 #include "Bits.h"
00009
00010 #include <array>
00011 #include <string>
00012 #include <vector>
00013
00014 class Buffer
00015 {
00016 public:
00017     Buffer() : m_Buffer(nullptr), m_Size(0), m_Capacity(0) {}
00018     virtual ~Buffer() {}
00019     Buffer(const bit8_t b[], const std::size_t& i) : m_Buffer(const_cast<bit8_t*>(&b[0])), m_Size(i),
m_Capacity(i) {}
00020     Buffer(const char b[], const std::size_t& i) : m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const
bit8_t*>(&b[0])), m_Size(i * sizeof(char)), m_Capacity(i * sizeof(char)) {}
00021     template<typename T> Buffer(const std::vector<T>& rawdata) :
m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const bit8_t*>(rawdata.data()))), m_Size(rawdata.size()
* sizeof(T)), m_Capacity(rawdata.capacity() * sizeof(T)) {}
00022     template<typename T, std::size_t N> Buffer(const std::array<T, N>& rawdata) :
m_Buffer(const_cast<bit8_t*>(reinterpret_cast<const bit8_t*>(rawdata.data()))), m_Size(rawdata.size()
* sizeof(T)), m_Capacity(rawdata.size() * sizeof(T)) {}
00023
00024     std::size_t size()const { return m_Size; }
00025     std::size_t capacity()const { return m_Capacity; }
00026
00027     bool empty() { return m_Size == 0; }
00028     void set(unsigned char* b) { m_Buffer = b; }
00029     void set(const Buffer& buffer)
00030     {
00031         m_Buffer = buffer.begin();
00032         m_Size = buffer.size();
00033         m_Capacity = buffer.capacity();
00034     }
00035     bit8_t* begin()const { return m_Buffer; }
00036     bit8_t* end()const { return m_Buffer + m_Size; }
00037     bit8_t& operator[](const std::size_t& pos) { return m_Buffer[pos]; }
00038     bit8_t& operator[](const std::size_t& pos)const { return m_Buffer[pos]; }
00039
00040     void setSize(const std::size_t& size) { m_Size = size; }
00041
00042 private:
00043     bit8_t* m_Buffer{nullptr};
00044     std::size_t m_Size{0};
00045     std::size_t m_Capacity{0};
00046 };

```

5.5 libs/core/include/BufferLooper.h File Reference

```
#include "AppVersion.h"
#include "Buffer.h"
#include "BufferLooperCounter.h"
#include "DetectorId.h"
#include "Formatters.h"
#include "PayloadParser.h"
#include "RawBufferNavigator.h"
#include "Timer.h"
#include "Words.h"
#include <algorithm>
#include <cassert>
#include <fmt/color.h>
#include <map>
#include <memory>
#include <spdlog/sinks/null_sink.h>
#include <spdlog/spdlog.h>
#include <string>
#include <vector>
```

Classes

- class [BufferLooper< SOURCE, DESTINATION >](#)

5.5.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [BufferLooper.h](#).

5.6 BufferLooper.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include "AppVersion.h"
00008 #include "Buffer.h"
00009 #include "BufferLooperCounter.h"
00010 #include "DetectorId.h"
00011 #include "Formatters.h"
00012 #include "PayloadParser.h"
00013 #include "RawBufferNavigator.h"
00014 #include "Timer.h"
00015 #include "Words.h"
00016
00017 #include <algorithm>
00018 #include <cassert>
00019 #include <fmt/color.h>
00020 #include <map>
00021 #include <memory>
00022 #include <spdlog/sinks/null_sink.h>
00023 #include <spdlog/spdlog.h>
00024 #include <string>
00025 #include <vector>
00026 // function to loop on buffers
00027
```



```

00028 template<typename SOURCE, typename DESTINATION> class BufferLooper
00029 {
00030 public:
00031     BufferLooper(SOURCE& source, DESTINATION& dest, bool debug = false) : m_Source(source),
        m_Destination(dest), m_Debug(debug)
00032     {
00033         m_Logger = spdlog::create<spdlog::sinks::null_sink_mt>("streamout");
00034         if(!spdlog::get("streamout")) { spdlog::register_logger(m_Logger); }
00035         m_Source.setLogger(m_Logger);
00036         m_Destination.setLogger(m_Logger);
00037     }
00038
00039     void addSink(const spdlog::sink_ptr& sink, const spdlog::level::level_enum& level =
        spdlog::get_level())
00040     {
00041         sink->set_level(level);
00042         m_Sinks.push_back(sink);
00043         m_Logger = std::make_shared<spdlog::logger>("streamout", begin(m_Sinks), end(m_Sinks));
00044         m_Source.setLogger(m_Logger);
00045         m_Destination.setLogger(m_Logger);
00046     }
00047
00048     void loop(const std::uint32_t& m_NbrEventsToProcess = 0)
00049     {
00050         // clang-format off
00051         fmt::print(fg(fmt::color::medium_orchid) | fmt::emphasis::bold,
00052             "\n"
00053             " SSSSSSSSSSSSSSSS      tttt
        tttt\n"
00054             "SS:::::::::::::::::S ttt::t
        ttt::t\n"
00055             "S::::SSSSSS:::::S t::::t
        t::::t\n"
00056             "S::::S      SSSSSSS t::::t
        t::::t\n"
00057             "S::::S      tttttt:::::ttttttt rrrrr rrrrrrrrrr eeeeeeeeeeee aaaaaaaaaaaaaa
        mmmmmmm mmmmmmm oooooooooo uuuuuu uuuuuutttttt:::::ttttttt\n"
00058             "S::::S      t:::::ttttttt r::rrrrrrrrr ee:::::::::ee a:::::::::a
        mm::::::m m:::::mm oo:::ttttttt oo u:::u u:::ut:::::ttttttt\n"
00059             " S::::SSSS t:::::ttttttt r::rrrrrrrrr e:::eeeee:::ee aaaaaaaaaa:::a
        m:::~::~mm:::~::mo:::~::ou:::u u:::ut:::::ttttttt\n"
00060             " SS:::::SSSSStttttt:::::tttttt rrrrrrrrrrrr re:::e e:::e a:::a
        m:::~::~mm:::~::mo:::~::oooo:::ou:::u u:::utttttt:::::ttttttt\n"
00061             " SSS:::::SS t::::t r::rr r::re:::eeeee:::ee aaaaaa:::a
        m:::~::~mmmm:::~::mm:::~::mo:::~::o o:::ou:::u u:::u t::::t\n"
00062             " SSSSSS:::S t::::t r::rr rrrrrrrre:::e aa:::::::::a m:::m
        m:::~::m m:::~::mo:::~::o o:::ou:::u u:::u t::::t\n"
00063             " S::::S t::::t r::rr e:::eeeee:::ee a:::aaaa:::a m:::m
        m:::~::m m:::~::mo:::~::o o:::ou:::u u:::u t::::t\n"
00064             " S::::S t::::t ttttttr::r e:::e a:::a a:::a m:::m
        m:::~::m m:::~::mo:::~::o o:::ou:::u u:::u t::::t tttttt\n"
00065             "SSSSSSS S::::S t:::::ttttt::tr::r e:::e a:::a a:::a m:::m
        m:::~::m m:::~::mo:::~::oooo:::ou:::u u:::u t:::::ttttt::t\n"
00066             "S:::::SSSSS::::S tt:::::tttr::r e:::eeeee:::ee a:::aaaa:::a m:::m
        m:::~::m m:::~::mo:::~::oooo:::ou:::u u:::u tt:::::ttttt::t\n"
00067             "S:::::SS tt:::::tttr::r ee:::::::::e a:::aa:::am:::m
        m:::~::m m:::~::mo:::~::oooo:::ou:::u u:::u tt:::::ttttt::t\n"
00068             " SSSSSSSSSSSSSS tttttttttt rrrrrrr eeeeeeeeeeee aaaaaaaa aaammmmmmm
        mmmmmmm mmmmmmm oooooooooo uuuuuuuu uuuu tttttttttt {} \n"
00069             "\n",
00070             fmt::format(fg(fmt::color::red) | fmt::emphasis::bold, "v{}", streamout_version.to_string()));
00071         // clang-format on
00072         log()->info("*****");
00073         log()->info("Streamout Version: {}", streamout_version.to_string());
00074         log()->info("Using InterfaceReader {} version {}", m_Source.getName(),
            m_Source.getVersion().to_string());
00075         log()->info("Using InterfaceWriter {} version {}", m_Destination.getName(),
            m_Destination.getVersion().to_string());
00076
00077         if(!m_Destination.checkCompatibility(m_Source.getName(), m_Source.getVersion().to_string()))
00078         {
00079             log()->critical("{} version {} is not compatible with {} version {} ! ", m_Source.getName(),
                m_Source.getVersion().to_string(), m_Destination.getName(), m_Destination.getVersion().to_string());
00080             log()->info("Compatible Interfaces for {} are", m_Destination.getName());
00081             for(std::map<std::string, std::string>::iterator it = m_Destination.getCompatibility().begin();
                it != m_Destination.getCompatibility().end(); ++it) { log()->info("{} version {}", it->first,
                    it->second); }
00082             std::exit(-1);
00083         }
00084         if(!m_DetectorIDs.empty())
00085         {
00086             std::string ids;
00087             for(std::vector<DetectorID>::const_iterator it = m_DetectorIDs.cbegin(); it !=
                m_DetectorIDs.cend(); ++it) ids += std::to_string(static_cast<std::uint16_t>(*it)) + ";";
00088             log()->info("Detector ID(s) other than {} will be ignored", ids);
00089         }
00090         log()->info("*****");

```

```

00091     RawBufferNavigator bufferNavigator;
00092     Timer timer;
00093     timer.start();
00094     m_Source.start();
00095     m_Destination.start();
00096     while(m_Source.nextEvent() && m_NbrEventsToProcess >= m_NbrEvents)
00097     {
00098         /*****/
00099         /*** START EVENT ***/
00100         m_Source.startEvent();
00101         m_Destination.startEvent();
00102         /*****/
00103
00104         m_Logger->warn("==== Event {} =====", m_NbrEvents);
00105         while(m_Source.nextDIFbuffer())
00106         {
00107             const Buffer& buffer = m_Source.getBuffer();
00108
00109             bufferNavigator.setBuffer(buffer);
00110             if(std::find(m_DetectorIDs.begin(), m_DetectorIDs.end(),
static_cast<DetectorID>(bufferNavigator.getDetectorID())) == m_DetectorIDs.end())
00111             {
00112                 m_Logger->debug("Ignoring detector ID : {}", bufferNavigator.getDetectorID());
00113                 continue;
00114             }
00115
00116             std::int32_t idstart = bufferNavigator.getStartOfPayload();
00117             if(m_Debug && idstart == -1) m_Logger->info(to_hex(buffer));
00118             c.DIFStarter[idstart]++;
00119             if(!bufferNavigator.validPayload())
00120             {
00121                 m_Logger->error("!bufferNavigator.validBuffer()");
00122                 continue;
00123             }
00124
00125             /*****/
00126             /*** START DIF ***/
00127             m_Source.startDIF();
00128             m_Destination.startDIF();
00129             /*****/
00130             PayloadParser d;
00131             // This is really a big error so skip DIF entirely if exception occurs
00132             try
00133             {
00134                 d.setBuffer(bufferNavigator.getPayload());
00135             }
00136             catch(const Exception& e)
00137             {
00138                 m_Logger->error("{} ", e.what());
00139                 continue;
00140             }
00141
00142             if(buffer.end() != d.end()) m_Logger->error("DIF BUFFER END {} {}", fmt::ptr(buffer.end()),
fmt::ptr(d.end()));
00143             assert(buffer.end() == d.end());
00144
00145             m_Logger->error("CRC : {}", d.getDIF_CRC());
00146             c.DIFPtrValueAtReturnedPos[d.begin() [d.getEndOfDIFData()-3]]++;
00147             assert(d.begin() [d.getEndOfDIFData()-3] == 0xa0);
00148
00149
00150             c.SizeAfterDIFPtr[d.getSizeAfterDIFPtr()]++;
00151             m_Destination.processDIF(d);
00152             for(std::size_t i = 0; i < d.getNumberOfFrames(); ++i)
00153             {
00154                 /*****/
00155                 /*** START FRAME ***/
00156                 m_Source.startFrame();
00157                 m_Destination.startFrame();
00158                 /*****/
00159                 m_Destination.processFrame(d, i);
00160                 for(std::size_t j = 0; j < static_cast<std::size_t>(Hardware::NUMBER_PAD); ++j)
00161                 {
00162                     if(d.getThresholdStatus(i, j) != 0)
00163                     {
00164                         m_Source.startPad();
00165                         m_Destination.startPad();
00166                         m_Destination.processPadInFrame(d, i, j);
00167                         m_Source.endPad();
00168                         m_Destination.endPad();
00169                     }
00170                 }
00171                 /*****/
00172                 /*** END FRAME ***/
00173                 m_Source.endFrame();
00174                 m_Destination.endFrame();
00175                 /*****/

```

```

00176     }
00177     // If I want SlowControl I need to check for it first, If there is an error then it's not a
big deal just continue and say is bad SlowControl
00178     /*try
00179     {
00180     d.setSCBuffer();
00181     }
00182     catch(const Exception& e)
00183     {
00184     m_Logger->error("{} ", e.what());
00185     }
00186
00187     bool processSC = false;
00188     if(d.hasSlowControl())
00189     {
00190     c.hasSlowControl++;
00191     processSC = true;
00192     }
00193     if(d.badSCData())
00194     {
00195     c.hasBadSlowControl++;
00196     processSC = false;
00197     }
00198     if(processSC) { m_Destination.processSlowControl(d.getSCBuffer()); }*/
00199
00200     //Buffer eod = d.getEndOfAllData();
00201     //c.SizeAfterAllData[eod.size()]++;
00202     // bit8_t* debug_variable_3 = eod.end();
00203     // if(buffer.end() != debug_variable_3) m_Logger->info("END DATA BUFFER END {} {}",
fmt::ptr(buffer.end()), fmt::ptr(debug_variable_3));
00204     // assert(buffer.end() == debug_variable_3);
00205     //if(eod.size() != 0) m_Logger->info("End of Data remaining stuff : {} ", to_hex(eod));*/
00206
00207     /*int nonzeroCount = 0;
00208     for(bit8_t* it = eod.begin(); it != eod.end(); it++)
00209     if(static_cast<int>(*it) != 0) nonzeroCount++;
00210     c.NonZeroValusAtEndOfData[nonzeroCount]++;*/
00211
00212     /******
00213     *** END DIF ***
00214     m_Source.endDIF();
00215     m_Destination.endDIF();
00216     *****/
00217     } // end of DIF while loop
00218     m_Logger->warn("***** Event {} *****", m_NbrEvents);
00219     m_NbrEvents++;
00220     /******
00221     *** END EVENT ***
00222     m_Source.endEvent();
00223     m_Destination.endEvent();
00224     *****/
00225     } // end of event while loop
00226     m_Destination.end();
00227     m_Source.end();
00228     timer.stop();
00229     fmt::print(fg(fmt::color::green) | fmt::emphasis::bold, "=== elapsed time {}ms ({}ms/event)
===\n", timer.getElapsedTime() / 1000, timer.getElapsedTime() / (1000 * m_NbrEvents));
00230     }
00231     void printAllCounters() { c.printAllCounters(); }
00232     std::shared_ptr<spdlog::logger> log() { return m_Logger; }
00233
00234     void setDetectorIDs(const std::vector<DetectorID>& detectorIDs) { m_DetectorIDs = detectorIDs; }
00235
00236 private:
00237     std::vector<DetectorID> m_DetectorIDs;
00238     std::shared_ptr<spdlog::logger> m_Logger{nullptr};
00239     std::vector<spdlog::sink_ptr> m_Sinks;
00240     BufferLooperCounter c;
00241     SOURCE& m_Source{nullptr};
00242     DESTINATION& m_Destination{nullptr};
00243     bool m_Debug{false};
00244     std::uint32_t m_NbrEvents{1};
00245 };

```

5.7 libs/core/include/BufferLooperCounter.h File Reference

```

#include <map>
#include <memory>
#include <string>
#include <ios>

```

Classes

- struct [BufferLooperCounter](#)

5.7.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [BufferLooperCounter.h](#).

5.8 BufferLooperCounter.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <map>
00008 #include <memory>
00009 #include <string>
00010 #include<ios>
00011
00012 struct BufferLooperCounter
00013 {
00014 public:
00015     int             hasSlowControl    = 0;
00016     int             hasBadSlowControl = 0;
00017     std::map<int, int> DIFStarter;
00018     std::map<int, int> DIFPtrValueAtReturnedPos;
00019     std::map<int, int> SizeAfterDIFPtr;
00020     std::map<int, int> SizeAfterAllData;
00021     std::map<int, int> NonZeroValusAtEndOfData;
00022
00023     void printCounter(const std::string& description, const std::map<int, int>& m, const
std::ios_base::fmtflags& base= std::ios_base::dec);
00024     void printAllCounters();
00025 };
```

5.9 libs/core/include/DetectorId.h File Reference

```
#include <cstdint>
```

Enumerations

- enum class [DetectorID](#) : std::uint16_t { [HARDROC](#) = 100 , [HARDROC_NEW](#) = 150 , [RUNHEADER](#) = 255 }

5.9.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [DetectorId.h](#).

5.9.2 Enumeration Type Documentation

5.9.2.1 DetectorID enum class [DetectorID](#) : std::uint16_t [strong]

Enumerator

HARDROC	
HARDROC_NEW	
RUNHEADER	

Definition at line 9 of file [DetectorId.h](#).

```
00010 {
00011     HARDROC      = 100,
00012     HARDROC_NEW  = 150,
00013     RUNHEADER    = 255
00014 };
```

5.10 DetectorId.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <stdint>
00008
00009 enum class DetectorID : std::uint16_t
00010 {
00011     HARDROC      = 100,
00012     HARDROC_NEW  = 150,
00013     RUNHEADER    = 255
00014 };
```

5.11 libs/core/include/DIFSlowControl.h File Reference

```
#include <bitset>
#include <stdint>
#include <iosfwd>
#include <map>
#include <string>
```

Classes

- class [DIFSlowControl](#)

Functions

- std::string [to_string](#) (const [DIFSlowControl](#) &c)

5.11.1 Detailed Description**Copyright**

2022 G.Grenier F.Lagarde

Definition in file [DIFSlowControl.h](#).

5.11.2 Function Documentation

5.11.2.1 to_string() std::string to_string (const DIFSlowControl & c)

Definition at line 256 of file DIFSlowControl.cc.

```
00257 {
00258     std::string ret;
00259     for(std::map<int, std::map<std::string, int>>::const_iterator it = c.cbegin(); it != c.cend(); it++)
00260     {
00261         ret += "ASIC " + std::to_string(it->first) + " :\n";
00262         for(std::map<std::string, int>::const_iterator jt = (it->second).begin(); jt !=
00263             (it->second).end(); jt++) ret += jt->first + " : " + std::to_string(jt->second) + "\n";
00264     }
00265     return ret;
00266 }
```

5.12 DIFSlowControl.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <bitset>
00008 #include <cstdint>
00009 #include <iosfwd>
00010 #include <map>
00011 #include <string>
00012
00013 class DIFSlowControl
00014 {
00015 public:
00017     DIFSlowControl(const std::uint8_t& version, const std::uint8_t& DIFid, unsigned char* buf);
00023
00025     std::uint8_t getDIFid();
00026
00028
00031     std::map<int, std::map<std::string, int> getChipsMap();
00032
00034
00038     std::map<std::string, int> getChipSlowControl(const int& asicid);
00039
00041
00045     int getChipSlowControl(const std::int8_t& asicid, const std::string& param);
00046
00047     std::map<int, std::map<std::string, int>>::const_iterator cbegin()const { return m_MapSC.cbegin(); }
00048
00049     std::map<int, std::map<std::string, int>>::const_iterator cend()const { return m_MapSC.cend(); }
00050
00051 private:
00053     DIFSlowControl() = delete;
00055     void FillHR1(const int& header_shift, unsigned char* cbuf);
00057     void FillHR2(const int& header_shift, unsigned char* cbuf);
00059     void FillAsicHR1(const std::bitset<72 * 8>& bs);
00061     void FillAsicHR2(const std::bitset<109 * 8>& bs);
00062
00063     unsigned int m_DIFid{0};
00064     unsigned int m_Version{0};
00065     unsigned int m_AsicType{0}; // asicType_
00066     unsigned int m_NbrAsic{0};
00067     std::map<int, std::map<std::string, int> m_MapSC;
00068 };
00069
00070 std::string to_string(const DIFSlowControl& c);
00071 /* void setSCBuffer()
00072 {
00073     if(!hasSlowControl()) return;
00074     if(m_SCbuffer.size() != 0) return; // deja fait
00075     if(m_BadSlowControl) return;
00076     m_SCbuffer.set(&(begin()[getEndOfDIFData()]));
00077     // compute Slow Control size
00078     std::size_t maxsize{size() - getEndOfDIFData() + 1}; // should I +1 here ?
00079     uint32_t k{1}; // SC Header
```

```

00080 uint32_t      dif_ID{m_SCbuffer[1]};
00081 uint32_t      chipSize{m_SCbuffer[3]};
00082 while((dif_ID != 0x1 && m_SCbuffer[k] != 0x1 && k < maxsize) || (dif_ID == 0x1 && m_SCbuffer[k + 2]
== chipSize && k < maxsize))
00083 {
00084     k += 2; // DIF ID + ASIC Header
00085     uint32_t scsize = m_SCbuffer[k];
00086     if(scsize != 74 && scsize != 109)
00087     {
00088         k = 0;
00089         m_BadSlowControl = true;
00090         throw Exception(fmt::format("PROBLEM WITH SC SIZE {}", scsize));
00091     }
00092     k++; // skip size bit
00093     k += scsize; // skip the data
00094 }
00095 if(m_SCbuffer[k] == 0x1 && !m_BadSlowControl) m_SCbuffer.setSize(k + 1); // add the trailer
00096 else
00097 {
00098     m_BadSlowControl = true;
00099     throw Exception(fmt::format("PROBLEM SC TRAILER NOT FOUND "));
00100 }
00101 }*/

```

5.13 libs/core/include/Exception.h File Reference

```

#include <stdint>
#include <exception>
#include <string>

```

Classes

- class [Exception](#)

5.13.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Exception.h](#).

5.14 Exception.h

[Go to the documentation of this file.](#)

```

00001
00005 #pragma once
00006
00007 #include <stdint>
00008 #include <exception>
00009 #include <string>
00010
00011 class Exception
00012 {
00013 public:
00014     virtual const char* what() const noexcept { return m_What.c_str(); }
00015     explicit Exception(const std::string& message) : m_Message(message) { constructWhat(); }
00016     Exception(const std::int32_t& error, const std::string& message) : m_Error(error),
m_Message(message) { constructWhat(); }
00017     std::int32_t error() { return m_Error; }
00018     std::string message() { return m_Message; }
00019
00020 private:
00021     void constructWhat()
00022     {
00023         if(m_Error == 0) m_What = m_Message;
00024         else
00025             m_What = std::string("Error ") + std::to_string(m_Error) + std::string(" : ") + m_Message;
00026     }
00027     std::string m_What;
00028     std::string m_Message;
00029     std::int32_t m_Error{0};
00030 };

```

5.15 libs/core/include/Filesystem.h File Reference

```
#include <string>
```

Functions

- `std::string path` (`const std::string &`)
- `std::string extension` (`const std::string &`)
- `std::string filename` (`const std::string &`)

5.15.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Filesystem.h](#).

5.15.2 Function Documentation

5.15.2.1 extension() `std::string extension (`
`const std::string & file)`

Definition at line 13 of file [Filesystem.cc](#).

```
00014 {  
00015     std::size_t position = file.find_last_of(".");  
00016     return (std::string::npos == position || position == 0) ? "" : file.substr(position + 1);  
00017 }
```

5.15.2.2 filename() `std::string filename (`
`const std::string & file)`

Definition at line 19 of file [Filesystem.cc](#).

```
00020 {  
00021     std::size_t position = file.find_last_of(".");  
00022     std::size_t pos      = file.find_last_of("\\\\");  
00023     return (std::string::npos == pos) ? file.substr(0, position) : file.substr(pos + 1, position - pos  
- 1);  
00024 }
```

5.15.2.3 path() `std::string path (`
`const std::string & file)`

Definition at line 7 of file [Filesystem.cc](#).

```
00008 {  
00009     std::size_t pos = file.find_last_of("\\\\");  
00010     return (std::string::npos == pos) ? "" : file.substr(0, pos);  
00011 }
```


5.16 Filesystem.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <string>
00008
00009 std::string path(const std::string&);
00010 std::string extension(const std::string&);
00011 std::string filename(const std::string&);
```

5.17 libs/core/include/Formatters.h File Reference

```
#include "Bits.h"
#include <iosfwd>
#include <string>
```

Functions

- `std::string to_dec` (const [Buffer](#) &b, const `std::size_t` &begin=0, const `std::size_t` &end=-1)
- `std::string to_dec` (const `bit8_t` &)
- `std::string to_dec` (const `bit16_t` &)
- `std::string to_dec` (const `bit32_t` &)
- `std::string to_dec` (const `bit64_t` &)
- `std::string to_hex` (const [Buffer](#) &b, const `std::size_t` &begin=0, const `std::size_t` &end=-1)
- `std::string to_hex` (const `bit8_t` &)
- `std::string to_hex` (const `bit16_t` &)
- `std::string to_hex` (const `bit32_t` &)
- `std::string to_hex` (const `bit64_t` &)
- `std::string to_bin` (const [Buffer](#) &b, const `std::size_t` &begin=0, const `std::size_t` &end=-1)
- `std::string to_bin` (const `bit8_t` &)
- `std::string to_bin` (const `bit16_t` &)
- `std::string to_bin` (const `bit32_t` &)
- `std::string to_bin` (const `bit64_t` &)
- `std::string to_oct` (const [Buffer](#) &b, const `std::size_t` &begin=0, const `std::size_t` &end=-1)
- `std::string to_oct` (const `bit8_t` &)
- `std::string to_oct` (const `bit16_t` &)
- `std::string to_oct` (const `bit32_t` &)
- `std::string to_oct` (const `bit64_t` &)

5.17.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Formatters.h](#).

5.17.2 Function Documentation

5.17.2.1 to_bin() [1/5] std::string to_bin (
const bit16_t & b)

Definition at line 71 of file [Formatters.cc](#).

```
00071 { return fmt::format("{:#016b}", b); }
```

5.17.2.2 to_bin() [2/5] std::string to_bin (
const bit32_t & b)

Definition at line 73 of file [Formatters.cc](#).

```
00073 { return fmt::format("{:#032b}", b); }
```

5.17.2.3 to_bin() [3/5] std::string to_bin (
const bit64_t & b)

Definition at line 75 of file [Formatters.cc](#).

```
00075 { return fmt::format("{:#064b}", b); }
```

5.17.2.4 to_bin() [4/5] std::string to_bin (
const bit8_t & b)

Definition at line 69 of file [Formatters.cc](#).

```
00069 { return fmt::format("{:#08b}", b); }
```

5.17.2.5 to_bin() [5/5] std::string to_bin (
const Buffer & b,
const std::size_t & begin = 0,
const std::size_t & end = -1)

Definition at line 56 of file [Formatters.cc](#).

```
00057 {  
00058     std::size_t iend = end;  
00059     if(iend == -1) iend = b.size();  
00060     std::string ret;  
00061     for(std::size_t k = begin; k < iend; k++)  
00062     {  
00063         ret += to_bin(b[k]);  
00064         ret += " - ";  
00065     }  
00066     return ret;  
00067 }
```

5.17.2.6 to_dec() [1/5] std::string to_dec (
const bit16_t & b)

Definition at line 29 of file [Formatters.cc](#).

```
00029 { return fmt::format("{:#d}", b); }
```

5.17.2.7 to_dec() [2/5] std::string to_dec (
const bit32_t & b)

Definition at line 31 of file [Formatters.cc](#).

```
00031 { return fmt::format("{:#d}", b); }
```

5.17.2.8 to_dec() [3/5] std::string to_dec (
const bit64_t & b)

Definition at line 33 of file [Formatters.cc](#).

```
00033 { return fmt::format("{:#d}", b); }
```

5.17.2.9 to_dec() [4/5] std::string to_dec (
const bit8_t & b)

Definition at line 27 of file [Formatters.cc](#).

```
00027 { return fmt::format("{:#d}", b); }
```

5.17.2.10 to_dec() [5/5] std::string to_dec (
const Buffer & b,
const std::size_t & begin = 0,
const std::size_t & end = -1)

Definition at line 14 of file [Formatters.cc](#).

```
00015 {  
00016     std::size_t iend = end;  
00017     if(iend == -1) iend = b.size();  
00018     std::string ret;  
00019     for(std::size_t k = begin; k < iend; k++)  
00020     {  
00021         ret += to_dec(b[k]);  
00022         ret += " - ";  
00023     }  
00024     return ret;  
00025 }
```

5.17.2.11 to_hex() [1/5] std::string to_hex (
const bit16_t & b)

Definition at line 50 of file [Formatters.cc](#).

```
00050 { return fmt::format("{:#04x}", b); }
```

5.17.2.12 to_hex() [2/5] std::string to_hex (
const bit32_t & b)

Definition at line 52 of file [Formatters.cc](#).

```
00052 { return fmt::format("{:#08x}", b); }
```

5.17.2.13 to_hex() [3/5] std::string to_hex (
const bit64_t & b)

Definition at line 54 of file [Formatters.cc](#).

```
00054 { return fmt::format("{:#016x}", b); }
```

5.17.2.14 to_hex() [4/5] std::string to_hex (
const bit8_t & b)

Definition at line 48 of file [Formatters.cc](#).

```
00048 { return fmt::format("{:#02x}", b); }
```

5.17.2.15 to_hex() [5/5] std::string to_hex (
const Buffer & b,
const std::size_t & begin = 0,
const std::size_t & end = -1)

Definition at line 35 of file [Formatters.cc](#).

```
00036 {  
00037     std::size_t iend = end;  
00038     if(iend == -1) iend = b.size();  
00039     std::string ret;  
00040     for(std::size_t k = begin; k < iend; k++)  
00041     {  
00042         ret += to_hex(b[k]);  
00043         ret += " - ";  
00044     }  
00045     return ret;  
00046 }
```

5.17.2.16 to_oct() [1/5] std::string to_oct (
const bit16_t & b)

Definition at line 92 of file [Formatters.cc](#).

```
00092 { return fmt::format("{:#08o}", b); }
```

5.17.2.17 to_oct() [2/5] std::string to_oct (
const bit32_t & b)

Definition at line 94 of file [Formatters.cc](#).

```
00094 { return fmt::format("{:#016o}", b); }
```

5.17.2.18 to_oct() [3/5] std::string to_oct (
const bit64_t & b)

Definition at line 96 of file [Formatters.cc](#).

```
00096 { return fmt::format("{:#032o}", b); }
```

5.17.2.19 to_oct() [4/5] std::string to_oct (
const bit8_t & b)

Definition at line 90 of file [Formatters.cc](#).

```
00090 { return fmt::format("{:#04o}", b); }
```

5.17.2.20 to_oct() [5/5] std::string to_oct (
const Buffer & b,
const std::size_t & begin = 0,
const std::size_t & end = -1)

Definition at line 77 of file [Formatters.cc](#).

```
00078 {  
00079     std::size_t iend = end;  
00080     if(iend == -1) iend = b.size();  
00081     std::string ret;  
00082     for(std::size_t k = begin; k < iend; k++)  
00083     {  
00084         ret += to_oct(b[k]);  
00085         ret += " - ";  
00086     }  
00087     return ret;  
00088 }
```

5.18 Formatters.h

[Go to the documentation of this file.](#)

```
00001  
00005 #pragma once  
00006  
00007 #include "Bits.h"  
00008  
00009 #include <iosfwd>  
00010 #include <string>  
00011  
00012 class Buffer;  
00013  
00014 std::string to_dec(const Buffer& b, const std::size_t& begin = 0, const std::size_t& end = -1);  
00015 std::string to_dec(const bit8_t&);  
00016 std::string to_dec(const bit16_t&);  
00017 std::string to_dec(const bit32_t&);  
00018 std::string to_dec(const bit64_t&);  
00019  
00020 std::string to_hex(const Buffer& b, const std::size_t& begin = 0, const std::size_t& end = -1);  
00021 std::string to_hex(const bit8_t&);  
00022 std::string to_hex(const bit16_t&);  
00023 std::string to_hex(const bit32_t&);  
00024 std::string to_hex(const bit64_t&);  
00025  
00026 std::string to_bin(const Buffer& b, const std::size_t& begin = 0, const std::size_t& end = -1);  
00027 std::string to_bin(const bit8_t&);  
00028 std::string to_bin(const bit16_t&);  
00029 std::string to_bin(const bit32_t&);  
00030 std::string to_bin(const bit64_t&);  
00031  
00032 std::string to_oct(const Buffer& b, const std::size_t& begin = 0, const std::size_t& end = -1);  
00033 std::string to_oct(const bit8_t&);  
00034 std::string to_oct(const bit16_t&);  
00035 std::string to_oct(const bit32_t&);  
00036 std::string to_oct(const bit64_t&);
```

5.19 libs/core/include/Interface.h File Reference

```
#include "AppVersion.h"  
#include "Buffer.h"  
#include "Version.h"
```

```
#include <map>
#include <memory>
#include <semver.hpp>
#include <spdlog/logger.h>
#include <string>
```

Classes

- class [Interface](#)
- class [InterfaceReader](#)
- class [InterfaceWriter](#)

Enumerations

- enum class [InterfaceType](#) { [Unknown](#) = 0 , [Reader](#) = 1 , [Writer](#) = 2 }
template class should implement void SOURCE::start(); bool SOURCE::next(); void SOURCE::end(); const [Buffer](#)& SOURCE::getBuffer();

5.19.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Interface.h](#).

5.19.2 Enumeration Type Documentation

5.19.2.1 [InterfaceType](#) enum class [InterfaceType](#) [strong]

template class should implement void SOURCE::start(); bool SOURCE::next(); void SOURCE::end(); const [Buffer](#)& SOURCE::getBuffer();

void DESTINATION::begin(); void DESTINATION::processDIF(const DIFPtr&); void DESTINATION::processPadInFrame(const DIFPtr&,const std::uint32_t& frameIndex); void DESTINATION::processSlowControl(const [Buffer](#)&); void DESTINATION::end();

Enumerator

Unknown	
Reader	
Writer	

Definition at line 31 of file [Interface.h](#).

```

00032 {
00033     Unknown = 0,
00034     Reader  = 1,
00035     Writer  = 2
00036 };

```

5.20 Interface.h

[Go to the documentation of this file.](#)

```

00001
00004 #pragma once
00005
00006 #include "AppVersion.h"
00007 #include "Buffer.h"
00008 #include "Version.h"
00009
00010 #include <map>
00011 #include <memory>
00012 #include <semver.hpp>
00013 #include <spdlog/logger.h>
00014 #include <string>
00015
00031 enum class InterfaceType
00032 {
00033     Unknown = 0,
00034     Reader  = 1,
00035     Writer  = 2
00036 };
00037
00038 class Interface
00039 {
00040 public:
00041     Interface(const std::string& name, const std::string& version, const InterfaceType& type) :
00042         m_Name(name), m_Version(version) {}
00043     virtual ~Interface() = default;
00044     virtual void startEvent() {}
00045     virtual void endEvent() {}
00046     virtual void startDIF() {}
00047     virtual void endDIF() {}
00048     virtual void startFrame() {}
00049     virtual void endFrame() {}
00050     virtual void startPad() {}
00051     virtual void endPad() {}
00052     std::shared_ptr<spdlog::logger> log() { return m_Logger; }
00053     void setLogger(const std::shared_ptr<spdlog::logger> & logger) { m_Logger
= logger; }
00054     std::string getName() { return m_Name; }
00055     Version getVersion() { return m_Version; }
00056 private:
00057     std::shared_ptr<spdlog::logger> m_Logger{nullptr};
00058     std::string m_Name;
00059     Version m_Version;
00060     InterfaceType m_Type{InterfaceType::Unknown};
00061 };
00062
00063 class InterfaceReader : public Interface
00064 {
00065 public:
00066     InterfaceReader(const std::string& name, const std::string& version) : Interface(name, version,
InterfaceType::Reader) {}
00067     virtual ~InterfaceReader() = default;
00068
00069 protected:
00070     Buffer m_Buffer;
00071 };
00072
00073 class InterfaceWriter : public Interface
00074 {
00075 public:
00076     InterfaceWriter(const std::string& name, const std::string& version) : Interface(name, version,
InterfaceType::Writer) {}
00077
00078     void addCompatibility(const std::string& name, const std::string& version) { m_Compatible[name] =
version; }
00079
00080     std::map<std::string, std::string> getCompatibility() { return m_Compatible; }
00081
00082     bool checkCompatibility(const std::string& name, const std::string& version)
00083     {
00084         if (m_Compatible.find(name) != m_Compatible.end())
00085         {

```

```
00086         auto                ran = semver::range::detail::range(m_Compatible[name]);
00087         semver::version ver = semver::version(version);
00088         if(ran.satisfies(ver, false)) return true;
00089         else
00090             return false;
00091     }
00092     else
00093         return false;
00094 }
00095
00096 virtual ~InterfaceWriter() = default;
00097
00098 private:
00099     std::map<std::string, std::string> m_Compatible;
00100 };
```

5.21 libs/core/include/PayloadParser.h File Reference

```
#include "Bits.h"
#include "Buffer.h"
#include "Exception.h"
#include "Formatters.h"
#include "Utilities.h"
#include "Words.h"
#include <stdint>
#include <spdlog/spdlog.h>
#include <string>
#include <vector>
```

Classes

- class [PayloadParser](#)

5.21.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [PayloadParser.h](#).

5.22 PayloadParser.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include "Bits.h"
00008 #include "Buffer.h"
00009 #include "Exception.h"
00010 #include "Formatters.h"
00011 #include "Utilities.h"
00012 #include "Words.h"
00013
00014 #include <stdint>
00015 #include <spdlog/spdlog.h>
00016 #include <string>
00017 #include <vector>
00018
00036 class PayloadParser : public Buffer
00037 {
```



```

00038 public:
00039     PayloadParser() = default;
00040
00041     void setBuffer(const Buffer& buffer);
00042
00043     bool hasTemperature() const;
00044
00045     bool hasAnalogReadout() const;
00046
00047     bool hasSlowControl() const;
00048
00049     float getTemperatureDIF() const;
00050
00051     float getTemperatureASU1() const;
00052
00053     float getTemperatureASU2() const;
00054
00055     Buffer getSlowControl() const;
00056
00057     std::vector<bit8_t*> getFramesVector() const;
00058
00059     std::vector<bit8_t*> getLinesVector() const;
00060
00061     std::uint32_t getSizeAfterDIFPtr() const;
00062     std::uint32_t getEndOfDIFData() const;
00063     std::uint32_t getDTC() const;
00064     std::uint32_t getGTC() const;
00065     std::uint64_t getAbsoluteBCID() const;
00066     std::uint32_t getBCID() const;
00067     bool hasLine(const std::uint32_t&) const;
00068     std::uint32_t getNumberOfFrames() const;
00069     bit8_t* getFramePtr(const std::uint32_t&) const;
00070     std::uint32_t getFrameBCID(const std::uint32_t&) const;
00071     std::uint32_t getFrameTimeToTrigger(const std::uint32_t&) const;
00072     bool getFrameLevel(const std::uint32_t&, const std::uint32_t&, const std::uint32_t&) const;
00073     std::uint32_t getDIFid() const;
00074     std::uint32_t getASICid(const std::uint32_t&) const;
00075     std::uint32_t getThresholdStatus(const std::uint32_t&, const std::uint32_t&) const;
00076     std::uint32_t getDIF_CRC() const;
00077 private:
00078     std::uint16_t m_Version{13};
00079     std::uint32_t parsePayload();
00080     std::uint32_t getNumberLines() const;
00081     std::uint32_t parseAnalogLine(const std::uint32_t& idx);
00082     std::uint32_t getTASU1() const;
00083     std::uint32_t getTASU2() const;
00084     std::uint32_t getTDIF() const;
00085
00086     std::vector<bit8_t*> m_Lines;
00087     std::vector<bit8_t*> m_Frames;
00088     std::uint32_t theGetFramePtrReturn_{0};
00089 };
00090
00091 inline void PayloadParser::setBuffer(const Buffer& buffer)
00092 {
00093     set(buffer);
00094     m_Frames.clear();
00095     m_Lines.clear();
00096     theGetFramePtrReturn_ = parsePayload();
00097 }
00098
00099 inline std::uint32_t PayloadParser::parsePayload()
00100 {
00101     std::uint32_t fshift{static_cast<std::uint32_t>(Size::GLOBAL_HEADER)}; // Pass Global Header
00102     if(m_Version >= 13)
00103     {
00104         // Pass DIF_ID, DIF Trigger counter, Information counter, Global Trigger counter, Absolute BCID,
00105         // BCID DIF, NB line
00106         fshift += Size::DIF_IF + Size::DIF_TRIGGER_COUNTER + Size::INFORMATION_COUNTER +
00107             Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF + Size::NUMBER_LINE;
00108         // If has temperature infos then pass Temp ASU 1, Temp ASU 2, Temp DIF
00109         if(hasTemperature()) fshift += Size::TEMP_ASU1 + Size::TEMP_ASU2 + Size::TEMP_DIF;
00110         // If has AnalogReadout pass them
00111         if(hasAnalogReadout()) fshift = parseAnalogLine(fshift); // to be implemented
00112     }
00113     else
00114         throw Exception(fmt::format("Version {} is not implemented", m_Version));
00115     while(static_cast<std::uint8_t>(begin()[fshift]) !=
00116           static_cast<std::uint8_t>(Value::GLOBAL_TRAILER))
00117     {
00118         // If I found a FRAME_HEADER there is 2 cases :
00119         // 1) Nothing inside so FRAME_TRAILER comes just after
00120         // 2) Come MICROROC Header, BCID, DATA max 128 times
00121         if(static_cast<std::uint8_t>(begin()[fshift]) == static_cast<std::uint8_t>(Value::FRAME_HEADER))
00122         {
00123             fshift += +Size::FRAME_HEADER;
00124         }
00125     }

```

```

00122         if(static_cast<std::uint8_t>(begin()[fshift]) == static_cast<std::uint8_t>(Value::FRAME_TRAILER)
|| static_cast<std::uint8_t>(begin()[fshift]) ==
static_cast<std::uint8_t>(Value::FRAME_TRAILER_ERROR)) { fshift += +Size::FRAME_TRAILER; }
00123     else
00124     {
00125         while(static_cast<std::uint8_t>(begin()[fshift]) !=
static_cast<std::uint8_t>(Value::FRAME_TRAILER) && static_cast<std::uint8_t>(begin()[fshift]) !=
static_cast<std::uint8_t>(Value::FRAME_TRAILER_ERROR))
00126         {
00127             m_Frames.push_back(&begin()[fshift]);
00128             fshift += Size::MICROROC_HEADER + Size::BCID + Size::DATA;
00129         }
00130         fshift += +Size::FRAME_TRAILER;
00131     }
00132 }
00133 }
00134 // Pass Global trailer
00135 fshift += +Size::GLOBAL_TRAILER;
00136 // Pass CRC MSB, CRC LSB
00137 fshift += Size::CRC_MSB + Size::CRC_LSB;
00138 return fshift;
00139 }
00140
00141 inline bool PayloadParser::hasTemperature()const { return (static_cast<std::uint8_t>(begin()[0]) ==
static_cast<std::uint8_t>(Value::GLOBAL_HEADER_TEMP)); }
00142
00143 inline bool PayloadParser::hasAnalogReadout()const { return getNumberLines() != 0; }
00144
00145 inline std::uint32_t PayloadParser::getNumberLines()const
00146 {
00147     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF};
00148     return ((begin()[shift] >> 4) & 0x5);
00149 }
00150
00151 inline std::uint32_t PayloadParser::parseAnalogLine(const std::uint32_t& idx)
00152 {
00153     std::uint32_t fshift{idx};
00154     // Pass Header line
00155     if(static_cast<std::uint8_t>(begin()[fshift]) != static_cast<std::uint8_t>(Value::HEADER_LINE))
return fshift;
00156     else
00157         fshift += +Size::HEADER_LINE;
00158     while(static_cast<std::uint8_t>(begin()[fshift]) != static_cast<std::uint8_t>(Value::TRAILER_LINE))
00159     {
00160         m_Lines.push_back(&begin()[fshift]);
00161         // Get Number of CHIPS
00162         std::uint32_t nchip{begin()[fshift]};
00163         // Pass Number of CHIPS, NB AsicLine*64*16bits
00164         fshift += +Size::NUMBER_CHIPS + static_cast<std::uint32_t>(Size::LINE_SIZE) * nchip;
00165     }
00166     // Pass Trailer line
00167     fshift += +Size::TRAILER_LINE;
00168     return fshift;
00169 }
00170
00171 inline bool PayloadParser::hasSlowControl()const { return theGetFramePtrReturn_ != size(); }
00172
00173 inline std::uint32_t PayloadParser::getTASU1()const
00174 {
00175     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF +
Size::NUMBER_LINE};
00176     return (begin()[shift] << 24) + (begin()[shift + 1] << 16) + (begin()[shift + 2] << 8) + begin()[shift
+ 3];
00177 }
00178
00179 inline std::uint32_t PayloadParser::getTASU2()const
00180 {
00181     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF +
Size::NUMBER_LINE + Size::TEMP_ASU1};
00182     return (begin()[shift] << 24) + (begin()[shift + 1] << 16) + (begin()[shift + 2] << 8) + begin()[shift
+ 3];
00183 }
00184
00185 inline std::uint32_t PayloadParser::getTDIF()const
00186 {
00187     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF +
Size::NUMBER_LINE + Size::TEMP_ASU1 + Size::TEMP_ASU2};
00188     return begin()[shift];
00189 }
00190
00191 inline float PayloadParser::getTemperatureDIF()const
00192 {
00193     if(!hasTemperature()) throw Exception("Don't have TemperatureDIF information");

```

```

00194     return 0.508 * getTDIF() - 9.659;
00195 }
00196
00197 inline float PayloadParser::getTemperatureASU1() const
00198 {
00199     if(!hasTemperature()) throw Exception("Don't have TemperatureASU1 information");
00200     return (getTASU1() » 3) * 0.0625;
00201 }
00202
00203 inline float PayloadParser::getTemperatureASU2() const
00204 {
00205     if(!hasTemperature()) throw Exception("Don't have TemperatureASU2 information");
00206     return (getTASU2() » 3) * 0.0625;
00207 }
00208
00209 inline Buffer PayloadParser::getSlowControl() const
00210 {
00211     if(hasSlowControl()) return Buffer(&begin()[getEndOfDIFData()], size() - getEndOfDIFData());
00212     else
00213         return Buffer();
00214 }
00215
00216 inline std::vector<bit8_t*> PayloadParser::getFramesVector() const
00217 {
00218     return m_Frames;
00219 }
00220
00221 inline std::vector<bit8_t*> PayloadParser::getLinesVector() const
00222 {
00223     return m_Lines;
00224 }
00225
00226 inline std::uint32_t PayloadParser::getDTC() const
00227 {
00228     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF};
00229     return (begin()[shift] « 24) + (begin()[shift + 1] « 16) + (begin()[shift + 2] « 8) + begin()[shift
+ 3];
00230 }
00231
00232 inline std::uint32_t PayloadParser::getGTC() const
00233 {
00234     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER};
00235     return (begin()[shift] « 24) + (begin()[shift + 1] « 16) + (begin()[shift + 2] « 8) + begin()[shift
+ 3];
00236 }
00237
00238 inline std::uint64_t PayloadParser::getAbsoluteBCID() const
00239 {
00240     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER};
00241     std::uint64_t LBC = ((begin()[shift] « 16) | (begin()[shift + 1] « 8) | (begin()[shift + 2])) *
16777216ULL /* to shift the value from the 24 first bits*/
+ ((begin()[shift + 3] « 16) | (begin()[shift + 4] « 8) | (begin()[shift + 5]));
00242     return LBC;
00243 }
00244 }
00245
00246 inline std::uint32_t PayloadParser::getBCID() const
00247 {
00248     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID};
00249     return (begin()[shift] « 16) + (begin()[shift + 1] « 8) + begin()[shift + 2];
00250 }
00251
00252 inline bool PayloadParser::hasLine(const std::uint32_t& line) const
00253 {
00254     std::uint32_t shift{Size::GLOBAL_HEADER + Size::DIF_IF + Size::DIF_TRIGGER_COUNTER +
Size::INFORMATION_COUNTER + Size::GLOBAL_TRIGGER_COUNTER + Size::ABSOLUTE_BCID + Size::BCID_DIF};
00255     return ((begin()[shift] » line) & 0x1);
00256 }
00257
00258 inline std::uint32_t PayloadParser::getNumberOfFrames() const { return m_Frames.size(); }
00259
00260 inline bit8_t* PayloadParser::getFramePtr(const std::uint32_t& i) const { return m_Frames[i]; }
00261
00262 inline std::uint32_t PayloadParser::getFrameBCID(const std::uint32_t& i) const
00263 {
00264     std::uint32_t shift{+Size::MICROROC_HEADER};
00265     return GrayToBin((m_Frames[i][shift] « 16) + (m_Frames[i][shift + 1] « 8) + m_Frames[i][shift + 2]);
00266 }
00267
00268 inline std::uint32_t PayloadParser::getFrameTimeToTrigger(const std::uint32_t& i) const { return
getBCID() - getFrameBCID(i); }
00269
00270 inline bool PayloadParser::getFrameLevel(const std::uint32_t& i, const std::uint32_t& ipad, const
std::uint32_t& ilevel) const
00271 {

```

```

00272     std::uint32_t shift{Size::MICROROC_HEADER + Size::BCID};
00273     return ((m_Frames[i][shift + ((3 - ipad / 16) * 4 + (ipad % 16) / 4)] >> (7 - ((ipad % 16) % 4) * 2
+ ilevel))) & 0x1);
00274 }
00275
00276 inline std::uint32_t PayloadParser::getDIFid() const
00277 {
00278     std::uint32_t shift{+Size::GLOBAL_HEADER};
00279     return begin()[shift] & 0xFF;
00280 }
00281
00282 inline std::uint32_t PayloadParser::getASICid(const std::uint32_t& i) const { return m_Frames[i][0] &
0xFF; }
00283
00284 inline std::uint32_t PayloadParser::getThresholdStatus(const std::uint32_t& i, const std::uint32_t&
ipad) const { return (((std::uint32_t) getFrameLevel(i, ipad, 1)) << 1) |
((std::uint32_t) getFrameLevel(i, ipad, 0)); }
00285
00286 inline std::uint32_t PayloadParser::getDIF_CRC() const
00287 {
00288     std::uint32_t shift{getEndOfDIFData() - (Size::CRC_MSB + Size::CRC_LSB)};
00289     return (begin()[shift] << 8) + begin()[shift + 1];
00290 }
00291
00292 inline std::uint32_t PayloadParser::getSizeAfterDIFPtr() const { return size() - theGetFramePtrReturn_;
}
00293
00294 inline std::uint32_t PayloadParser::getEndOfDIFData() const { return theGetFramePtrReturn_; }

```

5.23 libs/core/include/RawBufferNavigator.h File Reference

```
#include "Buffer.h"
```

Classes

- class [RawBufferNavigator](#)

class to navigate in the raw data buffer parse the header and send the payload as [Buffer](#)

5.23.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [RawBufferNavigator.h](#).

5.24 RawBufferNavigator.h

[Go to the documentation of this file.](#)

```

00001
00005 #pragma once
00006
00007 #include "Buffer.h"
00008
00013 class RawBufferNavigator
00014 {
00015 public:
00016     static void StartAt(const int& start);
00017     RawBufferNavigator();
00018     ~RawBufferNavigator() = default;
00019     void setBuffer(const Buffer&);
00020     std::uint8_t getDetectorID();
00021     bool findStartOfPayload();
00022     std::int32_t getStartOfPayload();
00023     bool validPayload();
00024     Buffer getPayload();
00025
00026 private:
00027     static int m_Start;
00028     Buffer m_Buffer;
00029     bool m_StartPayloadDone{false};
00030     std::int32_t m_StartPayload{-1}; // -1 Means not found !
00031 };

```

5.25 libs/core/include/Timer.h File Reference

```
#include <chrono>
```

Classes

- class [Timer](#)

5.25.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Timer.h](#).

5.26 Timer.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <chrono>
00008
00009 class Timer
00010 {
00011 public:
00012     void start() { m_StartTime = std::chrono::high_resolution_clock::now(); }
00013     void stop() { m_StopTime = std::chrono::high_resolution_clock::now(); }
00014     float getElapsedTime() { return std::chrono::duration_cast<std::chrono::microseconds>(m_StopTime -
m_StartTime).count(); }
00015
00016 private:
00017     std::chrono::time_point<std::chrono::high_resolution_clock> m_StartTime;
00018     std::chrono::time_point<std::chrono::high_resolution_clock> m_StopTime;
00019 };
```

5.27 libs/core/include/Utilities.h File Reference

```
#include <cstdint>
```

Functions

- `std::uint64_t GrayToBin (const std::uint64_t &n)`

5.27.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Utilities.h](#).

5.27.2 Function Documentation

5.27.2.1 GrayToBin() `std::uint64_t GrayToBin (const std::uint64_t & n) [inline]`

Definition at line 9 of file [Utilities.h](#).

```
00010 {
00011     std::uint64_t ish{1};
00012     std::uint64_t anss{n};
00013     std::uint64_t idiv{0};
00014     std::uint64_t ishmax{sizeof(std::uint64_t) * 8};
00015     while(true)
00016     {
00017         idiv = anss » ish;
00018         anss ^= idiv;
00019         if(idiv <= 1 || ish == ishmax) return anss;
00020         ish «= 1;
00021     }
00022 }
```

5.28 Utilities.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <cstdint>
00008
00009 inline std::uint64_t GrayToBin(const std::uint64_t& n)
00010 {
00011     std::uint64_t ish{1};
00012     std::uint64_t anss{n};
00013     std::uint64_t idiv{0};
00014     std::uint64_t ishmax{sizeof(std::uint64_t) * 8};
00015     while(true)
00016     {
00017         idiv = anss » ish;
00018         anss ^= idiv;
00019         if(idiv <= 1 || ish == ishmax) return anss;
00020         ish «= 1;
00021     }
00022 }
```

5.29 libs/core/include/Version.h File Reference

```
#include <cstdint>
#include <semver.hpp>
#include <string>
```

Classes

- class [Version](#)

5.29.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Version.h](#).

5.30 Version.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <cstdint>
00008 #include <semver.hpp>
00009 #include <string>
00010
00011 class Version : public semver::version
00012 {
00013 public:
00014     Version(const std::uint8_t& mj, const std::uint8_t& mn, const std::uint8_t& pt, const
semver::prerelease& prt = semver::prerelease::none, const std::uint8_t& prn = 0) noexcept :
semver::version(mj, mn, pt, prt, prn) {}
00015     explicit Version(const std::string_view& str) : semver::version(str) {}
00016     Version() = default;
00017     std::uint8_t getMajor();
00018     std::uint8_t getMinor();
00019     std::uint8_t getPatch();
00020     std::string getPreRelease();
00021     std::uint8_t getPreReleaseNumber();
00022 };
```

5.31 libs/core/include/Words.h File Reference

```
#include <cstdint>
```

Enumerations

- enum class [Hardware](#) : std::uint8_t { [NUMBER_PAD](#) = 64 }
- enum class [Size](#) : std::uint8_t {
[DATA_FORMAT_VERSION](#) = 1 , [DAQ_SOFTWARE_VERSION](#) = 2 , [SDCC_FIRMWARE_VERSION](#) = 2 ,
[DIF_FIRMWARE_VERSION](#) = 2 ,
[TIMESTAMP_SECONDES](#) = 4 , [TIMESTAMP_MILLISECONDS](#) = 4 , [GLOBAL_HEADER](#) = 1 , [DIF_IF](#) = 1 ,
[DIF_TRIGGER_COUNTER](#) = 4 , [INFORMATION_COUNTER](#) = 4 , [GLOBAL_TRIGGER_COUNTER](#) = 4 ,
[ABSOLUTE_BCID](#) = 6 ,
[BCID_DIF](#) = 3 , [NUMBER_LINE](#) = 1 , [TEMP_ASU1](#) = 4 , [TEMP_ASU2](#) = 4 ,
[TEMP_DIF](#) = 1 , [HEADER_LINE](#) = 1 , [NUMBER_CHIPS](#) = 1 , [LINE_SIZE](#) = 64 * 2 ,
[TRAILER_LINE](#) = 1 , [FRAME_HEADER](#) = 1 , [MICROROC_HEADER](#) = 1 , [BCID](#) = 3 ,
[DATA](#) = 16 , [FRAME_TRAILER](#) = 1 , [GLOBAL_TRAILER](#) = 1 , [CRC_MSB](#) = 1 ,
[CRC_LSB](#) = 1 , [SC_HEADER](#) = 1 , [DIF_ID](#) = 1 , [ASIC_HEADER](#) = 1 ,
[SC_ASIC_SIZE](#) = 1 , [SC_TRAILER](#) = 1 }
- enum class [Value](#) : std::uint8_t {
[GLOBAL_HEADER](#) = 0xb0 , [GLOBAL_HEADER_TEMP](#) = 0xbb , [HEADER_LINE](#) = 0xc4 , [TRAILER_LINE](#) =
0xd4 ,
[FRAME_HEADER](#) = 0xb4 , [FRAME_TRAILER](#) = 0xa3 , [FRAME_TRAILER_ERROR](#) = 0xc3 ,
[GLOBAL_TRAILER](#) = 0xa0 ,
[SC_HEADER](#) = 0xb1 , [SC_TRAILER](#) = 0xa1 }

5.31.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Words.h](#).

5.31.2 Enumeration Type Documentation

5.31.2.1 Hardware `enum class Hardware : std::uint8_t [strong]`

Enumerator

NUMBER_PAD	
------------	--

Definition at line 9 of file [Words.h](#).

```
00010 {  
00011     NUMBER_PAD = 64,  
00012 };
```

5.31.2.2 Size `enum class Size : std::uint8_t [strong]`

Enumerator

DATA_FORMAT_VERSION	
DAQ_SOFTWARE_VERSION	
SDCC_FIRMWARE_VERSION	
DIF_FIRMWARE_VERSION	
TIMESTAMP_SECONDES	
TIMESTAMP_MILLISECONDS	
GLOBAL_HEADER	
DIF_IF	
DIF_TRIGGER_COUNTER	
INFORMATION_COUNTER	
GLOBAL_TRIGGER_COUNTER	
ABSOLUTE_BCID	
BCID_DIF	
NUMBER_LINE	
TEMP_ASU1	
TEMP_ASU2	
TEMP_DIF	
HEADER_LINE	
NUMBER_CHIPS	
LINE_SIZE	
TRAILER_LINE	
FRAME_HEADER	
MICROROC_HEADER	
BCID	
DATA	
FRAME_TRAILER	
GLOBAL_TRAILER	
CRC_MSB	
CRC_LSB	
SC_HEADER	

Enumerator

DIF_ID	
ASIC_HEADER	
SC_ASIC_SIZE	
SC_TRAILER	

Definition at line 14 of file [Words.h](#).

```

00015 {
00016     // Header
00017     DATA_FORMAT_VERSION    = 1,
00018     DAQ_SOFTWARE_VERSION    = 2,
00019     SDCC_FIRMWARE_VERSION   = 2,
00020     DIF_FIRMWARE_VERSION    = 2,
00021     TIMESTAMP_SECONDS        = 4,
00022     TIMESTAMP_MILLISECONDS   = 4,
00023     // Payload
00024     GLOBAL_HEADER            = 1,
00025     DIF_IF                   = 1,
00026     DIF_TRIGGER_COUNTER      = 4,
00027     INFORMATION_COUNTER      = 4,
00028     GLOBAL_TRIGGER_COUNTER   = 4,
00029     ABSOLUTE_BCID            = 6,
00030     BCID_DIF                 = 3,
00031     NUMBER_LINE              = 1,
00032     TEMP_ASU1                = 4,
00033     TEMP_ASU2                = 4,
00034     TEMP_DIF                 = 1,
00035     HEADER_LINE              = 1,
00036     NUMBER_CHIPS             = 1,
00037     LINE_SIZE                 = 64 * 2,
00038     TRAILER_LINE             = 1,
00039     FRAME_HEADER             = 1,
00040     MICROROC_HEADER          = 1,
00041     BCID                     = 3,
00042     DATA                    = 16,
00043     FRAME_TRAILER            = 1,
00044     GLOBAL_TRAILER           = 1,
00045     CRC_MSB                  = 1,
00046     CRC_LSB                  = 1,
00047     // Slowcontrol
00048     SC_HEADER                = 1,
00049     DIF_ID                   = 1,
00050     ASIC_HEADER              = 1,
00051     SC_ASIC_SIZE             = 1,
00052     SC_TRAILER               = 1
00053 };

```

5.31.2.3 Value `enum class Value : std::uint8_t [strong]`

Enumerator

GLOBAL_HEADER	
GLOBAL_HEADER_TEMP	
HEADER_LINE	
TRAILER_LINE	
FRAME_HEADER	
FRAME_TRAILER	
FRAME_TRAILER_ERROR	
GLOBAL_TRAILER	
SC_HEADER	
SC_TRAILER	

Definition at line 59 of file [Words.h](#).

```

00060 {
00061     GLOBAL_HEADER      = 0xb0,
00062     GLOBAL_HEADER_TEMP = 0xbb,
00063     HEADER_LINE        = 0xc4,
00064     TRAILER_LINE       = 0xd4,
00065     FRAME_HEADER       = 0xb4,
00066     FRAME_TRAILER      = 0xa3,
00067     FRAME_TRAILER_ERROR = 0xc3,
00068     GLOBAL_TRAILER     = 0xa0,
00069     SC_HEADER          = 0xb1,
00070     SC_TRAILER         = 0xa1
00071 };

```

5.32 Words.h

[Go to the documentation of this file.](#)

```

00001
00005 #pragma once
00006
00007 #include <cstdint>
00008
00009 enum class Hardware : std::uint8_t
00010 {
00011     NUMBER_PAD = 64,
00012 };
00013
00014 enum class Size : std::uint8_t
00015 {
00016     // Header
00017     DATA_FORMAT_VERSION = 1,
00018     DAQ_SOFTWARE_VERSION = 2,
00019     SDCC_FIRMWARE_VERSION = 2,
00020     DIF_FIRMWARE_VERSION = 2,
00021     TIMESTAMP_SECONDES = 4,
00022     TIMESTAMP_MILLISECONDS = 4,
00023     // Payload
00024     GLOBAL_HEADER = 1,
00025     DIF_IF = 1,
00026     DIF_TRIGGER_COUNTER = 4,
00027     INFORMATION_COUNTER = 4,
00028     GLOBAL_TRIGGER_COUNTER = 4,
00029     ABSOLUTE_BCID = 6,
00030     BCID_DIF = 3,
00031     NUMBER_LINE = 1,
00032     TEMP_ASU1 = 4,
00033     TEMP_ASU2 = 4,
00034     TEMP_DIF = 1,
00035     HEADER_LINE = 1,
00036     NUMBER_CHIPS = 1,
00037     LINE_SIZE = 64 * 2,
00038     TRAILER_LINE = 1,
00039     FRAME_HEADER = 1,
00040     MICROROC_HEADER = 1,
00041     BCID = 3,
00042     DATA = 16,
00043     FRAME_TRAILER = 1,
00044     GLOBAL_TRAILER = 1,
00045     CRC_MSB = 1,
00046     CRC_LSB = 1,
00047     // Slowcontrol
00048     SC_HEADER = 1,
00049     DIF_ID = 1,
00050     ASIC_HEADER = 1,
00051     SC_ASIC_SIZE = 1,
00052     SC_TRAILER = 1
00053 };
00054
00055 static inline std::uint32_t operator+(const Size& a, const Size& b) { return
    static_cast<std::uint32_t>(a) + static_cast<std::uint32_t>(b); }
00056 static inline std::uint32_t operator+(const std::uint32_t& a, const Size& b) { return a +
    static_cast<std::uint32_t>(b); }
00057 static inline std::uint32_t operator+(const Size& a) { return static_cast<std::uint32_t>(a); }
00058
00059 enum class Value : std::uint8_t
00060 {
00061     GLOBAL_HEADER      = 0xb0,
00062     GLOBAL_HEADER_TEMP = 0xbb,
00063     HEADER_LINE        = 0xc4,
00064     TRAILER_LINE       = 0xd4,
00065     FRAME_HEADER       = 0xb4,
00066     FRAME_TRAILER      = 0xa3,
00067     FRAME_TRAILER_ERROR = 0xc3,

```

```

00068 GLOBAL_TRAILER    = 0xa0,
00069 SC_HEADER          = 0xb1,
00070 SC_TRAILER          = 0xa1
00071 };

```

5.33 `libs/core/src/Bits.cc` File Reference

```
#include "Bits.h"
```

Functions

- `std::ostream & operator<< (std::ostream &os, const bit8_t &c)`
Stream operator to print `bit8_t` aka `std::uint8_t` and not char or unsigned char.

5.33.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file `Bits.cc`.

5.33.2 Function Documentation

5.33.2.1 `operator<<()` `std::ostream & operator<< (`
`std::ostream & os,`
`const bit8_t & c)`

Stream operator to print `bit8_t` aka `std::uint8_t` and not char or unsigned char.

Definition at line 8 of file `Bits.cc`.

```
00008 { return os << c + 0; }
```

5.34 `Bits.cc`

[Go to the documentation of this file.](#)

```

00001
00006 #include "Bits.h"
00007
00008 std::ostream& operator<<(std::ostream& os, const bit8_t& c) { return os << c + 0; }

```

5.35 `libs/core/src/BufferLooperCounter.cc` File Reference

```

#include "BufferLooperCounter.h"
#include "Formatters.h"
#include <fmt/color.h>

```

5.36 BufferLooperCounter.cc

[Go to the documentation of this file.](#)

```
00001
00005 #include "BufferLooperCounter.h"
00006 #include "Formatters.h"
00007
00008 #include <fmt/color.h>
00009
00010 void BufferLooperCounter::printAllCounters()
00011 {
00012     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, "BUFFER LOOP FINAL STATISTICS : \n");
00013     printCounter("Start of DIF header", DIFStarter);
00014     printCounter("Value after DIF data are processed", DIFPtrValueAtReturnedPos, std::ios_base::hex);
00015     printCounter("Size remaining in buffer after end of DIF data", SizeAfterDIFPtr);
00016     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, "Number of Slow Control found {} out of
which {} are bad\n", hasSlowControl, hasBadSlowControl);
00017     printCounter("Size remaining after all of data have been processed", SizeAfterAllData);
00018     printCounter("Number on non zero values in end of data buffer", NonZeroValusAtEndOfData);
00019 }
00020
00021 void BufferLooperCounter::printCounter(const std::string& description, const std::map<int, int>&
m, const std::ios_base::fmtflags& base)
00022 {
00023     std::string out{"statistics for " + description + " : \n"};
00024     for(std::map<int, int>::const_iterator it = m.begin(); it != m.end(); it++)
00025     {
00026         if(it != m.begin()) out += ",";
00027         out += " [";
00028         switch(base)
00029         {
00030             case std::ios_base::dec:
00031                 out += to_dec(static_cast<std::uint32_t>(it->first));
00032                 break;
00033             case std::ios_base::hex:
00034                 out += to_hex(static_cast<std::uint32_t>(it->first));
00035                 break;
00036             case std::ios_base::oct:
00037                 out += to_oct(static_cast<std::uint32_t>(it->first));
00038                 break;
00039             default:
00040                 out += to_dec(static_cast<std::uint32_t>(it->first));
00041                 break;
00042         }
00043         out += "]=" + std::to_string(it->second);
00044     }
00045     out += "\n";
00046     fmt::print(fg(fmt::color::crimson) | fmt::emphasis::bold, out);
00047 }
```

5.37 libs/core/src/DIFSlowControl.cc File Reference

```
#include "DIFSlowControl.h"
```

Functions

- std::string [to_string](#) (const [DIFSlowControl](#) &c)

5.37.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [DIFSlowControl.cc](#).

5.37.2 Function Documentation

5.37.2.1 to_string() std::string to_string (const DIFSlowControl & c)

Definition at line 256 of file DIFSlowControl.cc.

```
00257 {
00258     std::string ret;
00259     for(std::map<int, std::map<std::string, int>>::const_iterator it = c.cbegin(); it != c.cend(); it++)
00260     {
00261         ret += "ASIC " + std::to_string(it->first) + " :\n";
00262         for(std::map<std::string, int>::const_iterator jt = (it->second).begin(); jt !=
00263             (it->second).end(); jt++) ret += jt->first + " : " + std::to_string(jt->second) + "\n";
00264     }
00265     return ret;
00266 }
```

5.38 DIFSlowControl.cc

[Go to the documentation of this file.](#)

```
00001
00005 #include "DIFSlowControl.h"
00006
00007 DIFSlowControl::DIFSlowControl(const std::uint8_t& version, const std::uint8_t& DIFId, unsigned char*
00008     cbuf) : m_Version(version), m_DIFId(DIFId), m_AsicType(2)
00009 {
00010     if(cbuf[0] != 0xb1) return;
00011     int header_shift(6);
00012     if(m_Version < 8) m_NbrAsic = cbuf[5];
00013     else
00014     {
00015         m_DIFId = cbuf[1];
00016         m_NbrAsic = cbuf[2];
00017         header_shift = 3;
00018     }
00019     int size_hardroc1 = m_NbrAsic * 72 + header_shift + 1;
00020     if(cbuf[size_hardroc1 - 1] != 0xal) size_hardroc1 = 0;
00021     int size_hardroc2 = m_NbrAsic * 109 + header_shift + 1;
00022     if(cbuf[size_hardroc2 - 1] != 0xal) size_hardroc2 = 0;
00023     if(size_hardroc1 != 0)
00024     {
00025         FillHR1(header_shift, cbuf);
00026         m_AsicType = 1;
00027     }
00028     else if(size_hardroc2 != 0)
00029     {
00030         FillHR2(header_shift, cbuf);
00031     }
00032     return;
00033 }
00034 inline std::uint8_t DIFSlowControl::getDIFId() { return m_DIFId; }
00035
00036 inline std::map<int, std::map<std::string, int> DIFSlowControl::getChipsMap() { return m_MapSC; }
00037
00038 inline std::map<std::string, int> DIFSlowControl::getChipSlowControl(const int& asicid) { return
00039     m_MapSC[asicid]; }
00040
00041 inline int DIFSlowControl::getChipSlowControl(const std::int8_t& asicid, const std::string& param) {
00042     return getChipSlowControl(asicid)[param]; }
00043
00044 void DIFSlowControl::FillHR1(const int& header_shift, unsigned char* cbuf)
00045 {
00046     int nasic(cbuf[header_shift - 1]);
00047     int idx(header_shift);
00048     for(int k = 0; k < nasic; k++)
00049     {
00050         std::bitset<72 * 8> bs;
00051         // printf("%x %x \n", cbuf[idx+k*72+69], cbuf[idx+k*72+70]);
00052         for(int l = 71; l >= 0; l--)
00053         {
00054             // printf("%d %x : %d -->", l, cbuf[idx+k*72+l], (71-l)*8);
00055             for(int m = 0; m < 8; m++)
00056             {
00057                 // ...
00058             }
00059         }
00060     }
00061 }
```

```

00055         if(((1 < m) & cbuf[idx + k * 72 + 1]) != 0) bs.set((71 - 1) * 8 + m, 1);
00056     else
00057         bs.set((71 - 1) * 8 + m, 0);
00058     // printf("%d", (int) bs[(71-1)*8+m]);
00059 }
00060 // printf("\n");
00061 }
00062 FillAsicHR1(bs);
00063 }
00064 }
00065
00066 void DIFSlowControl::FillHR2(const int& header_shift, unsigned char* cbuf)
00067 {
00068     // int scsizer=cbuf[header_shift-1]*109+(header_shift-1)+2;
00069     int nasic{cbuf[header_shift - 1]};
00070     int idx{header_shift};
00071     // std::cout<<" DIFSlowControl::FillHR nasic "<nasic<<std::endl;
00072     for(int k = 0; k < nasic; k++)
00073     {
00074         std::bitset<109 * 8> bs;
00075         // printf("%x %x \n",cbuf[idx+k*109+69],cbuf[idx+k*109+70]);
00076         for(int l = 108; l >= 0; l--)
00077         {
00078             // printf("%d %x : %d -->",l,cbuf[idx+k*109+1], (71-1)*8);
00079             for(int m = 0; m < 8; m++)
00080             {
00081                 if(((1 < m) & cbuf[idx + k * 109 + 1]) != 0) bs.set((108 - 1) * 8 + m, 1);
00082             else
00083                 bs.set((108 - 1) * 8 + m, 0);
00084             // printf("%d", (int) bs[(71-1)*8+m]);
00085         }
00086         // printf("\n");
00087     }
00088     FillAsicHR2(bs);
00089 }
00090 }
00091
00092 void DIFSlowControl::FillAsicHR1(const std::bitset<72 * 8>& bs)
00093 {
00094     // Asic Id
00095     int asicid{0};
00096     for(int j = 0; j < 8; j++)
00097         if(bs[j + 9] != 0) asicid += (1 << (7 - j));
00098     std::map<std::string, int> mAsic;
00099     // Slow Control
00100     mAsic["SSC0"] = static_cast<int>(bs[575]);
00101     mAsic["SSC1"] = static_cast<int>(bs[574]);
00102     mAsic["SSC2"] = static_cast<int>(bs[573]);
00103     mAsic["Choix_caisson"] = static_cast<int>(bs[572]);
00104     mAsic["SW_50k"] = static_cast<int>(bs[571]);
00105     mAsic["SW_100k"] = static_cast<int>(bs[570]);
00106     mAsic["SW_100f"] = static_cast<int>(bs[569]);
00107     mAsic["SW_50f"] = static_cast<int>(bs[568]);
00108
00109     mAsic["Valid_DC"] = static_cast<int>(bs[567]);
00110     mAsic["ON_Discri"] = static_cast<int>(bs[566]);
00111     mAsic["ON_Fsb"] = static_cast<int>(bs[565]);
00112     mAsic["ON_Otaq"] = static_cast<int>(bs[564]);
00113     mAsic["ON_W"] = static_cast<int>(bs[563]);
00114     mAsic["ON_Ss"] = static_cast<int>(bs[562]);
00115     mAsic["ON_Buf"] = static_cast<int>(bs[561]);
00116     mAsic["ON_Paf"] = static_cast<int>(bs[560]);
00117     // Gain
00118     for(int i = 0; i < 64; i++)
00119     {
00120         int gain{0};
00121         for(int j = 0; j < 6; j++)
00122             if(bs[176 + i * 6 + j] != 0) gain += (1 << j);
00123         mAsic["Channel_" + std::to_string(i) + "_" + "Gain"] = gain;
00124         mAsic["Channel_" + std::to_string(i) + "_" + "cTest"] = bs[112 + i];
00125         mAsic["Channel_" + std::to_string(i) + "_" + "Valid_trig"] = static_cast<int>(bs[25 + i]);
00126     }
00127
00128     mAsic["ON_Otabg"] = static_cast<int>(bs[111]);
00129     mAsic["ON_Dac"] = static_cast<int>(bs[110]);
00130     mAsic["ON_Otadac"] = static_cast<int>(bs[109]);
00131     // DAC
00132     int dac1{0};
00133     for(int j = 0; j < 10; j++)
00134         if(bs[j + 99] != 0) dac1 += (1 << j);
00135     mAsic["DAC1"] = dac1;
00136     int dac0{0};
00137     for(int j = 0; j < 10; j++)
00138         if(bs[j + 89] != 0) dac0 += (1 << j);
00139     mAsic["DAC0"] = dac0;
00140     mAsic["EN_Raz_Ext"] = static_cast<int>(bs[23]);
00141     mAsic["EN_Raz_Int"] = static_cast<int>(bs[22]);

```

```

00142 mAsic["EN_Out_Raz_Int"] = static_cast<int>(bs[21]);
00143 mAsic["EN_Trig_Ext"] = static_cast<int>(bs[20]);
00144 mAsic["EN_Trig_Int"] = static_cast<int>(bs[19]);
00145 mAsic["EN_Out_Trig_Int"] = static_cast<int>(bs[18]);
00146 mAsic["Bypass_Chip"] = static_cast<int>(bs[17]);
00147 mAsic["HardrocHeader"] = static_cast<int>(asicid);
00148 mAsic["EN_Out_Discr"] = static_cast<int>(bs[8]);
00149 mAsic["EN_Transmit_On"] = static_cast<int>(bs[7]);
00150 mAsic["EN_Dout"] = static_cast<int>(bs[6]);
00151 mAsic["EN_RamFull"] = static_cast<int>(bs[5]);
00152 m_MapSC[asicid] = mAsic;
00153 }
00154
00155 void DIFSlowControl::FillAsicHR2(const std::bitset<109 * 8>& bs)
00156 {
00157     int asicid{0};
00158     for(int j = 0; j < 8; j++)
00159         if(bs[j + (108 - 7) * 8 + 2] != 0) asicid += (1 << (7 - j));
00160     std::map<std::string, int> mAsic;
00161     for(int i = 0; i < 64; i++)
00162     {
00163         int gain{0};
00164         int mask{0};
00165         mAsic["Channel_" + std::to_string(i) + "_" + "cTest"] = bs[i];
00166         for(int j = 0; j < 8; j++)
00167             if(bs[64 + i * 8 + j] != 0) gain += (1 << j);
00168         mAsic["Channel_" + std::to_string(i) + "_" + "Gain"] = gain;
00169         for(int j = 0; j < 3; j++)
00170             if(bs[8 * 77 + 2 + i * 3 + j] != 0) mask += (1 << j);
00171         mAsic["Channel_" + std::to_string(i) + "_" + "Mask"] = mask;
00172     }
00173     mAsic["PwrOnPA"] = static_cast<int>(bs[8 * 72]);
00174     mAsic["Cmdb3SS"] = static_cast<int>(bs[8 * 72 + 1]);
00175     mAsic["Cmdb2SS"] = static_cast<int>(bs[8 * 72 + 2]);
00176     mAsic["Cmdb1SS"] = static_cast<int>(bs[8 * 72 + 3]);
00177     mAsic["Cmdb0SS"] = static_cast<int>(bs[8 * 72 + 4]);
00178     mAsic["SwSsc0"] = static_cast<int>(bs[8 * 72 + 5]);
00179     mAsic["SwSsc1"] = static_cast<int>(bs[8 * 72 + 6]);
00180     mAsic["SwSsc2"] = static_cast<int>(bs[8 * 72 + 7]);
00181
00182     mAsic["PwrOnBuff"] = static_cast<int>(bs[8 * 73]);
00183     mAsic["PwrOnSS"] = static_cast<int>(bs[8 * 73 + 1]);
00184     mAsic["PwrOnW"] = static_cast<int>(bs[8 * 73 + 2]);
00185     mAsic["Cmdb3Fsb2"] = static_cast<int>(bs[8 * 73 + 3]);
00186     mAsic["Cmdb2Fsb2"] = static_cast<int>(bs[8 * 73 + 4]);
00187     mAsic["Cmdb1Fsb2"] = static_cast<int>(bs[8 * 73 + 5]);
00188     mAsic["Cmdb0Fsb2"] = static_cast<int>(bs[8 * 73 + 6]);
00189     mAsic["Sw50k2"] = static_cast<int>(bs[8 * 73 + 7]);
00190
00191     mAsic["Sw100k2"] = static_cast<int>(bs[8 * 74]);
00192     mAsic["Sw100f2"] = static_cast<int>(bs[8 * 74 + 1]);
00193     mAsic["Sw50f2"] = static_cast<int>(bs[8 * 74 + 2]);
00194     mAsic["Cmdb3Fsb1"] = static_cast<int>(bs[8 * 74 + 3]);
00195     mAsic["Cmdb2Fsb1"] = static_cast<int>(bs[8 * 74 + 4]);
00196     mAsic["Cmdb1Fsb1"] = static_cast<int>(bs[8 * 74 + 5]);
00197     mAsic["Cmdb0Fsb1"] = static_cast<int>(bs[8 * 74 + 6]);
00198     mAsic["Sw50k1"] = static_cast<int>(bs[8 * 74 + 7]);
00199
00200     mAsic["Sw100k1"] = static_cast<int>(bs[8 * 75]);
00201     mAsic["Sw100f1"] = static_cast<int>(bs[8 * 75 + 1]);
00202     mAsic["Sw50f1"] = static_cast<int>(bs[8 * 75 + 2]);
00203     mAsic["Sel0"] = static_cast<int>(bs[8 * 75 + 3]);
00204     mAsic["Sel11"] = static_cast<int>(bs[8 * 75 + 4]);
00205     mAsic["PwrOnFsb"] = static_cast<int>(bs[8 * 75 + 5]);
00206     mAsic["PwrOnFsb1"] = static_cast<int>(bs[8 * 75 + 6]);
00207     mAsic["PwrOnFsb2"] = static_cast<int>(bs[8 * 75 + 7]);
00208
00209     mAsic["Sw50k0"] = static_cast<int>(bs[8 * 76]);
00210     mAsic["Sw100k0"] = static_cast<int>(bs[8 * 76 + 1]);
00211     mAsic["Sw100f0"] = static_cast<int>(bs[8 * 76 + 2]);
00212     mAsic["Sw50f0"] = static_cast<int>(bs[8 * 76 + 3]);
00213     mAsic["EnOtaQ"] = static_cast<int>(bs[8 * 76 + 4]);
00214     mAsic["OtaQ_PwrADC"] = static_cast<int>(bs[8 * 76 + 5]);
00215     mAsic["Discr_PwrA"] = static_cast<int>(bs[8 * 76 + 6]);
00216     mAsic["Discr2"] = static_cast<int>(bs[8 * 76 + 7]);
00217
00218     mAsic["Discr1"] = static_cast<int>(bs[8 * 77]);
00219     mAsic["RS_or_Discr"] = static_cast<int>(bs[8 * 77 + 1]);
00220
00221     mAsic["Header"] = asicid;
00222     for(int i = 0; i < 3; i++)
00223     {
00224         int B = 0;
00225         for(int j = 0; j < 10; j++)
00226             if(bs[8 * 102 + 2 + i * 10 + j] != 0) B += (1 << j);
00227         mAsic["B" + std::to_string(i)] = B;
00228     }

```

```

00229
00230 mAsic["Smallldac"] = static_cast<int>(bs[8 * 106]);
00231 mAsic["DacSw"] = static_cast<int>(bs[8 * 106 + 1]);
00232 mAsic["OtagBgSw"] = static_cast<int>(bs[8 * 106 + 2]);
00233 mAsic["Trig2b"] = static_cast<int>(bs[8 * 106 + 3]);
00234 mAsic["Trig1b"] = static_cast<int>(bs[8 * 106 + 4]);
00235 mAsic["Trig0b"] = static_cast<int>(bs[8 * 106 + 5]);
00236 mAsic["EnTrigOut"] = static_cast<int>(bs[8 * 106 + 6]);
00237 mAsic["DiscrOrOr"] = static_cast<int>(bs[8 * 106 + 7]);
00238
00239 mAsic["TrigExtVal"] = static_cast<int>(bs[8 * 107]);
00240 mAsic["RazChnIntVal"] = static_cast<int>(bs[8 * 107 + 1]);
00241 mAsic["RazChnExtVal"] = static_cast<int>(bs[8 * 107 + 2]);
00242 mAsic["ScOn"] = static_cast<int>(bs[8 * 107 + 3]);
00243 mAsic["CLKMux"] = static_cast<int>(bs[8 * 107 + 4]);
00244
00245 // EnOCDout1b EnOCDout2b EnOCTransmitOn1b EnOCTransmitOn2b EnOCChipsatb SelStartReadout
SelEndReadout
00246 mAsic["SelEndReadout"] = static_cast<int>(bs[8 * 108 + 1]);
00247 mAsic["SelStartReadout"] = static_cast<int>(bs[8 * 108 + 2]);
00248 mAsic["EnOCChipsatb"] = static_cast<int>(bs[8 * 108 + 3]);
00249 mAsic["EnOCTransmitOn2b"] = static_cast<int>(bs[8 * 108 + 4]);
00250 mAsic["EnOCTransmitOn1b"] = static_cast<int>(bs[8 * 108 + 5]);
00251 mAsic["EnOCDout2b"] = static_cast<int>(bs[8 * 108 + 6]);
00252 mAsic["EnOCDout1b"] = static_cast<int>(bs[8 * 108 + 7]);
00253 m_MapSC[asid] = mAsic;
00254 }
00255
00256 std::string to_string(const DIFSlowControl& c)
00257 {
00258     std::string ret;
00259     for(std::map<int, std::map<std::string, int>::const_iterator it = c.cbegin(); it != c.cend(); it++)
00260     {
00261         ret += "ASIC " + std::to_string(it->first) + " :\n";
00262         for(std::map<std::string, int>::const_iterator jt = (it->second).begin(); jt !=
(it->second).end(); jt++) ret += jt->first + " : " + std::to_string(jt->second) + "\n";
00263     }
00264     return ret;
00265 }

```

5.39 libs/core/src/FileSystem.cc File Reference

```
#include "FileSystem.h"
```

Functions

- `std::string path` (const `std::string` &file)
- `std::string extension` (const `std::string` &file)
- `std::string filename` (const `std::string` &file)

5.39.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [FileSystem.cc](#).

5.39.2 Function Documentation

5.39.2.1 extension() `std::string extension (`
`const std::string & file)`

Definition at line 13 of file [Filesystem.cc](#).

```
00014 {
00015     std::size_t position = file.find_last_of(".");
00016     return (std::string::npos == position || position == 0) ? "" : file.substr(position + 1);
00017 }
```

5.39.2.2 filename() `std::string filename (`
`const std::string & file)`

Definition at line 19 of file [Filesystem.cc](#).

```
00020 {
00021     std::size_t position = file.find_last_of(".");
00022     std::size_t pos      = file.find_last_of("\\\\/");
00023     return (std::string::npos == pos) ? file.substr(0, position) : file.substr(pos + 1, position - pos
- 1);
00024 }
```

5.39.2.3 path() `std::string path (`
`const std::string & file)`

Definition at line 7 of file [Filesystem.cc](#).

```
00008 {
00009     std::size_t pos = file.find_last_of("\\\\/");
00010     return (std::string::npos == pos) ? "" : file.substr(0, pos);
00011 }
```

5.40 Filesystem.cc

[Go to the documentation of this file.](#)

```
00001
00005 #include "Filesystem.h"
00006
00007 std::string path(const std::string& file)
00008 {
00009     std::size_t pos = file.find_last_of("\\\\/");
00010     return (std::string::npos == pos) ? "" : file.substr(0, pos);
00011 }
00012
00013 std::string extension(const std::string& file)
00014 {
00015     std::size_t position = file.find_last_of(".");
00016     return (std::string::npos == position || position == 0) ? "" : file.substr(position + 1);
00017 }
00018
00019 std::string filename(const std::string& file)
00020 {
00021     std::size_t position = file.find_last_of(".");
00022     std::size_t pos      = file.find_last_of("\\\\/");
00023     return (std::string::npos == pos) ? file.substr(0, position) : file.substr(pos + 1, position - pos
- 1);
00024 }
```

5.41 libs/core/src/Formatters.cc File Reference

```
#include "Formatters.h"
#include "Bits.h"
#include "Buffer.h"
#include "Words.h"
#include <fmt/format.h>
```

Functions

- `std::string to_dec (const Buffer &b, const std::size_t &begin, const std::size_t &end)`
- `std::string to_dec (const bit8_t &b)`
- `std::string to_dec (const bit16_t &b)`
- `std::string to_dec (const bit32_t &b)`
- `std::string to_dec (const bit64_t &b)`
- `std::string to_hex (const Buffer &b, const std::size_t &begin, const std::size_t &end)`
- `std::string to_hex (const bit8_t &b)`
- `std::string to_hex (const bit16_t &b)`
- `std::string to_hex (const bit32_t &b)`
- `std::string to_hex (const bit64_t &b)`
- `std::string to_bin (const Buffer &b, const std::size_t &begin, const std::size_t &end)`
- `std::string to_bin (const bit8_t &b)`
- `std::string to_bin (const bit16_t &b)`
- `std::string to_bin (const bit32_t &b)`
- `std::string to_bin (const bit64_t &b)`
- `std::string to_oct (const Buffer &b, const std::size_t &begin, const std::size_t &end)`
- `std::string to_oct (const bit8_t &b)`
- `std::string to_oct (const bit16_t &b)`
- `std::string to_oct (const bit32_t &b)`
- `std::string to_oct (const bit64_t &b)`

5.41.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Formatters.cc](#).

5.41.2 Function Documentation

5.41.2.1 to_bin() [1/5] `std::string to_bin (const bit16_t & b)`

Definition at line 71 of file [Formatters.cc](#).

```
00071 { return fmt::format("{:#016b}", b); }
```

5.41.2.2 to_bin() [2/5] `std::string to_bin (const bit32_t & b)`

Definition at line 73 of file [Formatters.cc](#).

```
00073 { return fmt::format("{:#032b}", b); }
```

5.41.2.3 to_bin() [3/5] std::string to_bin (
const bit64_t & b)

Definition at line 75 of file [Formatters.cc](#).

```
00075 { return fmt::format("{:#064b}", b); }
```

5.41.2.4 to_bin() [4/5] std::string to_bin (
const bit8_t & b)

Definition at line 69 of file [Formatters.cc](#).

```
00069 { return fmt::format("{:#08b}", b); }
```

5.41.2.5 to_bin() [5/5] std::string to_bin (
const Buffer & b,
const std::size_t & begin,
const std::size_t & end)

Definition at line 56 of file [Formatters.cc](#).

```
00057 {  
00058     std::size_t iend = end;  
00059     if(iend == -1) iend = b.size();  
00060     std::string ret;  
00061     for(std::size_t k = begin; k < iend; k++)  
00062     {  
00063         ret += to_bin(b[k]);  
00064         ret += " - ";  
00065     }  
00066     return ret;  
00067 }
```

5.41.2.6 to_dec() [1/5] std::string to_dec (
const bit16_t & b)

Definition at line 29 of file [Formatters.cc](#).

```
00029 { return fmt::format("{:#d}", b); }
```

5.41.2.7 to_dec() [2/5] std::string to_dec (
const bit32_t & b)

Definition at line 31 of file [Formatters.cc](#).

```
00031 { return fmt::format("{:#d}", b); }
```

5.41.2.8 to_dec() [3/5] std::string to_dec (
const bit64_t & b)

Definition at line 33 of file [Formatters.cc](#).

```
00033 { return fmt::format("{:#d}", b); }
```

5.41.2.9 to_dec() [4/5] `std::string to_dec (`
`const bit8_t & b)`

Definition at line 27 of file [Formatters.cc](#).

```
00027 { return fmt::format("{:d}", b); }
```

5.41.2.10 to_dec() [5/5] `std::string to_dec (`
`const Buffer & b,`
`const std::size_t & begin,`
`const std::size_t & end)`

Definition at line 14 of file [Formatters.cc](#).

```
00015 {  
00016     std::size_t iend = end;  
00017     if(iend == -1) iend = b.size();  
00018     std::string ret;  
00019     for(std::size_t k = begin; k < iend; k++)  
00020     {  
00021         ret += to_dec(b[k]);  
00022         ret += " - ";  
00023     }  
00024     return ret;  
00025 }
```

5.41.2.11 to_hex() [1/5] `std::string to_hex (`
`const bit16_t & b)`

Definition at line 50 of file [Formatters.cc](#).

```
00050 { return fmt::format("{:04x}", b); }
```

5.41.2.12 to_hex() [2/5] `std::string to_hex (`
`const bit32_t & b)`

Definition at line 52 of file [Formatters.cc](#).

```
00052 { return fmt::format("{:08x}", b); }
```

5.41.2.13 to_hex() [3/5] `std::string to_hex (`
`const bit64_t & b)`

Definition at line 54 of file [Formatters.cc](#).

```
00054 { return fmt::format("{:016x}", b); }
```

5.41.2.14 to_hex() [4/5] `std::string to_hex (`
`const bit8_t & b)`

Definition at line 48 of file [Formatters.cc](#).

```
00048 { return fmt::format("{:02x}", b); }
```

5.41.2.15 to_hex() [5/5] std::string to_hex (
 const Buffer & b,
 const std::size_t & begin,
 const std::size_t & end)

Definition at line 35 of file [Formatters.cc](#).

```
00036 {  
00037     std::size_t iend = end;  
00038     if(iend == -1) iend = b.size();  
00039     std::string ret;  
00040     for(std::size_t k = begin; k < iend; k++)  
00041     {  
00042         ret += to_hex(b[k]);  
00043         ret += " - ";  
00044     }  
00045     return ret;  
00046 }
```

5.41.2.16 to_oct() [1/5] std::string to_oct (
 const bit16_t & b)

Definition at line 92 of file [Formatters.cc](#).

```
00092 { return fmt::format("{:#08o}", b); }
```

5.41.2.17 to_oct() [2/5] std::string to_oct (
 const bit32_t & b)

Definition at line 94 of file [Formatters.cc](#).

```
00094 { return fmt::format("{:#016o}", b); }
```

5.41.2.18 to_oct() [3/5] std::string to_oct (
 const bit64_t & b)

Definition at line 96 of file [Formatters.cc](#).

```
00096 { return fmt::format("{:#032o}", b); }
```

5.41.2.19 to_oct() [4/5] std::string to_oct (
 const bit8_t & b)

Definition at line 90 of file [Formatters.cc](#).

```
00090 { return fmt::format("{:#04o}", b); }
```

```

5.41.2.20 to_oct() [5/5] std::string to_oct (
    const Buffer & b,
    const std::size_t & begin,
    const std::size_t & end )

```

Definition at line 77 of file [Formatters.cc](#).

```

00078 {
00079     std::size_t iend = end;
00080     if(iend == -1) iend = b.size();
00081     std::string ret;
00082     for(std::size_t k = begin; k < iend; k++)
00083     {
00084         ret += to_oct(b[k]);
00085         ret += " - ";
00086     }
00087     return ret;
00088 }

```

5.42 Formatters.cc

[Go to the documentation of this file.](#)

```

00001
00006 #include "Formatters.h"
00007
00008 #include "Bits.h"
00009 #include "Buffer.h"
00010 #include "Words.h"
00011
00012 #include <fmt/format.h>
00013
00014 std::string to_dec(const Buffer& b, const std::size_t& begin, const std::size_t& end)
00015 {
00016     std::size_t iend = end;
00017     if(iend == -1) iend = b.size();
00018     std::string ret;
00019     for(std::size_t k = begin; k < iend; k++)
00020     {
00021         ret += to_dec(b[k]);
00022         ret += " - ";
00023     }
00024     return ret;
00025 }
00026
00027 std::string to_dec(const bit8_t& b) { return fmt::format(":{:d}", b); }
00028
00029 std::string to_dec(const bit16_t& b) { return fmt::format(":{:d}", b); }
00030
00031 std::string to_dec(const bit32_t& b) { return fmt::format(":{:d}", b); }
00032
00033 std::string to_dec(const bit64_t& b) { return fmt::format(":{:d}", b); }
00034
00035 std::string to_hex(const Buffer& b, const std::size_t& begin, const std::size_t& end)
00036 {
00037     std::size_t iend = end;
00038     if(iend == -1) iend = b.size();
00039     std::string ret;
00040     for(std::size_t k = begin; k < iend; k++)
00041     {
00042         ret += to_hex(b[k]);
00043         ret += " - ";
00044     }
00045     return ret;
00046 }
00047
00048 std::string to_hex(const bit8_t& b) { return fmt::format(":{:02x}", b); }
00049
00050 std::string to_hex(const bit16_t& b) { return fmt::format(":{:04x}", b); }
00051
00052 std::string to_hex(const bit32_t& b) { return fmt::format(":{:08x}", b); }
00053
00054 std::string to_hex(const bit64_t& b) { return fmt::format(":{:016x}", b); }
00055
00056 std::string to_bin(const Buffer& b, const std::size_t& begin, const std::size_t& end)
00057 {
00058     std::size_t iend = end;
00059     if(iend == -1) iend = b.size();
00060     std::string ret;
00061     for(std::size_t k = begin; k < iend; k++)
00062     {
00063         ret += to_bin(b[k]);

```

```

00064     ret += " - ";
00065 }
00066 return ret;
00067 }
00068
00069 std::string to_bin(const bit8_t& b) { return fmt::format("{:08b}", b); }
00070
00071 std::string to_bin(const bit16_t& b) { return fmt::format("{:016b}", b); }
00072
00073 std::string to_bin(const bit32_t& b) { return fmt::format("{:032b}", b); }
00074
00075 std::string to_bin(const bit64_t& b) { return fmt::format("{:064b}", b); }
00076
00077 std::string to_oct(const Buffer& b, const std::size_t& begin, const std::size_t& end)
00078 {
00079     std::size_t iend = end;
00080     if(iend == -1) iend = b.size();
00081     std::string ret;
00082     for(std::size_t k = begin; k < iend; k++)
00083     {
00084         ret += to_oct(b[k]);
00085         ret += " - ";
00086     }
00087     return ret;
00088 }
00089
00090 std::string to_oct(const bit8_t& b) { return fmt::format("{:04o}", b); }
00091
00092 std::string to_oct(const bit16_t& b) { return fmt::format("{:08o}", b); }
00093
00094 std::string to_oct(const bit32_t& b) { return fmt::format("{:016o}", b); }
00095
00096 std::string to_oct(const bit64_t& b) { return fmt::format("{:032o}", b); }

```

5.43 libs/core/src/RawBufferNavigator.cc File Reference

```

#include "RawBufferNavigator.h"
#include "Words.h"

```

5.43.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [RawBufferNavigator.cc](#).

5.44 RawBufferNavigator.cc

[Go to the documentation of this file.](#)

```

00001
00005 #include "RawBufferNavigator.h"
00006
00007 #include "Words.h"
00008
00009 int RawBufferNavigator::m_Start = 92;
00010
00011 void RawBufferNavigator::StartAt(const int& start)
00012 {
00013     if(start >= 0) m_Start = start;
00014 }
00015
00016 RawBufferNavigator::RawBufferNavigator() {}
00017
00018 void RawBufferNavigator::setBuffer(const Buffer& b)
00019 {
00020     m_Buffer = b;
00021     m_StartPayload = -1;

```

```

00022     m_StartPayloadDone = false;
00023 }
00024
00025 std::uint8_t RawBufferNavigator::getDetectorID() { return m_Buffer[0]; }
00026
00027 bool RawBufferNavigator::findStartOfPayload()
00028 {
00029     if(m_StartPayloadDone == true)
00030     {
00031         if(m_StartPayload == -1) return false;
00032         else
00033             return true;
00034     }
00035     else
00036     {
00037         m_StartPayloadDone = true;
00038         for(std::size_t i = m_Start; i < m_Buffer.size(); i++)
00039         {
00040             if(static_cast<std::uint8_t>(m_Buffer[i]) == static_cast<std::uint8_t>(Value::GLOBAL_HEADER) ||
static_cast<std::uint8_t>(m_Buffer[i]) == static_cast<std::uint8_t>(Value::GLOBAL_HEADER_TEMP))
00041             {
00042                 m_StartPayload = i;
00043                 return true;
00044             }
00045         }
00046         m_StartPayload = -1;
00047         return false;
00048     }
00049 }
00050
00051 std::int32_t RawBufferNavigator::getStartOfPayload()
00052 {
00053     findStartOfPayload();
00054     return m_StartPayload;
00055 }
00056
00057 bool RawBufferNavigator::validPayload() { return m_StartPayload != -1; }
00058
00059 Buffer RawBufferNavigator::getPayload() { return Buffer(&(m_Buffer.begin())[m_StartPayload],
m_Buffer.size() - m_StartPayload); }

```

5.45 libs/core/src/Version.cc File Reference

```
#include "Version.h"
```

5.45.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Version.cc](#).

5.46 Version.cc

[Go to the documentation of this file.](#)

```

00001
00005 #include "Version.h"
00006
00007 const static Version streamout_version;
00008
00009 std::uint8_t Version::getMajor() { return major; }
00010
00011 std::uint8_t Version::getMinor() { return minor; }
00012
00013 std::uint8_t Version::getPatch() { return patch; }
00014
00015 std::string Version::getPreRelease()
00016 {

```



```

00017     switch(prerelease_type)
00018     {
00019         case semver::prerelease::alpha: return "alpha";
00020         case semver::prerelease::beta:  return "beta";
00021         case semver::prerelease::rc:    return "rc";
00022         case semver::prerelease::none:  return "";
00023         default: return "";
00024     }
00025 }
00026
00027 std::uint8_t Version::getPreReleaseNumber() { return prerelease_number; }

```

5.47 libs/interface/Dump/include/textDump.h File Reference

```

#include "Interface.h"
#include "PayloadParser.h"
#include "spdlog/sinks/stdout_color_sinks.h"
#include <memory>
#include <spdlog/logger.h>

```

Classes

- class [textDump](#)

5.47.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [textDump.h](#).

5.48 textDump.h

[Go to the documentation of this file.](#)

```

00001
00005 #pragma once
00006
00007 #include "Interface.h"
00008 #include "PayloadParser.h"
00009 #include "spdlog/sinks/stdout_color_sinks.h"
00010
00011 #include <memory>
00012 #include <spdlog/logger.h>
00013
00014 class textDump : public InterfaceWriter
00015 {
00016 public:
00017     textDump();
00018     void start();
00019     void processDIF(const PayloadParser&);
00020     void processFrame(const PayloadParser&, uint32_t frameIndex);
00021     void processPadInFrame(const PayloadParser&, uint32_t frameIndex,
uint32_t channelIndex);
00022     void processSlowControl(Buffer);
00023     void end();
00024     std::shared_ptr<spdlog::logger> print() { return m_InternalLogger; }
00025     void setLevel(const spdlog::level::level_enum& level) {
m_InternalLogger->set_level(level); }
00026
00027 private:
00028     // This class is a dumb class to print on terminal so we need the logger + the standard one given by
the interface.
00029     std::shared_ptr<spdlog::logger> m_InternalLogger{nullptr};
00030 };

```

5.49 libs/interface/Dump/src/textDump.cc File Reference

```
#include "textDump.h"
#include "PayloadParser.h"
```

5.49.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [textDump.cc](#).

5.50 textDump.cc

[Go to the documentation of this file.](#)

```
00001
00005 #include "textDump.h"
00006
00007 #include "PayloadParser.h"
00008
00009 textDump::textDump() : InterfaceWriter("textDump", "1.0.0")
00010 {
00011     m_InternalLogger = std::make_shared<spdlog::logger>("textDump",
00012         std::make_shared<spdlog::sinks::stdout_color_sink_mt>());
00013     m_InternalLogger->set_level(spdlog::level::trace);
00014     addCompatibility("RawdataReader", ">=1.0.0");
00015     addCompatibility("DIFdataExample", ">=1.0.0");
00016 }
00017 void textDump::start() { print()->info("Will dump bunch of DIF data"); }
00018
00019 void textDump::processDIF(const PayloadParser& d) { print()->info("DIF_ID : {}, DTC : {}, GTC : {},
00020     DIF BCID {}, Absolute BCID : {}, Nbr frames {}", d.getDIFid(), d.getDTC(), d.getGTC(), d.getBCID(),
00021     d.getAbsoluteBCID(), d.getNumberOfFrames()); }
00022
00023 void textDump::processFrame(const PayloadParser& d, uint32_t frameIndex)
00024 {
00025     print()->info("\tDisplaying frame number {} : ASIC ID {}, Frame BCID {}, Frame Time To Trigger
00026     (a.k.a timestamp) is {}", frameIndex, d.getASICid(frameIndex), d.getFrameBCID(frameIndex),
00027     d.getFrameTimeToTrigger(frameIndex));
00028 }
00029
00030 void textDump::processPadInFrame(const PayloadParser& d, uint32_t frameIndex, uint32_t channelIndex)
00031 {
00032     if(d.getThresholdStatus(frameIndex, channelIndex) > 0) { print()->info("\t\tChannel {}, Threshold
00033     {}", channelIndex, d.getThresholdStatus(frameIndex, channelIndex)); }
00034 }
00035
00036 void textDump::processSlowControl(Buffer) { print()->error("textDump::processSlowControl not
00037     implemented yet."); }
00038
00039 void textDump::end() { print()->info("textDump end of report"); }
```

5.51 libs/interface/LCIO/include/LCIOWriter.h File Reference

5.51.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [LCIOWriter.h](#).

5.52 LCIOWriter.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
```

5.53 libs/interface/LCIO/src/LCIOWriter.cc File Reference

5.53.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [LCIOWriter.cc](#).

5.54 LCIOWriter.cc

[Go to the documentation of this file.](#)

```
00001
```

5.55 libs/interface/RawDataReader/include/RawdataReader.h File Reference

```
#include "Interface.h"
#include <array>
#include <cstdlib>
#include <fstream>
#include <string>
#include <vector>
```

Classes

- class [RawdataReader](#)

5.55.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [RawdataReader.h](#).

5.56 RawdataReader.h

[Go to the documentation of this file.](#)

```

00001
00005 #pragma once
00006
00007 #include "Interface.h"
00008
00009 #include <array>
00010 #include <stdint>
00011 #include <fstream>
00012 #include <string>
00013 #include <vector>
00014
00015 class Buffer;
00016
00017 class RawdataReader : public InterfaceReader
00018 {
00019 public:
00020     explicit RawdataReader(const char* fileName);
00021     void start();
00022     void end();
00023     float getFileSize();
00024     void openFile(const std::string& fileName);
00025     void closeFile();
00026     bool nextEvent();
00027     bool nextDIFbuffer();
00028     const Buffer& getBuffer();
00029     virtual ~RawdataReader() { closeFile(); }
00030     static void setDefaultBufferSize(const std::size_t& size);
00031
00032 private:
00033     void uncompress();
00034     std::ifstream m_FileStream;
00035     void setFileSize(const std::size_t& size);
00036     static std::size_t m_BufferSize;
00037     std::size_t m_FileSize{0};
00038     std::uint32_t m_NumberOfDIF{0};
00039     std::uint32_t m_EventNumber{0};
00040     std::vector<bit8_t> m_buf;
00041     std::string m_Filename;
00042 };

```

5.57 libs/interface/RawDataReader/src/RawdataReader.cc File Reference

```

#include "RawdataReader.h"
#include "Exception.h"
#include <stdint>
#include <cstring>
#include <stdexcept>
#include <zlib.h>

```

5.57.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [RawdataReader.cc](#).

5.58 RawdataReader.cc

[Go to the documentation of this file.](#)

```

00001
00004 #include "RawdataReader.h"
00005
00006 #include "Exception.h"
00007
00008 #include <stdint>
00009 #include <cstring>
00010 #include <stdexcept>
00011 #include <zlib.h>
00012
00014 std::size_t RawdataReader::m_BufferSize = 0x100000;
00015
00016 void RawdataReader::setDefaultBufferSize(const std::size_t& size) { m_BufferSize = size; }
00017
00018 RawdataReader::RawdataReader(const char* fileName) : InterfaceReader("RawdataReader", "1.0.0")
00019 {
00020     m_buf.reserve(m_BufferSize);
00021     m_Filename = fileName;
00022 }
00023
00024 void RawdataReader::start() { openFile(m_Filename); }
00025
00026 void RawdataReader::end() { closeFile(); }
00027
00028 void RawdataReader::uncompress()
00029 {
00030     static const std::size_t size_buffer{0x20000};
00031     std::size_t shift{3 * sizeof(std::uint32_t) + sizeof(std::uint64_t)};
00032     static bit8_t obuf[size_buffer];
00033     unsigned long size_buffer_end{0x20000}; // NOLINT(runtime/int)
00034     std::int8_t rc = ::uncompress(obuf, &size_buffer_end, &m_Buffer[shift], m_Buffer.size()
- shift);
00035     switch(rc)
00036     {
00037         case Z_OK: break;
00038         case Z_MEM_ERROR: throw Exception(Z_MEM_ERROR, "Not enough memory"); break;
00039         case Z_BUF_ERROR: throw Exception(Z_BUF_ERROR, "Not enough room in the output buffer"); break;
00040         case Z_DATA_ERROR: throw Exception(Z_DATA_ERROR, "The input data was corrupted or incomplete");
break;
00041         default: throw Exception("The input data was corrupted or incomplete"); break;
00042     }
00043     memcpy(&m_Buffer[shift], obuf, size_buffer_end);
00044     m_Buffer.setSize(size_buffer_end + shift);
00045 }
00046
00047 void RawdataReader::closeFile()
00048 {
00049     try
00050     {
00051         if(m_FileStream.is_open()) m_FileStream.close();
00052     }
00053     catch(const std::ios_base::failure& e)
00054     {
00055         log()->error("Caught an ios_base::failure in closeFile : {} {}", e.what(), e.code().value());
00056         throw;
00057     }
00058 }
00059
00060 void RawdataReader::openFile(const std::string& fileName)
00061 {
00062     try
00063     {
00064         m_FileStream.rdbuf()->pubsetbuf(0, 0);
00065         m_FileStream.exceptions(std::ifstream::failbit | std::ifstream::badbit);
00066         m_FileStream.open(fileName.c_str(), std::ios::in | std::ios::binary | std::ios::ate); // Start at
the end to directly calculate the size of the file then come back to beginning
00067         m_FileStream.rdbuf()->pubsetbuf(0, 0);
00068         if(m_FileStream.is_open())
00069         {
00070             setFileSize(m_FileStream.tellg());
00071             m_FileStream.seekg(0, std::ios::beg);
00072         }
00073     }
00074     catch(const std::ios_base::failure& e)
00075     {
00076         log()->error("Caught an ios_base::failure in openFile : {}", e.what());
00077         throw;
00078     }
00079 }
00080
00081 bool RawdataReader::nextEvent()
00082 {
00083     try

```

```

00084 {
00085     m_FileStream.read(reinterpret_cast<char*>(&m_EventNumber), sizeof(std::uint32_t));
00086     m_FileStream.read(reinterpret_cast<char*>(&m_NumberOfDIF), sizeof(std::uint32_t));
00087 }
00088 catch(const std::ios_base::failure& e)
00089 {
00090     return false;
00091 }
00092 return true;
00093 }
00094
00095 bool RawdataReader::nextDIFbuffer()
00096 {
00097     try
00098     {
00099         static int DIF_processed{0};
00100         if(DIF_processed >= m_NumberOfDIF)
00101         {
00102             DIF_processed = 0;
00103             return false;
00104         }
00105         else
00106         {
00107             DIF_processed++;
00108             std::uint32_t bsize{0};
00109             m_FileStream.read(reinterpret_cast<char*>(&bsize), sizeof(std::uint32_t));
00110             m_FileStream.read(reinterpret_cast<char*>(&m_buf[0]), bsize);
00111             m_Buffer = Buffer(m_buf);
00112         }
00113     }
00114     catch(const std::ios_base::failure& e)
00115     {
00116         log()->error("Caught an ios_base::failure in openFile : {}", e.what());
00117         return false;
00118     }
00119     return true;
00120 }
00121
00122 const Buffer& RawdataReader::getBuffer()
00123 {
00124     uncompress();
00125     return m_Buffer;
00126 }
00127
00128 void RawdataReader::setFileSize(const std::size_t& size) { m_FileSize = size; }
00129
00130 float RawdataReader::getFileSize() { return m_FileSize; }

```

5.59 libs/interface/ROOT/include/DIF.h File Reference

```

#include "Hit.h"
#include <TObject.h>
#include <cstdint>
#include <map>
#include <vector>

```

Classes

- class [DIF](#)

Typedefs

- using [Hits_const_iterator](#) = std::vector< [Hit](#) >::const_iterator

5.59.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [DIF.h](#).

5.59.2 Typedef Documentation

5.59.2.1 Hits_const_iterator using Hits_const_iterator = std::vector<Hit>::const_iterator

Definition at line 14 of file [DIF.h](#).

5.60 DIF.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include "Hit.h"
00008
00009 #include <TObject.h>
00010 #include <cstdint>
00011 #include <map>
00012 #include <vector>
00013
00014 using Hits_const_iterator = std::vector<Hit>::const_iterator;
00015
00016 class DIF : public TObject
00017 {
00018 public:
00019     void                clear();
00020     void                addHit(const Hit&);
00021     void                setID(const std::uint8_t&);
00022     std::uint8_t        getID() const;
00023     void                setDTC(const std::uint32_t&);
00024     std::uint32_t        getDTC() const;
00025     void                setGTC(const std::uint32_t&);
00026     std::uint32_t        getGTC() const;
00027     void                setDIFBCID(const std::uint32_t&);
00028     std::uint32_t        getDIFBCID() const;
00029     void                setAbsoluteBCID(const std::uint64_t&);
00030     std::uint64_t        getAbsoluteBCID() const;
00031     std::vector<Hit>::const_iterator cbegin() const;
00032     std::vector<Hit>::const_iterator cend() const;
00033
00034 private:
00035     std::uint8_t        m_ID{0};
00036     std::uint32_t        m_DTC{0};
00037     std::uint32_t        m_GTC{0};
00038     std::uint32_t        m_DIFBCID{0};
00039     std::uint64_t        m_AbsoluteBCID{0};
00040     std::vector<Hit>    m_Hits;
00041     ClassDef(DIF, 1);
00042 };
```

5.61 libs/interface/ROOT/include/DIFLinkDef.h File Reference

```
#include <vector>
```

5.61.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [DIFLinkDef.h](#).

5.62 DIFLinkDef.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006 #include <vector>
00007
00008 #ifdef __CLING__
00009 #pragma link C++ class DIF;
00010 #pragma link C++ class Hit;
00011 #pragma link C++ class std::vector < Hit>;
00012 #endif
```

5.63 libs/interface/ROOT/include/Event.h File Reference

```
#include "DIF.h"
#include <TObject.h>
#include <cstdint>
#include <map>
```

Classes

- class [Event](#)

Typedefs

- using [DIFs_const_iterator](#) = std::map< std::uint8_t, [DIF](#) >::const_iterator

5.63.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Event.h](#).

5.63.2 Typedef Documentation

5.63.2.1 DIFs_const_iterator using [DIFs_const_iterator](#) = std::map<std::uint8_t, [DIF](#)>::const_iterator↵
iterator

Definition at line 13 of file [Event.h](#).

5.64 Event.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include "DIF.h"
00008
00009 #include <TObject.h>
00010 #include <cstdint>
00011 #include <map>
00012
00013 using DIFs_const_iterator = std::map<std::uint8_t, DIF>::const_iterator;
00014
00015 class Event : public TObject
00016 {
00017 public:
00018     void clear();
00019     void addDIF(const DIF& dif);
00020     std::map<std::uint8_t, DIF>::const_iterator cbegin() const;
00021     std::map<std::uint8_t, DIF>::const_iterator cend() const;
00022
00023 private:
00024     std::map<std::uint8_t, DIF> DIFs;
00025     ClassDef(Event, 1);
00026 };
```

5.65 libs/interface/ROOT/include/EventLinkDef.h File Reference

```
#include <cstdint>
#include <map>
#include <vector>
```

5.65.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [EventLinkDef.h](#).

5.66 EventLinkDef.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006 #include <cstdint>
00007 #include <map>
00008 #include <vector>
00009 #ifdef __CLING__
00010 #pragma link C++ class DIF;
00011 #pragma link C++ class std::vector < DIF>;
00012 #pragma link C++ class Hit;
00013 #pragma link C++ class std::vector < Hit>;
00014 #pragma link C++ class Event;
00015 #pragma link C++ class std::vector < Event>;
00016 #pragma link C++ class std::map < std::uint8_t, DIF>;
00017 #endif
```

5.67 libs/interface/ROOT/include/Hit.h File Reference

```
#include <TObject.h>
#include <cstdint>
```

Classes

- class [Hit](#)

5.67.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Hit.h](#).

5.68 Hit.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006
00007 #include <TObject.h>
00008 #include <cstdint>
00009
00010 class Hit : public TObject
00011 {
00012 public:
00013     void                clear();
00014     void                setDIF(const std::uint8_t&);
00015     void                setASIC(const std::uint8_t&);
00016     void                setChannel(const std::uint8_t&);
00017     void                setThreshold(const std::uint8_t&);
00018     void                setDTC(const std::uint32_t&);
00019     void                setGTC(const std::uint32_t&);
00020     void                setDIFBCID(const std::uint32_t&);
00021     void                setFrameBCID(const std::uint32_t&);
00022     void                setTimestamp(const std::uint32_t&);
00023     void                setAbsoluteBCID(const std::uint64_t&);
00024     std::uint8_t        getDIFid() const;
00025     std::uint8_t        getASICid() const;
00026     std::uint8_t        getChannel() const;
00027     std::uint8_t        getThreshold() const;
00028     std::uint32_t        getDTC() const;
00029     std::uint32_t        getGTC() const;
00030     std::uint32_t        getDIFBCID() const;
00031     std::uint32_t        setFrameBCID() const;
00032     std::uint32_t        getTimestamp() const;
00033     std::uint64_t        getAbsoluteBCID() const;
00034
00035 private:
00036     std::uint8_t        m_DIF{0};
00037     std::uint8_t        m_ASIC{0};
00038     std::uint8_t        m_Channel{0};
00039     std::uint8_t        m_Threshold{0};
00040     std::uint32_t        m_DTC{0};
00041     std::uint32_t        m_GTC{0};
00042     std::uint32_t        m_DIFBCID{0};
00043     std::uint32_t        m_FrameBCID{0};
00044     std::uint32_t        m_Timestamp{0};
00045     std::uint64_t        m_AbsoluteBCID{0};
00046     ClassDef(Hit, 1);
00047 };
```

5.69 libs/interface/ROOT/include/HitLinkDef.h File Reference

5.69.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [HitLinkDef.h](#).

5.70 HitLinkDef.h

[Go to the documentation of this file.](#)

```
00001
00005 #pragma once
00006 #ifdef __CLING__
00007 #pragma link C++ class Hit;
00008 #endif
```

5.71 libs/interface/ROOT/include/ROOTWriter.h File Reference

```
#include "Buffer.h"
#include "Event.h"
#include "Interface.h"
#include "PayloadParser.h"
#include <TFile.h>
#include <TTree.h>
#include <string>
#include <vector>
```

Classes

- class [ROOTWriter](#)

5.72 ROOTWriter.h

[Go to the documentation of this file.](#)

```
00001
00006 #pragma once
00007
00008 #include "Buffer.h"
00009 #include "Event.h"
00010 #include "Interface.h"
00011 #include "PayloadParser.h"
00012
00013 #include <TFile.h>
00014 #include <TTree.h>
00015 #include <string>
00016 #include <vector>
00017
00018 class ROOTWriter : public InterfaceWriter
00019 {
00020 public:
00021     ROOTWriter();
00022
00023     void setFilename(const std::string&);
00024
00025     void start();
00026     void processDIF(const PayloadParser&);
00027     void processFrame(const PayloadParser&, const std::uint32_t& frameIndex);
00028     void processPadInFrame(const PayloadParser&, const std::uint32_t& frameIndex, const std::uint32_t&
channelIndex);
00029     void processSlowControl(const Buffer&) { ; }
00030     void end();
00031
00032     virtual void startEvent();
00033     virtual void endEvent();
00034     virtual void startDIF();
00035     virtual void endDIF();
00036     virtual void startFrame();
00037     virtual void endFrame();
00038     virtual void startPad();
00039     virtual void endPad();
00040
00041 private:
00042     TFile* m_File{nullptr};
00043     TTree* m_Tree{nullptr};
00044     Event* m_Event{nullptr};
00045     DIF* m_DIF{nullptr};
00046     Hit* m_Hit{nullptr};
00047     std::string m_Filename;
00048 };
```

5.73 libs/interface/ROOT/src/DIF.cc File Reference

```
#include "DIF.h"
#include <stdint>
```

5.73.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [DIF.cc](#).

5.74 DIF.cc

[Go to the documentation of this file.](#)

```
00001
00006 #include "DIF.h"
00007
00008 #include <stdint>
00009
00010 void DIF::addHit(const Hit& hit) { m_Hits.push_back(hit); }
00011
00012 void DIF::setID(const std::uint8_t& id) { m_ID = id; }
00013
00014 std::uint8_t DIF::getID()const { return m_ID; }
00015
00016 void DIF::setDTC(const std::uint32_t& dtc) { m_DTC = dtc; }
00017
00018 std::uint32_t DIF::getDTC()const { return m_DTC; }
00019
00020 void DIF::setGTC(const std::uint32_t& gtc) { m_GTC = gtc; }
00021
00022 std::uint32_t DIF::getGTC()const { return m_GTC; }
00023
00024 void DIF::setDIFBCID(const std::uint32_t& difbcid) { m_DIFBCID = difbcid; }
00025
00026 std::uint32_t DIF::getDIFBCID()const { return m_DIFBCID; }
00027
00028 void DIF::setAbsoluteBCID(const std::uint64_t& absolutebcid) { m_AbsoluteBCID = absolutebcid; }
00029
00030 std::uint64_t DIF::getAbsoluteBCID()const { return m_AbsoluteBCID; }
00031
00032 std::vector<Hit>::const_iterator DIF::cbegin()const { return m_Hits.cbegin(); }
00033
00034 std::vector<Hit>::const_iterator DIF::cend()const { return m_Hits.cend(); }
00035
00036 void DIF::clear() { m_Hits.clear(); }
```

5.75 libs/interface/ROOT/src/Event.cc File Reference

```
#include "Event.h"
```

5.75.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Event.cc](#).

5.76 Event.cc

[Go to the documentation of this file.](#)

```
00001
00006 #include "Event.h"
00007
00008 void Event::clear() { DIFs.clear(); }
00009
00010 void Event::addDIF(const DIF& dif) { DIFs[dif.getID()] = dif; }
00011
00012 std::map<std::uint8_t, DIF>::const_iterator Event::cbegin()const { return DIFs.cbegin(); }
00013
00014 std::map<std::uint8_t, DIF>::const_iterator Event::cend()const { return DIFs.cend(); }
```

5.77 libs/interface/ROOT/src/Hit.cc File Reference

```
#include "Hit.h"
```

5.77.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [Hit.cc](#).

5.78 Hit.cc

[Go to the documentation of this file.](#)

```
00001
00006 #include "Hit.h"
00007 void Hit::clear()
00008 {
00009     m_DIF          = 0;
00010     m_ASIC         = 0;
00011     m_Channel      = 0;
00012     m_Threshold    = 0;
00013     m_DTC          = 0;
00014     m_GTC          = 0;
00015     m_DIFBCID     = 0;
00016     m_FrameBCID    = 0;
00017     m_Timestamp    = 0;
00018     m_AbsoluteBCID = 0;
00019 }
00020
00021 void Hit::setDIF(const std::uint8_t& dif) { m_DIF = dif; }
00022
00023 void Hit::setASIC(const std::uint8_t& asic) { m_ASIC = asic; }
00024
00025 void Hit::setChannel(const std::uint8_t& channel) { m_Channel = channel; }
00026
00027 void Hit::setThreshold(const std::uint8_t& threshold) { m_Threshold = threshold; }
00028
00029 void Hit::setDTC(const std::uint32_t& dtc) { m_DTC = dtc; }
00030
00031 void Hit::setGTC(const std::uint32_t& gtc) { m_GTC = gtc; }
00032
00033 void Hit::setDIFBCID(const std::uint32_t& difbcid) { m_DIFBCID = difbcid; }
00034
00035 void Hit::setFrameBCID(const std::uint32_t& framebcid) { m_FrameBCID = framebcid; }
00036
00037 void Hit::setTimestamp(const std::uint32_t& timestamp) { m_Timestamp = timestamp; }
00038
00039 void Hit::setAbsoluteBCID(const std::uint64_t& absolutebcid) { m_AbsoluteBCID = absolutebcid; }
00040
00041 std::uint8_t Hit::getDIFid()const { return m_DIF; }
00042
```

```

00043 std::uint8_t Hit::getASICId()const { return m_ASIC; }
00044
00045 std::uint8_t Hit::getChannel()const { return m_Channel; }
00046
00047 std::uint8_t Hit::getThreshold()const { return m_Threshold; }
00048
00049 std::uint32_t Hit::getDTC()const { return m_DTC; }
00050
00051 std::uint32_t Hit::getGTC()const { return m_GTC; }
00052
00053 std::uint32_t Hit::getDIFBCID()const { return m_DIFBCID; }
00054
00055 std::uint32_t Hit::getFrameBCID()const { return m_FrameBCID; }
00056
00057 std::uint32_t Hit::getTimestamp()const { return m_Timestamp; }
00058
00059 std::uint64_t Hit::getAbsoluteBCID()const { return m_AbsoluteBCID; }

```

5.79 libs/interface/ROOT/src/ROOTWriter.cc File Reference

```
#include "ROOTWriter.h"
```

5.79.1 Detailed Description

Copyright

2022 G.Grenier F.Lagarde

Definition in file [ROOTWriter.cc](#).

5.80 ROOTWriter.cc

[Go to the documentation of this file.](#)

```

00001
00006 #include "ROOTWriter.h"
00007
00008 void ROOTWriter::setFilename(const std::string& filename) { m_Filename = filename; }
00009
00010 ROOTWriter::ROOTWriter() : InterfaceWriter("ROOTWriter", "1.0.0") { addCompatibility("RawdataReader",
    ">=1.0.0"); }
00011
00012 void ROOTWriter::start()
00013 {
00014     m_File = TFile::Open(m_Filename.c_str(), "RECREATE", m_Filename.c_str(),
    ROOT::CompressionSettings(ROOT::kZLIB, 5));
00015     m_Tree = new TTree("RawData", "Raw SDHCAL data tree");
00016     m_Tree->Branch("Events", &m_Event, 512000, 99);
00017 }
00018
00019 void ROOTWriter::end()
00020 {
00021     if(m_Tree) m_Tree->Write();
00022     if(m_File)
00023     {
00024         m_File->Write();
00025         m_File->Close();
00026     }
00027     if(m_File) delete m_File;
00028 }
00029
00030 void ROOTWriter::processDIF(const PayloadParser& d)
00031 {
00032     m_DIF->setID(d.getDIFid());
00033     m_DIF->setDTC(d.getDTC());
00034     m_DIF->setGTC(d.getGTC());
00035     m_DIF->setDIFBCID(d.getBCID());
00036     m_DIF->setAbsoluteBCID(d.getAbsoluteBCID());
00037 }
00038

```

```
00039 void ROOTWriter::processFrame(const PayloadParser& d, const std::uint32_t& frameIndex)
00040 {
00041     m_Hit->setDIF(d.getDIFid());
00042     m_Hit->setASIC(d.getASICid(frameIndex));
00043     m_Hit->setDTC(d.getDTC());
00044     m_Hit->setGTC(d.getGTC());
00045     m_Hit->setDIFBCID(d.getBCID());
00046     m_Hit->setAbsoluteBCID(d.getAbsoluteBCID());
00047     m_Hit->setFrameBCID(d.getFrameBCID(frameIndex));
00048     m_Hit->setTimestamp(d.getFrameTimeToTrigger(frameIndex));
00049 }
00050
00051 void ROOTWriter::processPadInFrame(const PayloadParser& d, const std::uint32_t& frameIndex, const
std::uint32_t& channelIndex)
00052 {
00053     m_Hit->setChannel(channelIndex);
00054     m_Hit->setThreshold(static_cast<std::uint8_t>(d.getThresholdStatus(frameIndex, channelIndex)));
00055 }
00056
00057 void ROOTWriter::startEvent()
00058 {
00059     m_Event = new Event();
00060     // m_Event->clear();
00061 }
00062
00063 void ROOTWriter::endEvent()
00064 {
00065     m_Tree->Fill();
00066     if(m_Event) delete m_Event;
00067 }
00068
00069 void ROOTWriter::startDIF()
00070 {
00071     m_DIF = new DIF();
00072     // m_DIF->clear();
00073 }
00074
00075 void ROOTWriter::endDIF()
00076 {
00077     m_Event->addDIF(*m_DIF);
00078     delete m_DIF;
00079 }
00080
00081 void ROOTWriter::startFrame()
00082 {
00083     m_Hit = new Hit();
00084     // m_Hit->clear();
00085 }
00086
00087 void ROOTWriter::endFrame()
00088 {
00089     m_DIF->addHit(*m_Hit);
00090     delete m_Hit;
00091 }
00092
00093 void ROOTWriter::startPad() {}
00094
00095 void ROOTWriter::endPad() {}
```

