

SOFTWARE TEST PLAN

Blood Bank Management System (BBMS)

Software Engineering Mini-Project — Deliverable Part 1

Document ID	BBMS-TP-001
Version	1.0
Status	Draft / Test Execution Pending
Date	27 September 2026
Project	Blood Bank Management System (BBMS)
Technology	Python (Django) / JavaScript (Node.js), JavaScript/HTML/CSS, SQLite
Team	Team T9
Authors	Uttam (PES1UG24CS697); Abhinav K (PES1UG24CS701); Akshay Arcot (PES1UG24CS705); Navaneeth Tanuboddi (PES1UG24CS709)

Table of Contents

1. Introduction
2. Test Items / System Overview
3. Features to Be Tested
4. Features Not to Be Tested
5. Test Approach / Test Strategy
 - 5.1 Security Validation
 - 5.2 Functional Testing
 - 5.3 Integration Testing
 - 5.4 System / End-to-End Testing
 - 5.5 Regression Testing
 - 5.6 Performance Testing
 - 5.7 Reliability / Stress Testing
 - 5.8 Usability / Accessibility Testing
 - 5.9 Portability / Compatibility Testing
6. Test Environment
7. Test Data
8. Entry Criteria
9. Exit Criteria
10. Pass / Fail Criteria
11. Suspension and Resumption Criteria
12. Test Deliverables
13. Test Schedule / Milestones
14. Risks and Contingencies
15. Responsibilities / Roles
16. Requirements Traceability
17. Approvals

1. Introduction

1.1 Purpose

This Software Test Plan defines the test strategy, scope, environment, test data, acceptance criteria, test cases, security validation activities, and requirements traceability for the Blood Bank Management System (BBMS). The plan is aligned with the functional, non-functional, and security requirements in the BBMS Software Requirements Specification (SRS) v1.0. The purpose is to provide a repeatable method for verifying that implemented BBMS behavior satisfies the specified requirements.

1.2 Scope

Testing covers the browser-based BBMS workflows from donor and hospital registration through donation, testing, inventory, requisition, compatibility checking, allocation, dispatch, delivery confirmation, auditing, administration, reporting, and public availability. Non-functional validation covers performance, reliability, usability/accessibility, maintainability, portability, and scalability requirements. Security validation covers authentication, password protection, server-side RBAC, SQL injection prevention, input validation/XSS, session security, brute-force/rate limiting, HTTPS/TLS, and auditability.

1.3 Test Objectives

- Verify that each major functional workflow satisfies its corresponding BBMS-F requirement.
- Verify that measurable non-functional requirements are validated using defined thresholds and test methods.
- Validate that security controls satisfy BBMS-SR-001 through BBMS-SR-008.
- Identify defects, inconsistencies, boundary conditions, and integration failures before acceptance.
- Maintain bidirectional traceability between SRS requirements and test cases.

1.4 References

- BBMS Software Requirements Specification (SRS), Version 1.0, Software Engineering Mini-Project, Deliverable Part 1.
- IEEE Std 830-1998, used by the SRS as a structural reference.
- Applicable course guidance for Software Engineering Mini-Project Part 1, including the required Test Plan sections and security validation.

1.5 Definitions and Acronyms

Term	Meaning
BBMS	Blood Bank Management System
SRS	Software Requirements Specification
FEFO	First-Expiry-First-Out
RBAC	Role-Based Access Control
API	Application Programming Interface
REST	Representational State Transfer
SQLi	SQL Injection
XSS	Cross-Site Scripting
STAT	Immediate / emergency priority request
Bag ID	Unique identifier assigned to a collected blood unit
WCAG	Web Content Accessibility Guidelines

1.6 Document Overview

Sections 2–4 define what is under test and what is excluded. Section 5 defines the test strategy, including the required Section 5.1 security validation. Sections 6–15 define execution conditions, criteria, deliverables, schedule, risks, and responsibilities. Section 16 provides requirements traceability, and Section 17 records approvals.

2. Test Items / System Overview

2.1 System Under Test

BBMS is a standalone academic web application supporting the workflow donor → collection → testing → inventory → requisition → dispatch. It uses a browser-based client, a Python (Django) or Node.js (Express) backend, an ORM/data-access layer, and an embedded SQLite database. Outbound email notifications use SMTP as described in the SRS.

2.2 Major Functional Modules

Module	Primary Scope	SRS Coverage
Authentication / Access	Registration, login, reset, sessions, RBAC	F-001–F-005; F-040–F-042; F-060–F-063; SR-001–SR-007
Donor	Profiles, eligibility, appointments, history	F-006–F-019
Collection / Blood Unit	Collection, Bag ID, blood group	F-017–F-023
Testing / Quarantine	Serology, quarantine, discard	F-024–F-030
Inventory / FEFO	Components, counts, expiry, FEFO	F-031–F-039
Hospital / Requisition	Registration, requisitions, STAT queue	F-040–F-048
Matching / Allocation	Compatibility and allocation	F-049–F-055
Dispatch / Delivery	Dispatch records and receipt	F-052–F-057
Audit / Admin	Audit, users, roles	F-058–F-063; SR-008
Reports / Public Portal	Reports and availability lookup	F-064–F-068
Quality Attributes	Performance, reliability, UX, portability, scale	NF-001–NF-015

2.3 User Roles

- Donor — registers, completes eligibility, books appointments, donates, and views history.
- Hospital User — registers, requests blood, tracks requisitions, and confirms delivery.
- Blood Bank Staff — records collection, testing, quarantine, component separation, inventory, approval, allocation, and dispatch.
- Administrator — manages users/roles, approves hospitals, reviews audit logs, and generates reports.
- Public / Guest — views public blood availability only.

2.4 Test Levels

- Unit testing for business-logic modules and validation routines.
- Integration testing for API, database, authentication, notification, inventory, and cross-module interactions.
- System/end-to-end testing for complete role-based workflows.
- Non-functional testing for measurable performance, reliability, usability/accessibility, portability, maintainability, and scalability requirements.

3. Features to Be Tested

The following features are in test scope. Each entry is mapped to the exact SRS requirement identifiers.

Feature	SRS Requirement IDs
Donor registration, age validation, unique email, authentication, password reset	F-001–F-005
Donor profile, donation history, next eligible donation date	F-006–F-008
Medical eligibility questionnaire and outcome recording	F-009–F-011
Appointment booking, slot capacity, reschedule, cancel, notification	F-012–F-016
Blood collection, volume/time capture, donor history update	F-017–F-019
Unique Bag ID generation and duplicate prevention	F-020–F-021
ABO/Rh blood-group support and confirmed blood-group correction	F-022–F-023
Serology tests, quarantine default, pass/fail, discard on reactive result	F-024–F-027
Quarantine visibility, availability exclusion, status audit, quarantine list	F-028–F-030
Component separation and origin traceability	F-031–F-032
Real-time inventory, filtering, count updates	F-033–F-036
Expiry calculation, FEFO ordering, automatic expiry handling	F-037–F-039
Hospital registration/approval/login	F-040–F-042
Hospital requisitions, IDs, approval/partial/rejection, history	F-043–F-046
Emergency/STAT prioritization and alerts	F-047–F-048

Feature	SRS Requirement IDs
Compatibility determination, allocation restrictions/override, outcome recording	F-049–F-051
Allocation, dispatch records, status updates, fulfilment status	F-052–F-055
Delivery confirmation and delivered status	F-056–F-057
Audit logging and administrator-only read-only audit access	F-058–F-059
Admin user/role management and hospital approval	F-060–F-063
CSV reports and public blood availability without identifying data	F-064–F-068
Performance, reliability, usability/accessibility, maintainability, portability, scalability	NF-001–NF-015
Authentication, password hashing, RBAC, SQLi prevention, XSS, session security, brute-force/rate limiting, HTTPS/TLS and auditability	SR-001–SR-008

4. Features Not to Be Tested

The following are explicitly out of scope because the SRS identifies them as excluded from the mini-project. They may be reviewed for scope compliance but are not functional test targets.

- Integration with national or regional blood-bank registries or government health systems (SRS 1.2).
- Payment processing or billing of any kind (SRS 1.2).
- Direct interfacing with physical laboratory testing equipment; serology results are entered manually by staff (SRS 1.2 and 2.6).
- Native mobile applications; testing is limited to the responsive web application (SRS 1.2).
- Multi-language localization (SRS 1.2).

5. Test Approach / Test Strategy

Testing uses a risk-based, requirement-driven approach. Functional tests verify specified behavior using representative positive, negative, boundary, and authorization cases. Integration and end-to-end tests verify that workflows remain consistent across UI, REST API, authentication, database, email notification, and business rules. Non-functional tests use measurable SRS thresholds. Security validation is performed before acceptance of security-sensitive functionality.

5.1 Security Validation

Security testing shall validate each SRS security requirement using controlled positive and negative test cases. Tests shall be performed against a non-production test environment and shall not use real donor or hospital data.

Test Case	Requirement	Area	Method	Expected Security Result
TC-SEC-01	SR-001	Authentication	Attempt access to role-specific function without login; verify authenticated access succeeds.	Unauthenticated request is denied; authenticated valid user is granted access appropriate to role.
TC-SEC-02	SR-002	Password hashing	Register/change password, inspect stored credential representation and logs/responses.	Only one-way salted hashes are stored; plaintext password is absent from logs/responses.
TC-SEC-03	SR-003	RBAC	Attempt donor/hospital access to staff/admin endpoint; verify server-side authorization.	Unauthorized request receives HTTP 403 and protected data/action is not exposed.
TC-SEC-04	SR-004	SQL injection	Submit SQL injection payloads in authentication/search/form inputs and review API/database behavior.	Input is treated as data; no unauthorized query execution or data exposure occurs.
TC-SEC-05	SR-005	Input validation/XSS	Submit malformed fields and stored/reflected XSS probes.	Invalid payloads are rejected/encoded and script content is not executed.
TC-SEC-06	SR-006	Session/cookies	Inspect session cookies and test logout/inactivity expiration.	Cookies are HttpOnly, Secure, have defined expiry; logout and 30-minute inactivity invalidate session.
TC-SEC-07	SR-007	Brute-force/rate limit	Perform repeated failed logins and rapid login requests.	Account locks for 15 minutes after 5 consecutive failures; requests beyond 10/IP/min are rate-limited.

Test Case	Requirement	Area	Method	Expected Security Result
TC-SEC-08	SR-008	HTTPS/TLS + audit	Connect over HTTP/HTTPS and perform security-relevant actions.	Client-server traffic uses HTTPS/TLS; login attempts, lockouts, role changes and other security events are recorded in tamper-evident audit trail.

5.2 Functional Testing

Functional testing verifies each workflow against its SRS acceptance condition. Tests include valid input, invalid input, boundary cases, duplicate data, unavailable inventory, incompatible blood groups, unauthorized roles, and state transitions.

5.3 Integration Testing

Integration testing verifies interfaces between frontend and REST API, API and SQLite/ORM, authentication and authorization middleware, collection and inventory, testing and quarantine, requisitions and matching, allocation and dispatch, notifications and SMTP, and audit logging with all data-changing operations.

5.4 System / End-to-End Testing

End-to-end scenarios shall follow complete user journeys: donor registration → eligibility → appointment → collection → testing → availability; and hospital registration → requisition → approval → matching → allocation → dispatch → delivery confirmation.

5.5 Regression Testing

Regression testing shall be rerun after changes affecting authentication, inventory, blood status transitions, requisition allocation, cross-matching, reporting, or database schemas. Previously passed tests shall be executed again against affected modules.

5.6 Performance Testing

Performance testing shall validate the SRS thresholds: blood-availability search within 2 seconds under up to 50 concurrent users (NF-001), appointment booking within 3 seconds (NF-002), and at least 50 concurrent authenticated users without exceeding the stated response limits (NF-003).

5.7 Reliability / Stress Testing

Reliability testing shall validate 99% scheduled availability (NF-004), committed transaction persistence across application restart without data loss (NF-005), and server-side logging of unhandled application errors with timestamp and stack trace (NF-006).

5.8 Usability / Accessibility Testing

Usability testing shall verify that a first-time donor can complete registration without external assistance in under 5 minutes (NF-007), primary workflows conform to WCAG 2.1 Level AA colour-contrast and keyboard-navigation requirements (NF-008), and validation errors clearly identify the affected field and issue (NF-009).

5.9 Portability / Compatibility Testing

The client shall be tested on the latest two stable versions of Chrome, Firefox, and Edge (NF-012). Deployment shall be exercised on a host supporting Python 3.10+ or Node.js 18+ without code modification (NF-013). Maintainability and scalability requirements NF-010, NF-011, NF-014, and NF-015 shall be validated through code review, unit-test coverage, schema review, and architecture review as applicable.

6. Test Environment

Category	Planned Environment
Hardware	Standard PC/laptop or single virtual machine; no specialized hardware required.
Server OS	Host OS supporting Python 3.10+ or Node.js 18+.

Category	Planned Environment
Backend	Python 3.10+ with Django or Node.js 18+ with Express, per implementation choice.
Database	SQLite embedded database via ORM/data-access layer.
Client	Modern JavaScript-enabled browser over LAN/internet connectivity.
Browsers	Latest two stable versions of Chrome, Firefox, and Edge for portability testing.
Network	HTTPS/TLS for client-server communication; SMTP for outbound email tests.
Tools	Node.js test runner and Supertest where applicable; ApacheBench for load tests; Lighthouse for accessibility; controlled SQL injection testing tool/manual payloads.
Test Data Isolation	Synthetic donor, hospital, inventory, and requisition records only; no production/real patient data.

Note: Tool usage is planned from the SRS-described test approach; this document does not claim that any test has already been executed.

7. Test Data

Data Category	Examples / Conditions
Donors	Valid adult donor; under-18 donor; duplicate email; valid and invalid contact details.
Eligibility	All eligible answers; each configured disqualifying condition; recorded outcome linked to appointment.
Appointments	Available slot; full-capacity slot; cancellation; reschedule inside/outside 24-hour window.
Blood Units	Unique Bag IDs; duplicate ID attempt; all eight ABO/Rh groups; component types.
Serology	Pass for all required tests; single Fail; incomplete test set; quarantine transitions.
Inventory	Available, Quarantined, Discarded, Expired, Dispatched, Delivered units; multiple expiry dates for FEFO.
Hospitals	Pending approval; approved; rejected; deactivated credentials.
Requisitions	Routine and Emergency/STAT; full, partial, rejected, incompatible and compatible requests.
Security Inputs	SQL injection strings; XSS probes; invalid payload sizes/types; repeated failed logins.
Performance Data	Synthetic concurrent sessions and repeated blood-availability queries up to 50 users.

8. Entry Criteria

- Approved SRS and Test Plan baseline is available.
- Build/deployment candidate is available in a controlled test environment.
- Database schema and required seed/configuration data are available.
- Test accounts for Donor, Hospital User, Blood Bank Staff, and Administrator exist or can be created.
- Required test tools and browser versions are available.
- No known blocker prevents execution of core test workflows.

9. Exit Criteria

- All planned functional and security test cases have been executed or formally marked Blocked with reason.
- No unresolved Critical or High severity defect remains for an acceptance-critical feature.
- All mandatory performance thresholds in NF-001 through NF-003 have been evaluated.
- Reliability, usability/accessibility, portability, maintainability, and scalability requirements have been assessed using their defined methods.
- Requirements Traceability Matrix is updated with actual test status and defect references.

10. Pass / Fail Criteria

A test case is Pass when all stated expected results are observed without an unacceptable defect. A test case is Fail when any mandatory expected result is not satisfied. A test may be marked Blocked when execution cannot proceed because of an environment, dependency, or unresolved prerequisite issue. “Not Run” is used before execution. No result is pre-labelled Pass in this plan.

11. Suspension and Resumption Criteria

Testing may be suspended when the build cannot start, the database is unavailable, a blocker prevents execution of core workflows, test data is corrupted, or the environment is materially different from the approved baseline.

Testing resumes after the blocker is resolved, the environment is revalidated, and affected tests are rerun from the applicable baseline.

12. Test Deliverables

- Approved Software Test Plan (.docx).
- Detailed functional and non-functional test cases.
- Security validation test set.
- Test execution records with Actual Result and Status fields.
- Defect records and retest evidence, if defects are found.
- Updated Requirements Traceability Matrix.
- Test summary / acceptance report after execution.

13. Test Schedule / Milestones

Milestone	Planned Activity	Target
T1	Test-plan baseline and environment readiness	Before system test execution
T2	Functional and integration test execution	After build is available
T3	Security validation	After authentication/RBAC/input controls are integrated
T4	Performance, reliability, accessibility, portability tests	After core workflows stabilize
T5	Regression and retesting	After defect fixes
T6	Final traceability and test summary	Before project acceptance

14. Risks and Contingencies

Risk	Impact	Mitigation / Contingency
SQLite write concurrency limitations	Performance/availability limits during concurrent tests	Keep load within SRS mini-project scope; measure and document observed limits.
Unstable build or incomplete integration	Blocks functional tests	Freeze a test build before execution; maintain a known-good baseline.
Incorrect test data or time configuration	False failures in expiry/eligibility tests	Use seeded, versioned test data and server-authoritative timestamps.
Security test payloads affect test data	Data contamination	Use isolated test database and synthetic accounts only.
Email/SMTP unavailable	Notification tests blocked	Record dependency as Blocked; verify non-email on-screen behavior separately where specified.
Browser/version differences	UI compatibility defects	Execute portability tests on required browsers and record deviations.
High-severity defect discovered late	Acceptance delay	Prioritize blocker/high-severity fixes and focused regression on affected modules.

15. Responsibilities / Roles

Role	Responsibilities
Project / Test Lead	Maintain Test Plan, coordinate execution, review evidence, update traceability and test summary.

Role	Responsibilities
Developer / Module Owner	Provide builds, support test-data setup, fix defects, and support root-cause analysis.
Tester	Execute test cases, record evidence, classify defects, and perform retesting/regression.
Security Validation Owner	Execute SR-001–SR-008 validation and document security findings.
Academic Evaluator	Review deliverables and acceptance evidence as required by the course.

16. Requirements Traceability

The following matrix links the exact SRS requirement groups to planned test cases. Status is “Not Run” until execution occurs. Where a single test case validates a group of closely related requirements, the mapping is explicit.

SRS Req.	Module / Feature	Test Case ID(s)	Verification Type	Status
F-001–F-005	Donor registration/login/recovery	TC-AUTH-01, TC-AUTH-02	Functional / Security	Not Run
F-006–F-008	Donor profile/history/eligibility date	TC-DNR-01	Functional	Not Run
F-009–F-011	Medical eligibility questionnaire	TC-ELG-01	Functional	Not Run
F-012–F-016	Appointment booking/reschedule/cancel/notification	TC-APT-01, TC-APT-02	Functional / Integration	Not Run
F-017–F-019	Blood collection	TC-COL-01	Functional	Not Run
F-020–F-021	Bag ID uniqueness	TC-BAG-01	Functional	Not Run
F-022–F-023	Blood group management	TC-BAG-02	Functional	Not Run
F-024–F-027	Serology and unsafe-unit handling	TC-SER-01, TC-SER-02	Functional / Security	Not Run
F-028–F-030	Quarantine controls	TC-QNT-01	Functional / Audit	Not Run
F-031–F-032	Component separation	TC-CMP-01	Functional	Not Run
F-033–F-036	Inventory management	TC-INV-01, TC-INV-02	Functional / Integration	Not Run
F-037–F-039	Expiry and FEFO	TC-EXP-01	Functional	Not Run
F-040–F-042	Hospital registration/login	TC-AUTH-03	Functional / Authorization	Not Run
F-043–F-046	Blood requisition	TC-REQ-01, TC-REQ-02	Functional	Not Run
F-047–F-048	Emergency/STAT	TC-REQ-03	Functional / Integration	Not Run
F-049–F-051	Compatibility/cross-matching	TC-MATCH-01	Functional	Not Run
F-052–F-055	Allocation/dispatch	TC-DISP-01	Functional / Integration	Not Run
F-056–F-057	Delivery confirmation	TC-DEL-01	Functional	Not Run
F-058–F-059	Audit logging	TC-AUD-01	Functional / Security	Not Run
F-060–F-063	Admin/user/role management	TC-ADM-01	Functional / Security	Not Run
F-064–F-066	Reports/analytics	TC-RPT-01	Functional	Not Run
F-067–F-068	Public availability/privacy	TC-PUB-01	Functional / Security	Not Run
NF-001–NF-003	Performance/concurrency	TC-NF-01	Performance	Not Run
NF-004–NF-006	Reliability/availability/error logging	TC-NF-02	Reliability	Not Run
NF-007–NF-009	Usability/accessibility/errors	TC-NF-03	Usability / Accessibility	Not Run
NF-010–NF-011	Maintainability/unit-test coverage	TC-NF-04	Maintainability	Not Run
NF-012–NF-013	Portability/browser/runtime	TC-NF-05	Portability	Not Run
NF-014–NF-015	Scalability/location extension	TC-NF-06	Scalability / Architecture	Not Run
SR-001	Authentication	TC-SEC-01	Security	Not Run
SR-002	Password hashing	TC-SEC-02	Security	Not Run
SR-003	RBAC/authorization	TC-SEC-03	Security	Not Run
SR-004	SQL injection prevention	TC-SEC-04	Security	Not Run
SR-005	Input validation/XSS	TC-SEC-05	Security	Not Run
SR-006	Session/cookie security	TC-SEC-06	Security	Not Run
SR-007	Brute-force/rate limiting	TC-SEC-07	Security	Not Run
SR-008	HTTPS/TLS and security auditability	TC-SEC-08, TC-AUD-01	Security / Audit	Not Run

16.1 Detailed Test Cases

TC-AUTH-01 — Valid donor registration and login

Field	Details
Requirement ID	BBMS-F-001, F-002, F-003, F-004
Module / Feature	Authentication
Priority	High
Objective	Verify valid donor registration, age validation, unique email, and subsequent authentication.
Preconditions	Registration page available; email not previously registered.
Test Data	Adult donor details; unique email; valid password.
Test Steps	1. Submit valid registration. 2. Confirm account creation. 3. Log in with the registered credentials. 4. Attempt duplicate registration with the same email.

Field	Details
Expected Result	Valid donor account is created and can authenticate; under-age data is rejected; duplicate email registration is rejected.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-DNR-01 — Donor profile and history

Field	Details
Requirement ID	BBMS-F-006–F-008
Module / Feature	Donor Profile
Priority	Medium
Objective	Verify profile update, donation history display, and next eligible donation date calculation.
Preconditions	Authenticated donor with prior successful donation record.
Test Data	Updated contact/address/blood group; prior donation date.
Test Steps	1. Open profile. 2. Update permitted fields. 3. View donation history. 4. Compare displayed next eligible date to configured interval.
Expected Result	Profile changes persist; history shows date/location/Bag ID; next eligible date reflects the configured interval.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-ELG-01 — Medical eligibility questionnaire

Field	Details
Requirement ID	BBMS-F-009–F-011
Module / Feature	Eligibility
Priority	High
Objective	Verify questionnaire is completed before booking and disqualifying answers produce temporary ineligibility.
Preconditions	Donor has a selectable appointment slot.
Test Data	One eligible response set and one disqualifying response set.
Test Steps	1. Attempt booking without questionnaire. 2. Complete eligible questionnaire and book. 3. Repeat with disqualifying response.
Expected Result	Booking cannot be confirmed before questionnaire; eligible donor can proceed; disqualifying answer marks donor temporarily ineligible and records outcome.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-APT-01 — Appointment capacity and cancellation

Field	Details
Requirement ID	BBMS-F-012, F-013, F-015, F-016
Module / Feature	Appointment Booking
Priority	High
Objective	Verify slot availability/capacity, cancellation, and notification behavior.
Preconditions	A configured appointment slot with known capacity.
Test Data	Bookings up to capacity; cancellation request.
Test Steps	1. Fill slot to capacity. 2. Attempt an additional booking. 3. Cancel an existing appointment. 4. Retry booking.
Expected Result	Capacity limit prevents excess booking; cancellation releases capacity; confirmation is shown and/or sent according to the SRS.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-COL-01 — Blood collection and donor update

Field	Details
Requirement ID	BBMS-F-017–F-019
Module / Feature	Blood Collection
Priority	High
Objective	Verify staff can record collection details and donor history is updated immediately.
Preconditions	Confirmed donor appointment and staff account.

Field	Details
Test Data	Collection volume and timestamp.
Test Steps	1. Start collection. 2. Record volume/date/time. 3. Complete collection. 4. Check donor history and last-donation date.
Expected Result	Collection is stored against appointment; required volume/time are captured; donor last-donation date and history update immediately.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-BAG-01 — Bag ID uniqueness

Field	Details
Requirement ID	BBMS-F-020, F-021
Module / Feature	Blood Unit
Priority	High
Objective	Verify a unique Bag ID is generated and duplicates are rejected.
Preconditions	Collection can be completed.
Test Data	Two collection events; forced duplicate Bag ID attempt.
Test Steps	1. Complete first collection. 2. Record generated Bag ID. 3. Complete second collection. 4. Attempt to reuse the first Bag ID.
Expected Result	Each collection receives a unique Bag ID; duplicate Bag ID creation is rejected.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SER-01 — Serology quarantine and availability

Field	Details
Requirement ID	BBMS-F-024–F-027
Module / Feature	Serology / Quarantine
Priority	High
Objective	Verify all required tests are recorded and unsafe units cannot become available.
Preconditions	Collected unit exists in Quarantined state.
Test Data	Pass results for all tests; separate case with one Fail.
Test Steps	1. Record incomplete tests. 2. Verify unit remains quarantined. 3. Record all Pass results. 4. Verify status becomes Available. 5. Record a Fail for another unit.
Expected Result	Unit remains quarantined until all tests pass; all-pass unit can become Available; any Fail sets Discarded and blocks allocation/dispatch.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-INV-01 — Inventory counts and FEFO

Field	Details
Requirement ID	BBMS-F-033–F-039
Module / Feature	Inventory / FEFO
Priority	High
Objective	Verify count updates, expiry handling, and first-expiring selection.
Preconditions	At least two available compatible units with different expiry dates.
Test Data	Units U1/U2 with ordered expiry dates; one expired unit.
Test Steps	1. Verify counts. 2. Allocate a unit. 3. Recheck count. 4. Run allocation suggestion. 5. Advance/test expiry condition.
Expected Result	Counts update correctly; FEFO selects the closest expiry; expired units are flagged and excluded from counts/allocation.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-REQ-03 — Emergency/STAT prioritization

Field	Details
Requirement ID	BBMS-F-047, F-048
Module / Feature	Hospital Requisition
Priority	High
Objective	Verify Emergency/STAT requests are prioritized and staff are notified.

Field	Details
Preconditions	Approved hospital user and pending routine request.
Test Data	Routine request and later Emergency/STAT request.
Test Steps	1. Submit routine request. 2. Submit Emergency/STAT request. 3. Open staff queue. 4. Check alert/notification.
Expected Result	STAT request appears at top of pending queue and available staff receive an on-screen alert and/or email immediately.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-MATCH-01 — ABO/Rh compatibility and allocation restriction

Field	Details
Requirement ID	BBMS-F-049–F-051
Module / Feature	Cross-Matching
Priority	High
Objective	Verify compatible units are accepted and incompatible units are blocked unless authorized override is recorded.
Preconditions	Approved requisition and inventory containing compatible/incompatible units.
Test Data	Compatible and incompatible blood groups; optional override justification.
Test Steps	1. View compatible group list. 2. Attempt incompatible allocation. 3. Attempt authorized override with justification. 4. Review recorded outcome.
Expected Result	Compatible groups are displayed; incompatible allocation is prevented unless authorized override is recorded; outcome is logged as Compatible/Incompatible/Overridden.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-DISP-01 — Allocation and dispatch

Field	Details
Requirement ID	BBMS-F-052–F-055
Module / Feature	Dispatch
Priority	High
Objective	Verify allocation by Bag ID, dispatch record, status changes, and fulfilment status.
Preconditions	Approved requisition with sufficient compatible inventory.
Test Data	One or more Bag IDs.
Test Steps	1. Allocate units to requisition. 2. Generate dispatch record. 3. Dispatch units. 4. Review inventory and requisition status.
Expected Result	Allocated Bag IDs are linked to requisition; dispatch record captures requisition, Bag IDs, staff and timestamp; units become Dispatched and are removed from available counts; requisition becomes Fulfilled or Partially Fulfilled as applicable.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-DEL-01 — Delivery confirmation

Field	Details
Requirement ID	BBMS-F-056, F-057
Module / Feature	Delivery
Priority	Medium
Objective	Verify hospital receipt confirmation updates custody records and unit status.
Preconditions	Dispatched unit linked to hospital requisition.
Test Data	Receiving hospital user.
Test Steps	1. Open delivered requisition. 2. Confirm receipt. 3. Review receipt record and unit status.
Expected Result	Timestamp and receiving staff identity are recorded; unit status changes to Delivered.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-AUD-01 — Audit logging and read-only access

Field	Details
Requirement ID	BBMS-F-058, F-059
Module / Feature	Audit
Priority	High
Objective	Verify data-changing actions create audit records and only administrators can view/edit audit entries.
Preconditions	Users in multiple roles; test records available.
Test Data	Create/update/delete actions and role changes.
Test Steps	1. Perform representative data changes. 2. Review audit log as Administrator. 3. Attempt audit access/edit as non-admin.
Expected Result	Audit entries contain actor, action, timestamp and record ID; non-admin access is denied; audit entries are read-only and non-deletable.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-01 — Performance under concurrent load

Field	Details
Requirement ID	BBMS-NF-001–NF-003
Module / Feature	Performance
Priority	High
Objective	Measure blood-availability search, appointment booking and authenticated-user response limits.
Preconditions	Stable test build; load tool configured.
Test Data	Synthetic dataset and up to 50 concurrent sessions.
Test Steps	1. Run blood-availability search load. 2. Run appointment-booking transaction timings. 3. Run concurrent authenticated-user scenario. 4. Record response metrics.
Expected Result	Availability search completes within 2 seconds under up to 50 concurrent users; booking completes within 3 seconds; concurrency requirement is met without exceeding stated response limit.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-03 — Usability and accessibility validation

Field	Details
Requirement ID	BBMS-NF-007–NF-009
Module / Feature	Usability / Accessibility
Priority	Medium
Objective	Verify registration duration, WCAG 2.1 AA requirements, and error-message clarity.
Preconditions	Accessible browser build and primary workflows available.
Test Data	First-time user scenario; invalid form entries.
Test Steps	1. Time first-time registration. 2. Run Lighthouse/manual accessibility checks. 3. Submit invalid form values.
Expected Result	Registration completes in under 5 minutes without assistance; primary workflows satisfy the specified WCAG color-contrast and keyboard-navigation criteria; errors clearly identify field and issue.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-02 — Password hashing and plaintext protection

Field	Details
Requirement ID	BBMS-SR-002
Module / Feature	Security / Authentication
Priority	High
Objective	Verify passwords are stored as salted one-way hashes and are not exposed.
Preconditions	Controlled test account and database access for inspection.
Test Data	Synthetic password.
Test Steps	1. Register/change password. 2. Inspect credential storage. 3. Inspect server logs and API responses.

Field	Details
Expected Result	Only salted one-way hash representation is stored; plaintext password is absent from logs and responses.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-03 — Server-side RBAC enforcement

Field	Details
Requirement ID	BBMS-SR-003
Module / Feature	Security / Authorization
Priority	High
Objective	Verify each protected API endpoint enforces server-side role authorization.
Preconditions	Donor, Hospital, Staff and Administrator accounts.
Test Data	Unauthorized endpoint requests.
Test Steps	1. Authenticate as each lower-privilege role. 2. Call protected endpoints directly. 3. Record HTTP responses.
Expected Result	Unauthorized requests are rejected with HTTP 403 and no protected operation/data is exposed.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-04 — SQL injection prevention

Field	Details
Requirement ID	BBMS-SR-004
Module / Feature	Security / Database
Priority	High
Objective	Verify raw SQL injection attempts cannot alter query semantics or access unauthorized data.
Preconditions	Test environment with synthetic database.
Test Data	Common SQL injection payloads in authentication and search inputs.
Test Steps	1. Submit payloads. 2. Observe API responses and server behavior. 3. Verify no unintended data access or state change.
Expected Result	Payloads are treated as data; database operations remain parameterized/ORM-backed; no SQL injection effect occurs.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-05 — Input validation and XSS prevention

Field	Details
Requirement ID	BBMS-SR-005
Module / Feature	Security / Input
Priority	High
Objective	Verify malformed inputs are rejected and stored/reflected XSS is prevented.
Preconditions	Forms and API endpoints available.
Test Data	Oversized values, invalid types, script/event-handler payloads.
Test Steps	1. Submit malformed payloads. 2. Submit XSS probes in stored and reflected contexts. 3. Reload affected pages.
Expected Result	Invalid input is rejected/validated; output is safely encoded; scripts do not execute.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-06 — Session and cookie security

Field	Details
Requirement ID	BBMS-SR-006
Module / Feature	Security / Session
Priority	High
Objective	Verify cookie flags, logout invalidation and inactivity timeout.
Preconditions	Authenticated browser session.
Test Data	Session cookie and controlled inactivity period.

Field	Details
Test Steps	1. Inspect cookie attributes. 2. Logout and retry protected request. 3. Simulate 30 minutes inactivity.
Expected Result	Session cookies are HttpOnly/Secure with defined expiry; logout invalidates the session; inactivity beyond 30 minutes invalidates the session.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-07 — Brute-force lockout and rate limiting

Field	Details
Requirement ID	BBMS-SR-007
Module / Feature	Security / Authentication
Priority	High
Objective	Verify repeated failed attempts trigger lockout and rapid requests are rate-limited.
Preconditions	Controlled test account and client IP.
Test Data	Six failed attempts; >10 login requests within one minute.
Test Steps	1. Submit five consecutive failed login attempts. 2. Attempt sixth login during lockout. 3. Generate rapid requests within one minute.
Expected Result	Account is locked for 15 minutes after five failures; rapid login traffic beyond 10 requests per minute per source IP receives rate limiting.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-SEC-08 — HTTPS/TLS and security-event auditing

Field	Details
Requirement ID	BBMS-SR-008
Module / Feature	Security / Transport / Audit
Priority	High
Objective	Verify encrypted communication and tamper-evident logging of security-relevant events.
Preconditions	HTTPS-enabled test environment.
Test Data	Login attempts, lockout and role-change actions.
Test Steps	1. Access application over HTTP and HTTPS. 2. Perform security-relevant events. 3. Review security audit records.
Expected Result	Client-server communication uses HTTPS/TLS; security-relevant events such as login attempts, lockouts and role changes are recorded in the audit trail.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-02 — Reliability, restart persistence and error logging

Field	Details
Requirement ID	BBMS-NF-004–NF-006
Module / Feature	Reliability
Priority	High
Objective	Verify committed transactions survive application restart and unhandled errors are logged while availability target is assessed.
Preconditions	Test build with persistence enabled.
Test Data	Committed donation, requisition and dispatch records; controlled fault case.
Test Steps	1. Create and commit records. 2. Restart application. 3. Verify records. 4. Trigger controlled unhandled error path. 5. Review error log.
Expected Result	Committed transaction data persists without loss; unhandled errors are logged with timestamp and stack trace; availability evidence is collected for scheduled test period.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-04 — Maintainability and unit-test coverage review

Field	Details
Requirement ID	BBMS-NF-010–NF-011
Module / Feature	Maintainability
Priority	Low
Objective	Verify modular/layered separation and minimum backend unit-test coverage.
Preconditions	Source tree and test suite available.
Test Data	Backend repository and coverage report.
Test Steps	1. Review module boundaries. 2. Verify inventory change does not require unrelated reporting changes. 3. Generate unit-test coverage report.
Expected Result	Backend follows layered/modular structure and backend business-logic coverage is at least 60%.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-05 — Browser and runtime portability

Field	Details
Requirement ID	BBMS-NF-012–NF-013
Module / Feature	Portability
Priority	Medium
Objective	Verify client rendering on required browsers and backend deployment on supported OS/runtime.
Preconditions	Access to required browser versions and one supported host.
Test Data	Primary BBMS workflows.
Test Steps	1. Execute smoke workflow on latest two stable Chrome/Firefox/Edge. 2. Deploy backend on supported Python/Node runtime host. 3. Execute smoke tests.
Expected Result	Web client renders correctly on required browser versions; backend deploys without code modification on supported runtime/host.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-NF-06 — Scalability architecture review

Field	Details
Requirement ID	BBMS-NF-014–NF-015
Module / Feature	Scalability
Priority	Low
Objective	Verify data-access abstraction supports future RDBMS migration and new blood-bank locations.
Preconditions	Source, schema, and architecture artifacts available.
Test Data	Database schema and location-related modules.
Test Steps	1. Inspect data-access interfaces. 2. Review location model boundaries. 3. Verify no donor/hospital/inventory module changes are inherently required for a new location.
Expected Result	SQLite-specific persistence is isolated behind data-access interfaces and the architecture supports a new location without modifying donor, hospital, or inventory modules as specified.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-REQ-01 — Routine blood requisition lifecycle

Field	Details
Requirement ID	BBMS-F-043–F-046
Module / Feature	Hospital Requisition
Priority	High
Objective	Verify valid requisition creation, unique ID, staff decision and hospital tracking.
Preconditions	Approved hospital user and available staff account.
Test Data	Blood group, component, quantity and required-by date.
Test Steps	1. Submit requisition. 2. Confirm unique ID and Pending status. 3. Approve/partially fulfil/reject as a staff user. 4. Review hospital history.

Field	Details
Expected Result	Required requisition fields are accepted; unique ID and Pending status are set; staff can approve/partially fulfil/reject and rejection reason is recorded; hospital sees current status/history.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-RPT-01 — Reports and analytics

Field	Details
Requirement ID	BBMS-F-064–F-066
Module / Feature	Reports
Priority	Medium
Objective	Verify required report data and date-range filtering.
Preconditions	Inventory, donation and requisition test records exist.
Test Data	Selected date range and records.
Test Steps	1. Generate inventory report. 2. Generate donation activity report. 3. Generate requisition fulfilment report. 4. Compare totals with underlying test records.
Expected Result	CSV inventory report contains group/component levels; donation report shows totals/units collected/discarded; fulfilment report shows received/fulfilled/partial/rejected counts for selected date range.
Actual Result	[To be recorded during execution]
Status	Not Run

TC-PUB-01 — Public blood availability and privacy

Field	Details
Requirement ID	BBMS-F-067–F-068
Module / Feature	Public Portal
Priority	High
Objective	Verify unauthenticated availability lookup and absence of identifying information.
Preconditions	Public portal available with synthetic stock.
Test Data	Inventory across blood groups/locations; donor/hospital identifying records.
Test Steps	1. Open public page without login. 2. Verify current availability by group/location. 3. Inspect page/API payload for identifiers.
Expected Result	Availability is visible without authentication and no donor-identifying or hospital-identifying information is exposed.
Actual Result	[To be recorded during execution]
Status	Not Run

17. Approvals

Approval is to be completed by the designated project/team authority and course evaluator after review. No approval is implied by this draft document.

Role	Name	Signature	Date
Project / Test Lead			
Faculty / Course Evaluator			