

# **Architecture & ETL Data Flow**

Cheng Han Chung

11/04/2025

# Architecture & ETL Data Flow

01

## Data Source

MongoDB stores agricultural readings (e.g., temperature, humidity, etc.)

02

## Cache Layer

Redis is used to temporarily store frequently accessed readings.

03

## Flow Overview

- a. Client → API request (GET /cache-aside/:sensorId)
- b. App checks Redis cache
  - If hit → return cached data
  - If miss → query MongoDB, then store result in Redis
- c. TTL (Time-to-Live) ensures cache entries auto-expire and refresh from MongoDB.

# Key Lessons from Implementation



1

Implementing caching significantly reduces response time (from ~80ms to <1ms after caching).

2

Cache-Aside pattern gives more control over when data is refreshed.

3

TTL (Expiration) helps maintain data freshness automatically.

4

Learned how Redis and MongoDB complement each other — Redis for speed, MongoDB for persistence.

# Challenges and Observations



## Good things:

- Cache layer integration improved performance dramatically.
- TTL ensured automatic invalidation without manual cleanup.



## Bad things:

- Initial connection setup, especially Redis + MongoDB credentials, took time to debug.
- Needed to handle missing cache carefully to avoid “stale data.”
- Performance varies slightly depending on network and dataset size.