Task 1: Requirements (IoT Context)

Prompt : Generate user requirements for an IoT indoor light monitoring system that detects low-light conditions and sends alerts to users.

Result Summary:

Requirement	Description
Continuous Light Monitoring	Monitor ambient indoor light levels continuously using light sensors.
Low-Light Detection	Detect when light levels fall below a user-defined threshold.
Multiple Room Support	Allow monitoring of light conditions in multiple rooms or zones.
Instant Alerts	Send real-time alerts to users upon detecting low-light conditions.
Alert Delivery Channels	Deliver alerts via preferred channels (mobile app, SMS, email).
User-Friendly Dashboard	Provide a dashboard to view real-time and historical light data per room.
Customizable Thresholds	Enable users to set and adjust low-light thresholds for each room/zone.
Device Management	Allow users to add, configure, and remove monitoring devices/sensors.
Alert History and Logging	Keep a log of all low-light events and alerts sent for user review.
Battery and Connectivity Status	Notify users about device battery and connectivity issues.
User Permissions and Security	Require secure authentication and support role-based access control.

Integration Capabilities	Support integration with other smart home systems (e.g., trigger smart lights automatically).

Pro:
The requirements are **comprehensive and system-oriented**, covering sensing (continuous monitoring), processing (threshold detection), actuation (alerts), and user interaction (dashboard, device management). This aligns well with an end-to-end IoT pipeline and supports scalability (e.g., multi-room support, integrations).

Con:
The requirements remain **high-level and lack operational constraints**, such as sensor accuracy, calibration strategy, latency bounds for “instant alerts,” network reliability assumptions, and edge-case handling (e.g., fluctuating light/noise), which are critical for a real IoT deployment.

Task 2: Architecture (IoT Pipeline)

Prompt: Generate an image for the architecture diagram for an IoT light sensor system including sensor, microcontroller, cloud, and user interface. focus on database

Result Summary:



Proc:

The AI-generated image (e.g., architecture diagram or system flow) improves conceptual clarity by visually representing components like sensors, microcontroller, cloud, and user interface. This is especially valuable in IoT systems where data flow and component interaction are critical.

Cons:

The image is often high-level and lacks technical precision, such as missing protocols (MQTT/HTTP), unclear data flow directions, or absence of deployment-level details (e.g., edge vs cloud processing boundaries). This limits its direct usability for implementation.

Task 3: Implementation (Backend API)

Prompt: Write a Node.js API endpoint to receive light sensor data and store it in a database.

Result Summary:

The AI generated a backend implementation using **Express.js** and **MongoDB (via Mongoose)** to handle IoT light sensor data. It defined a schema (sensorId, value, timestamp) and created a POST /api/sensordata endpoint to receive and store incoming sensor readings. The API includes basic input validation (required fields), timestamp handling, and error responses. Overall, it provides a minimal but functional pipeline for ingesting sensor data into a database.

Pro:

The implementation provides a **clean, functional backend scaffold** with clear separation of concerns (model + API route). It correctly uses Express for routing and Mongoose for schema enforcement, enabling quick integration with an IoT pipeline where sensors push data to a centralized database.

Con:

The API is **not production-ready**, lacking critical IoT system requirements such as authentication (to prevent unauthorized device writes), data validation rigor (e.g., range checks for light values), rate limiting, and resilience features (e.g., handling burst traffic from multiple sensors or intermittent connectivity).

Task 4: Testing (Sensor Data Logic)

Prompt: Generate unit tests for validating light sensor data processing logic including threshold detection.

Result Summary:

The AI generated unit tests using Jest to validate the processLightData function for an IoT light sensor system. The tests cover core scenarios including threshold comparison (below, equal, above), invalid inputs (missing or non-numeric values), and boundary conditions such as zero and negative thresholds. It ensures correct classification of light states (LOW_LIGHT vs OK) and basic error handling. Overall, the output focuses on validating decision logic rather than system-level behavior

Pros:

Provides strong coverage of core logic and edge cases, ensuring the threshold-based decision mechanism behaves correctly under typical and boundary conditions.

Cons:

Does not account for real-world IoT data challenges, such as noisy sensor readings, temporal fluctuations, or the need for smoothing/debouncing before classification.

Task 5: Verification (System Behavior)

Prompt: Verify that an IoT light sensor system correctly detects low-light conditions and triggers alerts under defined thresholds.

Result Summary:

The AI generated high-level test cases to verify system behavior for alert triggering based on light intensity thresholds. The tests validate that an alert condition (LOW_LIGHT) is produced when the sensor value falls below the threshold, and no alert (OK) is triggered when the value meets or exceeds it. It also conceptually includes assertions for alert system invocation, though the actual integration or mocking of the alert mechanism is not implemented.

Procs:

Clearly validates the core system behavior (alert triggering logic) by checking both triggering and non-triggering conditions, aligning well with verification goals in the V-Model.

Cons:

The tests are **incomplete at the system level**, as they only check return values and do not actually verify alert delivery (e.g., missing mocks/spies for notification services or integration with the alerting mechanism).