INTRODUCTION

SEA.AI Sentry system is capable of pan and tilt movements, where pan is a horizontal movement and tilt is a vertical movement. The pan movement allows for continuous 360° operation, and the tilt movement allows for a of ±20° operation.

Due to the environments in which Sentry systems are installed, there may be visual obstructions in the field of view of the system, which may cause the system to produce false positive alarms. These obstructions may include structures on vessels, such as antennas. Therefore, obstructions need to be captured and saved in the system's memory to be excluded from the artificial intelligence algorithms. This is accomplished by creating a Camera Obstruction Mask, explained below.

⚠	**WARNNING: HITTING AN OBSTACLE WHILE THE SENTRY SYSTEM IS IN MOTION COULD CAUSE A MOUNTING OR OTHER STRUCTURAL FAILURE THAT COULD RESULT IN INJURY OR DEATH.**

REQUIREMENTS

The following are the minimal requirements:

1. SEA.AI Sentry System
2. Sentry Software Version 3.5 and higher
3. Sentry Installer Login: Password obtained from service@sea.ai
4. Vessel needs to be outside of the harbor

STEP-BY-STEP INSRUCTIONS

Ensure that the Sentry system has been properly installed by qualified personnel. Additionally, ensure that the system is clear to move in both axes (pan and tilt) without hitting any obstructions before applying power to it.

1. On the main User Interface, go to Settings.
2. Select the Setup tab and scroll down to the *Installer Login* section.
3. In the Password field, type in the password and select Login as installer. If successful, there will be a *Service Mode* icon on the main User Interface.
4. Under Setup scroll down to *Camera Obstruction Mask*.
5. Select Run camera mask diagnostic. This make take up to 20 minutes.
6. Once the operation is complete, select Download mask file. The file name is panorama_image_full.tiff
7. Attach the panorama_image_full.tiff file to an email and send it to service@sea.ai.

The information contained in this document is proprietary to SEA.AI GmbH and is to be used only for the purpose for which it is supplied. It shall not be disclosed, in whole or in part, to any other party without the expressed written permission of SEA.AI GmbH.

8. The Professional Services team at SEA.AI will create a mask and send you back an e-mail with an attachment file named mask.tiff.

9. Download the attachment to your local computer.

10. Repeat steps 1 through 4 above, and under the select file field, navigate to the mask.tiff file sent to you by the Professional Services team.

11. Select Upload file to upload the mask to the Sentry system.

12. Restart the Sentry system to finish the upload.

13. Once the system has been restarted, you can toggle the Display camera mask in the image to see the image and the mask.

14. The setup is now COMPLETED.

The information contained in this document is proprietary to SEA.AI GmbH and is to be used only for the purpose for which it is supplied. It shall not be disclosed, in whole or in part, to any other party without the expressed written permission of SEA.AI GmbH.