model_training: small training examples

What this folder shows

The paper only uses models that others trained and published, so nothing in the reproduction trains a model. This folder shows, at a small scale, how each kind of model in the paper is trained: `train_mlp_example.py` (a plain network, scikit-learn), `train_cnn_example.py` (a convolutional network, PyTorch) and `train_transformer_example.py` (a small Transformer, PyTorch). The models they save cannot be used by the certificate scripts, which expect the published model files.

Before you start

`requirements.txt` for the plain network, `requirements-ml.txt` for the other two, and some traces: the TCHES20 download works with `--dataset ascad_desync_0`, `ascad_desync_50`, `ascad_desync_100`, `aes_rd` or `dpav4`. The first two examples run on a CPU in minutes. The Transformer example uses a GPU if one is present; on a CPU, lower the number of epochs or shorten the window.

Run

```
T=datasets/raw/tches20/TCHES20V3_CNN_SCA
python -m model_training.train_mlp_example --dataset ascad_desync_0 --data-dir $T/datasets --tches20-src-dir $T/src
```

```
$ T=datasets/raw/tches20/TCHES20V3_CNN_SCA; python -m model_training.train_mlp_example --dataset ascad_desyn
    c_0 --data-dir $T/datasets --tches20-src-dir $T/src
[... earlier output omitted; key lines kept ...]
[...]
Iteration 7, loss = 5.14499616
Validation score: 0.005833
Iteration 8, loss = 4.99942495
Validation score: 0.001667
Iteration 9, loss = 4.83513662
Validation score: 0.005000
Iteration 10, loss = 4.65186182
Validation score: 0.004167
Iteration 11, loss = 4.46369898
Validation score: 0.005000
Iteration 12, loss = 4.27612801
Validation score: 0.005000
Iteration 13, loss = 4.06112644
Validation score: 0.004167
Iteration 14, loss = 3.85434941
Validation score: 0.003333
Iteration 15, loss = 3.65443757
Validation score: 0.005000
Iteration 16, loss = 3.46244354
Validation score: 0.005000
Iteration 17, loss = 3.26435261
Validation score: 0.005000
Iteration 18, loss = 3.09986383
Validation score: 0.005000
Validation score did not improve more than tol=0.000100 for 10 consecutive epochs. Stopping.
```

```
validation_accuracy=0.004000
holdout_accuracy=0.005750
wrote checkpoints/model_training/ascad_desync_0/mlp

100%|██████████| 10000/10000 [00:02<00:00, 4447.26it/s]
[exit code 0, 18 s]
```

```
python -m model_training.train_cnn_example --dataset ascad_desync_0 --data-dir $T/datasets --tches20-src-dir $T/src --epochs 3
```

```
$ T=datasets/raw/tches20/TCHES20V3_CNN_SCA; python -m model_training.train_cnn_example --dataset ascad_desyn
    c_0 --data-dir $T/datasets --tches20-src-dir $T/src --epochs 3
Creating all target labels for the attack traces:
  Loaded via TCHES20 dataLoaders: 50000 profiling traces, 700 features
epoch=1 loss=5.546150 val_accuracy=0.004000
epoch=2 loss=5.541989 val_accuracy=0.004000
epoch=3 loss=5.538558 val_accuracy=0.004250
holdout_accuracy=0.003250
wrote checkpoints/model_training/ascad_desync_0/cnn

100%|██████████| 10000/10000 [00:02<00:00, 4572.40it/s]
[exit code 0, 27 s]
```

```
$ ls -R checkpoints/model_training && \
    cat checkpoints/model_training/ascad_desync_0/mlp/metadata.json
checkpoints/model_training:
ascad_desync_0

checkpoints/model_training/ascad_desync_0:
cnn
mlp

checkpoints/model_training/ascad_desync_0/cnn:
metadata.json
model.pt
scaler.pkl

[... 11 lines omitted ...]
    "hidden_layers": "512,256",
    "holdout_size": 0.2,
    "learning_rate": 0.001,
    "max_samples": 20000,
    "out_dir": "checkpoints/model_training",
    "seed": 1,
    "stratify": false,
    "tches20_src_dir": "datasets/raw/tches20/TCHES20V3_CNN_SCA/src",
    "train_size": 0.6,
    "val_size": 0.2,
    "window_end": null,
    "window_start": null
  },
  "metrics": {
    "holdout_accuracy": 0.00575,
    "val_accuracy": 0.004
  }
}
[exit code 0, 0 s]
```

What to look for

Each example prints the sizes of the training, validation and test parts, the training progress, and the accuracy on the test part. It saves the model and a `metadata.json` with the settings and results. With `--dataset ascad` (the plain ASCAD file rather than the TCHES20 copy) the loader mixes training and attack traces, so that accuracy is not a clean test number.