SEASUG Paper 104-2026

Box Office Success Predictor Tool

Kaden N. Swords, Oklahoma State University; Benjamin V. Hennel, Oklahoma State University

ABSTRACT

Film production decisions have long relied on industry relationships and experience rather than on data-driven evidence. This study builds a predictive model that estimates a film's probability of box-office success from its budget, genre, and the historical track record of its key contributors — actors, directors, writers, producers, and production companies. The Oracle of Bacon database, maintained by Dr. Patrick Reynolds, supplied 22,748,885 movie and television records. Television records were removed, leaving only theatrical films with a positive budget, positive revenue, and a known release date. Genres were condensed into five groups (Drama, Documentary, Family, Suspense, and Adventure) plus an Other category, and people and companies that appeared in fewer than 10 films were excluded from individual identification. Success was defined using the industry standard 2.5x rule: a film is considered successful if its revenue reaches at least 2.5 times its budget. Movies were divided chronologically, by release date, into an 80% training set and a 20% testing set, so the model is always evaluated on films it has not seen.

For each role and for production companies, historical weighted success rates identified the top 100, middle 100, and bottom 100 performers; all condensed genres were included. These selections, together with genre membership and log-transformed budget, were converted into indicator variables and analyzed using a hierarchical (mixed-effects) Bayesian logistic regression, fit with variational inference. Each known person, company, or genre receives its own shrunk weight around its role's baseline, so that individuals with only a handful of films are not over- or under-trusted relative to individuals with long track records.

The model achieved ROC AUCs of 0.788 on the training set and 0.639 on the testing set. Actor indicators tended to carry larger coefficient magnitudes than director and production-company indicators, while genre membership contributed comparatively little to the overall prediction. A companion web-based tool lets a user enter a hypothetical film's budget, cast, and crew and see an estimated probability of success. The model shows potential to help industry decision-makers gauge a film's chances before it is greenlit, and its accuracy may improve with additional data and refinement.

INTRODUCTION

This research began with a different, more limited data set. Our original goal was to identify which variables were associated with greater box-office success. Using quantitative techniques, we found that films released in more languages and more countries tended to achieve higher success metrics. That finding seemed intuitive, but having data to support it raised a broader question: what other factors contribute to a film's success or failure?

Unsatisfied with the limited scope of our earlier data, we began searching for a more comprehensive source. After some time, we made contact with Dr. Patrick Reynolds of the Oracle of Bacon, who generously granted us permission to use his database for this work. A general rule within the film industry, the 2.5x rule, holds that a film must earn at least 2.5 times its budget to break even once marketing, distribution, and exhibitor costs are accounted for. We adopted the 2.5x rule as our success metric and used it to evaluate the influence of several variables, including director, actor, producer, production company, writer, genre, and budget.

The film industry, since its inception, has largely run on personal relationships and experience. That approach has produced many of the most iconic films of all time; even so, we believe data can help make good decisions even better. More data is available today than ever before to help this industry make more informed decisions. We believe that, on a large scale, historical data can be used to forecast a film's success with more reliability than the current standard of relying primarily on relationships and gut instinct.

The remainder of this paper describes the data source and preparation, the definition of success used throughout the study, and the method used to select and weight known actors, directors, writers, producers, and production companies. It then describes the hierarchical logistic regression model, reports its performance on training and testing data, and introduces a companion web-based tool that applies the fitted model to new, hypothetical films. The paper closes with a discussion of the model's limitations and directions for future work.

DATA AND METHODOLOGY

Building a model that predicts box-office success first required assembling a clean, consistent data set from a very large and heterogeneous source, then defining success and the pool of “known” contributors in a way that would generalize to films the model had not seen.

Data Source and Preparation

The Oracle of Bacon database contained 22,748,885 movie and television records, spanning films, cast and crew credits, production companies, and genres. Because the study focuses on theatrical box-office performance, television records were removed, and the remaining films were filtered to those with a positive budget, a positive revenue figure, and a known release date before a fixed cutoff date. Production companies were included only if they appeared in more than 10 films in the data set, which removed one-off or shell companies that would otherwise add noise without adding predictive signal. The data were loaded into a local SQLite database and processed with Python (pandas, NumPy, and statsmodels), which allowed the full record set to be filtered, joined, and reshaped efficiently before modeling.

Defining Success

Success was defined using the industry-standard 2.5x rule: a film is labeled successful if its revenue is at least 2.5 times its budget. This threshold accounts for the substantial marketing, distribution, and exhibitor costs that are not reflected in a film's production budget alone, and it is the same rule used informally throughout the film industry to describe a profitable release.

Rather than splitting the data randomly, movies were divided chronologically by release date into an 80% training set and a 20% testing set. A chronological split ensures that the model is trained only on films that were actually available at some earlier point in time and is tested only on films released afterward, which mirrors how the model would be used in practice — to forecast the success of an upcoming film using only what is already known.

Genre Consolidation

The source data contained many overlapping and sparsely populated genre labels. To avoid a proliferation of indicator variables for genres with very few films, the original genre labels were condensed into five broader groups, with any remaining genre placed in an Other category:

• Drama — Drama, Romance

• Documentary — Documentary, Music, History, War

• Family — Comedy, Family, Animation

• Suspense — Crime, Mystery, Thriller, Horror

• Adventure — Action, Adventure, Fantasy, Science Fiction, Western

A film could belong to more than one condensed genre if its original genre tags spanned more than one group.

Selecting and Weighting Known Entities

For each role — lead actor, director, producer, writer — and for production companies, every person or company with at least 10 appearances in the training period was assigned a weighted success rate, smoothed toward its role's overall baseline using Bayesian shrinkage (a prior weight equivalent to 5 films) so that a handful of successes or failures could not distort the rate for a person with very little history. For the lead-actor role, only the top-billed actor on each film counted; for director, producer, and writer, every credited member of that role on a film shared the film's indicator equally. Within each role and for production companies, the 100 highest-rated, 100 middle-rated, and 100 lowest-rated entities by weighted success rate were retained as "known" and given their own indicator variable. Anyone who did not meet the 10-appearance minimum, or who fell outside the top, middle, or bottom 100 for their role, was treated as unknown and absorbed into that role's baseline, which in turn is absorbed into the model's overall intercept.

Table 1 shows a sample of the top-ranked lead actors that resulted from this process, ordered by weighted success rate. Each actor's fitted weight (in log-odds) reflects how much that actor shifts a film's estimated success above or below the actor role's baseline, once the number of films they have appeared in has been taken into account.

Table 1. Sample of Top-Ranked Lead Actors by Weighted Success Rate

Actor	Appearances	Weighted Success Rate (%)	Weight (log-odds)	Baseline + Weight	Odds Multiplier
Tom Cruise	33	70.73	0.837	1.042	2.838
Jim Carrey	23	63.85	0.662	0.868	2.381
Paul Newman	20	63.51	0.639	0.845	2.327
Will Smith	17	67.63	0.621	0.827	2.286
Tom Hanks	37	63.99	0.576	0.782	2.186
Sandra Bullock	18	60.34	0.562	0.768	2.155
Steve Carell	14	62.51	0.512	0.717	2.050

As Table 1 illustrates, a higher weighted success rate does not always translate into a proportionally larger fitted weight: an actor's number of appearances also matters, because the shrinkage procedure pulls estimates based on fewer films back toward the baseline more aggressively than estimates based on many films.

HIERARCHICAL LOGISTIC REGRESSION MODEL

Model Specification

The indicator variables described above — lead actor, director, producer, writer, production company, and condensed genre — along with log-transformed budget, were combined into a hierarchical (mixed-effects) Bayesian logistic regression. For a given film, the model's log-odds of success is the sum of an intercept, a term for standardized log-budget, and, for each role, the film's known-baseline term plus the fitted weight of each known person, company, or genre attached to that film:

log-odds = Intercept + Budget term + Σ (role known-baseline + entity weight), summed over each role's known members present in the film

Every known entity's weight is treated as a random effect: it is shrunk toward its role's baseline, with the amount of shrinkage controlled by a spread parameter estimated separately for each role (actor, director, producer, writer, company, and genre). This prevents a person or company with only a few films from receiving an extreme weight based on limited evidence. Unknown people and companies — anyone who did not meet the appearance minimum or was not selected as a top, middle, or bottom performer — sit at their role's baseline by construction, which cannot be distinguished mathematically from the model's overall intercept and is therefore absorbed into it. The model was fit on the training films only, using variational Bayesian inference; the testing films then reuse those fitted weights, with any person or company that appears only in the testing period treated as unknown.

Model Performance

The fitted model achieved a ROC AUC of 0.788 on the training data and 0.639 on the testing data. The gap between the two is expected: the training AUC reflects, in part, how well the model fits the specific actors, directors, producers, writers, and companies it was allowed to learn individual weights for, while the testing AUC reflects how well those same weights generalize to films released after the training period, some of which involve people and companies the model has never seen. A testing AUC of 0.639 indicates that the model has real, if moderate, discriminative power — meaningfully better than chance (0.5) but well short of a highly reliable predictor.

Because the data set is not class-balanced — successful films, by the 2.5x definition, are the minority class — the model's classification cutoff was set to the training set's overall success rate rather than the conventional 0.5, so that the model does not simply label almost every film unsuccessful. Across the fitted weights, actor indicators tended to have larger coefficient magnitudes than director and production-company indicators, suggesting that a film's lead actor carries relatively more weight in the model's prediction than any single director or company. Genre membership, by contrast, contributed comparatively little to the overall prediction once budget, cast, and crew were accounted for.


The Web-Based Prediction Tool

To make the fitted model usable without any statistical background, the project produced a standalone, self-contained web page that reproduces the model's log-odds calculation entirely in the browser, with no server or internet connection required. A user enters a hypothetical film's budget, lead actor, director, producers, writers, and production companies, and selects one or more genres; the page looks up each entry against the model's known entities (falling back to that role's baseline for anyone not on the list), sums the resulting terms on the log-odds scale, and converts the total into a percentage likelihood of success, shown alongside the training-set classification cutoff for reference.

Figure 1 shows the tool applied to a hypothetical $100,000,000 film starring Kevin Bacon (an unknown-tier lead actor for this example) and directed by Christopher Nolan (a top-tier director), produced by Brad Pitt, Aditya Chopra, and Agústin Almodóvar, written by Jon Lucas, produced by 20th Century Fox

Animation, and classified as a Drama. The tool combines each term's contribution — for example, +0.613 log-odds for the director and +1.565 log-odds for the production company in this example — into a total of +1.892 log-odds, which converts to an estimated 86.9% likelihood of success, well above the 37.6% classification cutoff derived from the training data.

Figure 1. The Box Office Success Predictor Web Tool



Every input row in the tool also displays whether the selected person, company, or genre falls in the top, middle, or bottom tier from the training data, or whether it is unrecognized and therefore treated at that role's baseline, so a user can see at a glance how much of the prediction is driven by specific, known contributors versus generic role-level assumptions.

CONCLUSION

This study shows that historical data on a film's budget, genre, and the track record of its cast and crew can be combined into a model that meaningfully distinguishes financially successful films from unsuccessful ones, achieving a testing ROC AUC of 0.639 on films the model had never seen during training. Actor identity emerged as a particularly influential factor, more so than any single director or production company, while genre played a comparatively minor role once other factors were accounted for.

At the same time, the gap between the training AUC of 0.788 and the testing AUC of 0.639 indicates that the model still has room to improve, and that some of its apparent accuracy on training data does not fully carry over to new films. Future work could expand the pool of known entities, incorporate additional variables such as release timing, marketing spend, or franchise and sequel status, test the model against a longer or more recent out-of-sample window, and experiment with alternative shrinkage settings to better balance the tradeoff between fitting known contributors closely and generalizing to new ones. Even in its current form, the model — and the accompanying web-based tool — offers industry decision-makers a data-informed complement to the relationship-driven judgment that has long guided which films get made.

REFERENCES

Reynolds, Patrick. “The Oracle of Bacon.” Available at https://oracleofbacon.org/.

CONTACT INFORMATION

Your comments and questions are valued and encouraged. Contact the author at:

Kaden N. Swords

5807490513

kaden.swords@okstate.edu

www.linkedin.com/in/kaden-swords

Benjamin V. Hennel

4698347559

ben.hennel@okstate.edu

https://www.linkedin.com/in/benjamin-hennel/