Network Basics

Using The traceroute Command

Using traceroute

Where do all those packets really go when we send them over the Internet? And, how do all the packets actually get to their destinations? Well, we can use the **TCP/IP traceroute** (*tracert with Windows*) command-line utility to help us answer both questions because its output will show us every router interface a TCP/IP packet passes through on the way to its destination.

Traceroute (trace for short) displays the path a packet takes to get to a remote device by using something we call **IP packet Time to Live (TTL) time-outs** and **Internet Control Message Protocol (ICMP)** error messages. And it's also a handy tool for troubleshooting an internetwork because we can use it to figure out which router along a path through that internetwork happens to be causing a network failure when a certain destination machine or network is, or suddenly becomes, unreachable.

To use **tracert**, at a Windows command prompt, type `tracert`, a space, and the `Domain Name Service (DNS) name` or `IP address` of the host machine to which you want to find the route. The **tracert utility** will respond with a list of all the DNS names and IP addresses of the routers that the packet is passing through on its way. Plus, tracert uses TTL to indicate the time it takes for each attempt.

Following is the *tracert output* from a local pc to clarusway.com server:

```
Microsoft Windows [Version 10.0.18363.657]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\Users\clarusway>tracert www.clarusway.com

Tracing route to www.clarusway.com [54.164.151.235]
over a maximum of 30 hops:

  1     1 ms     1 ms     1 ms  192.168.1.1
  2     4 ms     4 ms     *     195.87.128.37
  3    10 ms    10 ms     *     10.135.53.154
  4    11 ms    10 ms     *     10.135.53.153
  5    11 ms    11 ms     *     46.234.28.57
  6    11 ms    10 ms     *     ae4-17-ucr1.tuz.cw.net [195.2.23.129]
  7   133 ms   134 ms   132 ms  195.2.25.86
  8   130 ms   130 ms   130 ms  195.2.28.57
  9   132 ms   133 ms   132 ms  ae17.pcr1.fnt.cw.net [195.2.20.226]
 10     *        *      131 ms  ae15-pcr1.ptl.cw.net [195.2.9.126]
 11   131 ms   131 ms   133 ms  et-7-1-0-xcr1.nyh.cw.net [195.2.24.241]
 12   131 ms   131 ms   155 ms  ae13-xcr2.nyk.cw.net [195.2.25.69]
 13   132 ms   132 ms   132 ms  52.95.216.78
 14   141 ms   135 ms   131 ms  52.93.4.85
 15   131 ms   131 ms   132 ms  52.93.4.46
 16     *        *        *     Request timed out.
 17   140 ms   136 ms   137 ms  150.222.242.116
 18     *        *        *     Request timed out.
 19     *        *        *     Request timed out.
 20     *        *        *     Request timed out.
 21     *        *        *     Request timed out.
 22   137 ms   158 ms   140 ms  150.222.241.173
 23     *        *        *     Request timed out.
 24     *        *        *     Request timed out.
 25     *        *        *     Request timed out.
 26     *        *        *     Request timed out.
 27     *        *        *     Request timed out.
 28     *        *        *     Request timed out.
 29     *        *        *     Request timed out.
 30     *        *        *     Request timed out.

Trace complete.
```

You see that the packet bounces through several routers before arriving at its destination. This utility is useful if you are having problems reaching a web server on the Internet and you want to know if a wide area network (WAN) link is down or if the server just isn't responding. What this means to you is that, basically, wherever the trace stops is a great place to start troubleshooting. Notice in the output the *ms*. This is the latency of each hop, meaning the delay. `Tracert` (or `traceroute`) is a great troubleshooting tool you can use to find out where your network bottlenecks are.

If you use `traceroute` or `tracert` and receive an asterisk, this indicates that the attempt to reach that router took longer than the default time-out value. This is very good to know because it can mean that either the router is extremely busy or a particular link is slow. Another reason for getting an asterisk could be that the administrator has disabled ICMP on the router that the packet is trying to hop through because of security reasons. It

happens to be a typical strategic move done on the routers that interface to the ISP to conceal their actual location so bad guys can't hack into them and therefore into your internetwork.

In addition to `traceroute` and `tracert`, you can use `pathping` (for Windows), which is a lot like `traceroute`:

```
C:\Users\clarusway>pathping www.clarusway.com

Tracing route to www.clarusway.com [54.164.151.235]
over a maximum of 30 hops:
  0  freestyler.home [192.168.1.22]
  1  192.168.1.1
  2  195.87.128.37
  3  10.135.53.154
  4  10.135.53.153
  5  46.234.28.57
  6  ae4-17-ucr1.tuz.cw.net [195.2.23.129]
  7  ae2-ucr1.pra.cw.net [195.2.25.86]
  8  ae16-xcr1.fix.cw.net [195.2.28.57]
  9  ae17.pcr1.fnt.cw.net [195.2.20.226]
 10  ae15-pcr1.ptl.cw.net [195.2.9.126]
 11  et-7-1-0-xcr1.nyh.cw.net [195.2.24.241]
 12  ae13-xcr2.nyk.cw.net [195.2.25.69]
 13  52.95.216.78
 14  52.93.4.85
 15  52.93.4.46
 16     *        *        *
Computing statistics for 375 seconds...
            Source to Here   This Node/Link
Hop  RTT    Lost/Sent = Pct  Lost/Sent = Pct  Address
  0                                           freestyler.home
[192.168.1.22]
                                  0/ 100 =  0%   |
  1    1ms     0/ 100 =  0%     0/ 100 =  0%  192.168.1.1
                                  0/ 100 =  0%   |
  2  ---     100/ 100 =100%   100/ 100 =100%  195.87.128.37
                                  0/ 100 =  0%   |
  3   13ms     0/ 100 =  0%     0/ 100 =  0%  10.135.53.154
                                  0/ 100 =  0%   |
  4   12ms     0/ 100 =  0%     0/ 100 =  0%  10.135.53.153
                                  0/ 100 =  0%   |
  5   12ms     0/ 100 =  0%     0/ 100 =  0%  46.234.28.57
                                  0/ 100 =  0%   |
  6   15ms     0/ 100 =  0%     0/ 100 =  0%  ae4-17-ucr1.tuz.cw.net
[195.2.23.129]
                                  0/ 100 =  0%   |
  7   47ms     0/ 100 =  0%     0/ 100 =  0%  ae2-ucr1.pra.cw.net
[195.2.25.86]
                                  0/ 100 =  0%   |
  8   56ms     0/ 100 =  0%     0/ 100 =  0%  ae16-xcr1.fix.cw.net
[195.2.28.57]
                                  0/ 100 =  0%   |
  9   59ms     0/ 100 =  0%     0/ 100 =  0%  ae17.pcr1.fnt.cw.net
[195.2.20.226]
                                  0/ 100 =  0%   |
 10   64ms     0/ 100 =  0%     0/ 100 =  0%  ae15-pcr1.ptl.cw.net
[195.2.9.126]
                                  0/ 100 =  0%   |
 11  134ms     0/ 100 =  0%     0/ 100 =  0%  et-7-1-0-xcr1.nyh.cw.net
[195.2.24.241]
                                  0/ 100 =  0%   |
 12  133ms     0/ 100 =  0%     0/ 100 =  0%  ae13-xcr2.nyk.cw.net
[195.2.25.69]
                               100/ 100 =100%   |
```

```
 13  ---     100/ 100 =100%     0/ 100 =  0%  52.95.216.78

                                0/ 100 =  0%   |
 14  ---     100/ 100 =100%     0/ 100 =  0%  52.93.4.85
                                0/ 100 =  0%   |
 15  ---     100/ 100 =100%     0/ 100 =  0%  52.93.4.46

Trace complete.
```

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The traceroute Command

Using the ipconfig Utility

With the new Mac, Windows 10, and Windows Server 2016 operating systems, you can now see the IPv6 configuration because IPv6 is enabled by default. The output of the `ipconfig` command provides the basic routed protocol information on your machine. From a DOS prompt, type `ipconfig`, and you'll see something like this:

```
C:\Users\clarusway>ipconfig

Windows IP Configuration

Ethernet adapter Ethernet:
   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 3:
   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:
   Connection-specific DNS Suffix  . : home
   Link-local IPv6 Address . . . . . : fe80::19ac:8efb:2c6e:f512%10
   IPv4 Address. . . . . . . . . . . : 192.168.1.22
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . : 192.168.1.1

Tunnel adapter Teredo Tunneling Pseudo-Interface:
   Connection-specific DNS Suffix  . :
   IPv6 Address. . . . . . . . . . . :
2001:0:2851:782c:148e:f3fd:6aff:55b8
   Link-local IPv6 Address . . . . . : fe80::148e:f3fd:6aff:55b8%17
   Default Gateway . . . . . . . . . : ::
```

You can see that Ethernet adapter shows up first, and it has an IP address, a mask, and a default gateway plus an IPv6 address and a DNS suffix. The next configured interface is the wireless local area network (LAN) adapter, which has an IP address, a mask, a default gateway, an IPv6 address, and the IPv6 default gateway as well.

The next adapters are disconnected because they are logical interfaces and are not being used. But just in case the `ipconfig` command doesn't provide enough information for you, try the `ipconfig /all` command. Here's the beginning of that output:

```
C:\Users\clarusway>ipconfig /all

Windows IP Configuration

   Host Name . . . . . . . . . . . . : clarusway
   Primary Dns Suffix  . . . . . . . :
   Node Type . . . . . . . . . . . . : Hybrid
   IP Routing Enabled. . . . . . . . : No
   WINS Proxy Enabled. . . . . . . . : No
   DNS Suffix Search List. . . . . . : home

Ethernet adapter Ethernet:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Intel(R) I211 Gigabit Network
Connection
   Physical Address. . . . . . . . . : 9C-5C-8E-CE-D9-C9
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes

Ethernet adapter Ethernet 3:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Intel(R) Ethernet Connection (2)
I219-V
   Physical Address. . . . . . . . . : 9C-5C-8E-CE-D9-CA
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes

Wireless LAN adapter Local Area Connection* 3:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Microsoft Wi-Fi Direct Virtual
Adapter
   Physical Address. . . . . . . . . : 76-C6-3B-00-62-86
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes

Wireless LAN adapter Local Area Connection* 13:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Microsoft Wi-Fi Direct Virtual
Adapter #2
   Physical Address. . . . . . . . . : 76-C6-3B-00-6A-86
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes

Wireless LAN adapter Wi-Fi:

   Connection-specific DNS Suffix  . : home
   Description . . . . . . . . . . . : Broadcom 802.11ac Network
Adapter
   Physical Address. . . . . . . . . : 74-C6-3B-00-62-86
   DHCP Enabled. . . . . . . . . . . : Yes
```

```
   Autoconfiguration Enabled . . . . : Yes

   Link-local IPv6 Address . . . . . :
fe80::19ac:8efb:2c6e:f512%10(Preferred)
   IPv4 Address. . . . . . . . . . . : 192.168.1.22(Preferred)
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Lease Obtained. . . . . . . . . . : March 3, 2020 01:01:19 PM
   Lease Expires . . . . . . . . . . : March 4, 2020 02:54:14 PM
   Default Gateway . . . . . . . . . : 192.168.1.1
   DHCP Server . . . . . . . . . . . : 192.168.1.1
   DHCPv6 IAID . . . . . . . . . . . : 242533947
   DHCPv6 Client DUID. . . . . . . . : 00-01-00-01-21-FA-0A-0E-9C-5C-
8E-CE-D9-C9
   DNS Servers . . . . . . . . . . . : 192.168.1.1
                                       192.168.1.1
   NetBIOS over Tcpip. . . . . . . . : Enabled

Tunnel adapter Teredo Tunneling Pseudo-Interface:

   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Microsoft Teredo Tunneling
Adapter
   Physical Address. . . . . . . . . : 00-00-00-00-00-00-00-E0
   DHCP Enabled. . . . . . . . . . . : No
   Autoconfiguration Enabled . . . . : Yes
   IPv6 Address. . . . . . . . . . . :
2001:0:2851:782c:148e:f3fd:6aff:55b8(Preferred)
   Link-local IPv6 Address . . . . . :
fe80::148e:f3fd:6aff:55b8%17(Preferred)
   Default Gateway . . . . . . . . . : ::
   DHCPv6 IAID . . . . . . . . . . . : 167772160
   DHCPv6 Client DUID. . . . . . . . : 00-01-00-01-21-FA-0A-0E-9C-5C-
8E-CE-D9-C9
   NetBIOS over Tcpip. . . . . . . . : Disabled
```

As you can see, it's more of the same—a whole lot more. The most important thing that you can see the hardware information about each interface, including the Media Access Control (MAC) address. Also significant is that you can see the Dynamic Host Configuration Protocol (DHCP) lease times and DNS addresses now.

There are two more valuable options you need to use with the `ipconfig` command. They are `/release` and `/renew`.

When you change networks, you need to get the IP address of that subnet and/or virtual LAN (VLAN). Windows 10 works most of the time without doing anything, but sometimes you have to renew the IP configuration when changing networks. For that, just type `ipconfig /renew` from a command prompt, and if you're connected to a DHCP server that's available. Now, if it still doesn't work, you'll need to release and renew your TCP/IP settings. To release your current DHCP TCP/IP information, you must elevate your command prompt or you'll get this warning:

```
C:\Users\clarusway>ipconfig /release
The requested operation requires elevation.
```

In order to avoid this, choose Start > All Programs > Accessories > Command Prompt, right-click, and choose Run As Administrator.

Once your command prompt has been duly elevated, you can use the `ipconfig /release` command and then the `ipconfig /renew` command to get new TCP/IP information for your host.

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The traceroute Command

Using the ifconfig Utility

There is a utility in Linux/Unix/Mac that will give you information similar to what `ipconfig` shows. It's called `ifconfig` (short for interface configuration). Although `ipconfig` and `ifconfig` show similar information, there are major differences between these two utilities.

The `ipconfig` utility is mainly used to view the TCP/IP configuration for a computer. You can use `ifconfig` to do the same thing, but `ifconfig` can also be used to configure a protocol or a particular network interface.

The general syntax of the `ifconfig` command is as follows:

```
ifconfig interface [address [parameters]]
```

The interface parameter equals the Unix name of the interface, such as eth0. If the optional address parameter is specified, the `ifconfig` command sets the IP address for the interface to the address you've specified. When the `ifconfig` command is used by itself with no parameters, all configured interfaces will be reported on. But if only the interface name is specified, you'll get output that looks like this:

```
# ifconfig eth0
eth0 Link encap 10Mbps Ethernet HWaddr 00:00:C0:90:B3:42
inetaddr 172.16.0.2 Bcast 172.16.0.255 Mask 255.255.255.0 UP
BROADCAST RUNNING MTU 1500 Metric 0
    RX packets 3136 errors 217 dropped 7 overrun 26
    TX packets 1752 errors 25 dropped 0 overrun 0
```

Looking at this, we can see that the eth0 interface is a 10 Mbps Ethernet interface. The interface's MAC and IP address information is displayed in this output as well. And, although not shown in the output, the `ifconfig` tool can show you the DNS information configured on the host.

Previous Next

Network Basics

Using The traceroute Command

Using the iptables Utility

The **iptables firewall utility** is built for the Linux operating system. It is a command-line utility that uses what are called chains to allow or disallow traffic. When traffic arrives, `iptables` looks for a rule that addresses that traffic type, and if none exists, it will enforce the default rule. There are three different chain types:

1. **Input:** Controls behavior for incoming connections
2. **Forward:** Used for incoming connections that aren't being delivered locally
3. **Output:** Used for outgoing connections

You can set the default action to accept, drop, or reject, with the difference between reject and drop being that reject sends an error message back to the source.

Examples of `iptables`

- To block a connection from the device at `192.168.10.1`, use this command:

```
iptables -A INPUT -s 192.168.10.1 -j DROP
```

- To block all connections from all devices in the `172.16.0.0/16` network, use this command:

```
iptables -A INPUT -s 172.16.0.0/16 -j DROP
```

- Here is the command to block SSH connections from `10.110.61.5`:

```
iptables -A INPUT -p tcp --dport ssh -s 10.110.61.5 -j DROP
```

- Use this command to block SSH connections from any IP address:

```
iptables -A INPUT -p tcp --dport ssh -j DROP
```

- The following command is used to save the changes in Ubuntu:

```
sudo /sbin/iptables-save
```

- In Red Hat/CentOS, use either of the following commands:

```
/sbin/service iptables save
/etc/init.d/iptables save
```

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The ping Utility

Using the ping Utility

The **ping utility** is the most basic TCP/IP utility, and it's included with most TCP/IP stacks for most platforms. In most cases, `ping` is a command-line utility, although there are many GUI implementations available. You use the ping utility for two primary purposes:

- To find out if a host is responding
- To find out if you can reach a host

Here's the syntax (you can use either command):

```
ping hostname
ping IP address
```

If you ping any station that has an IP address, the ICMP that's part of that particular host's TCP/IP stack will respond to the request. The ICMP test and response looks something like this:

```
C:\Users\clarusway>ping 3.225.75.90

Pinging 3.225.75.90 with 32 bytes of data:
Reply from 3.225.75.90: bytes=32 time=137ms TTL=233
Reply from 3.225.75.90: bytes=32 time=136ms TTL=233
Reply from 3.225.75.90: bytes=32 time=134ms TTL=233
Reply from 3.225.75.90: bytes=32 time=134ms TTL=233

Ping statistics for 3.225.75.90:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 134ms, Maximum = 137ms, Average = 135ms
```

Because we've received a reply from the destination station we know that we can reach the host and that it's responding to basic IP requests. Don't forget that you can use name resolution and ping to a name, such as `ping www.clarusway.com`. Most versions of `ping` work the same way, but there are some switches you can use to specify certain information, like the number of packets to send, how big a packet to send, and so on. And if you're running the Windows command-line version of `ping`, just use the `/?` or `-?` switch to display a list of the available options like this:

```
C:\Users\clarusway>ping /?

Usage: ping [-t] [-a] [-n count] [-l size] [-f] [-i TTL] [-v TOS]
            [-r count] [-s count] [[-j host-list] | [-k host-list]]
            [-w timeout] [-R] [-S srcaddr] [-c compartment] [-p]
            [-4] [-6] target_name

Options:
    -t             Ping the specified host until stopped.
                   To see statistics and continue - type Control-Break;
                   To stop - type Control-C.
    -a             Resolve addresses to hostnames.
    -n count       Number of echo requests to send.
    -l size        Send buffer size.
    -f             Set Don't Fragment flag in packet (IPv4-only).
    -i TTL         Time To Live.
    -v TOS         Type Of Service (IPv4-only. This setting has been
deprecated
                   and has no effect on the type of service field in
the IP
                   Header).
    -r count       Record route for count hops (IPv4-only).
    -s count       Timestamp for count hops (IPv4-only).
    -j host-list   Loose source route along host-list (IPv4-only).
    -k host-list   Strict source route along host-list (IPv4-only).
    -w timeout     Timeout in milliseconds to wait for each reply.
    -R             Use routing header to test reverse route also (IPv6-
only).
                   Per RFC 5095 the use of this routing header has been
                   deprecated. Some systems may drop echo requests if
                   this header is used.
    -S srcaddr     Source address to use.
    -c compartment Routing compartment identifier.
    -p             Ping a Hyper-V Network Virtualization provider
address.
    -4             Force using IPv4.
    -6             Force using IPv6.
```

As you can see, there are many options you can use with the `ping` command from a Windows DOS prompt.

The `-a` switch is handy if you have name resolution (such as a DNS server), you can see the name of the destination host even if you only know its IP address. The `-n` switch sets the number of echo requests to send, where four is the default, and the `-w` switch allows you to adjust the time-out in milliseconds. The default ping time-out is 1 second (1,000 ms).

The `-6` is also nice if you want to ping an IPv6 host. And then there's `-t`, which keeps the ping running.

From a MAC, you can use the `ping6` command. Here are the options:

```
$ ping6
usage: ping6 [-DdfHmnNoqrRtvwW] [-a addrtype] [-b bufsiz] [-B boundif]
[-c count][-g gateway] [-h hoplimit] [-I interface] [-i wait] [-l
preload][-p
pattern] [-S sourceaddr] [-s packetsize] [-z tclass]
```

```
[hops ...] host
```

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The Address Resolution Protocol

Using the Address Resolution Protocol

The **Address Resolution Protocol (ARP)** is part of the TCP/IP protocol stack. It's used to translate TCP/IP addresses to MAC addresses using broadcasts. When a machine running TCP/IP wants to know which machine on an Ethernet network is using a certain IP address, it will send an ARP broadcast that says, in effect, "Who is IP address xxx.xxx.xxx.xxx?" The machine that owns the specific address will respond with its own MAC address, supplying the answer. The machine that made the inquiry will respond by adding the newly gained information to its own ARP table.

The ARP table in Windows includes a list of TCP/IP addresses and their associated physical (MAC) addresses. This table is cached in memory so that Windows doesn't have to perform ARP lookups for frequently accessed TCP/IP addresses like those of servers and default gateways. Each entry contains an IP address and a MAC address plus a value for TTL that determines how long each entry will remain in the ARP table.

Remember that the ARP table contains two kinds of entries:

- Dynamic
- Static

Dynamic ARP table entries are created whenever the Windows TCP/IP stack performs an ARP lookup but the MAC address isn't found in the ARP table. When the MAC address of the requested IP address is finally found or resolved, that information is then added into the ARP table as a dynamic entry. Whenever a request to send a packet to the host is sent to the Data Link layer, the ARP cache is checked first before an ARP broadcast is sent out.

Previous Next

Network Basics

Using The Address Resolution Protocol

Using the arp Utility

ARP is used by IP to determine the MAC address of a device that exists on the same subnet as the requesting device. When a TCP/IP device needs to forward a packet to a device on the local subnet, it first looks in its own table, called an ARP cache or MAC address lookup table, for an association between the known IP address of the destination device on the local subnet and that same device's MAC address. The cache is called that because the contents are periodically weeded out.

If no association that includes the destination IP address can be found, the device will then send out an ARP broadcast that includes its own MAC and IP information as well as the IP address of the target device and a blank MAC address field. Filling in that blank is the object of the whole operation—it's the unknown value that the source device is requesting to be returned to it in the form of an ARP reply. Windows includes a utility called `arp` that allows us to check out the operating system's ARP cache. To view this, from a Windows DOS prompt, use the `arp` command like this:

```
C:\Users\clarusway>arp

Displays and modifies the IP-to-Physical address translation tables
used by
address resolution protocol (ARP).

ARP -s inet_addr eth_addr [if_addr]
ARP -d inet_addr [if_addr]
ARP -a [inet_addr] [-N if_addr] [-v]

  -a            Displays current ARP entries by interrogating the
current
                protocol data.  If inet_addr is specified, the IP and
Physical
                addresses for only the specified computer are
displayed.  If
                more than one network interface uses ARP, entries for
each ARP
                table are displayed.
  -g            Same as -a.
  -v            Displays current ARP entries in verbose mode.  All
invalid
                entries and entries on the loop-back interface will be
shown.
  inet_addr     Specifies an internet address.
  -N if_addr    Displays the ARP entries for the network interface
specified
                by if_addr.
  -d            Deletes the host specified by inet_addr. inet_addr may
be
                wildcarded with * to delete all hosts.
  -s            Adds the host and associates the Internet address
inet_addr
                with the Physical address eth_addr.  The Physical
address is
                given as 6 hexadecimal bytes separated by hyphens. The
entry
                is permanent.
  eth_addr      Specifies a physical address.
  if_addr       If present, this specifies the Internet address of the
                interface whose address translation table should be
modified.
                If not present, the first applicable interface will be
used.
Example:
  > arp -s 157.55.85.212   00-aa-00-62-c6-09  .... Adds a static entry.
  > arp -a
```

The Windows `arp` utility is primarily useful for resolving duplicate IP addresses. For example, let's say your workstation receives its IP address from a DHCP server but it accidentally receives the same address that some other workstation gets. And so, when you try to ping it, you get no response. Your workstation is basically confused—it's trying to determine the MAC address, and it can't because two machines are reporting that they have the same IP address. To solve this little snag, you can use the `arp` utility to view your local ARP table and see which TCP/IP address is resolved to which MAC address.

resolved to which MAC address.

To display the entire current ARP table, use the `arp` command with the `-a` switch like so to show you the mac address lookup table:

```
C:\Users\clarusway>arp -a

Interface: 192.168.1.22 --- 0xa
  Internet Address      Physical Address      Type
  192.168.1.1           24-00-ba-b8-c7-ec     dynamic
  192.168.1.255         ff-ff-ff-ff-ff-ff     static
  224.0.0.22            01-00-5e-00-00-16     static
  224.0.0.251           01-00-5e-00-00-fb     static
  224.0.0.252           01-00-5e-00-00-fc     static
  224.0.0.253           01-00-5e-00-00-fd     static
  239.255.255.250       01-00-5e-7f-ff-fa     static
  255.255.255.255       ff-ff-ff-ff-ff-ff     static
```

Now, from this output, you can tell which MAC address is assigned to which IP address. Then, for static assignments, you can tell which workstation has a specific IP address and if it's indeed supposed to have that address by examining your network documentation.

For DHCP-assigned addresses, you can begin to uncover problems stemming from multiple DHCP scopes or servers doling out identical addresses and other common configuration issues. And remember that under normal circumstances, you shouldn't see IP addresses in the ARP table that isn't a member of the same IP subnet as the interface.

Previous

Next

You have completed 0% of the lesson
0%

Jump to...

Network Basics

Using The nslookup Utility

Using the nslookup Utility

Whenever you're configuring a server or a workstation to connect to the Internet, you've got to start by configuring DNS if you want name resolution to happen. When configuring DNS, it's a very good thing to be able to test what IP address DNS is returning to ensure that it's working properly. The nslookup utility allows you to query a name server and quickly find out which name resolves to which IP address.

> **Tip:**
> - The Unix **dig** (short for domain information groper) utility does the exact same thing as **nslookup**. It's primarily a command-line utility that allows you to perform a single DNS lookup for a specific entity, but it can also be employed in batch mode for a series of lookups.

You can run `nslookup` from a Windows command prompt. When you're inside this utility, the command prompt will change from something similar to a `C:\>` sign to a shorter `>` sign. It will also display the name and IP address of the default DNS server you will be querying. Then you can start using `nslookup`. The following output gives you a sample of the display after the `nslookup` command has been entered at the `C:\>` prompt.

```
C:\Users\clarusway> nslookup
Default Server: gnt-corpdc1.globalnet.local
Address: 10.100.36.12
>
```

The primary job of `nslookup` is to tell you the many different features of a particular domain name, the names of the servers that serve it, and how they're configured. To get that, just type in a domain name at the `>` prompt, and the `nslookup` utility will then return this information:

```
> clarusway.com
Server:  UnKnown
Address:  192.168.1.1

Non-authoritative answer:
Name:    clarusway.com
Addresses:  3.225.75.90
          54.164.151.235
```

What this tells you is that the server that returned the information is not responsible (authoritative) for the zone information of the domain for which you requested an address and that the name server for the domain

clarusway.com is located at the IP address `3.225.75.90`.

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The mtr Command (pathping)

Using the mtr Utility

`Mtr` or **My traceroute** is a computer program that combines the functions of the traceroute and ping utilities in a single network diagnostic tool. It also adds round-trip time and packet loss to the output. `Mtr` probes routers on the route path by limiting the number of hops individual packets are allowed to traverse and listening to news of their termination. It will regularly repeat this process (usually once per second) and keep track of the response times of the hops along the path.

`Mtr` is available for Linux or Unix. Third-party applications of Mtr are available to install on Windows, but Microsoft did respond with its own version of Mtr —it's called `pathping` and it provides the same functions as `Mtr`. Here's a look at the output and the options:

```
C:\Users\clarusway>pathping

Usage: pathping [-g host-list] [-h maximum_hops] [-i address] [-n]
                [-p period] [-q num_queries] [-w timeout]
                [-4] [-6] target_name

Options:
    -g host-list     Loose source route along host-list.
    -h maximum_hops  Maximum number of hops to search for target.
    -i address       Use the specified source address.
    -n               Do not resolve addresses to hostnames.
    -p period        Wait period milliseconds between pings.
    -q num_queries   Number of queries per hop.
    -w timeout       Wait timeout milliseconds for each reply.
    -4               Force using IPv4.
    -6               Force using IPv6.
```

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The mtr Command (pathping)

Using the Nmap Utility

Nmap is one of the most popular port scanning tools used today. After performing scans with certain flags set in the scan packets, security analysts (and hackers) can make certain assumptions based on the responses received. These flags are used to control the TCP connection process and so are present only in TCP packets. The below figure shows a TCP header with the important flags circled. Normally flags are “turned on” because of the normal TCP process, but hackers can craft packets to check the flags they want to check.



TCP flags

- URG: Urgent pointer field significant
- ACK: Acknowledgment field significant
- PSH: Push function
- RST: Reset the connection
- SYN: Synchronize sequence numbers
- FIN: No more data from sender

Security analysts and hackers alike can perform scans with these flags set in the scan packets to get responses that allow them to determine the following information:

- If a port is open on a device
- If the port is blocked by a firewall before its gets to the device

Nmap can also be used as follows:

- To determine the live hosts on a network
- To create a logical “map” of the network

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The route Command

Using The route Command

The biggest reason for manipulating the routing table on a server is to create a firewall. For instance, let's say we're running an Application layer firewall on a server located between the demilitarized zone (DMZ) and the internal network.

This scenario would mean the routing that's happening on the server or hosts located in the DMZ wouldn't be able to reach the internal network's hosts and vice versa. To circumvent this problem, we would need to employ both static and default routing because running routing protocols on hosts and servers wouldn't be a good solution for today's networks.

To view the routing table on a Windows device, use the `route print` command, as shown below.

```
C:\Users\clarusway>route print
===========================================================================

Interface List
 14...9c 5c 8e ce d9 c9 ......Intel(R) I211 Gigabit Network Connection
 18...9c 5c 8e ce d9 ca ......Intel(R) Ethernet Connection (2) I219-V
 15...76 c6 3b 00 62 86 ......Microsoft Wi-Fi Direct Virtual Adapter
  8...76 c6 3b 00 6a 86 ......Microsoft Wi-Fi Direct Virtual Adapter #2
 10...74 c6 3b 00 62 86 ......Broadcom 802.11ac Network Adapter
  1...........................Software Loopback Interface 1
 17...00 00 00 00 00 00 00 e0 Microsoft Teredo Tunneling Adapter
===========================================================================

IPv4 Route Table
===========================================================================

Active Routes:
Network Destination        Netmask          Gateway       Interface
Metric
          0.0.0.0          0.0.0.0      192.168.1.1     192.168.1.22
35
        127.0.0.0        255.0.0.0         On-link         127.0.0.1
331
        127.0.0.1  255.255.255.255         On-link         127.0.0.1
331
  127.255.255.255  255.255.255.255         On-link         127.0.0.1
331
      192.168.1.0    255.255.255.0         On-link      192.168.1.22
291
     192.168.1.22  255.255.255.255         On-link      192.168.1.22
291
    192.168.1.255  255.255.255.255         On-link      192.168.1.22
291
        224.0.0.0        240.0.0.0         On-link         127.0.0.1
331
        224.0.0.0        240.0.0.0         On-link      192.168.1.22
291
  255.255.255.255  255.255.255.255         On-link         127.0.0.1
331
  255.255.255.255  255.255.255.255         On-link      192.168.1.22
291
===========================================================================

Persistent Routes:
  None

IPv6 Route Table
===========================================================================

Active Routes:
 If Metric Network Destination      Gateway
 17    331 ::/0                     On-link
  1    331 ::1/128                  On-link
 17    331 2001::/32                On-link
 17    331 2001:0:2851:782c:148e:f3fd:6aff:55b8/128
                                    On-link
 10    291 fe80::/64                On-link
 17    331 fe80::/64                On-link
```

```
 17    331 fe80::148e:f3fd:6aff:55b8/128
                                   On-link
 10    291 fe80::19ac:8efb:2c6e:f512/128
                                   On-link
  1    331 ff00::/8                 On-link
 10    291 ff00::/8                 On-link
 17    331 ff00::/8                 On-link
===========================================================================

Persistent Routes:
  None
```

In this output, you can see that each of the routes was added automatically when the system booted up. To see all the options available with the route command, type `route`.

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The route Command

route Command Options

To add a route to your routing table, use the following syntax:

```
route [-f] [-p] [Command] [Destination] [mask Netmask] [Gateway]
[metric Metric] [if Interface]
```

- `-f`: Using this command with any of the options like add, change, or delete will clear the routing table of all entries that aren't host routes, the loopback network route or routes, and any multicast routes
- `-p`: If you use this with the add command, the individual route will be added to the Registry and then used to initialize the IP routing table whenever TCP/IP is started. Important to remember is that by default, the routes you've statically added won't remain in the routing table the next time TCP/IP boots. And if you use `-p` with the `print` command, you'll get shown a list of the persistent routes that are stored in the Registry location of `HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Persistent Routes`.

Now, let's take a look at how and when you would use the route command. The below table shows the command options available and what they do when you are using the route command with them.

Command	Purpose
add	Adds a route
change	Modifies an existing route
delete	Deletes a route (or routes)
print	Prints a route (or routes)

Here's a description of some other tasks you can accomplish via the rest of the command's options:

- `Destination`: This will give you the network destination of a given route. If the host bits of the network address are set to 0, it will be depicted with the destination's IP network address, an IP address for a specific host route, or the default route of `0.0.0.0`.
- `mask netmask`: This will provide you with the subnet mask that's associated with the destination network. The default destination subnet mask is `0.0.0.0`, and typically you'll see `255.255.255.255` representing a host route

`0.0.0.0`, and typically you'll see `255.255.255.255` representing a host route.

- `Gateway`: The gateway depends on the network address and subnet mask. It defines the next-hop IP address. For routes located on a local subnet, the gateway address maps directly to a particular interface. If the destination is on a remote network, the gateway IP address will direct packets to the router.
- `metric`: Metric refers to the cost of a given route from the sender to the receiver device, and it has a value between 1 and 9999. Devices use this value to choose the best, or most efficient, routes among those in its routing table—the route with the lowest value wins. This decision can also include factors like the number of hops and the speed, reliability, and available bandwidth of the path being considered.
- `if interface`: This tool depends on information from the gateway address and determines the interface index for the specific interface that needs to receive the data. You can get a list of interfaces along with their relevant interface indexes by typing the route print command.
- `/?`: Using this will allow you to view help at the command prompt.

Previous

Next

Network Basics

Using The route Command

Some Examples of The route Command

It is recommended that you spend some time practicing them on a nonproduction server.

- To display the entire IP routing table, type:

```
route print
```

- To add a default route with the default gateway address `192.168.10.1`, type:

```
route add 0.0.0.0 mask 0.0.0.0 192.168.10.1
```

- To add a route to the destination `10.1.1.0` with the subnet mask `255.255.255.0` and the next-hop address `10.2.2.2`, type:

```
route add 10.1.1.0 mask 255.255.255.0 10.2.2.2
```

- If you want to add a persistent route to the destination `10.100.0.0` with the subnet mask `255.255.0.0` and the next-hop address `10.2.0.1`, type:

```
route -p add 10.100.0.0 mask 255.255.0.0 10.2.0.1
```

- If you want to delete the route to the destination `10.100.0.0` with the subnet mask `255.255.0.0`, enter:

```
route delete 10.100.0.0 mask 255.255.0.0
```

- If you want to change the next-hop address of a route with the destination `10.100.0.0` and the subnet mask `255.255.0.0` from `10.2.0.1` to `10.7.0.5`, type:

```
route change 10.100.0.0 mask 255.255.0.0 10.7.0.5
```

Previous Next

Network Basics

Using The netstat Utility

The netstat Utility

Using `netstat` is a great way to check out the inbound and outbound TCP/IP connections on your machine. You can also use it to view packet statistics like how many packets have been sent and received, the number of errors, and so on. When used without any options, `netstat` produces output similar to the following, which shows all the outbound TCP/IP connections. This utility is a great tool to use to determine the status of outbound web connections. Take a look:

```
C:\Users\clarusway>netstat

Active Connections
  Proto  Local Address          Foreign Address        State
  TCP    192.168.1.22:49812     ec2-35-157-203-133:https  ESTABLISHED
  TCP    192.168.1.22:49824     ed-in-f188:5228        ESTABLISHED
  TCP    192.168.1.22:50322     server-99-86-243-78:https  ESTABLISHED
  TCP    192.168.1.22:50918     54.239.31.91:https     ESTABLISHED
  TCP    192.168.1.22:51180     aeab55d76dd13c9bb:https  ESTABLISHED
  TCP    192.168.1.22:51211     ec2-18-205-93-210:https  ESTABLISHED
  TCP    192.168.1.22:51212     ec2-52-202-62-236:https  CLOSE_WAIT
  TCP    192.168.1.22:51213     ec2-18-205-93-141:https  CLOSE_WAIT
  TCP    192.168.1.22:51214     ec2-18-205-93-141:https  CLOSE_WAIT
  TCP    192.168.1.22:51215     ec2-18-205-93-141:https  CLOSE_WAIT
  TCP    192.168.1.22:51216     ec2-18-205-93-141:https  CLOSE_WAIT
  TCP    192.168.1.22:51281     aeab55d76dd13c9bb:https  ESTABLISHED
  TCP    192.168.1.22:51318     52.46.68.59:https      ESTABLISHED
  TCP    192.168.1.22:51346     ec2-3-225-75-90:https  ESTABLISHED
  TCP    192.168.1.22:51377     52.114.128.43:https    ESTABLISHED
  TCP    192.168.1.22:51391     aeab55d76dd13c9bb:https  ESTABLISHED
  TCP    192.168.1.22:61298     ec2-52-202-62-228:https  ESTABLISHED
  TCP    192.168.1.22:61317     ec2-3-120-198-117:https  ESTABLISHED
  TCP    192.168.1.22:61320     ec2-3-120-198-117:https  ESTABLISHED
  TCP    192.168.1.22:61330     ec2-3-120-198-117:https  ESTABLISHED
  TCP    192.168.1.22:62010     51.105.249.228:https   ESTABLISHED
```

The **Proto column** lists the protocol being used. The **Local Address** column lists the source address and the source port (source socket). The **Foreign Address** column lists the address of the destination machine (the hostname if it's been resolved). If the destination port is known, it will show up as a well-known port. The **State column** indicates the status of each connection. This column shows statistics only for TCP connections because the *User Datagram Protocol (UDP)* establishes no virtual circuit to the remote device. Usually, this column indicates **ESTABLISHED** when a TCP connection between your computer and the destination computer has been established.

> 💡**Tip:**
>
> - If the address of either your computer or the destination computer can be found in the HOSTS file on your computer, the destination computer's name, rather than the IP address, will show up in either the Local Address or Foreign Address column.

The output of the `netstat` utility depends on the switch. By using the `netstat /?` command, we can see the options available to us.

```
C:\Users\clarusway>netstat /?

Displays protocol statistics and current TCP/IP network connections.
NETSTAT [-a] [-b] [-e] [-f] [-n] [-o] [-p proto] [-r] [-s] [-x] [-t]
[interval]

  -a            Displays all connections and listening ports.
  -b            Displays the executable involved in creating each
connection or
                listening port. In some cases well-known executables
host
                multiple independent components, and in these cases the
                sequence of components involved in creating the
connection
                or listening port is displayed. In this case the
executable
                name is in [] at the bottom, on top is the component it
called,
                and so forth until TCP/IP was reached. Note that this
option
                can be time-consuming and will fail unless you have
sufficient
                permissions.
  -e            Displays Ethernet statistics. This may be combined with
the -s
                option.
  -f            Displays Fully Qualified Domain Names (FQDN) for
foreign
                addresses.
  -n            Displays addresses and port numbers in numerical form.
  -o            Displays the owning process ID associated with each
connection.
  -p proto      Shows connections for the protocol specified by proto;
proto
                may be any of: TCP, UDP, TCPv6, or UDPv6.  If used with
the -s
                option to display per-protocol statistics, proto may be
any of:
                IP, IPv6, ICMP, ICMPv6, TCP, TCPv6, UDP, or UDPv6.
  -q            Displays all connections, listening ports, and bound
                nonlistening TCP ports. Bound nonlistening ports may or
may not
                be associated with an active connection.
  -r            Displays the routing table.
  -s            Displays per-protocol statistics.  By default,
statistics are
                shown for IP, IPv6, ICMP, ICMPv6, TCP, TCPv6, UDP, and
UDPv6;
                the -p option may be used to specify a subset of the
default.
  -t            Displays the current connection offload state.
  -x            Displays NetworkDirect connections, listeners, and
shared
                endpoints.
  -y            Displays the TCP connection template for all
connections.
                Cannot be combined with the other options.
  interval      Redisplays selected statistics, pausing interval
```

```
seconds

                between each display.  Press CTRL+C to stop
redisplaying
                statistics.  If omitted, netstat will print the current
                configuration information once.
```

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The tcpdump Utility

Using tcpdump

The `tcpdump` utility is used to read either packets captured live from a network or packets that have been saved to a file. Although there is a Windows version called `windump`, `tcpdump` only works on Unix-like operating systems.

- Use this command to capture traffic on all interfaces:

```
# tcpdump -i any
```

- Here is the command to capture traffic on a particular interface:

```
# tcpdump -i eth0
```

- And to filter traffic by IP, whether it's the source or the destination, use this command:

```
# tcpdump host 192.168.5.5
```

Previous Next

Jump to...

Network Basics

Using The scp and curl Utility

scp Command

`scp` (Secure Copy) is a command-line tool that is used to transfer files and directories across the systems securely over the network. When we use `scp` command to copy files and directories from our local system to a remote system then in the backend it makes **ssh connection** to a remote system.

Syntax:

```
scp <options> <files_or_directories> user@target_host:/<folder>
scp <options> user@target_host:/files   <folder_local_system>
```

Some of the most widely used options in `scp` command are listed below:

command	Explanation
-C	Enable Compression
-i	identity File or private key
-l	limit the bandwidth while copying
-P	ssh port number of the target host
-r	Copy files and directories recursively
-p	Preserves modification times, access times, and modes from the original file
-q	Disables the progress meter

Examples:

- Copies the file "test.txt" from a remote host to the localhost:

```
scp your_username@hostname:text.txt /some/local/directory
```

- Copies the file "test.txt" from the local host to a remote host:

```
scp  text.txt your_username@hostname:/some/local/directory
```

- Copies multiple files from the remote host to your current directory on the localhost:

```
scp  text.txt your_username@hostname: /some/local/directory/\{a,b,c\}
```

> Q: How to copy a file from a remote server to a local machine?
> A: If you are on the local computer wanting to receive file from a remote computer:
> **scp** username@remote:/file/to/send /where/to/put
>
> — - Interview Q&A

Previous

Next

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Using The scp and curl Utility

curl Command

`curl` is a command-line tool to transfer data to or from a server, using any of the supported protocols.

Syntax:

```
curl [options] [URL...]
user@clarusway:~$ curl https://www.clarusway.com
```

- `-o`: Saves the downloaded file on the local machine with the name provided in the parameters.

```
curl -o [file_name] [URL...]
```

Example:

```
user@clarusway:~$ curl -o hello.zip ftp://speedtest.tele2.net/1MB.zip
```

Previous

End of Lesson

You have completed 0% of the lesson
0%

Jump to...

Network Basics

Network Configuration Files

Network Configuration Files

The graphical help tools use a few basic commands to edit a specific set of network configuration files. The exact names and location of the configuration files in the file system depend largely on your distribution and version of Linux.

File	Description
/etc/resolv.conf	List DNS servers for internet domain name resolution. Manual page for: /etc/resolv.conf
/etc/hosts	Lists hosts to be resolved locally (not by DNS). Manual page for: /etc/hosts
/etc/nsswitch.conf	List order of host name search. Typically look at local files, then NIS server, then DNS server. Manual page for: /etc/nsswitch.conf
Red Hat/Fedora/CentOS: /etc/sysconfig/network	Specify network configuration. eg. Static IP, DHCP, NIS, etc.
Red Hat/Fedora/CentOS: /etc/sysconfig/network-scripts/ifcfg-device	Specify TCP network information.
Ubuntu/Debian: /etc/network/interfaces	Specify network configuration and devices. eg. Static IP and info, DHCP, etc.

The `/etc/sysconfig/network` file

- The `/etc/sysconfig/network` file is a global (across all network cards) configuration file. It allows us to define whether we want networking (`NETWORKING=yes|no`), what the hostname should be (`HOSTNAME=`) and which gateway to use (`GATEWAY=`).
- Note that this file contains no settings at all in a default RHEL7 install (with networking enabled).

The `/etc/hosts` file

The main purpose of `/etc/hosts` configuration file is to resolve hostnames that cannot be resolved any other way. It can also be used to resolve hostnames on small networks with no DNS server.

The `/etc/resolv.conf` file

This file is used for configuring the DNS (Domain Name System) resolver library. The `resolv.conf` configuration file contains information parameters used by the DNS resolver. The DNS resolver allows for the operating system to translate domain names into IP addresses.

Example:



Typical default contents:

Directive	Description
auto	Indicates the device should be setup at boot time
lo	Loopback interface
iface	Interface
eth0	Ethernet device 0, typically the primary network adaptor

Directive	Description
inet	Indicates network adaptor has an IPv4 address space

dhcp	Network adaptor gets its configuration from a DHCP server
static	Indicates the adaptor uses fixed IP configuration
address	The IP address of the host
netmask	Network subnet mask
gateway	Gateway Address
network	The network portion of the IP address
nameserver	The IP of a DNS

Tips:

- The loopback (lo) interface will have an IP address of 127.0.0.1, which represents the host itself. Suppose you want to open a web page running on the same Linux server you are on. You could open http://127.0.0.1 in your web browser. That IP address won't be accessible over the network.
- The ethernet 0 (eth0) interface is typically the connection to the local network. Even if you are running Linux in a virtual machine (VM), you'll still have an eth0 interface that connects to the physical network interface of the host. Most commonly, you should ensure that eth0 is in an IP state and has an IP address so that you can communicate with the local network and likely over the Internet.

Previous

End of Lesson

You have completed 0% of the lesson

0%

Jump to...

Network Basics

Troubleshooting IP Addressing (Optional)

Troubleshooting IP Addressing

Troubleshooting IP addressing is obviously an important skill because running into trouble somewhere along the way is pretty much a sure thing, and it's going to happen to you.

Let's use the below figure as an example of basic IP trouble— David can't log in to the Windows server.



Basic IP troubleshooting

Let's get started by going over the basic troubleshooting steps.

1. Open a command prompt window on David's host, and ping `127.0.0.1`.

```
C:\>ping 127.0.0.1
Pinging 127.0.0.1 with 32 bytes of data:
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Ping statistics for 127.0.0.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

This is the diagnostic, or loopback address, and if you get a successful ping, your IP stack is considered to be initialized. If it fails, then you have an IP stack failure and need to reinstall TCP/IP on the host.

Tips:

- If you ping the loopback address and receive an **"unable to contact IP driver, error code 2"** message, you need to reinstall the TCP/IP protocol suite on the host.

2. Now, from the same command prompt window, ping the IP address of the localhost.

```
C:\>ping 172.16.10.2
Pinging 172.16.10.2 with 32 bytes of data:
Reply from 172.16.10.2: bytes=32 time<1ms TTL=128
Reply from 172.16.10.2: bytes=32 time<1ms TTL=128
Reply from 172.16.10.2: bytes=32 time<1ms TTL=128
Reply from 172.16.10.2: bytes=32 time<1ms TTL=128
Ping statistics for 172.16.10.2:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

If that's successful, your network interface card (NIC) is functioning. If it fails, there is a problem with the NIC.

3. From the command prompt window, ping the default gateway (router).

```
C:\>ping 172.16.10.1
Pinging 172.16.10.1 with 32 bytes of data:
Reply from 172.16.10.1: bytes=32 time<1ms TTL=128
Reply from 172.16.10.1: bytes=32 time<1ms TTL=128
Reply from 172.16.10.1: bytes=32 time<1ms TTL=128
Reply from 172.16.10.1: bytes=32 time<1ms TTL=128
Ping statistics for 172.16.10.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

If the ping works, it means that the NIC is plugged into the network and can communicate on the local network. If it fails, you have a local physical network problem that could be anywhere from the NIC to the router.

4. If steps 1 through 3 were successful, try to ping the remote server.

```
C:\>ping 172.16.20.2
Pinging 172.16.20.2 with 32 bytes of data:
Reply from 172.16.20.2: bytes=32 time<1ms TTL=128
Reply from 172.16.20.2: bytes=32 time<1ms TTL=128
Reply from 172.16.20.2: bytes=32 time<1ms TTL=128
Reply from 172.16.20.2: bytes=32 time<1ms TTL=128
Ping statistics for 172.16.20.2:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

If that works, then you know that you have IP communication between the local host and the remote server. You also know that the remote physical network is working.

If the user still can't communicate with the server after steps 1 through 4 are successful, you probably have some type of name resolution problem and need to check your **Domain Name System (DNS)** settings. But if the ping to the remote server fails, then you know you have some type of remote physical network problem and need to go to the server and work through steps 1 through 3 until you find the snag.

Previous

Next

Jump to...

Network Basics

Troubleshooting IP Addressing (Optional)

Determining IP Address Problems-1

It's common for a host, router, or other network devices to be configured with the wrong IP address, subnet mask, or default gateway. Because this happens way too often, in this example you will learn how to both determine and fix IP address configuration errors.

After you've worked through the four basic steps of troubleshooting and determined there's a problem, you obviously then need to find and fix it. Once you have your network accurately drawn out, including the IP addressing scheme, you need to verify each host's IP address, mask, and default gateway address to determine the problem. Let's check out the below example illustration. A user calls and tells you that he can't get to Server A. You ask him if he can get to Server B in the marketing department, but he doesn't know because he doesn't have the rights to log on to that server.



IP address problem

You ask the client to go through the four troubleshooting steps that you learned about in the preceding section. Steps 1 through 3 work, but step 4 fails. First, the WAN link between the R1 and the R2 shows the mask as a `/27`. You should already know that this mask is `255.255.255.224` and then determine that all networks are using this mask. The network address is

192.168.1.0. What are our valid subnets and hosts?

256 – 224 = 32,

so this makes our subnets 0, 32, 64, 96, 128, and so on. So, by looking at the figure, you can see that subnet 32 is being used by the clients, the WAN link is using subnet 96, and the servers are using subnet 64. Now you have to determine what the valid host ranges are for each subnet. The valid hosts for the Sales LAN are 33 through 62—the broadcast address is 63 because the next subnet is 64. For the servers, the valid hosts are 65 through 94 (broadcast 95), and for the WAN link, 97 through 126 (broadcast 127). By looking at the figure, you can determine that the default gateway on the Lab_B router is incorrect. That address is the broadcast address of the 64 subnet, so there's no way it could be a valid host.

Previous

Next

Network Basics

Troubleshooting IP Addressing (Optional)

Determining IP Address Problems-2

The below figure shows a network problem. A user can't get to Server B. You have the user run through the four basic troubleshooting steps and find that the host can communicate to the local network but not to the remote network. Find and define the IP addressing problem.



IP address problem

If you use the same steps used to solve the last problem, you can see first that the WAN link again provides the subnet mask to use— `/29`, or `255.255.255.248`. You need to determine what the valid subnets, broadcast addresses, and valid host ranges are to solve this problem.

The 248 mask is a block size of 8 (256 – 248 = 8), so the subnets both start and increment in multiples of 8. By looking at the figure, you see that the user is in the 24 subnet, the WAN is in the 40 subnet, and the servers are in the 80 subnet. Can you see the problem yet? The valid host range for the user's LAN is 25–30, and the configuration appears correct. The valid host range for the WAN link is 41–46, and this also appears correct. The valid host range for the 80 subnet is 81–86, with a broadcast address of 87 because the next subnet is 88. Server B has been configured with the broadcast address of the subnet. Now that you can figure out misconfigured IP addresses on hosts, what do you do if a host doesn't have

misconfigured IP addresses on hosts, what do you do if a host doesn't have

an IP address and you need to assign one? What you need to do is look at other hosts on the LAN and figure out the network, mask, and default gateway.

Let's take a look at a couple of examples of how to find and apply valid IP addresses to hosts. You need to assign a server and router IP addresses on a LAN. The subnet assigned on that segment is `192.168.20.24/29`, and the router needs to be assigned the first usable address and the server the last valid host ID. What are the IP address, mask, and default gateway assigned to the server?

To answer this, you must know that a `/29` is a `255.255.255.248` mask, which provides a block size of 8. The subnet is known as 24, the next subnet in a block of 8 is 32, so the broadcast address of the 24 subnet is 31, which makes the valid host range 25–30:

```
Server IP address: 192.168.20.30
Server mask: 255.255.255.248
Default gateway: 192.168.20.25 (router's IP address)
```

Previous

Next

Network Basics

Troubleshooting IP Addressing (Optional)

Determining IP Address Problems-3



Invalid Host

Look at the router's IP address on Ethernet0. What IP address, subnet mask, and valid host range could be assigned to the host?

The IP address of the router's Ethernet0 is `192.168.10.33/27`. As you already know, a `/27` is a `224` mask with a block size of 32. The router's interface is in the 32 subnet. The next subnet is 64, so that makes the broadcast address of the 32 subnet 63 and the valid host range 33–62:

```
Host IP address: 192.168.10.34-62 (any address in the range except for
33, which is assigned to the router)
Mask: 255.255.255.224
Default gateway: 192.168.10.33
```

The below figure shows two routers with Ethernet configurations already assigned. What are the host addresses and subnet masks of hosts A and B?



Invalid Host

Router 1 has an IP address of `192.168.10.65/26` and Router 2 has an IP address of `192.168.10.33/28`. What are the host configurations?

Router 1 Ethernet0 is in the `192.168.10.64` subnet, and Router 2 Ethernet0 is in the `192.168.10.32` network:

```
HostA IP address: 192.168.10.66-126
HostA mask: 255.255.255.192
HostA default gateway: 192.168.10.65
HostB IP address: 192.168.10.34-46
HostB mask: 255.255.255.240
HostB default gateway: 192.168.10.33
```

Previous

End of lesson

You have completed 0% of the lesson

0%

Jump to...