Difference-Aware Contrastive Transformer for Physical Commonsense Question Answering

Group 73

Abstract

Can a neural model trained from scratch answer physical commonsense questions more accurately when the differences between the candidate answers are modelled explicitly? We study this question with the Difference-Aware Contrastive Transformer (DACT). DACT marks the tokens on which two near-identical candidate solutions differ, compares the candidates with cross-solution attention, pools each candidate around its differing tokens and adds a jointly trained lexical score. We use DACT as a testbed for what such components contribute. On PIQA we compare it with five baselines, nine ablations and one control. DACT reaches 61.3% validation accuracy, above the BiLSTM and TF-IDF baselines (59.3 and 59.2%), although several ablated variants score as high or higher (up to 61.9%); on the evaluation split it is not significantly different from a TF-IDF baseline (61.9 vs. 61.2%, McNemar p=0.62). The ablations are the main result: adding only a lexical head to a vanilla Transformer recovers about two thirds of the validation gap to the full model (2.48 of 3.74 points, from a separate run and assuming no interaction between components), and the neural difference-aware components together account for the remaining 1.26. Most of the model's attention falls on the differing tokens, and wrong predictions attend to them slightly more than correct ones, so locating a difference is not enough to judge its physical plausibility.

1 Introduction

1.1 Background and Motivation

Physical commonsense, knowing how everyday objects behave and what they can be used for, is needed by assistants and robots. PIQA [2] tests this knowledge in a question answering format: each item pairs an everyday goal with two candidate solutions, exactly one of which achieves it. What makes the task hard is that the two candidates are usually near-duplicates. In our training split, the median share of solution tokens that differ between them is 15%, so the answer hinges on a few substituted words whose plausibility can only be judged with world knowledge. We therefore represent the differences between the candidates explicitly instead of scoring each one on its own.

1.2 Objectives and Main Findings

We ask whether a model trained from scratch, with no external data, can make use of the explicit differences between two candidate solutions. We (i) design an architecture that represents these differences at the input, comparison and pooling stages; (ii) compare it with baselines from a majority classifier to pretrained models; (iii) measure each component's contribution through ablations; and (iv) check whether attention concentrates on the differing tokens and how that relates to the errors. We find that DACT is above the two baselines trained from scratch on validation (several ablated variants score as high or higher) but not significantly better than a lexical baseline on the evaluation split; that, in this ordering, the lexical component accounts for about two thirds of the gain over a plain Transformer (2.48 of 3.74 points on validation) and the neural parts add 1.26 only in combination; and that its errors seem to come from missing world knowledge rather than from misplaced attention, an explanation we did not test directly.

1.3 Related Work

Bisk et al. [2] report 77.1% accuracy for RoBERTa-large and 94.9% for humans. In multiple-choice reading comprehension, the Option Comparison Network [17] and DCMN+ [22] compare the candidate answers with each other rather than scoring them independently. In natural language inference, ESIM [3] and the decomposable attention model [14] align two texts token by token and build comparison features from that alignment. Annotation

artefacts let shallow lexical cues solve many items [9, 15], so we include a lexical baseline and a lexical component.

2 Methodology

DACT is a Transformer-based model trained from scratch on the PIQA training data alone (Figure 1). The Transformer encoder, additive attention, byte-pair encoding and the ESIM comparison features come from prior work. Our contribution is to adapt and combine them for PIQA: difference-tag embeddings, a cross-solution comparison of the two competing solutions, difference-guided pooling, and a lexical scoring component trained jointly with the neural model.

2.1 Task Formulation

Each item has a goal g and two candidate solutions s_1 and s_2. The model computes a score z_k for each candidate $k \in \{1, 2\}$ and predicts $\hat{y} = \arg\max_k z_k$.

2.2 Input Representation and Difference Tags

Each candidate is encoded as $x^{(k)} = [\text{CLS}]\, g\, [\text{SEP}]\, s_k\, [\text{SEP}]$, using a byte-pair-encoding (BPE) vocabulary [18] learned on the training split. We align the token sequences of s_1 and s_2 with Python's `difflib` and tag every solution token as *shared* or *different*; goal and special tokens get the tag *other*. The input embedding at position i is

$$e_i = E_{tok}[x_i] + E_{pos}[i] + E_{seg}[\sigma_i] + E_{tag}[t_i], \quad (1)$$

followed by layer normalisation and dropout. Here E_{tok}, E_{pos}, E_{seg} and E_{tag} are learned token, position, segment and tag embeddings, t_i is the tag at position i, and σ_i indicates whether the position belongs to the goal or to the solution. The tag embedding tells the encoder from the first layer onwards where the candidates disagree. The tags assume that the candidates share most of their wording: for paraphrased candidates nearly every token is tagged as different, synonyms count as differences, and the alignment depends on the order of the options.

2.3 Shared Transformer Encoder

A pre-LayerNorm Transformer encoder [19, 21] maps each candidate sequence to hidden states $H^{(k)} \in \mathbb{R}^{L \times d}$. Since both candidates go through the same encoder, any difference between their representations comes from the inputs, not from separate parameters.

2.4 Cross-Solution Attention

Plausibility in PIQA is relative: a solution is right because it is better than its rival. Each token of candidate k therefore attends to the solution tokens of the other candidate $\bar{k}$ and to its CLS token, which serves as a target when a token has no counterpart:

$$c_i = \text{MHA}\big(\bar{h}_i^{(k)}, \bar{H}^{(\bar{k})}, \bar{H}^{(\bar{k})}\big), \quad \bar{h} = \text{LN}(h), \quad (2)$$

where MHA is multi-head attention with the keys restricted to these positions. The hidden states are then updated with ESIM's comparison features [3]: $\tilde{h}_i = \text{LN}\big(h_i + \text{FFN}([\bar{h}_i; c_i; \bar{h}_i - c_i; \bar{h}_i \odot c_i])\big)$. ESIM uses these features for premise–hypothesis pairs; we use them for two competing answers, so that each candidate is represented by what it contains in contrast to its rival.

2.5 Difference-Guided Attention Pooling

Additive attention [1], extended with a learned bias for each tag, summarises the solution tokens:

$$\alpha_i \propto \exp\big(v^\top \tanh(W\tilde{h}_i) + b_{t_i}\big), \quad p = \textstyle\sum_i \alpha_i \tilde{h}_i, \quad (3)$$

where v and W are learned, $b_{\textit{different}}$ starts at 1 and the other biases at 0. At the start of training, the bias steers the summary towards the substituted tokens; Section 4.3 checks whether the trained model still relies on it. A scoring MLP maps $[p; \tilde{h}_{\text{CLS}}]$ to a neural score s_k.

2.6 Lexical Scoring Component

Following the wide-and-deep idea [4], a sparse linear component scores the words of each solution directly. Every BPE unigram and bigram of s_k is hashed into one of 2^{18} buckets, each with a learned weight w_j initialised to 0:

$$\ell_k = \textstyle\sum_{j \in \text{ngrams}(s_k)} w_{h(j)}, \qquad z_k = s_k + \ell_k, \quad (4)$$

where h is the hash function. The prediction depends only on $z_1 - z_2$, so n-grams that appear in both candidates cancel out, and the component learns, much like a TF-IDF classifier, which substituted words signal a plausible solution. It is trained jointly with the Transformer but has its own learning rate.

2.7 Prediction and Training Objective

The two scores compete in a softmax, $P(k) = \text{softmax}(z_1, z_2)_k$, trained with cross-entropy and label smoothing of 0.1. This pairwise objective fits




Figure 1: Architecture of DACT. The two candidates share all weights, so swapping two already-encoded candidates swaps their scores. The `difflib` alignment that produces the tags does depend on the order of the options (Section 4.5).

PIQA's forced-choice format, in which exactly one candidate is correct. Before training on this objective, the selected configuration runs a 10-epoch masked-language-model (MLM) warm-up [5] on the text of the training split.

3 Experimental Setup

3.1 Dataset and Data Split

PIQA provides 16,113 labelled training items and 1,838 labelled development items; the labels of the official test set are not public. The unit's test files are byte-identical to the development items (same SHA-256), and we use them as our evaluation split. We held out a stratified 10% of the training file (seed 42) for validation, which gives 14,501 / 1,612 / 1,838 items for training, validation and evaluation, all label-balanced (50.0 / 50.0 / 50.5% label 1). An audit found six duplicate training rows and one evaluation item (index 1545) that also occurs in the training split. We kept the split and report the overlap: re-scoring the saved evaluation predictions without that item changes accuracy by about 0.02 points (DACT 61.86 → 61.84%, TF-IDF 61.21 → 61.19%).

3.2 Data Preprocessing

Whitespace is collapsed, and the BPE tokeniser applies NFKC normalisation and lower-casing. Goals are truncated to 40 BPE tokens and solutions to 96. For longer solutions (1.6% of the evaluation solutions), the 96-token window is centred on the differing span rather than keeping the prefix.

3.3 Training Configuration

The final model has d=128, two layers, four attention heads and a feed-forward width of 512, for 1.93 M parameters in total, 262 k of them in the lexical component. We train it with AdamW [12] (β_2=0.98, weight decay 0.05, learning rate 3×10^{-4} and 10^{-2} for the lexical component), a 6% linear warm-up followed by cosine decay, batches of 128 items, gradient clipping at norm 1.0 and dropout of 0.2, for at most 20 epochs, with early stopping on validation accuracy (patience 6). The MLM warm-up runs for 10 epochs at a learning rate of 5×10^{-4} with 15% of the tokens masked. All models trained from scratch use seeds 42–44 and fp16 mixed precision on a free Colab T4 GPU. We selected the configuration on validation, with one seed each, from five candidates: base (d=256, 4 layers) 61.8%, small (d=128, 2 layers, 4 heads) 61.4%, base with dropout 0.3 60.8%, and base/small with the MLM warm-up 60.8 / **61.8%**. The selected model, small with the warm-up, is 0.06 points ahead of base. The three best candidates lie within 0.43 points, less than one seed std of the final model (0.5), so the selection only rules out clearly worse settings (Section 4.5).

3.4 Baseline Models

All baseline results come from our own experiments. **B0** predicts the majority class and sets the chance level. **B1** is a logistic regression on TF-IDF features of the unigrams and bigrams of $s_2 - s_1$, with C tuned on validation, probing lexical cues [9]. **B2** is a two-layer BiLSTM with additive attention and the same tokeniser (5.1 M parameters) trained from scratch. The other two

baselines are pretrained reference points. **B3** fine-tunes `roberta-base` [11] (125 M parameters) with a multiple-choice head (4 epochs, learning rate 2×10^{-5}, 3 seeds, best epoch on validation); under a rule fixed in advance, a seed below 52% validation accuracy after the first epoch is restarted. **B4** applies `Qwen2.5-1.5B` [16] zero-shot: each solution follows the prompt "Goal: g / Solution:", and the solution with the higher length-normalised log-likelihood is selected.

3.5 Evaluation Metrics

Accuracy is PIQA's official metric. With balanced labels and exactly one correct candidate per item, accuracy is unbiased and its chance level is 50%. For the models trained with seeds 42–44 we report mean ± standard deviation. For the seed with the best validation accuracy we also compute, on the evaluation split, a 95% bootstrap confidence interval (2,000 resamples [8]) and an exact McNemar test [13] against DACT.

3.6 Experimental Protocol

Only validation accuracy was used for design and selection decisions. Even so, the evaluation split was not held out: it was scored in several development runs, and the lexical component was introduced after seeing earlier evaluation results (its configuration was chosen on validation alone), so information about it reached design decisions (leakage through adaptive reuse; its labels were never used for training). Its scores can compare models but are not an untouched estimate of generalisation; any bias favours the tuned models, so it cannot explain the missing advantage over TF-IDF. In the final run, the notebook reads the evaluation labels only in its last step and logs every read. The submitted notebook contains this complete run (commit `b880108`, no errors) and a cell that checks the tables against the result files. We verified, deterministically on CPU for DACT and the BiLSTM, that later code changes (diagnostics, data loading, storage paths) do not alter the trained weights or predictions; the pretrained baselines and the GPU run were not re-checked this way.

4 Results and Analysis

4.1 Overall Performance

DACT is more accurate than the two other baselines trained from scratch, the BiLSTM and TF-IDF, on both splits (Table 1; pairs of numbers are validation / evaluation), but it is not the best variant: several ablated variants match or exceed it within the seed spread (validation up to 61.9%, evaluation up to 62.0%; Table 2). It beats the BiLSTM by +2.0 / +3.1 points (McNemar p=0.09 on the evaluation split) and TF-IDF by +2.0 / +0.7 points. An earlier, independent A100 run showed the same 2-point validation lead over TF-IDF, but on the evaluation split no statistically significant difference was detected (p=0.62; p=0.88 in the A100 run). The pretrained baselines are much stronger: on the evaluation split the zero-shot language model (about 800 times more parameters) is 13.2 points above DACT, and RoBERTa (65 times more parameters) is about 8 points above on validation when its fine-tuning succeeds (69.0 vs. 61.3%). Model size, tokenisation, architecture and pretraining all differ between these models, so the gap cannot be attributed to world knowledge alone. RoBERTa's fine-tuning was unstable: only one of three seeds trained (65.3% validation; 53.8% and 58.4% for the others), so Table 1 reports both the three-seed mean and the seed that trained (Section 4.5), a known problem [6].

Model	Val.	Eval.
trained from scratch		
B0 majority	50.0	50.5
B1 TF-IDF + LR	59.2	61.2
B2 BiLSTM + attention	59.3 ± 0.7	58.7 ± 1.1
DACT (main model)	$\mathbf{61.3 \pm 0.5}$	$\mathbf{61.9 \pm 0.3}$
pretrained baselines		
B3 RoBERTa-base, three seeds[†]	59.2 ± 5.8	57.3 ± 6.9
seed 1042 only (trained)[†]	65.3	CI 62.4–66.6
validation re-run[‡]	69.0 ± 0.6	–
B4 Qwen2.5-1.5B, zero-shot	78.2	75.1

Table 1: Accuracy (%) on the validation (Val.) and evaluation (Eval.) splits, as mean ± standard deviation over three seeds; B0, B1 and B4 are deterministic single runs. 95% CI of DACT on the evaluation split: 59.6–64.0. [†]Seed 1042 (the pre-declared restart of the abandoned seed 42) trained: 65.3% validation, evaluation 95% CI 62.4–66.6. Seeds 43 and 44 stayed at chance-level loss (53.8% and 58.4%) and are reported, not dropped (mean of all three: 59.2 ± 5.8); the first row is the like-for-like comparison, the second shows what RoBERTa reaches when it trains. [‡]Same settings, validation only: all three seeds trained successfully (69.6 / 68.5 / 68.8). An earlier A100 run gave 68.0 / 66.7.

4.2 Ablation Study

Each ablation tests one hypothesis, with data, seeds and training budget held fixed (Table 2). Removing the difference-aware components together (the

Ablation (vs. full DACT)	Δ Val.	Δ Eval.	Δ Par.
− lexical head	−2.3	−0.3	−262k
pointwise BCE objective	−1.7	−1.4	0
− difference tags	−0.2	−1.3	−0.4k
mean pooling	−0.2	+0.2	0
− MLM warm-up	+0.1	−0.3	0
− tag bias in pooling	+0.1	−0.6	0
tag bias initialised at 0	+0.2	−0.7	0
− cross-solution attention	+0.6	−0.6	−149k
vanilla (4 components removed)	−3.7	−4.3	−411k
vanilla + lexical head†	−1.3	–	−149k

Table 2: Change in accuracy (percentage points) relative to the full model (1.93 M parameters), with three seeds per variant and one change at a time to the selected configuration. Differences of the unrounded three-seed means, rounded to 0.1 (seed std 0.1–1.1). Δ Par.: change in trainable parameters. Vanilla removes the tags, cross-solution attention, attention pooling and the lexical component. † The vanilla model with the lexical head added back: validation only, a separate three-seed run (60.0%, seed std 0.3), not a one-change ablation; the evaluation split was not scored.

vanilla model) reduced accuracy by 3.7 / 4.3 points, the largest drop and the only one with $p<0.05$ (McNemar; validation 0.009, evaluation 0.007), although neither survives a Holm correction over the nine ablations (0.08 / 0.06). Its consistency is more convincing: every vanilla seed is below every full-model seed on both splits, and the A100 run showed 2.5 / 2.4. The combined design therefore contributes information beyond a plain Transformer, but much of it comes from the lexical component: adding only the lexical head back to the vanilla model gives 60.0% on validation (a separate three-seed run), against 57.5% for the vanilla model (57.4% in a re-run in the same session). This recovers 2.48 of the 3.74 points and leaves 1.26 ($2.48 + 1.26 = 3.74$; Table 2 rounds to 0.1) to the neural difference-aware components together, which this experiment cannot attribute to any one of them. The split assumes that the two parts do not interact and compares runs from different sessions with different parameter counts, so it describes this ordering, not the cause of the gain. The forced-choice objective helps on both splits (independent binary scoring: 1.7 / 1.4). The difference tags help on the evaluation split only (0.2 / 1.3). The other components have no consistent effect: cross-solution attention (removing it gives +0.6 / −0.6), attention pooling (+0.2 on the evaluation split with mean pooling), the tag bias and its initial value, and the MLM warm-up (+0.1 / −0.3) all shift accuracy by less than a point, in opposite directions on the two splits, probably because they carry overlapping information about where the candidates differ. Differences smaller than one seed std are not conclusive, and with nine comparisons no single p-value should be over-interpreted [7].

DACT and TF-IDF agree on only 78.2% of the evaluation items: DACT alone solves 11.2% (206 items) and TF-IDF alone 10.6%, giving an oracle accuracy of 72.4%. The items only DACT solves include minimal pairs with a one-word difference inside long shared text (*release* vs. *do not release* the ignition key; the typo *sparrow bottle* vs. *spray bottle*). For such pairs the TF-IDF difference vector $s_2 - s_1$ is close to zero, while the alignment-based tags are at their most informative. Against RoBERTa, the oracle accuracy rises to 82.4%.

4.3 Attention Analysis

The trained model puts 78.0% of its pooling attention on differing tokens, which make up 24.8% of the solution tokens on average (per-item mean on the evaluation split; the median is 15%, as in the introduction). Two controls separate learned focus from the built-in prior (the tag bias starts at 1). An untrained model reaches only 38.9%, whereas the trained model with the bias set to 0 still reaches 62.0%, and the bias itself barely moved during training ($1.0 \rightarrow 1.03$). The focus is therefore not just the initial bias, which fits its small effect. It is not separated from the tag-informed token representations that feed the pooling, though: the tags stay decodable at every layer. On validation, the normalised pooling entropy is 0.59 (1 = uniform), for correct and wrong predictions alike (p=0.98). A linear probe for differing versus shared tokens reaches 62.0% balanced accuracy on the vanilla Transformer's embeddings and rises only to 63.0% after its encoder, against 100% in every layer of DACT: without tags, the encoder hardly learns where the candidates differ. Wrong predictions place slightly more attention on the differing tokens than correct ones (79.0 vs. 77.4%, Mann–Whitney p=0.03), so attending to them is not sufficient for a correct prediction. Attention weights show where the model puts weight when it aggregates, but they do not by themselves explain why it makes a prediction [10, 20].

4.4 Qualitative Analysis

Figure 2 shows two evaluation items the model predicted confidently, one correctly and one not. In




Figure 2: Pooling attention of the best-validation-seed model over the candidate solutions of two evaluation items (darker shading = higher weight; **bold** = tokens that differ between the candidates; p = predicted probability). Top: *becoming more mindful*, a correct prediction (p = 0.99 for option 1, the gold answer). Bottom: *adding scents to lotion bars*, an incorrect prediction (p = 0.96 for option 1; option 2 is gold).

the correct prediction (top), the pooling weight falls on *present*, *meditate* and *moment* in the gold option and on *relax*, *closed* and *focus* in the rival. For *adding scents to lotion bars* (bottom), the wrong option adds the oils "to the water in the bottom of the double boiler". The pooling peaks on *bottom*, exactly the part that makes the option wrong, and yet the model prefers this option with p = 0.96: attending to the decisive span did not lead to a correct judgement. The most confident error (*an exotic trip*, p = 0.98) involves options that share almost no words, so the lexical sum over n-grams gives extreme scores.

4.5 Stability and Limitations

We also pre-registered a goal-matching block (165 k parameters) and committed its acceptance rule (validation gain ≥ 1.0 point and > 2 pooled seed standard deviations) before training; it lost 0.3 points on validation and was rejected without an evaluation run. Results were sensitive to seeds and sessions: between the A100 run and the final run, single ablations and the from-scratch baselines moved by up to 1.6 points, and RoBERTa's fine-tuning succeeded in one, two or all three seeds. We therefore base our conclusions only on effects larger than this spread. The grid used a single seed per candidate, so the selected configuration may owe its place to that seed's variance (selection within noise) and its validation score may be optimistic.

The evaluation split was exposed during development (Section 3.6), so an untouched estimate of generalisation would need a fresh held-out split. One evaluation item overlaps with the training data, and the difference tags depend on the order of the options (102 evaluation items change tags when the options are swapped). Tokeniser training and the GPU kernels are not deterministic, so re-runs agree only up to seed-level variation. Finally, the model overfits quickly, reaching 85–92% training accuracy against about 61% validation accuracy at the selected epoch, so early stopping does most of the regularisation.

5 Conclusion

We built DACT, a difference-aware Transformer for PIQA trained from scratch. It scored above the BiLSTM and TF-IDF baselines on validation (several ablated variants scored as high or higher), but showed no significant difference from TF-IDF on the evaluation split, and pretrained models remain clearly stronger; we make no claim of competitive performance. Its value is diagnostic: of the 3.74 validation points above a vanilla Transformer, 2.48 (about two thirds) come from the lexical component alone and 1.26 from the neural difference-aware components together, in this ordering and assuming no interaction between them. The model's attention concentrates on the differing words, yet this does not stop it from making confident errors. Our results suggest that, for a model trained from scratch on PIQA, the bottleneck is not finding the relevant difference but judging it, which takes knowledge a training set of 14,501 items does not contain (we did not test this directly). Future work should evaluate on a fresh held-out split and transfer the difference-aware mechanisms to pretrained representations.

Team Contributions

The work was divided among the three members; each member implemented and tested their own part of the code and wrote the report sections that describe it.

Byron: original DACT pipeline (data processing, model, training and evaluation code, baselines B0–B4), the original A100 run, the final A100 runs of both versions and their comparison, and integration of the final notebook and report.

Ali: model revision (difference-aware truncation, lexical component and its validation pilot), attention controls and diagnostics, three-seed RoBERTa baseline, the free-T4 runs, and the first draft of the report; later, the vanilla + lexical head ablation and the revision of the report's claims (RoBERTa reporting, evaluation-split and grid caveats, rounding), with the checker and evidence updates.

Salah: evidence audit of the original run (training/evaluation overlap, order-dependent alignment, evaluation exposure), robustness and provenance code (validation, determinism, prediction export), and the local replication of the original model.

References

[1] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. 2015. Neural machine translation by jointly learning to align and translate. In *Proceedings of ICLR*.

[2] Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. 2020. PIQA: Reasoning about physical commonsense in natural language. In *Proceedings of AAAI*, volume 34, pages 7432–7439.

[3] Qian Chen, Xiaodan Zhu, Zhen-Hua Ling, Si Wei, Hui Jiang, and Diana Inkpen. 2017. Enhanced LSTM for natural language inference. In *Proceedings of ACL*, pages 1657–1668.

[4] Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, Rohan Anil, Zakaria Haque, Lichan Hong, Vihan Jain, Xiaobing Liu, and Hemal Shah. 2016. Wide & deep learning for recommender systems. In *Proceedings of the Workshop on Deep Learning for Recommender Systems*, pages 7–10.

[5] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT*, pages 4171–4186.

[6] Jesse Dodge, Gabriel Ilharco, Roy Schwartz, Ali Farhadi, Hannaneh Hajishirzi, and Noah A. Smith. 2020. Fine-tuning pretrained language models: Weight initializations, data orders, and early stopping. *arXiv preprint arXiv:2002.06305*.

[7] Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of ACL*, pages 1383–1392.

[8] Bradley Efron and Robert J. Tibshirani. 1993. *An Introduction to the Bootstrap*. Chapman and Hall/CRC.

[9] Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A. Smith. 2018. Annotation artifacts in natural language inference data. In *Proceedings of NAACL-HLT*, pages 107–112.

[10] Sarthak Jain and Byron C. Wallace. 2019. Attention is not explanation. In *Proceedings of NAACL-HLT*, pages 3543–3556.

[11] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*.

[12] Ilya Loshchilov and Frank Hutter. 2019. Decoupled weight decay regularization. In *Proceedings of ICLR*.

[13] Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157.

[14] Ankur Parikh, Oscar Täckström, Dipanjan Das, and Jakob Uszkoreit. 2016. A decomposable attention model for natural language inference. In *Proceedings of EMNLP*, pages 2249–2255.

[15] Adam Poliak, Jason Naradowsky, Aparajita Haldar, Rachel Rudinger, and Benjamin Van Durme. 2018. Hypothesis only baselines in natural language inference. In *Proceedings of *SEM*, pages 180–191.

[16] Qwen Team. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

[17] Qiu Ran, Peng Li, Weiwei Hu, and Jie Zhou. 2019. Option comparison network for multiple-choice reading comprehension. *arXiv preprint arXiv:1903.03033*.

[18] Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural machine translation of rare words with subword units. In *Proceedings of ACL*, pages 1715–1725.

[19] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30.

[20] Sarah Wiegreffe and Yuval Pinter. 2019. Attention is not not explanation. In *Proceedings of EMNLP-IJCNLP*, pages 11–20.

[21] Ruibin Xiong, Yunchang Yang, Di He, Kai Zheng, Shuxin Zheng, Chen Xing, Huishuai Zhang, Yanyan Lan, Liwei Wang, and Tie-Yan Liu. 2020. On layer normalization in the transformer architecture. In *Proceedings of ICML*, pages 10524–10533.

[22] Shuailiang Zhang, Hai Zhao, Yuwei Wu, Zhuosheng Zhang, Xi Zhou, and Xiang Zhou. 2020. DCMN+: Dual co-matching network for multi-choice reading comprehension. In *Proceedings of AAAI*, volume 34, pages 9563–9570.