

DAY 3 – SQL ASSIGNMENT

All operators are applied

```
CREATE TABLE Student (  
    id INT PRIMARY KEY,  
    name VARCHAR(50),  
    age INT,  
    marks INT,  
    city VARCHAR(50)  
);  
INSERT INTO Student VALUES (1, 'Arun', 20, 85, 'Chennai');  
INSERT INTO Student VALUES (2, 'Priya', 22, 90, 'Madurai');  
INSERT INTO Student VALUES (3, 'Karthik', 19, 70, 'Trichy');  
INSERT INTO Student VALUES (4, 'Divya', 21, 88, 'Chennai');  
INSERT INTO Student VALUES (5, 'Rahul', 23, 60, 'Salem');
```

```
SELECT * from Student ;
```

The screenshot shows the SQL Developer interface. On the left, the 'SCHEMAS' pane shows the 'student' schema. The main editor displays the SQL code for creating the 'Student' table and inserting five rows of data. Below the editor, the 'Result Grid' shows the output of the 'SELECT * FROM Student;' query, displaying columns: id, name, age, marks, city.

id	name	age	marks	city
1	Arun	20	85	Chennai
2	Priya	22	90	Madurai
3	Karthik	19	70	Trichy
4	Divya	21	88	Chennai
5	Rahul	23	60	Salem

-- Arithmetic operator

```
SELECT marks + 5 AS bonus_marks FROM Student;  
SELECT marks - 10 AS reduced_marks FROM Student;  
SELECT marks * 2 AS double_marks FROM Student;  
SELECT marks / 2 AS half_marks FROM Student;
```

Output:

The output consists of four separate result grids, each showing the result of an arithmetic operation on the 'marks' column of the 'Student' table.

bonus_marks
90
95
75
93
65

double_marks
170
180
140
176
120

half_marks
42.5000
45.0000
35.0000
44.0000
30.0000

reduced_marks
75
80
60
78
50

-- comparison

```
SELECT * FROM Student WHERE marks = 90;  
SELECT * FROM Student WHERE marks > 80;  
SELECT * FROM Student WHERE marks < 80;  
SELECT * FROM Student WHERE marks >= 85;  
SELECT * FROM Student WHERE marks <= 70;  
SELECT * FROM Student WHERE marks != 60;
```

Output:

	id	name	age	marks	city
▶	2	Priya	22	90	Madurai
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	3	Karthik	19	70	Trichy
	5	Rahul	23	60	Salem
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	3	Karthik	19	70	Trichy
	5	Rahul	23	60	Salem
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	3	Karthik	19	70	Trichy
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

-- logical operator

```
SELECT * FROM Student WHERE age > 20 AND marks > 80;  
SELECT * FROM Student WHERE city = 'Chennai' OR city = 'Madurai';  
SELECT * FROM Student WHERE NOT city = 'Salem';
```

Ouptut:

	id	name	age	marks	city
▶	2	Priya	22	90	Madurai
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	3	Karthik	19	70	Trichy
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

-- between

SELECT * FROM Student WHERE marks BETWEEN 70 AND 90;

Output :

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	3	Karthik	19	70	Trichy
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

-- in

SELECT * FROM Student WHERE city IN ('Chennai', 'Madurai');

Output :

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
	2	Priya	22	90	Madurai
	4	Divya	21	88	Chennai
*	NULL	NULL	NULL	NULL	NULL

-- Like

SELECT * FROM Student WHERE name LIKE 'A%';

Output :

	id	name	age	marks	city
▶	1	Arun	20	85	Chennai
*	NULL	NULL	NULL	NULL	NULL

-- ISNull

SELECT * FROM Student WHERE marks IS NULL;

-- Assignment operator

UPDATE Student SET marks = 95 WHERE id = 1;

Output

✓	35	16:03:28	UPDATE Student SET marks = 95 WHERE id = 1		
1	Arun	20	95	Chennai	