

# Short Term Rental (STR) - Single Digital Entry Point (SDEP)

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version     | DEV-undefined                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| OpenAPI     | 3.1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Description | <p>SDEP is a gateway for the electronic transmission of data between online short-term rental platforms (STR) and competent authorities (CA), ensuring timely, reliable and efficient data sharing processes.</p> <ul style="list-style-type: none"><li>- <a href="#">Github (open source)</a></li><li>- <a href="#">EU legislation</a></li><li>- <a href="#">STR Application Profile (STR-AP)</a></li><li>- <a href="#">STR origin prototype v0.0.67</a></li></ul> <p>Contact:</p> <ul style="list-style-type: none"><li>- <a href="mailto:boris.dijkmans@rijksoverheid.nl">boris.dijkmans@rijksoverheid.nl</a></li></ul> |

# Table of Contents

|                                           |           |
|-------------------------------------------|-----------|
| <b>1. Endpoints</b>                       | <b>4</b>  |
| 1.1 auth . . . . .                        | 4         |
| 1.1.1 POST /auth/token . . . . .          | 4         |
| 1.2 ca . . . . .                          | 5         |
| 1.2.1 GET /ca/activities . . . . .        | 5         |
| 1.2.2 GET /ca/activities/count . . . . .  | 6         |
| 1.2.3 POST /ca/areas . . . . .            | 7         |
| 1.2.4 GET /ca/areas . . . . .             | 8         |
| 1.2.5 GET /ca/areas/count . . . . .       | 9         |
| 1.2.6 GET /ca/areas/{areaid} . . . . .    | 10        |
| 1.2.7 DELETE /ca/areas/{areaid} . . . . . | 11        |
| 1.3 health . . . . .                      | 12        |
| 1.3.1 GET /ping . . . . .                 | 12        |
| 1.4 str . . . . .                         | 13        |
| 1.4.1 POST /str/activities/bulk . . . . . | 13        |
| 1.4.2 GET /str/areas . . . . .            | 15        |
| 1.4.3 GET /str/areas/count . . . . .      | 16        |
| 1.4.4 GET /str/areas/{areaid} . . . . .   | 17        |
| <b>2. Schemas</b>                         | <b>18</b> |
| 2.1 Activity.BulkRequest . . . . .        | 18        |
| 2.2 Activity.BulkResponse . . . . .       | 18        |
| 2.3 Activity.BulkResultItem . . . . .     | 18        |
| 2.4 Activity.CountResponse . . . . .      | 18        |
| 2.5 Activity.ListResponse . . . . .       | 19        |
| 2.6 Activity.Request . . . . .            | 19        |
| 2.7 Activity.Response . . . . .           | 20        |
| 2.8 Activity.Status . . . . .             | 20        |
| 2.9 Area.CountResponse . . . . .          | 20        |
| 2.10 Area.ListResponse . . . . .          | 20        |
| 2.11 Area.Request . . . . .               | 21        |
| 2.12 Area.Response . . . . .              | 21        |
| 2.13 Auth.TokenRequest . . . . .          | 21        |
| 2.14 Auth.TokenResponse . . . . .         | 21        |
| 2.15 Common.AddressRequest . . . . .      | 22        |
| 2.16 Common.AddressResponse . . . . .     | 22        |
| 2.17 Common.Regulation . . . . .          | 22        |
| 2.18 Common.TemporalRequest . . . . .     | 22        |

|                                        |    |
|----------------------------------------|----|
| 2.19 Common.TemporalResponse . . . . . | 23 |
| 2.20 Error.Detail . . . . .            | 23 |
| 2.21 Error.Response . . . . .          | 23 |
| 2.22 Health.Status . . . . .           | 23 |

|                            |           |
|----------------------------|-----------|
| <b>3. Security Schemes</b> | <b>24</b> |
|----------------------------|-----------|

|                                       |    |
|---------------------------------------|----|
| 3.1 OAuth2ClientCredentials . . . . . | 24 |
|---------------------------------------|----|

DRAFT

# 1. Endpoints

## 1.1 auth

### 1.1.1 POST /auth/token

#### Get access token (JWT bearer)

Token endpoint for machine-to-machine authentication using OAuth 2.0 Client Credentials Grant. Supports both HTTP Basic Authentication and form parameters

#### Request Body

| Media Type                        | Schema            | Required |
|-----------------------------------|-------------------|----------|
| application/x-www-form-urlencoded | Auth.TokenRequest | no       |

#### Responses

| Status | Description                                                                                                                                     | Schema                               |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Auth.TokenResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                      |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                      |
| 400    | Bad Request - missing client credentials                                                                                                        | application/json: Error.Response     |
| 401    | Unauthorized - authentication failed                                                                                                            | application/json: Error.Response     |

## 1.2 ca

### 1.2.1 GET /ca/activities

#### Get activities for the current authenticated competent authority

Get activities for the current authenticated competent authority. By default, returns all current activities (unlimited), including current records whose lifecycle status is cancelled. Use optional pagination parameters to limit results.

#### Each activity contains:

|                        |                                                                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| activityId             | Functional ID identifying this activity                                                                                                                                         |
| activityName           | Display name (optional) of the activity                                                                                                                                         |
| status                 | Lifecycle status of the activity record: finished or cancelled                                                                                                                  |
| areaId                 | Functional ID referencing the area where the activity took place                                                                                                                |
| competentAuthorityId   | Functional ID referencing the competent authority that owns the area                                                                                                            |
| competentAuthorityName | Display name (optional) of the competent authority                                                                                                                              |
| url                    | URL of the originating listing/advertisement                                                                                                                                    |
| address                | Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress) |
| registrationNumber     | Registration number for the address                                                                                                                                             |
| numberOfGuests         | Number of guests (1-1024)                                                                                                                                                       |
| countryOfGuests        | Array of country codes of guests (each element is ISO 3166-1 alpha-3 or N/A; length equals numberOfGuests)                                                                      |
| temporal               | Temporal composite (startDatetime, endDatetime)                                                                                                                                 |
| platformId             | Functional ID referencing the platform that owns the activity                                                                                                                   |
| platformName           | Display name (optional) of the platform                                                                                                                                         |
| createdAt              | Timestamp when this activity version was created (UTC)                                                                                                                          |

Security: OAuth2ClientCredentials

#### Parameters

| Name   | In    | Type           | Required | Description                                                                        |
|--------|-------|----------------|----------|------------------------------------------------------------------------------------|
| offset | query | integer        | no       | Number of records to skip (default: 0)                                             |
| limit  | query | integer   null | no       | Maximum number of records to return (default: unlimited, max: 1000 when specified) |

#### Responses

| Status | Description                                                                                                                                     | Schema                                  |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Activity.ListResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                         |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                         |
| 400    | Bad request - invalid query parameters                                                                                                          | application/json: Error.Response        |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response        |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                         |

### 1.2.2 GET /ca/activities/count

**Get activities count for the current authenticated competent authority (optional, to support pagination)**

Get activities count for the current authenticated competent authority (optional, to support pagination). Counts all current activity records, including those whose lifecycle status is cancelled.

Security: OAuth2ClientCredentials

#### Responses

| Status | Description                                                                                                                                     | Schema                                   |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Activity.CountResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                          |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                          |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response         |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                          |

### 1.2.3 POST /ca/areas

#### Submit a single area into the areas collection for the current authenticated competent authority

Submit a single area into the areas collection for the current authenticated competent authority (competentAuthorityId).

#### ID Pattern:

- areaId: provided by competent authority as business identifier (optional), otherwise generated as UUID (RFC 9562)

#### Versioning:

- Same areaId can be resubmitted → creates new version with different timestamp
- Unique constraint: (areaId, createdAt, current authenticated competent authority)

#### Limiting:

- Max. 1 MiB (1,048,576 bytes) per file
- This is to ensure predictable performance, reduce abuse risk, and improve overall reliability

#### The request contains (multipart/form-data):

|            |                                                                                                                                      |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|
| areaId     | Functional ID identifying this area (auto-generated UUID if not provided; alphanumeric with hyphens ^[A-Za-z0-9-]+\$ , max 64 chars) |
| areaName   | Display name (optional, max 64 chars)                                                                                                |
| regulation | Regulation type of the area - 'listing', 'activity', or 'all' (optional, defaults to 'all' when not supplied)                        |
| file       | Shapefile upload (max 1 MiB)                                                                                                         |

#### The response contains:

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| areaId                 | Functional ID identifying this area                           |
| areaName               | Display name (optional) of the area                           |
| regulation             | Regulation type of the area - 'listing', 'activity', or 'all' |
| filename               | Name of the area shapefile (e.g., 'area.zip')                 |
| competentAuthorityId   | Functional ID of the competent authority that owns the area   |
| competentAuthorityName | Display name (optional) of the competent authority            |
| createdAt              | Timestamp when this area version was created (UTC)            |

Security: OAuth2ClientCredentials

#### Request Body

| Media Type          | Schema       | Required |
|---------------------|--------------|----------|
| multipart/form-data | Area.Request | yes      |

#### Responses

| Status | Description                                                                                                                                     | Schema                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 201    | Area created successfully                                                                                                                       | application/json: Area.Response  |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                  |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                  |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                  |
| 422    | Validation Error - business rule violation                                                                                                      | application/json: Error.Response |

### 1.2.4 GET /ca/areas

#### Get areas for the current authenticated competent authority

Get all areas owned by the current authenticated competent authority. By default, returns all areas (unlimited). Use optional pagination parameters to limit results.

#### Scoping:

- Only returns areas belonging to the authenticated CA (based on JWT client\_id)

#### Each area contains:

|                        |                                                             |
|------------------------|-------------------------------------------------------------|
| areaId                 | Functional ID identifying this area                         |
| areaName               | Display name (optional) of the area                         |
| regulation             | Regulation type: 'listing', 'activity', or 'all'            |
| filename               | Name of the area shapefile (e.g., 'area.zip')               |
| competentAuthorityId   | Functional ID of the competent authority that owns the area |
| competentAuthorityName | Display name (optional) of the competent authority          |
| createdAt              | Timestamp when this area version was created (UTC)          |

#### Pagination:

|        |                                                          |
|--------|----------------------------------------------------------|
| offset | Number of records to skip (default: 0)                   |
| limit  | Maximum number of records to return (default: unlimited) |

Security: OAuth2ClientCredentials

#### Parameters

| Name   | In    | Type           | Required | Description                                                                        |
|--------|-------|----------------|----------|------------------------------------------------------------------------------------|
| offset | query | integer        | no       | Number of records to skip (default: 0)                                             |
| limit  | query | integer   null | no       | Maximum number of records to return (default: unlimited, max: 1000 when specified) |

#### Responses

| Status | Description                                                                                                                                     | Schema                              |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 200    | List of areas owned by the authenticated competent authority                                                                                    | application/json: Area.ListResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                     |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                     |
| 400    | Bad request - invalid query parameters                                                                                                          | application/json: Error.Response    |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response    |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                     |



### 1.2.5 GET /ca/areas/count

**Get areas count for the current authenticated competent authority (optional, to support pagination)**

Get areas count for the current authenticated competent authority (optional, to support pagination)

Security: OAuth2ClientCredentials

#### Responses

| Status | Description                                                                                                                                     | Schema                               |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Area.CountResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                      |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                      |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response     |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                      |

### 1.2.6 GET /ca/areas/{areald}

#### Get area (shapefile) for the current authenticated competent authority

Get area (shapefile) based on functional ID, scoped to the authenticated CA

Security: OAuth2ClientCredentials

#### Parameters

| Name   | In   | Type   | Required | Description |
|--------|------|--------|----------|-------------|
| areald | path | string | yes      |             |

#### Responses

| Status | Description                                                                                                                                     | Schema                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 200    | Successful Response                                                                                                                             | application/zip:                 |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                  |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                  |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                  |
| 404    | Resource Not Found - area unavailable, deleted, or not owned by this CA                                                                         |                                  |

### 1.2.7 DELETE /ca/areas/{areald}

**Delete (deactivate) an area from the areas collection for the current authenticated competent authority**

Delete (deactivate) an area by marking it as ended (now, UTC).

**Behavior:**

- Deletes (deactivates) the area
- The area will no longer appear in area listings
- Deleting an already-deleted area returns 404

Security: OAuth2ClientCredentials

**Parameters**

| Name   | In   | Type   | Required | Description |
|--------|------|--------|----------|-------------|
| areald | path | string | yes      |             |

**Responses**

| Status | Description                                                                                                                                     | Schema                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 204    | Success - area deleted (deactivate)                                                                                                             |                                  |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                  |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                  |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                  |
| 404    | Resource Not Found - area unavailable, already deleted, or not owned by this CA                                                                 |                                  |
| 422    | Validation Error - business rule violation                                                                                                      | application/json: Error.Response |

## 1.3 health

### 1.3.1 GET /ping

#### Ping application (authenticated)

Verify if API is reachable (requires authentication)

Security: OAuth2ClientCredentials

#### Responses

| Status | Description                                                                                                                                     | Schema                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Health.Status  |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                  |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                  |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response |

## 1.4 str

### 1.4.1 POST /str/activities/bulk

#### Submit activities in bulk for the current authenticated platform

Submit 1-1000 activities into the activities collection for the current authenticated platform (platformId).

#### ID pattern:

activityId is provided by the platform as a business identifier (optional).  
If not provided (or empty string), a UUID is auto-generated (RFC 9562).

#### Versioning:

The same activityId can be resubmitted - this creates a new version with a different timestamp.  
Unique constraint: (activityId, createdAt, current authenticated platform).

#### Validation flow (4 steps):

1. **Syntax and semantical validation** - each item is validated individually. Failed items are marked NOK with the error reason; valid items continue.
2. **Referential Integrity Check** - area IDs are verified. Items with unknown areaId are marked NOK; valid items continue.
3. **Bulk Insert** - all remaining valid items are inserted in a single multi-row INSERT.
4. **Feedback** - per-item OK/NOK response preserving original order.

#### Intra-batch duplicates (last-wins):

When the same activityId appears multiple times in a single batch, only the last occurrence is processed. Earlier occurrences receive NOK.

#### The request contains:

- activities: Array of activity objects to process (1-1000 items per batch)

#### Each activity item in the request contains:

|                    |                                                                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| activityId         | Functional ID identifying the activity (auto-generated UUID if not provided; alphanumeric with hyphens <code>^[A-Za-z0-9-]+\$</code> , max 64 chars)                            |
| activityName       | Display name of the activity (optional, max 64 chars)                                                                                                                           |
| status             | Lifecycle status of the activity record. Defaults to finished when omitted; may also be cancelled                                                                               |
| areaId             | Functional ID referencing the area where the activity took place                                                                                                                |
| url                | URL of the originating listing/advertisement (max 128 chars)                                                                                                                    |
| address            | Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress) |
| registrationNumber | Registration number (max 32 chars)                                                                                                                                              |
| numberOfGuests     | Number of guests (1-1024)                                                                                                                                                       |
| countryOfGuests    | Array of country codes (1-1024; each element is ISO 3166-1 alpha-3 or N/A, uppercase only). Its length <b>must equal</b> numberOfGuests.                                        |
| temporal           | Temporal composite (startDatetime, endDatetime)                                                                                                                                 |

#### The response contains:

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| totalReceived | Total number of items received in the request                     |
| succeeded     | Number of items successfully created (status OK)                  |
| failed        | Number of items that failed validation or processing (status NOK) |
| results       | Per-item results preserving the original request order            |

#### Each results item contains:

|               |                                                                                        |
|---------------|----------------------------------------------------------------------------------------|
| activityIndex | Zero-based index of this item in the original request list                             |
| activityId    | Activity functional ID provided by the client in the request                           |
| status        | Processing result - OK (created successfully) or NOK (failed validation or processing) |
| activity      | The full activity object (present for OK items, omitted for NOK items)                 |
| errors        | Structured error details (present for NOK items, omitted for OK items)                 |

**The activity object (for the OK items) contains:**

|                        |                                                                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| activityId             | Functional ID identifying this activity                                                                                                                                         |
| activityName           | Display name (optional) of the activity                                                                                                                                         |
| status                 | Lifecycle status of the activity record: finished or cancelled                                                                                                                  |
| areaId                 | Functional ID referencing the area where this activity took place                                                                                                               |
| competentAuthorityId   | Functional ID of the competent authority who owns the referenced area                                                                                                           |
| competentAuthorityName | Display name (optional) of the competent authority                                                                                                                              |
| url                    | URL of the originating listing/advertisement                                                                                                                                    |
| address                | Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress) |
| registrationNumber     | Registration number for the address                                                                                                                                             |
| numberOfGuests         | Number of guests (1-1024)                                                                                                                                                       |
| countryOfGuests        | Array of country codes of guests (each element is ISO 3166-1 alpha-3 or N/A). Length equals numberOfGuests.                                                                     |
| temporal               | Temporal composite (startDatetime, endDatetime)                                                                                                                                 |
| platformId             | Functional ID referencing the platform that owns the activity                                                                                                                   |
| platformName           | Display name (optional) of the platform                                                                                                                                         |
| createdAt              | Timestamp when this activity version was created (UTC)                                                                                                                          |

**Response HTTP status:**

- 201: all items created successfully
- 200: partial success (some OK, some NOK)
- 401: missing or invalid token
- 403: insufficient permissions
- 422: all items failed

Security: OAuth2ClientCredentials

**Request Body**

| Media Type       | Schema               | Required |
|------------------|----------------------|----------|
| application/json | Activity.BulkRequest | yes      |

**Responses**

| Status | Description                                                                                                                                     | Schema                                  |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| 201    | All activities created successfully                                                                                                             | application/json: Activity.BulkResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                         |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                         |
| 200    | Partial success - some activities created, some failed                                                                                          | application/json: Activity.BulkResponse |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response        |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                         |
| 422    | All activities failed validation                                                                                                                | application/json: Activity.BulkResponse |

## 1.4.2 GET /str/areas

### Get all areas

Get all areas. By default, returns all areas (unlimited). Use optional pagination parameters to limit results.

#### Each area contains:

|                        |                                                                      |
|------------------------|----------------------------------------------------------------------|
| areaId                 | Functional ID identifying this area                                  |
| areaName               | Display name (optional) of the area                                  |
| regulation             | Regulation type of the area - 'listing', 'activity', or 'all'        |
| filename               | Name of the area shapefile (e.g., 'area.zip')                        |
| competentAuthorityId   | Functional ID referencing the competent authority that owns the area |
| competentAuthorityName | Display name (optional) of the competent authority                   |
| createdAt              | Timestamp when this area version was created (UTC)                   |

Security: OAuth2ClientCredentials

#### Parameters

| Name   | In    | Type           | Required | Description                                                                        |
|--------|-------|----------------|----------|------------------------------------------------------------------------------------|
| offset | query | integer        | no       | Number of records to skip (default: 0)                                             |
| limit  | query | integer   null | no       | Maximum number of records to return (default: unlimited, max: 1000 when specified) |

#### Responses

| Status | Description                                                                                                                                     | Schema                              |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 200    | List of areas                                                                                                                                   | application/json: Area.ListResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                     |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                     |
| 400    | Bad request - invalid query parameters                                                                                                          | application/json: Error.Response    |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response    |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                     |

### 1.4.3 GET /str/areas/count

#### Get areas count (optional, to support pagination)

Get areas count (optional, to support pagination)

Security: OAuth2ClientCredentials

#### Responses

| Status | Description                                                                                                                                     | Schema                               |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| 200    | Successful Response                                                                                                                             | application/json: Area.CountResponse |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                      |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                      |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response     |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                      |



#### 1.4.4 GET /str/areas/{areald}

##### Get area (shapefile)

Get area (shapefile) based on functional ID

Security: OAuth2ClientCredentials

##### Parameters

| Name   | In   | Type   | Required | Description |
|--------|------|--------|----------|-------------|
| areald | path | string | yes      |             |

##### Responses

| Status | Description                                                                                                                                     | Schema                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 200    | Successful Response                                                                                                                             | application/zip:                 |
| 500    | Internal Server Error - an unexpected issue occurred that prevented the request from being completed                                            |                                  |
| 503    | Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server) |                                  |
| 401    | Unauthorized - missing or invalid token                                                                                                         | application/json: Error.Response |
| 403    | Forbidden - insufficient permissions                                                                                                            |                                  |
| 404    | Resource Not Found - area unavailable                                                                                                           |                                  |

## 2. Schemas

### 2.1 Activity.BulkRequest

Bulk activity request schema.

The `activities` field is typed as `list[ActivityRequest]` for the OpenAPI contract, but item-level validation is skipped at request-parse time (via `SkipValidation`). This preserves the Application-First Validation flow: each item is validated individually in the service layer, so one invalid item is marked NOK without failing the whole batch.

| Property   | Type                    | Required | Description                                                                                                                                                                           |
|------------|-------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| activities | array[Activity.Request] | yes      | List of activity objects to process (1-1000 items per batch). Each item is validated individually in the service layer; invalid items are marked NOK without failing the whole batch. |

### 2.2 Activity.BulkResponse

Bulk activity response schema.

Returns per-item OK/NOK feedback with summary counts.  
Validation flow Step 4: the original list enriched with status and error\_message.

| Property      | Type                           | Required | Description                                                       |
|---------------|--------------------------------|----------|-------------------------------------------------------------------|
| totalReceived | integer                        | yes      | Total number of items received in the request                     |
| succeeded     | integer                        | yes      | Number of items successfully created (status OK)                  |
| failed        | integer                        | yes      | Number of items that failed validation or processing (status NOK) |
| results       | array[Activity.BulkResultItem] | yes      | Per-item results preserving the original request order            |

### 2.3 Activity.BulkResultItem

Result for a single item in a bulk activity response.

| Property      | Type                     | Required | Description                                                                                                                                                                                                                   |
|---------------|--------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| activityIndex | integer                  | yes      | Zero-based index of this item in the original request list                                                                                                                                                                    |
| activityId    | string   null            | no       | Activity functional ID as supplied by the client in the request (null if not provided by client, even when a UUID was auto-generated)                                                                                         |
| status        | enum[OK, NOK]            | yes      | Processing status for this batch item: OK (created successfully) or NOK (failed validation or processing). This is distinct from <code>activity.status</code> , which is the lifecycle status of the created activity record. |
| activity      | Activity.Response   null | no       | The full activity object (present for OK items, omitted for NOK items)                                                                                                                                                        |
| errors        | Error.Response   null    | no       | Structured error details when status is NOK; omitted when status is OK                                                                                                                                                        |

### 2.4 Activity.CountResponse

Count of activities response schema.

| Property | Type    | Required | Description                      |
|----------|---------|----------|----------------------------------|
| count    | integer | yes      | Total number of activity records |

## 2.5 Activity.ListResponse

List of activities for GET responses.

| Property   | Type                     | Required | Description        |
|------------|--------------------------|----------|--------------------|
| activities | array[Activity.Response] | yes      | List of activities |

## 2.6 Activity.Request

Activity request schema for creating rental activities.

Platform:

- NOT in request payload (extracted from JWT token at API layer)
- PlatformId comes from token's client\_id claim
- PlatformName comes from token's client\_name claim
- Will be auto-created if it doesn't exist yet

Activity ID:

- Optional: If not provided, will be auto-generated (RFC 9562 UUID)

Activity Name:

- Optional: Display name (max 64 chars)

Validation Layer:

- Validates all syntax constraints (lengths, ranges, types)

Constraints (enforced at database level):

- Unique constraint: (activityId, createdAt, platform) for versioning support

| Property           | Type                   | Required | Description                                                                                                                                           |
|--------------------|------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| activityId         | string   null          | no       | Functional ID identifying this activity (auto-generated UUID if not provided; alphanumeric with hyphens <code>^[A-Za-z0-9-]+\$</code> , max 64 chars) |
| activityName       | string   null          | no       | Display name (optional, max 64 chars) of the activity                                                                                                 |
| status             | Activity.Status        | no       | Lifecycle status of the activity. Defaults to <code>finished</code> when omitted; may also be <code>cancelled</code> .                                |
| areald             | string                 | yes      | Functional ID referencing the area where the activity took place                                                                                      |
| url                | string                 | yes      | URL of the originating listing/advertisement (required)                                                                                               |
| address            | Common.AddressRequest  | yes      | Address composite (INSPIRE/STR-AP) containing thoroughfare, locatorDesignator sub-fields, postCode, and postName                                      |
| registrationNumber | string                 | yes      | Registration number for the address                                                                                                                   |
| numberOfGuests     | integer                | yes      | Number of guests (1-1024)                                                                                                                             |
| countryOfGuests    | array[string]          | yes      | Array of country codes of guests (1-1024; each element is ISO 3166-1 alpha-3 or 'N/A', uppercase only). Length must equal numberOfGuests.             |
| temporal           | Common.TemporalRequest | yes      | Temporal composite containing start and end date/time                                                                                                 |

## 2.7 Activity.Response

Activity response schema.

| Property               | Type                    | Required | Description                                                                                                   |
|------------------------|-------------------------|----------|---------------------------------------------------------------------------------------------------------------|
| activityId             | string                  | yes      | Functional ID identifying this activity                                                                       |
| activityName           | string   null           | no       | Display name (optional, max 64 chars) of the activity                                                         |
| status                 | Activity.Status         | yes      | Lifecycle status of the activity record: finished or cancelled.                                               |
| areaId                 | string                  | yes      | Functional ID referencing the area where this activity took place                                             |
| competentAuthorityId   | string                  | yes      | Functional ID referencing the competent authority that owns the area                                          |
| competentAuthorityName | string   null           | no       | Display name (optional, max 64 chars) of the competent authority                                              |
| url                    | string                  | yes      | URL of the originating listing/advertisement                                                                  |
| address                | Common.AddressResponse  | yes      | Address composite                                                                                             |
| registrationNumber     | string                  | yes      | Registration number for the address                                                                           |
| numberOfGuests         | integer                 | yes      | Number of guests (1-1024)                                                                                     |
| countryOfGuests        | array[string]           | yes      | Array of country codes of guests (each element is ISO 3166-1 alpha-3 or 'N/A'). Length equals numberOfGuests. |
| temporal               | Common.TemporalResponse | yes      | Temporal composite                                                                                            |
| platformId             | string                  | yes      | Functional ID referencing the platform that owns the activity                                                 |
| platformName           | string   null           | no       | Display name (optional, max 64 chars) of the platform                                                         |
| createdAt              | string(date-time)       | yes      | Timestamp when this activity version was created (UTC)                                                        |

## 2.8 Activity.Status

Lifecycle status for an activity record.

Type: string

Allowed values: finished, cancelled

## 2.9 Area.CountResponse

Count of areas response schema.

| Property | Type    | Required | Description                                                       |
|----------|---------|----------|-------------------------------------------------------------------|
| count    | integer | yes      | Total number of areas in context of the current SDEP/member state |

## 2.10 Area.ListResponse

List of areas response schema.

| Property | Type                 | Required | Description                                               |
|----------|----------------------|----------|-----------------------------------------------------------|
| areas    | array[Area.Response] | yes      | List of areas in context of the current SDEP/member state |

## 2.11 Area.Request

| Property   | Type                     | Required | Description |
|------------|--------------------------|----------|-------------|
| areald     | string   null            | no       |             |
| areaName   | string   null            | no       |             |
| regulation | Common.Regulation   null | no       |             |
| file       | string(binary)           | yes      |             |

## 2.12 Area.Response

Area response schema.

| Property               | Type              | Required | Description                                                      |
|------------------------|-------------------|----------|------------------------------------------------------------------|
| areald                 | string            | yes      | Functional ID identifying this area                              |
| areaName               | string   null     | no       | Display name (optional, max 64 chars) of the area                |
| regulation             | Common.Regulation | no       | Regulation type - 'listing', 'activity', or 'all'                |
| filename               | string            | yes      | Name of the area shapefile (e.g., 'area.zip')                    |
| competentAuthorityId   | string            | yes      | Functional ID of the competent authority that owns the area      |
| competentAuthorityName | string   null     | no       | Display name (optional, max 64 chars) of the competent authority |
| createdAt              | string(date-time) | yes      | Timestamp when this area version was created (UTC)               |

## 2.13 Auth.TokenRequest

| Property      | Type          | Required | Description                            |
|---------------|---------------|----------|----------------------------------------|
| client_id     | string   null | no       | Client ID for M2M authentication       |
| client_secret | string   null | no       | Client secret for M2M authentication   |
| grant_type    | string   null | no       | OAuth2 grant type (client_credentials) |

## 2.14 Auth.TokenResponse

OAuth2 token response model

| Property     | Type    | Required | Description                                                                                  |
|--------------|---------|----------|----------------------------------------------------------------------------------------------|
| access_token | string  | yes      | OAuth2 bearer access token to be used in the Authorization header of subsequent API requests |
| token_type   | string  | yes      | Type of token issued (typically 'Bearer')                                                    |
| expires_in   | integer | yes      | Lifetime of the access token in seconds                                                      |

## 2.15 Common.AddressRequest

Address composite schema for activity requests (INSPIRE/STR-AP field names).

Validation Layer:

- All syntax validation (lengths, types, constraints) happens here
- Service layer receives validated data

| Property                  | Type           | Required | Description                                                   |
|---------------------------|----------------|----------|---------------------------------------------------------------|
| thoroughfare              | string         | yes      | Street / public space name                                    |
| locatorDesignatorNumber   | integer   null | no       | Numeric house number component (optional, >= 0 when provided) |
| locatorDesignatorLetter   | string   null  | no       | Letter/character suffix (optional, e.g. 'a', 'bis', 'ter')    |
| locatorDesignatorAddition | string   null  | no       | Additional qualifier (optional, e.g. 'II', 'Apt 3')           |
| postCode                  | string         | yes      | Postal code (no spaces, alphanumeric)                         |
| postName                  | string         | yes      | City / town / village                                         |
| fullAddress               | string         | yes      | Full address as a single string (required, max 318 chars)     |

## 2.16 Common.AddressResponse

Address composite schema for activity responses (INSPIRE/STR-AP field names).

| Property                  | Type           | Required | Description                               |
|---------------------------|----------------|----------|-------------------------------------------|
| thoroughfare              | string         | yes      | Street / public space name                |
| locatorDesignatorNumber   | integer   null | no       | Numeric house number component (optional) |
| locatorDesignatorLetter   | string   null  | no       | Letter/character suffix (optional)        |
| locatorDesignatorAddition | string   null  | no       | Additional qualifier (optional)           |
| postCode                  | string         | yes      | Postal code                               |
| postName                  | string         | yes      | City / town / village                     |
| fullAddress               | string         | yes      | Full address as a single string           |

## 2.17 Common.Regulation

Regulation type for an area: 'listing', 'activity', or 'all' (covers both).

Type: string

Allowed values: listing, activity, all

## 2.18 Common.TemporalRequest

Temporal composite schema for activity requests.

Validation Layer:

- Validates datetime formats
- Date-only submissions are permitted, and will be stored internally using a 00:00:00 timestamp
- Ensures start year is >= 2025
- Ensures start is before end

| Property      | Type              | Required | Description                                                            |
|---------------|-------------------|----------|------------------------------------------------------------------------|
| startDatetime | string(date-time) | yes      | Start date and time of the rental activity (year must be >= 2025)      |
| endDatetime   | string(date-time) | yes      | End date and time of the rental activity (must be after startDatetime) |

## 2.19 Common.TemporalResponse

Temporal composite schema for activity responses.

| Property      | Type              | Required | Description                                |
|---------------|-------------------|----------|--------------------------------------------|
| startDatetime | string(date-time) | yes      | Start date and time of the rental activity |
| endDatetime   | string(date-time) | yes      | End date and time of the rental activity   |

## 2.20 Error.Detail

Detail of a single error.

| Property | Type                           | Required | Description                                        |
|----------|--------------------------------|----------|----------------------------------------------------|
| msg      | string                         | yes      | Human-readable error message                       |
| type     | string                         | yes      | Error type identifier                              |
| loc      | array[string   integer]   null | no       | Location of the error (e.g. ['body', 'fieldName']) |

## 2.21 Error.Response

Standardized error response format.

| Property | Type                | Required | Description           |
|----------|---------------------|----------|-----------------------|
| detail   | array[Error.Detail] | yes      | List of error details |

## 2.22 Health.Status

Status response schema

| Property | Type          | Required | Description    |
|----------|---------------|----------|----------------|
| status   | string   null | no       | Status message |

## 3. Security Schemes

### 3.1 OAuth2ClientCredentials

|       |                                                                                              |
|-------|----------------------------------------------------------------------------------------------|
| type  | oauth2                                                                                       |
| flows | {'clientCredentials': {'scopes': {}, 'tokenUrl': 'http://localhost:8000/api/v0/auth/token'}} |

DRAFT