

SDEP - Competent Authority (CA) API

Version	ca_v1
OpenAPI	3.1.0
Description	Endpoints for competent authorities to manage areas and view activities.

Table of Contents

1. Endpoints	3
1.1 ca	3
1.1.1 GET /activities	3
1.1.2 GET /activities/count	4
1.1.3 POST /areas	5
1.1.4 GET /areas	6
1.1.5 GET /areas/count	7
1.1.6 GET /areas/{areaid}	8
1.1.7 DELETE /areas/{areaid}	9
2. Schemas	10
2.1 Activity.CountResponse	10
2.2 Activity.ListResponse	10
2.3 Activity.Response	10
2.4 Activity.Status	10
2.5 Area.CountResponse	11
2.6 Area.ListResponse	11
2.7 Area.Request	11
2.8 Area.Response	11
2.9 Common.AddressResponse	11
2.10 Common.Regulation	12
2.11 Common.TemporalResponse	12
2.12 Error.Detail	12
2.13 Error.Response	12

1. Endpoints

1.1 ca

1.1.1 GET /activities

Get activities for the currently authenticated competent authority

Get activities for the currently authenticated competent authority. By default, returns all current activities (unlimited), including current records whose lifecycle status is cancelled. Use optional pagination parameters to limit results.

Each activity contains:

activityId	Functional ID identifying this activity
activityName	Display name (optional) of the activity
status	Lifecycle status of the activity: finished or cancelled
areaId	Functional ID referencing the area where the activity took place
competentAuthorityId	Functional ID referencing the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
url	URL of the originating listing/advertisement
address	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	Registration number of the address
numberOfGuests	Number of guests (1-1024)
countryOfGuests	Array of country codes of guests (each element is ISO 3166-1 alpha-3 or N/A; array length equals numberOfGuests)
temporal	Temporal composite (startDatetime, endDatetime)
platformId	Functional ID referencing the platform that owns the activity
platformName	Display name (optional) of the platform
createdAt	Timestamp when this activity version was created (UTC)

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
offset	query	integer	no	Number of records to skip (default: 0)
limit	query	integer null	no	Maximum number of records to return (default: unlimited, max: 1000 when specified)

Responses

Status	Description	Schema
200	Successful Response	application/json: Activity.ListResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad request - invalid query parameters	application/json: Error.Response
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.1.2 GET /activities/count

Get activities count for the currently authenticated competent authority (optional, to support pagination)

Get activities count for the currently authenticated competent authority (optional, to support pagination). Counts all current activity records, including those whose lifecycle status is cancelled.

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Activity.CountResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.1.3 POST /areas

Submit a single area into the areas collection for the currently authenticated competent authority

Submit a single area into the areas collection for the currently authenticated competent authority.

ID Pattern:

- areaId: provided by competent authority as business identifier (optional), otherwise generated as UUID (RFC 9562)

Versioning:

- Same areaId can be resubmitted → creates new version with different timestamp
- Unique constraint: (areaId, createdAt, current authenticated competent authority)

Limiting:

- Max. 1 MiB (1,048,576 bytes) per file
- This is to ensure predictable performance, reduce abuse risk, and improve overall reliability

The request contains (multipart/form-data):

areaId	Functional ID identifying this area (auto-generated UUID if not provided; alphanumeric with hyphens ^[A-Za-z0-9-]+\$, max 64 chars)
areaName	Display name (optional, max 64 chars)
regulation	Regulation type of the area - 'listing', 'activity', or 'all' (optional, defaults to 'all' when not supplied)
file	Shapefile upload (max 1 MiB)

The response contains:

areaId	Functional ID identifying this area
areaName	Display name (optional) of the area
regulation	Regulation type of the area - 'listing', 'activity', or 'all'
filename	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	Functional ID of the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
createdAt	Timestamp when this area version was created (UTC)

Security: OAuth2ClientCredentials

Request Body

Media Type	Schema	Required
multipart/form-data	Area.Request	yes

Responses

Status	Description	Schema
201	Area created successfully	application/json: Area.Response
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
422	Validation Error - business rule violation	application/json: Error.Response

1.1.4 GET /areas

Get areas for the currently authenticated competent authority

Get all areas owned by the currently authenticated competent authority. By default, returns all areas (unlimited). Use optional pagination parameters to limit results.

Scoping:

- Only returns areas belonging to the currently authenticated competent authority (based on JWT client_id)

Each area contains:

areaId	Functional ID identifying this area
areaName	Display name (optional) of the area
regulation	Regulation type: 'listing', 'activity', or 'all'
filename	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	Functional ID of the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
createdAt	Timestamp when this area version was created (UTC)

Pagination:

offset	Number of records to skip (default: 0)
limit	Maximum number of records to return (default: unlimited)

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
offset	query	integer	no	Number of records to skip (default: 0)
limit	query	integer null	no	Maximum number of records to return (default: unlimited, max: 1000 when specified)

Responses

Status	Description	Schema
200	List of areas owned by the authenticated competent authority	application/json: Area.ListResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad request - invalid query parameters	application/json: Error.Response
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.1.5 GET /areas/count

Get areas count for the currently authenticated competent authority (optional, to support pagination)

Get areas count for the currently authenticated competent authority (optional, to support pagination).

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Area.CountResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.1.6 GET /areas/{areaid}

Get area (shapefile) for the currently authenticated competent authority

Get area (shapefile) based on functional ID, scoped to the currently authenticated competent authority.

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
areaid	path	string	yes	

Responses

Status	Description	Schema
200	Successful Response	application/zip:
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
404	Resource Not Found - area unavailable, deleted, or not owned by this CA	

1.1.7 DELETE /areas/{areaid}

Delete (deactivate) an area from the areas collection for the currently authenticated competent authority

Delete (deactivate) an area by marking it as ended (now, UTC).

Behavior:

- Deletes (deactivates) the area
- The area will no longer appear in area listings
- Deleting an already-deleted area returns 404

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
areaid	path	string	yes	

Responses

Status	Description	Schema
204	Success - area deleted (deactivate)	
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
404	Resource Not Found - area unavailable, already deleted, or not owned by this CA	
422	Validation Error - business rule violation	application/json: Error.Response

2. Schemas

2.1 Activity.CountResponse

Count of activities response schema.

Property	Type	Required	Description
count	integer	yes	Total number of activity records

2.2 Activity.ListResponse

List of activities for GET responses.

Property	Type	Required	Description
activities	array[Activity.Response]	yes	List of activities

2.3 Activity.Response

Activity response schema.

Property	Type	Required	Description
activityId	string	yes	Functional ID identifying this activity
activityName	string null	no	Display name (optional) of the activity
status	Activity.Status	yes	Lifecycle status of the activity: finished or cancelled.
areaId	string	yes	Functional ID referencing the area where this activity took place
competentAuthorityId	string	yes	Functional ID referencing the competent authority that owns the area
competentAuthorityName	string null	no	Display name (optional) of the competent authority
url	string	yes	URL of the originating listing/advertisement
address	Common.AddressResponse	yes	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	string	yes	Registration number of the address
numberOfGuests	integer	yes	Number of guests (1-1024)
countryOfGuests	array[string]	yes	Array of country codes of guests (each element is ISO 3166-1 alpha-3 or 'N/A'); array length equals numberOfGuests.
temporal	Common.TemporalResponse	yes	Temporal composite (startDatetime, endDatetime)
platformId	string	yes	Functional ID referencing the platform that owns the activity
platformName	string null	no	Display name (optional) of the platform
createdAt	string(date-time)	yes	Timestamp when this activity version was created (UTC)

2.4 Activity.Status

Lifecycle status for an activity record.

Type: string

Allowed values: finished, cancelled

2.5 Area.CountResponse

Count of areas response schema.

Property	Type	Required	Description
count	integer	yes	Total number of areas in context of the current SDEP/member state

2.6 Area.ListResponse

List of areas response schema.

Property	Type	Required	Description
areas	array[Area.Response]	yes	List of areas in context of the current SDEP/member state

2.7 Area.Request

Property	Type	Required	Description
areald	string null	no	
areaName	string null	no	
regulation	Common.Regulation null	no	
file	string(binary)	yes	

2.8 Area.Response

Area response schema.

Property	Type	Required	Description
areald	string	yes	Functional ID identifying this area
areaName	string null	no	Display name (optional) of the area
regulation	Common.Regulation	no	Regulation type of the area - 'listing', 'activity', or 'all'
filename	string	yes	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	string	yes	Functional ID of the competent authority that owns the area
competentAuthorityName	string null	no	Display name (optional) of the competent authority
createdAt	string(date-time)	yes	Timestamp when this area version was created (UTC)

2.9 Common.AddressResponse

Address composite schema for activity responses (INSPIRE/STR-AP field names).

Property	Type	Required	Description
thoroughfare	string	yes	Street / public space name
locatorDesignatorNumber	integer null	no	Numeric house number component (optional)
locatorDesignatorLetter	string null	no	Letter/character suffix (optional)
locatorDesignatorAddition	string null	no	Additional qualifier (optional)
postCode	string	yes	Postal code
postName	string	yes	City / town / village
fullAddress	string	yes	Full address as a single string

2.10 Common.Regulation

Regulation type for an area: 'listing', 'activity', or 'all' (covers both).

Type: string

Allowed values: listing, activity, all

2.11 Common.TemporalResponse

Temporal composite schema for activity responses.

Property	Type	Required	Description
startDatetime	string(date-time)	yes	Start date and time of the rental activity
endDatetime	string(date-time)	yes	End date and time of the rental activity

2.12 Error.Detail

Detail of a single error.

Property	Type	Required	Description
msg	string	yes	Human-readable error message
type	string	yes	Error type identifier
loc	array[string integer] null	no	Location of the error (e.g. ['body', 'fieldName'])

2.13 Error.Response

Standardized error response format.

Property	Type	Required	Description
detail	array[Error.Detail]	yes	List of error details