

Short Term Rental (STR) - Single Digital Entry Point (SDEP)

Version	v1
OpenAPI	3.1.0
Description	SDEP is a gateway for the electronic transmission of data between online short-term rental platforms (STR) and competent authorities (CA), ensuring timely, reliable and efficient data sharing processes. - Github (open source) - EU legislation - STR Application Profile (STR-AP) - STR origin prototype v0.0.67 Contact: - boris.dijkmans@rijksoverheid.nl

Table of Contents

1. Endpoints	4
1.1 auth	4
1.1.1 POST /auth/token	4
1.2 ca	5
1.2.1 GET /ca/activities	5
1.2.2 GET /ca/activities/count	6
1.2.3 POST /ca/areas	7
1.2.4 GET /ca/areas	8
1.2.5 GET /ca/areas/count	9
1.2.6 GET /ca/areas/{areaid}	10
1.2.7 DELETE /ca/areas/{areaid}	11
1.3 health	12
1.3.1 GET /ping	12
1.4 str	13
1.4.1 POST /str/activities/bulk	13
1.4.2 GET /str/areas	15
1.4.3 GET /str/areas/count	16
1.4.4 GET /str/areas/{areaid}	17
2. Schemas	18
2.1 Activity.BulkRequest	18
2.2 Activity.BulkResponse	18
2.3 Activity.BulkResultItem	18
2.4 Activity.CountResponse	18
2.5 Activity.ListResponse	18
2.6 Activity.Request	19
2.7 Activity.Response	20
2.8 Activity.Status	20
2.9 Area.CountResponse	20
2.10 Area.ListResponse	20
2.11 Area.Request	21
2.12 Area.Response	21
2.13 Auth.TokenRequest	21
2.14 Auth.TokenResponse	21
2.15 Common.AddressRequest	22
2.16 Common.AddressResponse	22
2.17 Common.Regulation	22
2.18 Common.TemporalRequest	22

2.19 Common.TemporalResponse	23
2.20 Error.Detail	23
2.21 Error.Response	23
2.22 Health.Status	23

1. Endpoints

1.1 auth

1.1.1 POST /auth/token

Get access token (JWT bearer)

Token endpoint for machine-to-machine authentication using OAuth 2.0 Client Credentials Grant. Supports both HTTP Basic Authentication and form parameters.

Request Body

Media Type	Schema	Required
application/x-www-form-urlencoded	Auth.TokenRequest	no

Responses

Status	Description	Schema
200	Successful Response	application/json: Auth.TokenResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad Request - missing client credentials	application/json: Error.Response
401	Unauthorized - authentication failed	application/json: Error.Response

1.2 ca

1.2.1 GET /ca/activities

Get activities for the currently authenticated competent authority

Get activities for the currently authenticated competent authority. By default, returns all current activities (unlimited), including current records whose lifecycle status is cancelled. Use optional pagination parameters to limit results.

Each activity contains:

activityId	Functional ID identifying this activity
activityName	Display name (optional) of the activity
status	Lifecycle status of the activity: finished or cancelled
areaId	Functional ID referencing the area where the activity took place
competentAuthorityId	Functional ID referencing the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
url	URL of the originating listing/advertisement
address	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	Registration number of the address
numberOfGuests	Number of guests (1-1024)
countryOfGuests	Array of country codes of guests (each element is ISO 3166-1 alpha-3 or N/A; array length equals numberOfGuests)
temporal	Temporal composite (startDatetime, endDatetime)
platformId	Functional ID referencing the platform that owns the activity
platformName	Display name (optional) of the platform
createdAt	Timestamp when this activity version was created (UTC)

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
offset	query	integer	no	Number of records to skip (default: 0)
limit	query	integer null	no	Maximum number of records to return (default: unlimited, max: 1000 when specified)

Responses

Status	Description	Schema
200	Successful Response	application/json: Activity.ListResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad request - invalid query parameters	application/json: Error.Response
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.2.2 GET /ca/activities/count

Get activities count for the currently authenticated competent authority (optional, to support pagination)

Get activities count for the currently authenticated competent authority (optional, to support pagination). Counts all current activity records, including those whose lifecycle status is cancelled.

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Activity.CountResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.2.3 POST /ca/areas

Submit a single area into the areas collection for the currently authenticated competent authority

Submit a single area into the areas collection for the currently authenticated competent authority.

ID Pattern:

- areaId: provided by competent authority as business identifier (optional), otherwise generated as UUID (RFC 9562)

Versioning:

- Same areaId can be resubmitted → creates new version with different timestamp
- Unique constraint: (areaId, createdAt, current authenticated competent authority)

Limiting:

- Max. 1 MiB (1,048,576 bytes) per file
- This is to ensure predictable performance, reduce abuse risk, and improve overall reliability

The request contains (multipart/form-data):

areaId	Functional ID identifying this area (auto-generated UUID if not provided; alphanumeric with hyphens ^[A-Za-z0-9-]+\$, max 64 chars)
areaName	Display name (optional, max 64 chars)
regulation	Regulation type of the area - 'listing', 'activity', or 'all' (optional, defaults to 'all' when not supplied)
file	Shapefile upload (max 1 MiB)

The response contains:

areaId	Functional ID identifying this area
areaName	Display name (optional) of the area
regulation	Regulation type of the area - 'listing', 'activity', or 'all'
filename	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	Functional ID of the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
createdAt	Timestamp when this area version was created (UTC)

Security: OAuth2ClientCredentials

Request Body

Media Type	Schema	Required
multipart/form-data	Area.Request	yes

Responses

Status	Description	Schema
201	Area created successfully	application/json: Area.Response
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
422	Validation Error - business rule violation	application/json: Error.Response

1.2.4 GET /ca/areas

Get areas for the currently authenticated competent authority

Get all areas owned by the currently authenticated competent authority. By default, returns all areas (unlimited). Use optional pagination parameters to limit results.

Scoping:

- Only returns areas belonging to the currently authenticated competent authority (based on JWT client_id)

Each area contains:

areaId	Functional ID identifying this area
areaName	Display name (optional) of the area
regulation	Regulation type: 'listing', 'activity', or 'all'
filename	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	Functional ID of the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
createdAt	Timestamp when this area version was created (UTC)

Pagination:

offset	Number of records to skip (default: 0)
limit	Maximum number of records to return (default: unlimited)

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
offset	query	integer	no	Number of records to skip (default: 0)
limit	query	integer null	no	Maximum number of records to return (default: unlimited, max: 1000 when specified)

Responses

Status	Description	Schema
200	List of areas owned by the authenticated competent authority	application/json: Area.ListResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad request - invalid query parameters	application/json: Error.Response
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.2.5 GET /ca/areas/count

Get areas count for the currently authenticated competent authority (optional, to support pagination)

Get areas count for the currently authenticated competent authority (optional, to support pagination).

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Area.CountResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.2.6 GET /ca/areas/{areaid}

Get area (shapefile) for the currently authenticated competent authority

Get area (shapefile) based on functional ID, scoped to the currently authenticated competent authority.

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
areaid	path	string	yes	

Responses

Status	Description	Schema
200	Successful Response	application/zip:
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
404	Resource Not Found - area unavailable, deleted, or not owned by this CA	

1.2.7 DELETE /ca/areas/{areald}

Delete (deactivate) an area from the areas collection for the currently authenticated competent authority

Delete (deactivate) an area by marking it as ended (now, UTC).

Behavior:

- Deletes (deactivates) the area
- The area will no longer appear in area listings
- Deleting an already-deleted area returns 404

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
areald	path	string	yes	

Responses

Status	Description	Schema
204	Success - area deleted (deactivate)	
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
404	Resource Not Found - area unavailable, already deleted, or not owned by this CA	
422	Validation Error - business rule violation	application/json: Error.Response

1.3 health

1.3.1 GET /ping

Ping application (authenticated)

Verify if API is reachable (requires authentication).

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Health.Status
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response

1.4 str

1.4.1 POST /str/activities/bulk

Submit activities in bulk for the currently authenticated platform

Submit 1-1000 activities into the activities collection for the currently authenticated platform.

ID pattern:

activityId is provided by the platform as a business identifier (optional).
If not provided (or empty string), a UUID is auto-generated (RFC 9562).

Versioning:

The same activityId can be resubmitted - this creates a new version with a different timestamp.
Unique constraint: (activityId, createdAt, current authenticated platform).

Validation flow (4 steps):

1. **Syntax and semantical validation** - each item is validated individually. Failed items are marked NOK with the error reason; valid items continue.
2. **Referential Integrity Check** - area IDs are verified. Items with unknown areaId are marked NOK; valid items continue.
3. **Bulk Insert** - all remaining valid items are inserted in a single multi-row INSERT.
4. **Feedback** - per-item OK/NOK response preserving original order.

Intra-batch duplicates (last-wins):

When the same activityId appears multiple times in a single batch, only the last occurrence is processed. Earlier occurrences receive NOK.

The request contains:

- activities: Array of activity objects to process (1-1000 items per batch)

Each activity item in the request contains:

activityId	Functional ID identifying the activity (auto-generated UUID if not provided; alphanumeric with hyphens <code>^[A-Za-z0-9-]+\$</code> , max 64 chars)
activityName	Display name of the activity (optional, max 64 chars)
status	Lifecycle status of the activity. Defaults to <code>finished</code> when omitted; may also be <code>cancelled</code>
areaId	Functional ID referencing the area where the activity took place
url	URL of the originating listing/advertisement (max 128 chars)
address	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	Registration number of the address (max 32 chars)
numberOfGuests	Number of guests (1-1024)
countryOfGuests	Array of country codes of guests (1-1024; each element is ISO 3166-1 alpha-3 or N/A, uppercase only); array length must equal numberOfGuests.
temporal	Temporal composite (startDatetime, endDatetime)

The response contains:

totalReceived	Total number of items received in the request
succeeded	Number of items successfully created (status OK)
failed	Number of items that failed validation or processing (status NOK)
results	Per-item results preserving the original request order

Each results item contains:

activityIndex	Zero-based index of this item in the original request list
activityId	Activity functional ID provided by the client in the request
status	Processing result - OK (created successfully) or NOK (failed validation or processing)
activity	The full activity object (present for OK items, omitted for NOK items)
errors	Structured error details (present for NOK items, omitted for OK items)

The activity object (for the OK items) contains:

activityId	Functional ID identifying this activity
activityName	Display name (optional) of the activity
status	Lifecycle status of the activity: finished or cancelled
areaId	Functional ID referencing the area where this activity took place
competentAuthorityId	Functional ID of the competent authority that owns the referenced area
competentAuthorityName	Display name (optional) of the competent authority
url	URL of the originating listing/advertisement
address	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	Registration number of the address (max 32 chars)
numberOfGuests	Number of guests (1-1024)
countryOfGuests	Array of country codes of guests (each element is ISO 3166-1 alpha-3 or N/A); array length equals numberOfGuests.
temporal	Temporal composite (startDatetime, endDatetime)
platformId	Functional ID referencing the platform that owns the activity
platformName	Display name (optional) of the platform
createdAt	Timestamp when this activity version was created (UTC)

Response HTTP status:

- 201: all items created successfully
- 200: partial success (some OK, some NOK)
- 401: missing or invalid token
- 403: insufficient permissions
- 422: all items failed

Security: OAuth2ClientCredentials

Request Body

Media Type	Schema	Required
application/json	Activity.BulkRequest	yes

Responses

Status	Description	Schema
201	All activities created successfully	application/json: Activity.BulkResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
200	Partial success - some activities created, some failed	application/json: Activity.BulkResponse
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
422	All activities failed validation	application/json: Activity.BulkResponse

1.4.2 GET /str/areas

Get all areas

Get all areas. By default, returns all areas (unlimited). Use optional pagination parameters to limit results.

Each area contains:

areaId	Functional ID identifying this area
areaName	Display name (optional) of the area
regulation	Regulation type of the area - 'listing', 'activity', or 'all'
filename	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	Functional ID referencing the competent authority that owns the area
competentAuthorityName	Display name (optional) of the competent authority
createdAt	Timestamp when this area version was created (UTC)

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
offset	query	integer	no	Number of records to skip (default: 0)
limit	query	integer null	no	Maximum number of records to return (default: unlimited, max: 1000 when specified)

Responses

Status	Description	Schema
200	List of areas	application/json: Area.ListResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
400	Bad request - invalid query parameters	application/json: Error.Response
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.4.3 GET /str/areas/count

Get areas count (optional, to support pagination)

Get areas count (optional, to support pagination).

Security: OAuth2ClientCredentials

Responses

Status	Description	Schema
200	Successful Response	application/json: Area.CountResponse
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	

1.4.4 GET /str/areas/{areald}

Get area (shapefile)

Get area (shapefile) based on functional ID.

Security: OAuth2ClientCredentials

Parameters

Name	In	Type	Required	Description
areald	path	string	yes	

Responses

Status	Description	Schema
200	Successful Response	application/zip:
500	Internal Server Error - an unexpected issue occurred that prevented the request from being completed	
503	Service Unavailable - temporarily unable to process requests due to overload, maintenance, or dependency issues (database/authorization server)	
401	Unauthorized - missing or invalid token	application/json: Error.Response
403	Forbidden - insufficient permissions	
404	Resource Not Found - area unavailable	

2. Schemas

2.1 Activity.BulkRequest

Bulk activity request schema.

The `activities` field is typed as `list[ActivityRequest]` for the OpenAPI contract, but item-level validation is skipped at request-parse time (via `SkipValidation`). This preserves the Application-First Validation flow: each item is validated individually in the service layer, so one invalid item is marked NOK without failing the whole batch.

Property	Type	Required	Description
activities	array[Activity.Request]	yes	Array of activity objects to process (1-1000 items per batch)

2.2 Activity.BulkResponse

Bulk activity response schema.

Returns per-item OK/NOK feedback with summary counts.
Validation flow Step 4: the original list enriched with status and error message.

Property	Type	Required	Description
totalReceived	integer	yes	Total number of items received in the request
succeeded	integer	yes	Number of items successfully created (status OK)
failed	integer	yes	Number of items that failed validation or processing (status NOK)
results	array[Activity.BulkResultItem]	yes	Per-item results preserving the original request order

2.3 Activity.BulkResultItem

Result for a single item in a bulk activity response.

Property	Type	Required	Description
activityIndex	integer	yes	Zero-based index of this item in the original request list
activityId	string null	no	Activity functional ID provided by the client in the request
status	enum[OK, NOK]	yes	Processing result - OK (created successfully) or NOK (failed validation or processing)
activity	Activity.Response null	no	The full activity object (present for OK items, omitted for NOK items)
errors	Error.Response null	no	Structured error details (present for NOK items, omitted for OK items)

2.4 Activity.CountResponse

Count of activities response schema.

Property	Type	Required	Description
count	integer	yes	Total number of activity records

2.5 Activity.ListResponse

List of activities for GET responses.

Property	Type	Required	Description
activities	array[Activity.Response]	yes	List of activities

2.6 Activity.Request

Activity request schema for creating rental activities.

Platform:

- NOT in request payload (extracted from JWT token at API layer)
- PlatformId comes from token's client_id claim
- PlatformName comes from token's client_name claim
- Will be auto-created if it doesn't exist yet

Activity ID:

- Optional: If not provided, will be auto-generated (RFC 9562 UUID)

Activity Name:

- Optional: Display name (max 64 chars)

Validation Layer:

- Validates all syntax constraints (lengths, ranges, types)

Constraints (enforced at database level):

- Unique constraint: (activityId, createdAt, platform) for versioning support

Property	Type	Required	Description
activityId	string null	no	Functional ID identifying the activity (auto-generated UUID if not provided; alphanumeric with hyphens [^] [A-Za-z0-9-]+\$, max 64 chars)
activityName	string null	no	Display name of the activity (optional, max 64 chars)
status	Activity.Status	no	Lifecycle status of the activity. Defaults to finished when omitted; may also be cancelled.
areald	string	yes	Functional ID referencing the area where the activity took place
url	string	yes	URL of the originating listing/advertisement (max 128 chars)
address	Common.AddressRequest	yes	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	string	yes	Registration number of the address (max 32 chars)
numberOfGuests	integer	yes	Number of guests (1-1024)
countryOfGuests	array[string]	yes	Array of country codes of guests (1-1024; each element is ISO 3166-1 alpha-3 or 'N/A', uppercase only). Length must equal numberOfGuests.
temporal	Common.TemporalRequest	yes	Temporal composite (startDatetime, endDatetime)

2.7 Activity.Response

Activity response schema.

Property	Type	Required	Description
activityId	string	yes	Functional ID identifying this activity
activityName	string null	no	Display name (optional) of the activity
status	Activity.Status	yes	Lifecycle status of the activity: finished or cancelled.
areaId	string	yes	Functional ID referencing the area where this activity took place
competentAuthorityId	string	yes	Functional ID referencing the competent authority that owns the area
competentAuthorityName	string null	no	Display name (optional) of the competent authority
url	string	yes	URL of the originating listing/advertisement
address	Common.AddressResponse	yes	Address composite (thoroughfare, locatorDesignatorNumber (optional), locatorDesignatorLetter (optional), locatorDesignatorAddition (optional), postCode, postName, fullAddress)
registrationNumber	string	yes	Registration number of the address
numberOfGuests	integer	yes	Number of guests (1-1024)
countryOfGuests	array[string]	yes	Array of country codes of guests (each element is ISO 3166-1 alpha-3 or 'N/A'); array length equals numberOfGuests.
temporal	Common.TemporalResponse	yes	Temporal composite (startDatetime, endDatetime)
platformId	string	yes	Functional ID referencing the platform that owns the activity
platformName	string null	no	Display name (optional) of the platform
createdAt	string(date-time)	yes	Timestamp when this activity version was created (UTC)

2.8 Activity.Status

Lifecycle status for an activity record.

Type: string

Allowed values: finished, cancelled

2.9 Area.CountResponse

Count of areas response schema.

Property	Type	Required	Description
count	integer	yes	Total number of areas in context of the current SDEP/member state

2.10 Area.ListResponse

List of areas response schema.

Property	Type	Required	Description
areas	array[Area.Response]	yes	List of areas in context of the current SDEP/member state

2.11 Area.Request

Property	Type	Required	Description
areald	string null	no	
areaName	string null	no	
regulation	Common.Regulation null	no	
file	string(binary)	yes	

2.12 Area.Response

Area response schema.

Property	Type	Required	Description
areald	string	yes	Functional ID identifying this area
areaName	string null	no	Display name (optional) of the area
regulation	Common.Regulation	no	Regulation type of the area - 'listing', 'activity', or 'all'
filename	string	yes	Name of the area shapefile (e.g., 'area.zip')
competentAuthorityId	string	yes	Functional ID of the competent authority that owns the area
competentAuthorityName	string null	no	Display name (optional) of the competent authority
createdAt	string(date-time)	yes	Timestamp when this area version was created (UTC)

2.13 Auth.TokenRequest

Property	Type	Required	Description
client_id	string null	no	Client ID for M2M authentication
client_secret	string null	no	Client secret for M2M authentication
grant_type	string null	no	OAuth2 grant type (client_credentials)

2.14 Auth.TokenResponse

OAuth2 token response model

Property	Type	Required	Description
access_token	string	yes	OAuth2 bearer access token to be used in the Authorization header of subsequent API requests
token_type	string	yes	Type of token issued (typically 'Bearer')
expires_in	integer	yes	Lifetime of the access token in seconds

2.15 Common.AddressRequest

Address composite schema for activity requests (INSPIRE/STR-AP field names).

Validation Layer:

- All syntax validation (lengths, types, constraints) happens here
- Service layer receives validated data

Property	Type	Required	Description
thoroughfare	string	yes	Street / public space name
locatorDesignatorNumber	integer null	no	Numeric house number component (optional, >= 0 when provided)
locatorDesignatorLetter	string null	no	Letter/character suffix (optional, e.g. 'a', 'bis', 'ter')
locatorDesignatorAddition	string null	no	Additional qualifier (optional, e.g. 'II', 'Apt 3')
postCode	string	yes	Postal code (no spaces, alphanumeric)
postName	string	yes	City / town / village
fullAddress	string	yes	Full address as a single string (required, max 318 chars)

2.16 Common.AddressResponse

Address composite schema for activity responses (INSPIRE/STR-AP field names).

Property	Type	Required	Description
thoroughfare	string	yes	Street / public space name
locatorDesignatorNumber	integer null	no	Numeric house number component (optional)
locatorDesignatorLetter	string null	no	Letter/character suffix (optional)
locatorDesignatorAddition	string null	no	Additional qualifier (optional)
postCode	string	yes	Postal code
postName	string	yes	City / town / village
fullAddress	string	yes	Full address as a single string

2.17 Common.Regulation

Regulation type for an area: 'listing', 'activity', or 'all' (covers both).

Type: string

Allowed values: listing, activity, all

2.18 Common.TemporalRequest

Temporal composite schema for activity requests.

Validation Layer:

- Validates datetime formats
- Date-only submissions are permitted, and will be stored internally using a 00:00:00 timestamp
- Ensures start year is >= 2025
- Ensures start is before end

Property	Type	Required	Description
startDatetime	string(date-time)	yes	Start date and time of the rental activity (year must be >= 2025)
endDatetime	string(date-time)	yes	End date and time of the rental activity (must be after startDatetime)

2.19 Common.TemporalResponse

Temporal composite schema for activity responses.

Property	Type	Required	Description
startDatetime	string(date-time)	yes	Start date and time of the rental activity
endDatetime	string(date-time)	yes	End date and time of the rental activity

2.20 Error.Detail

Detail of a single error.

Property	Type	Required	Description
msg	string	yes	Human-readable error message
type	string	yes	Error type identifier
loc	array[string integer] null	no	Location of the error (e.g. ['body', 'fieldName'])

2.21 Error.Response

Standardized error response format.

Property	Type	Required	Description
detail	array[Error.Detail]	yes	List of error details

2.22 Health.Status

Status response schema

Property	Type	Required	Description
status	string null	no	Status message