




TYPICAL DUCT BANK SECTION FOR 1 POWER & 1 FIBER CONDUITS ref: E201 scale: NONE




TYPICAL DUCT BANK SECTION FOR 3 & 4 POWER AND FIBER CONDUITS ref: E201 scale: NONE




DUCT BANK SECTION
PBP-01 & PBF-01 TO PBP-02 & PBF-02
ref: E201 scale: NONE





TYPICAL DUCT BANK SECTION FOR 5 & 6 POWER AND FIBER CONDUITS ref. E201 scale: NONE



DUCT BANK SECTION MH-01 TO PBP-01 & PBF-01 ref: E201 scale: NONE

GENERAL NOTES

- UG CONDUIT SHALL BE SUPPORTED EVERY 10 FEET WITH CARLON SNAP-LOC SPACERS OR APPROVED EQUAL. CONTRACTOR SHALL SIZE SPACERS PER CONDUIT CALL OUT IN CABLE SCHEDULE.
- INTERDUCT FOR FIBEROPTIC CABLE SHALL BE CARLON PLENUM-GARD #CG4X1C OR APPROVED EQUAL.
- 3. SAND AND BACKFILL SHALL BE PLACED AND COMPACTED TO 98% STANDARD PROCTOR.

