

PCB, 5 x 20 or 6.3 x 32 mm, IP 40



250 VAC · 3.2 W / 10 A (VDE) · 16 A (UL/CSA)

**Description**

- Kicked or straight PCB-terminals
- Vertical style

Standards

- IEC 60127-6
- UL 512
- CSA C22.2 no. 39

Approvals

- VDE License Number: 6945 UG
- UL File Number: E39328

References

General Product Information


WeblinksApprovals: <http://www.schurter.com/approvals>RoHS: <http://www.schurter.com/rohs>**Technical Data**

Shocksafe Category	PC2
Fuse-Link	5 x 20 or 6.3 x 32 mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	250 VAC
Rated Current	10 A (VDE) , 16 A (UL/CSA)
Rated Power Acceptance IEC	3.2 W / 10 A @ Ta 23 °C 2.5 W / 10 A for 5x20 mm fuse-link, see derating curves
Degree of Protection	IP 40
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoplastic, black, UL 94V-0
Material: Terminals	Tin-Plated Copper Alloy
Unit Weight (Socket/Cap)	6.5 g / 2.3 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	Type, Voltage Rating, Current Rating, Approvals

Soldering Methods	Wave
Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A
Contact Resistance	< 5 mΩ at 20 mV
Dielectric Strength	> 3 kV between L-N (50 Hz; 1 min)
Impulse Withstand Voltage	> 4 kV between L-N
Insulation Resistance	> 10 MΩ between L-N (500 VDC; 1 min)
Overvoltage Category	I - III acc. to IEC 60664-1
Pollution Degree	1 - 3 acc. to IEC 60664-1

Dimensions


Length | 47.5 mm



Variant 0031.3803 and 0031.3804

Drilling diagram

Derating Curves



Variants

Order Number	Holder	Cap	Fuse-Link	Terminal	Degree of Protection	Colour Cap
0031.3803	●		5 x 20 or 6.3 x 32mm	Straight	IP 40	
0031.3804	●		5 x 20 or 6.3 x 32mm	Kicked	IP 40	
0031.1661		Slot Knob	6.3 x 32mm		IP 40	
0031.1663		Slot Knob	5 x 20mm		IP 40	
0031.1666		Slot Knob	6.3 x 32mm		IP 40	Grey

Packaging Unit Bulk (100 pcs.)