# Four papers: the essential map

**A concise but detailed reading brief for Narrative Benchmarking (P6). Read it to understand the questions, evidence and limitations well enough to discuss the literature and justify a project.**

## The four central messages

- PolyNarrative: narrative detection can be operationalized as assigning multiple predefined categories to news paragraphs. Fine distinctions and human disagreement make the task difficult.
- From Repetition to Recognition: matching existing categories and discovering candidates beyond them are different evaluation problems. A good aggregate score can conceal lost topic coverage.
- Fighting Fire with Fire (F3): the same family of language models can generate and detect misleading text, but detection changes with data origin, subtlety and distribution.
- NarraBench: narrative understanding has many dimensions. A benchmark tests selected abilities rather than a universal capacity to understand narratives.

## How to read this document

| Pages | Purpose |
|---|---|
| 2 | Vocabulary and task boundaries |
| 3-4 | PolyNarrative: task, experiments, limitations |
| 5-6 | Repetition to Recognition: discovery and coverage |
| 7-8 | F3: data construction and transfer |
| 9-10 | NarraBench: theory and benchmark design |
| 11-13 | Comparison, metrics and discussion practice |
| 14 | References and targeted original reading |

> Keep three levels separate: AUTHORS' FINDINGS are what a study reports. EXPLANATION clarifies a concept. DISCUSSION / PROJECT IMPLICATIONS are reasoned interpretations, not additional experimental results.

Scope: only the four P6 starting papers. DiNaM, HELM and other previously found sources are not reviewed as additional papers here. Models and numerical results are described as historical experiments in the specified papers, not as current API recommendations.

Both language editions cover the same material. English technical terms are retained in the Russian edition. The brief is a study aid, not the original papers or a completed graded literature review. All numerical findings remain tied to their own datasets and evaluation settings.

# Vocabulary before methods

## Topic, claim and narrative

A topic names a subject. A claim makes a particular assertion. A narrative, in the news-analysis sense used by PolyNarrative, is a recurring explicit or implicit claim promoting an interpretation of an ongoing issue. NarraBench uses a broader narratological framework, so the definitions are not identical.

| Level | Fictional teaching example |
|---|---|
| Topic | Climate policy |
| Claim | This proposed levy would increase household bills. |
| Narrative | Climate policy burdens ordinary people. |

These are author-created teaching examples, not quoted findings or real news. Different articles can express the same interpretation with different vocabulary. A single paragraph can convey several narratives, and some paragraphs match none of a selected taxonomy.

## What the system is asked to do

- Classification: select IDs from an existing taxonomy. The label inventory is known in advance.
- Induction / label generation: formulate narrative labels from a corpus rather than merely assign existing IDs.
- Discovery: identify potentially valid candidates outside available taxonomies. It requires evaluation beyond exact agreement with known labels.
- Truth / disinformation detection: judge whether content is credible or misleading. This is different from identifying which interpretation it expresses.

## Terms used repeatedly

Taxonomy is a structured category inventory; a codebook adds definitions and annotation rules. Multilabel permits several categories per item. Coarse/fine distinguish broad categories from subcategories. Gold labels are a reference annotation, not infallible truth. An embedding is a numerical text representation; clustering groups similar representations.

> Presence is not endorsement or falsity. A text may present, quote or reject an interpretation. The operational rule must be explicit. PolyNarrative specifically warns against treating every matching claim as misinformation.

Zero-shot uses instructions without task examples; few-shot adds examples in the prompt. Fine-tuning changes model parameters using training data. A longer prompt is not equivalent to fine-tuning. A baseline is a simpler comparison system, not automatically a weak one.

# PolyNarrative: task and design

**[1] Nikolaidis et al., ACL 2025. The contribution is a dataset, operationalized taxonomy and strong baseline experiments for granular news-narrative detection.**

## Problem and output

Whole-article labels hide where a narrative is expressed and can force an oversimplified single-label view. The study treats detection as hierarchical multilabel classification at paragraph level. Article-level gold is the union of its paragraphs' labels. "Extraction" here mainly means locating/assigning known narrative categories, not unrestricted discovery.

## Data and category inventory

- Two domains: Climate Change (CC) and the Ukraine-Russia War (URW). Four languages: Bulgarian, English, Portuguese and Russian. Coverage is not identical across every language/domain combination; Table 3 has no Russian CC agreement value.
- Section 3.2 specifies 10 broad / 36 fine categories for CC and 11 broad / 38 fine categories for URW. Appendix A defines categories. Other conventions need separate inspection.
- Article collection combines topical retrieval, model-based relevance/persuasiveness ranking and human selection. The corpus therefore targets relevant discourse rather than constituting a random media sample.
- Two annotators label an article, with curation and guideline refinement. Categories may be explicit or implicit. Similar labels are clarified through examples and repeated discussion.

## Systems and comparisons

XLM-RoBERTa-large is fine-tuned for coarse or fine labels. Llama 3.1-70B is prompted with label names, full guidelines, both, or a two-stage coarse-to-fine procedure. A stratified random baseline supplies a reference. The experiments vary paragraph/document units and broad/detailed labels, so results must retain all these qualifiers.

> EXPLANATION: hierarchy and multilabel solve different issues. Hierarchy relates broad and narrow categories; multilabel permits several simultaneous interpretations. Neither automatically resolves ambiguous boundaries.

Take into discussion: "This paper makes narrative detection measurable by specifying annotation units, category definitions and reference labels. Those choices are part of the task, not neutral background details."

# PolyNarrative: findings and interpretation

## Selected evidence from Table 4

The following CC document-level results are examples, averaged over languages in that evaluation. They illustrate different strengths; they are not a universal model ranking. “Guidelines + labels” denotes the corresponding Llama variant.

| Configuration | Coarse Macro-F1 | Fine Macro-F1 | Fine sample-F1 |
|---|---|---|---|
| XLM-R fine | 0.457 | 0.198 | 0.347 |
| Llama guidelines + labels | 0.573 | 0.168 | 0.199 |

- Prompted Llama is competitive for broad categories. Fine-tuned XLM-R generally performs better for detailed classification, particularly under sample-F1. Metric, domain and granularity can change the comparison.
- Full guidelines alone generally do worse than label names alone. Combining labels and guidelines helps relative to guidelines alone; hierarchical prompting is not consistently competitive. More instructions do not automatically produce a better task specification for a model.
- Paragraph-level scores and fine labels remain difficult. Other labels are challenging because they collect diverse cases. Language differences also interact with differing label distributions and source selection.

## Human annotation is part of the uncertainty

Table 3 reports Krippendorff alpha of 0.571 for coarse and 0.480 for fine labels across languages/domains. These are agreement coefficients, not “57.1% accuracy” or hard ceilings on model performance. Within-parent confusions account for much of the fine-label disagreement.

## Limitations and source checks

Taxonomies reflect participating analysts and overrepresent interests of Western institutions. Labels and sources are imbalanced, and the corpus is not representative of all national media. Table 1 prints totals of 1,465 articles / 13,487 paragraphs, while the Conclusion reports 1,476 / 13,625. Preserve the discrepancy and recount the actual release before replication.

> YOUR POSITION: “I would begin with explicit coarse labels and report per-label support and disagreement. I would test prompt variants rather than assume that a longer codebook or a larger model is better.” This is a proposed research choice, not the paper’s experimental conclusion.

# Repetition to Recognition: the framework

**[2] Upravitelev et al., arXiv:2609.11128v1 (2026), a preprint. The central problem is evaluating generated narrative labels when existing taxonomies are incomplete.**

## What changes relative to PolyNarrative?

Instead of merely assigning known labels to paragraphs, pipelines produce a set of narrative labels from a corpus. A useful output should express a general core message, called a superclaim, rather than just name a topic or repeat an isolated event. Evaluation then asks what those generated labels recover or add.

| Tier | Reference and question |
|---|---|
| Recovery | Corpus + its own taxonomy: can the known categories be recovered? |
| Mining | Same corpus + independent taxonomy: do labels align with external categories? |
| Discovery | No fixed reference set: are outputs valid candidates beyond available labels? |

These are independent evaluation settings, not three mandatory sequential steps. A pipeline can recover a source codebook well yet fail to generalize to another taxonomy. Exact comparison with known categories cannot reward genuinely uncovered candidates.

## Pipeline families

- No-LLM SVO baseline: dependency parsing extracts subject-verb-object triples; embeddings, dimensionality reduction and clustering yield representative labels.
- Claim clustering: an LLM extracts claims; embeddings represent them; UMAP reduces dimensionality; HDBSCAN finds dense groups and treats sparse points as noise. An LLM then formulates each group’s label.
- Graph communities: extract semantic units, entities and relations, build a graph, use Leiden community detection to find densely connected groups, and summarize their content.
- Persona variants: four analytical personas extract claims, followed by deduplication and clustering or community aggregation. The persona branches share the extraction stage.

> EXPLANATION: a cluster groups similar points; a graph community groups connected nodes. Different structures can preserve or discard different sparse evidence. Neither structure is automatically more truthful.

Closed-world evaluation uses seven disinformation corpora; human discovery validation focuses on Climate Obstruction and PolyNarrative. Final generated labels are English even when source documents are multilingual.

# Repetition to Recognition: what the results mean

## The metric-dependent comparison

In the recovery comparison, clustering wins on WCD in 13 of 14 comparisons, graph aggregation wins on Hungarian similarity in 12 of 14, and graph methods match or improve Collapse in all 14. These measures reward different properties; this is not a single universal winner.

## A failure hidden by aggregate evaluation

In Table 5, the PolyNarrative claim-cluster pipeline with HDBSCAN settings (25, 20) produces 141 labels, of which only 2.1% are climate-related. At (15, 10), it produces 332 labels with 33.7% climate coverage. Graph Pcom at default Leiden resolution produces 824 labels and 28.8% climate coverage. These are shares of generated labels, not classification accuracy or true corpus prevalence.

The mechanism is thresholding: small minority-topic groups can be treated as noise and disappear before summarization. Lower thresholds restore some coverage but increase output volume and human-review effort. The reported graph resilience is conditional on the tested algorithms and corpora.

## Singletons and human validation

Singleton candidates rely on one extracted claim in the corpus. They comprise 30-62% of graph outputs across the main configurations. Some are accepted as recognizable narrative candidates even though repetition is not observed in that corpus. Prior knowledge may support recognition, but this is an interpretation, not a demonstrated cognitive mechanism.

- Two annotators, both co-authors, conduct a pilot on two corpora. Accepted candidates are not established gold labels or automatic taxonomy additions.
- Other means in-domain but unmatched among retrieved candidates; None means outside the corpus topics. Other-rate is only an upper bound on novelty because retrieval may miss an existing matching label.
- Tested LLM judges agree more with each other than with humans and cannot replace human discovery validation in this setup. Withheld support counts also limit what acceptance establishes.

> YOUR POSITION: “I would report category coverage, label count and human validation burden alongside semantic scores. A system that outputs many labels or a plausible singleton has not necessarily discovered a new narrative.”

# F3: the question and experiment

**[3] Lucas et al., EMNLP 2023. This study addresses disinformation generation and detection rather than fixed-taxonomy narrative extraction.**

## The two research questions

- RQ1: can prompting induce a model to create misleading variants of news, and how can researchers check whether the intended true/false category is actually preserved?
- RQ2: how well do zero-shot LLMs detect human-written and synthetic disinformation compared with trained detectors across different conditions?

## Data design

Human-written source material comes from CoAID, FakeNewsNet and newly collected F3 examples, including articles and social posts. Paraphrases are intended to preserve factual content; perturbations alter it, with minor, major and critical severity. The important methodological point is control of the intended label, not merely the ability to generate fluent text.

## PURIFY: checking the generated dataset

A generated “real” variant can accidentally introduce an error, while an intended “fake” variant may remain consistent with the source. PURIFY combines logical/factual alignment checks with contextual and semantic checks. These include natural-language inference, AlignScore, BERTScore and semantic-distance measures.

In plain language: natural-language inference tests entailment or contradiction; AlignScore checks consistency with a source; BERTScore compares contextual word representations; semantic distance measures proximity. None alone establishes external-world truth.

The paper describes an initial 43,272 synthetic outputs and 27,667 retained examples after filtering. Filtering establishes the authors’ operational dataset; it does not turn every retained item into independently verified real-world truth. Semantic similarity alone cannot determine factual validity.

## Detection and split design

The detector comparison includes GPT-3.5, LLaMA-2 variants, Dolly, domain-specific neural detectors and fine-tuned transformers. Prompted detection uses cloze-style true/false decisions with different reasoning-oriented instructions. The older-data portion uses a 70/20/10 train/validation/test split; later data form an out-of-distribution evaluation under the paper’s temporal design.

> EXPLANATION: in-distribution means similar to the development/training setting; out-of-distribution means a changed setting. Here temporal change, source/content differences and synthetic generation can interact. A date-based split alone does not reveal every model’s actual training exposure.

# F3: findings without overclaiming

## The key comparison in Table 5

These are averages of reported Macro-F1 across the table's eight article/post and human/synthetic conditions. They are not one universal accuracy score, and category-specific behavior varies.

| System / group | In-distribution | Out-of-distribution |
|---|---|---|
| GPT-3.5 | 0.7178 | 0.6825 |
| Fine-tuned transformers | 0.9283 | 0.8039 |
| Customized neural models | 0.6563 | 0.4679 |

- Fine-tuned transformers have the strongest aggregate absolute scores in this comparison, including the out-of-distribution mean. They nevertheless lose more performance than GPT-3.5 between the two settings.
- Among generative models, GPT-3.5 performs strongly in the tested setup. Detection of subtle alterations is difficult. Human versus model authorship and article versus post length also affect performance.
- The study reports useful self-detection behavior, but a generator evaluating its own style is not an independent guarantee of factual reliability.

## What the study supports

A detector should be evaluated across meaningful shifts rather than one familiar test set. Synthetic labels require quality checks. Robustness, absolute score and cost are separate properties. Model rankings depend on the evaluation slices and metric.

## Limitations and a careful reading

The experiment concerns models and prompts from the 2023 study, not current service capability. Synthetic generation and automatic filtering can create artifacts. The same LLM ecosystem participates in data construction and detection, limiting independence. Refusals and prompt-dependent behavior also affect the tested sample.

The abstract uses accuracy language for a broad 68-72% summary, whereas the main detection evaluation specifies Macro-F1. Use Table 5's metric when citing its numbers. The paper's discussion mentions few-shot promise, but Limitations explicitly says few-shot capabilities remain unevaluated.

> YOUR POSITION: "I distinguish robustness from winning. A smaller drop on new data does not mean a higher final score. I would retain an independent new-data test and show human-written and synthetic conditions separately."

# NarraBench: what “understanding” includes

**[4] Hamilton, Wilkens and Piper, EACL 2026. This is a theoretical evaluation framework, benchmark survey and testing harness, rather than another news-narrative classifier.**

## The motivation

Existing tests often emphasize easily scored story facts and assume a single correct answer. Narrative interpretation also involves perspective, form and context. The authors organize these abilities so that benchmark selection follows a theory of the target construct.

| Dimension | Meaning and example question |
|---|---|
| Story | Content: agents, relationships, events, plot and setting. Who acted, and what changed? |
| Narration | Perspective and style. Who speaks or perceives, and how is language used? |
| Discourse | Organization of telling. In what order and duration are events presented? |
| Situatedness | Communication context. Who tells the story, through which medium, and for what purpose? |

The four dimensions contain 12 primary features and 50 task/aspect combinations. This structure includes both storyworld information and the conditions under which a story is told. It is broader than news-taxonomy assignment.

## Three evaluation criteria

- Scale: local passages versus global synthesis, with meso-level reasoning for sequences. A local fact-retrieval test does not necessarily assess a whole narrative.
- Mode: discrete answers, progressive sequences or holistic natural-language judgments. Answer form affects what automatic scoring is appropriate.
- Variance: deterministic answers, consensus tendencies or perspectival distributions. Some interpretations legitimately admit more than one supported answer.

> EXPLANATION: “Who is named?” can have a fixed answer. “What motivates this character?” may permit several text-grounded interpretations. A deterministic answer key can wrongly treat legitimate interpretive variation as model error.

Take into discussion: “Before choosing a score, I would specify the narrative ability, textual scale and acceptable variation. A benchmark measures an operationalized construct, not understanding in the abstract.”

# NarraBench: evidence and boundaries

## Survey findings

- The survey identifies 78 candidate benchmarks. Only 39 have accessible data/repositories under the authors' selection process. Table 2 retains 34 with alignment ratings of poor or better, excluding five rated bad.
- Existing benchmarks favor story-level content and classification. Style, perspective, revelation and other dimensions are less well served. Four of the 39 shortlisted benchmarks are multilingual.
- The authors estimate approximately 27% coverage of their taxonomy. This expresses fit to the framework, not "LLMs understand 27% of narratives" or coverage of every possible narrative skill.

## What the harness adds

The implementation assembles suitable existing tests and demonstrates nonuniform model behavior across narrative aspects. A strong result on one task does not reliably summarize the others. The study is therefore both a map of missing evaluations and a proposal for organizing expandable benchmark suites.

## Limitations acknowledged by the authors

- Theory: the framework privileges a classical narratological lineage. Other cognitive, rhetorical and postclassical approaches can emphasize different properties.
- Coverage: accessible resources skew toward English, Western-centric and textual material. Dataset availability influences what enters the survey.
- Measurement: separating features into modular tasks can understate their interaction in actual interpretation. The importance and weighting of dimensions remain conceptual rather than empirically established.
- Scoring: perspectival evaluation, generative scoring and LLM judges remain difficult. Recognizing subjectivity does not mean every answer is acceptable; interpretations still require support.

> YOUR POSITION: "Our news benchmark targets selected category-recognition abilities. I would report those abilities explicitly, while avoiding a claim that a high F1 proves general narrative understanding."

Critical distinction: NarraBench does not supply a directly interchangeable replacement for PolyNarrative's news labels. Its main value for P6 is construct validity: checking whether the claimed ability matches the task and evaluation method.

# Compare the papers, not their score columns

## A compact comparison

| Paper | Input and output | What counts as success |
|---|---|---|
| PolyNarrative | News paragraphs/articles to fixed category sets | Match human labels at a stated level and unit |
| Repetition to Recognition | A corpus to generated narrative labels | Recover/match taxonomies or validate candidates |
| F3 | Human/synthetic news to veracity decisions | Detect the intended category under data shifts |
| NarraBench | Narrative tasks to benchmark assessments | Match evaluation design to the claimed ability |

## Shared lessons

- Definitions are experimental choices. The same word narrative can refer to a recurring superclaim or to a richly structured act of telling.
- Reference labels are useful but incomplete or interpretive. Disagreement can reflect vague category boundaries, legitimate perspectives or inadequate instructions.
- Aggregation hides structure. Inspect category coverage, input type, language, granularity and transfer conditions rather than relying only on a mean.
- A convincing output is not automatically valid evidence. Matching wording, fluent explanations and human familiarity each establish different things.

## Claims the four papers do not justify

They do not establish that generative LLMs always beat trained classifiers, that a large model always benefits from longer instructions, that graphs universally dominate clustering, or that a narrative label proves a falsehood. They also do not validate every modern API model or a universal automatic discovery metric.

## A defensible connection to the project

A fixed-taxonomy benchmark with source evidence is closest to PolyNarrative. Corpus-level label generation is closer to [2] and needs a separate evaluation. F3 motivates new-data testing; NarraBench requires narrow ability claims. API price and latency measurements are a proposed project extension, not results established by these four studies.

> DISCUSSION: a coherent literature review argues why one task and evaluation are appropriate. It should not combine four different scores into a single leaderboard or simply retell four abstracts.

Source: [1]-[4]; synthesis and project implications are the brief's interpretation

# Metrics explained with one example

## Classification: precision, recall and F1

Teaching example: gold labels are {A, B}; the system predicts {A, C}. A is a true positive (TP), C a false positive (FP), and missed B a false negative (FN). Thus TP=1, FP=1, FN=1.

Precision = TP / (TP + FP) = 0.5
Recall = TP / (TP + FN) = 0.5
F1 = 2TP / (2TP + FP + FN) = 0.5
Exact match = 0 because the complete label sets differ.

- Macro-F1: compute each label's F1, then average with equal category weight. Rare labels matter, but low support and absent-label conventions can strongly affect the score.
- Micro-F1: pool TP/FP/FN before computing F1. Frequent labels contribute more. This is an explanatory comparison, not a claim that every reviewed study uses Micro-F1.
- Sample-F1: compute a label-set F1 per item and average. Different treatment of empty/empty sets changes the result; conventions must be disclosed.

## Generated-label matching in [2]

Embeddings map reference and generated labels into a numerical space. Cosine similarity estimates semantic proximity; it does not establish logical equivalence, correct stance or factual truth. Hungarian similarity selects a best one-to-one matching. WCD averages nearest distances in both directions, with lower values better in [2]. Collapse counts reference categories whose nearest generated labels collide; the normalized rate enables some cross-taxonomy comparison.

## Human agreement and uncertainty

Krippendorff alpha and Cohen kappa adjust agreement for a chance model, but they are different coefficients applied to different annotation setups. Neither is simply annotator accuracy. In [2], the top-2 retrieval per taxonomy restricts the labels a human sees, so Other is not proof that no match exists anywhere.

Questions before trusting a score: What unit? Which labels? Which domain/language? Which averaging? What gold construction? What failed outputs? What uncertainty? These details determine whether two numbers can be compared.

Source: [1] §5.2; [2] §§3.1.1-3.1.2; [3] §6; worked example is explanatory

# Discussion practice and your own position

## Questions you should be able to answer

- What is a narrative here? A recurring interpretation in the news studies, but a broader communicative structure in NarraBench. Always name the definition before comparing methods.
- Why is the task multilabel? A paragraph can communicate more than one interpretation. Selecting one “main” category changes the task and can discard information.
- Why not trust an aggregate score? It may hide lost topic coverage, rare-label errors or changed data conditions. [2] provides a concrete coverage example.
- Can a singleton be a narrative? In [2], some are accepted as generalizable candidates. That does not prove within-corpus repetition, historical novelty or sufficient factual support.
- Why not replace people with a model judge? Judges can share biases. [2] finds limited agreement with human discovery validation; [4] highlights unresolved perspectival scoring.
- Which model is best? No universal answer follows. State the task, unit, metric and data. In F3, a smaller performance drop does not imply the highest absolute OOD score.

## Three defensible comments of your own

1. Definition first: “I would freeze a codebook and rules for quotation/negation before model selection. Otherwise the benchmark can measure inconsistent annotation rather than a model difference.”

2. Coverage as a separate goal: “I would show per-label results and output volume. Restoring rare categories may increase review cost, so I want to measure that trade-off rather than optimize one average.”

3. Scope of understanding: “A source quotation makes an answer inspectable, but it is not proof of internal reasoning or truth. I would evaluate classification and semantic support separately.”

> Turn a comment into a research question: Does a fixed few-shot codebook improve rare-category recall on new articles enough to justify added API tokens? This is a proposed test inspired by the reading, not a conclusion already established by the four papers.

One-minute synthesis: the papers jointly motivate clear task definitions, multiple diagnostics, careful reference labels and independent validation. They do not collapse into a single method or leaderboard.

# References and selective original reading

## The four sources

[1] Nikolaidis, N. et al. (2025). *PolyNarrative: A Multilingual, Multilabel, Multi-domain Dataset for Narrative Extraction from News Articles.* ACL, pp. 31323-31345. DOI: 10.18653/v1/2025.acl-long.1513.

ACL Anthology: PolyNarrative

[2] Upravitelev, M. et al. (2026). *From Repetition to Recognition: Inductive Discovery of Disinformation Narratives.* arXiv:2609.11128v1, submitted 10 September 2026. Preprint; this brief analyzes that version.

arXiv: version and full text

[3] Lucas, J. et al. (2023). *Fighting Fire with Fire: The Dual Role of LLMs in Crafting and Detecting Elusive Disinformation.* EMNLP, pp. 14279-14305. DOI: 10.18653/v1/2023.emnlp-main.883.

ACL Anthology: F3

[4] Hamilton, S., Wilkens, M., & Piper, A. (2026). *NarraBench: A Comprehensive Framework for Narrative Benchmarking.* EACL, pp. 3786-3801. DOI: 10.18653/v1/2026.eacl-long.176.

ACL Anthology: NarraBench

## If you open only a few original pages

| Paper | Priority sections | PDF pages |
|---|---|---|
| [1] | §§3-5, Tables 3-4, Limitations | 4-10 |
| [2] | §3.1, §4, §5.2, Limitations | 3-4, 6-10 |
| [3] | §5.3, §6, Table 5, Limitations | 5-10 |
| [4] | §§3-5, Limitations | 3-7, 9 |

PDF-page positions count from the first page of each downloaded file; they differ from conference publication page numbers. Appendices are useful when implementing prompts, taxonomies or annotation rules.

> Final self-check: explain each paper's question, input/output, evidence and one limitation without reading its abstract. Be able to distinguish the authors' result from your interpretation. This is the central preparation goal; use the original tables when citing exact numbers.

Prepared for Vsevolod Drabych, P6. English/Russian study editions, 2 November 2026. Based on the complete locally available papers, with emphasis on the cited methods, results and limitations. Explanatory examples and suggested project positions are not empirical findings.