

Problem Session 5

Problem 5-1. Graph Radius

In any undirected graph $G = (V, E)$, the **eccentricity** $\epsilon(u)$ of a vertex $u \in V$ is the shortest distance to its farthest vertex v , i.e., $\epsilon(u) = \max\{\delta(u, v) \mid v \in V\}$. The **radius** $R(G)$ of an undirected graph $G = (V, E)$ is the smallest eccentricity of any vertex, i.e., $R(G) = \min\{\epsilon(u) \mid u \in V\}$.

- (a) Given connected undirected graph G , describe an $O(|V||E|)$ -time algorithm to determine the radius of G .
- (b) Given connected undirected graph G , describe an $O(|E|)$ -time algorithm to determine an upper bound R^* on the radius of G , such that $R(G) \leq R^* \leq 2R(G)$.

Problem 5-2. Internet Investigation

MIT has heard complaints regarding the speed of their WiFi network. The network consists of r routers, some of which are marked as **entry points** which are connected to the rest of the internet. Some pairs of routers are directly connected to each other via bidirectional wires. Each wire w_i between two routers has a known length ℓ_i measured in a positive integer number of feet. The **latency** of a router in the network is proportional to the minimum feet of wire a signal from the router must pass through to reach an entry point. Assume the latency of every router is finite and there is at most $100r$ feet of wire in the entire network. Given a schematic of the network depicting all routers and the lengths of all wires, describe an $O(r)$ -time algorithm to determine the sum total latency, summed over all routers in the network.

Problem 5-3. Quadwizard Quest

Wizard Potry Harter and her three wizard friends have been tasked with searching every room of a Labyrinth for magical artifacts. The Labyrinth consists of n rooms, where each room has at most four doors leading to other rooms. Assume all doors begin closed and every room in the Labyrinth is reachable from a specified entry room by traversing doors between rooms. Some doors are protected by evil enchantments that must be **disenchanted** before they can be opened; but all other doors may be opened freely. Given a map of the Labyrinth marking each door as enchanted or not, describe an $O(n)$ -time algorithm to determine the minimum number of doors that must be disenchanted in order to visit every room of the Labyrinth, beginning from the entry room.

Problem 5-4. Purity Atlantic

Brichard Ranson is the founder of Purity Atlantic, an international tour company that specializes in planning luxury honeymoon getaways for newlywed couples. To book a customized tour, a couple submits their home city, and the names of three touring cities they would like to visit during their honeymoon. Then Purity will arrange all accommodations, including a **flight itinerary**: a sequence of flights from their home to each touring city (in any order), then returning back to their home. Unfortunately, it's not always possible to fly directly between any two cities, so multiple flights may be required. While cost and time are not a factor, couples prefer to minimize the number of direct flights they will have to take during their honeymoon. Given a list of c cities and a list of all f available direct flights, where each direct flight is specified by an ordered pair of cities (origin, destination), describe an efficient algorithm to determine a flight itinerary for a given couple that minimizes the number of direct flights they will have to take.


```

1  # ----- #
2  # REWRITE SOLVE IMPLEMENTING PART (e) #
3  # ----- #
4  def solve(config):
5      # Return a sequence of moves to solve config, or None if not possible
6
7      # Fully explore graph using BFS
8      parent, frontier = {config: None}, [config]
9      while len(frontier) != 0:
10         frontier = explore_frontier(frontier, parent, True)
11         print('Searched %s reachable configurations' % len(parent))
12
13         # Check whether solved state visited and reconstruct path
14         if SOLVED in parent:
15             path = path_to_config(SOLVED, parent)
16             return moves_from_path(path)
17         return None
18
19  # ----- #
20  # READ, BUT DO NOT MODIFY CODE BELOW HERE #
21  # ----- #
22  # Pocket Cube configurations are represented by length 24 strings
23  # Each character represents the color of a small cube face
24  # Faces are layed out in reading order of a Latin cross unfolding of the cube
25
26  SOLVED = '000011223344112233445555'
27
28  def config_str(config):
29      # Return config string representation as a Latin cross unfolding
30      return """
31          %s%s
32          %s%s
33          %s%s%s%s%s%s%s
34          %s%s%s%s%s%s%s
35          %s%s
36          %s%s
37          """ % tuple(config)
38
39  def shift(A, d, ps):
40      # Circularly shift values at indices ps in list A by d positions
41      values = [A[p] for p in ps]
42      k = len(ps)
43      for i in range(k):
44          A[ps[i]] = values[(i - d) % k]
45
46  def rotate(config, face, sgn):
47      # Returns new config by rotating input face of input config
48      # Rotation is clockwise if sgn == 1, counterclockwise if sgn == -1
49      assert face in (0, 1, 2)
50      assert sgn in (-1, 1)
51      if face is None: return config
52      new_config = list(config)
53      if face == 0:
54          shift(new_config, 1*sgn, [0,1,3,2])
55          shift(new_config, 2*sgn, [11,10,9,8,7,6,5,4])

```

```

56     elif face == 1:
57         shift(new_config, 1*sgn, [4,5,13,12])
58         shift(new_config, 2*sgn, [0,2,6,14,20,22,19,11])
59     elif face == 2:
60         shift(new_config, 1*sgn, [6,7,15,14])
61         shift(new_config, 2*sgn, [2,3,8,16,21,20,13,5])
62     return ''.join(new_config)
63
64 def neighbors(config):
65     # Return neighbors of config
66     ns = []
67     for face in (0, 1, 2):
68         for sgn in (-1, 1):
69             ns.append(rotate(config, face, sgn))
70     return ns
71
72 def explore_frontier(frontier, parent, verbose = False):
73     # Explore frontier, adding new configs to parent and new_frontier
74     # Prints size of frontier if verbose is True
75     if verbose:
76         print('Exploring next frontier containing # configs: %s' % len(frontier))
77     new_frontier = []
78     for f in frontier:
79         for config in neighbors(f):
80             if config not in parent:
81                 parent[config] = f
82                 new_frontier.append(config)
83     return new_frontier
84
85 def path_to_config(config, parent):
86     # Return path of configurations from root of parent tree to config
87     path = [config]
88     while path[-1] is not None:
89         path.append(parent[path[-1]])
90     path.pop()
91     path.reverse()
92     return path
93
94 def moves_from_path(path):
95     # Given path of configurations, return list of moves relating them
96     # Returns None if any adjacent configs on path are not related by a move
97     moves = []
98     for i in range(1, len(path)):
99         move = None
100         for face in (0, 1, 2):
101             for sgn in (-1, 1):
102                 if rotate(path[i - 1], face, sgn) == path[i]:
103                     move = (face, sgn)
104                     moves.append(move)
105         if move is None:
106             return None
107     return moves
108
109
110

```

```

111 def path_from_moves(config, moves):
112     # Return the path of configurations from input config applying input moves
113     path = [config]
114     for move in moves:
115         face, sgn = move
116         config = rotate(config, face, sgn)
117         path.append(config)
118     return path
119
120 def scramble(config, n):
121     # Returns new configuration by applying n random moves to config
122     from random import randint
123     for _ in range(n):
124         ns = neighbors(config)
125         i = randint(0, 2)
126         config = ns[i]
127     return config
128
129 def check(config, moves, verbose = False):
130     # Checks whether applying moves to config results in the solved config
131     if verbose:
132         print('Making %s moves from starting configuration:' % len(moves))
133     path = path_from_moves(config, moves)
134     if verbose:
135         print(config_str(config))
136     for i in range(1, len(path)):
137         face, sgn = moves[i - 1]
138         direction = 'clockwise'
139         if sgn == -1:
140             direction = 'counterclockwise'
141         if verbose:
142             print('Rotating face %s %s:' % (face, direction))
143             print(config_str(path[i]))
144     return path[-1] == SOLVED
145
146 def test(config):
147     print('Solving configuration:')
148     print(config_str(config))
149     moves = solve(config)
150     if moves is None:
151         print('Path to solved state not found... :(')
152         return
153     print('Path to solved state found!')
154     if check(config, moves):
155         print('Move sequence terminated at solved state!')
156     else:
157         print('Move sequence did not terminate at solved state... :(')
158
159 if __name__ == '__main__':
160     config = scramble(SOLVED, 100)
161     test(config)

```