

BOB ROGERS

PRIVATE ENTRANCE ACCESS
(CLINTO AVENUE UNRECORDED)

RETAINING WALL.
REFER TO CIVIL DWG

RESTAURANT
1 STORY
+/- 7,000 SQFT

HOME 2 SUITES
115 KEYS
4 STORIES
BUILDING FOOTPRINT:
+/- 17,699 SQFT

26' FIRE TRUCK LANE

26' FIRE TRUCK LANE


26' FIRE TRUCK LANE

US HIGHWAY 277

CONCEPTUAL SITE PLAN
1" = 20'-0"

KEYED NOTES - SITE PLAN

- MONUMENT SIGN LOCATION
- ACCESSIBLE PASSENGER DROP OFF AREA W/ ADJACENT CLEAR ACCESS AISLE - DROP OFF AND ACCESS AISLE SHALL BE AT THE SAME LEVEL & SHALL HAVE A SLOPE NOT TO EXCEED 1:48 (1:64 RECOMMENDED). DRIVE AISLES SHALL RAMP UP TO LEVEL OF WALK AT DROP OFF AREA - REFER TO MATERIAL LEGEND FOR SPECIFIC PAVING OF THIS AREA. REFER TO THE HADG FOR MORE INFORMATION REGARDING ACCESSIBLE PASSENGER LOADING ZONES.
- ACCESSIBLE CURB RAMP TO MEET ALL ACCESSIBILITY REQUIREMENTS, MAXIMUM SLOPE OF RUN 1:12 (1:14 RECOMMENDED), MAXIMUM CROSS SLOPE OF 1:48 (1:64 RECOMMENDED), REFER TO THE HAD FOR FURTHER INFORMATION.
- ACCESSIBLE PARKING SPACES, SIGNAGE, LOGOS, WHEEL STOPS AND ACCESS AISLES MUST MEET ALL ACCESSIBILITY REQUIREMENTS - PROVIDE SPACES IN SIZE, QUANTITY AND LOCATIONS REQ'D BY ACCESSIBILITY AND BY APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION. PROVIDE A MAXIMUM SLOPE IN EITHER DIRECTION OF 1:48 (1:64 RECOMMENDED), REFER TO HADG FOR FURTHER INFORMATION.
- OPTIONAL FLAGPOLE WITH IN-GROUND UPLIGHT
- PET RELIEF STATION
- PAVED WALKWAY - SLOPE AWAY FROM BLDG. (MAX 2% CROSS SLOPE) - SILICA-BASED AGGREGATE WITH BROOM-FINISHED CONCRETE
- DECORATIVE NON-SLIP PAVING
- LINE OF CANOPY ROOF ABOVE
- UNUSED
- EXTERIOR GARDEN STORAGE AREA
- PET RELIEF STATION
- PROPERTY LINE
- CURB CUT & DRIVEWAY ACCESS - SIZE & LOCATE CURB CUTS & DRIVE AISLES PER LOCAL REQUIREMENTS - MAINTAIN APPROPRIATE SIGHT LINES
- OUTDOOR LOUNGE - REFER TO FF&E SPECS FOR LOOSE FURNISHINGS
- POOL PATIO - REFER TO FF&E SPECS FOR LOOSE FURNISHINGS
- ACCENT PLANTINGS - SPECIES DETERMINED BY LOCAL CLIMATE CONDITIONS - REFER TO LANDSCAPE DESIGN INTENT PLAN FOR LANDSCAPING GUIDELINES
- TRELLIS ABOVE - SEE DETAILS SHEET A-305
- ACCESSIBLE ROUTE FROM ACCESSIBLE PARKING TO BUILDING ENTRANCE. PROVIDE A RUNNING SLOPE OF MAXIMUM 1:20 AND A CROSS SLOPE OF MAXIMUM 1:48 (1:64 RECOMMENDED). REFER TO HADG FOR FURTHER INFORMATION.
- BOLLARDS - 48" HIGH 6" DIA. CONC. FILLED STL.
- PROPOSED TRANSFORMER & CONCRETE PAD LOCATION - ADJUST LOCATION AS REQUIRED TO MEET LOCAL CODES & UTILITY ACCESS
- PARKING LOT STRIPING MUST BE WHITE, EXCEPT WHERE OTHER COLORS ARE REQUIRED BY LOCAL CODES FOR FIRE LANES, ACCESSIBLE PARKING, NO PARKING ZONES, ETC.
- TREES - SPECIES DETERMINED BY LOCAL CLIMATE COND. - TREES SHALL NOT INTERFERE W/ PARKING OR PEDESTRIAN ACTIVITY - REFER TO LANDSCAPE DESIGN INTENT PLAN FOR LANDSCAPING GUIDELINES
- ASPHALT OR CONC. PAVING SHALL COMPLY W/ LOCAL REQUIREMENTS - PROVIDE POSITIVE DRAINAGE AWAY FROM BLDG. - COORDINATE SITE DRAINAGE & DETENTION W/ CIVIL ENGINEER
- PARTIAL HEIGHT WALL
- ACCESSIBLE WALKWAY: RUNNING SLOPE OF MAXIMUM 1:20 AND CROSS SLOPE OF MAXIMUM 1:48 (1:64 RECOMMENDED). REFER TO HADG FOR FURTHER INFORMATION. SCORE DECORATIVE CONC.
- CONTINUOUS CONCRETE CURB - TYP.
- CONDENSING UNIT LOCATION - SCREENED FROM VIEW
- ACCESSIBLE PATH AWAY FROM BUILDING
- EXTERIOR FIRE PIT WITH MANUAL EMERGENCY REMOTE SHUT-OFF VALVE. SECURE IN PLACE TO RESIST MOVEMENT. FEED WITH UNDERGROUND LINE FROM BUILDING GAS SERVICE. PROVIDE APPROPRIATELY SIZED SAFETY SCREEN
- EXPANSION JOINT
- CONTROL JOINT
- LANDSCAPE AREA - REFER TO LANDSCAPE SHEETS FOR PLANTING PLAN
- REFER TO FLOOR PLANS FOR HATCHED AREA
- PRIMED AND PAINTED TUBE STEEL CANOPY COLUMNS
- ACCESSIBLE ROUTE TO PUBLIC RIGHT OF WAY (1 REQUIRED). MAX. RUNNING SLOPE OF 1:20 AND MAX. CROSS SLOPE OF 1:48 (1:64 RECOMMENDED). ALL PAVED SURFACES, CURB RAMP AND TRANSITIONS ALONG PATH TO MEET ACCESSIBILITY REQ'S
- EXTERIOR GAS GRILL. GRILLS REQUIRE REMOTE EMERGENCY SHUT OFF.
- PARKING LOT & DRIVEWAY LIGHTING (P-1) - SHOWN FOR DESIGN INTENT
- FLUSH CURB ALONG ENTIRE LENGTH OF ACCESSIBLE DROP OFF
- TRASH, RECYCLING, AND ASH BIN
- 24" X 54" FRC PLANTERS
- POOL
- EV CHARGING STATION. PROVIDE CONCRETE FOOTING AND ELECTRICAL
- EMERGENCY GAS SHUT OFF
- PROVIDE POWER FOR PLUG IN STRIP LIGHT AT TRELLIS
- PROVIDE POWER FOR PLUG IN STRING LIGHTS
- INFORMATION KIOSK
- SOLAR CONDUIT STUB - FINAL QUANTITY AND LOCATION TO BE VERIFIED IN FIELD
- THREE 3" KIOSK CONDUIT STUB - FINAL LOCATION TO BE VERIFIED IN FIELD
- PUBLIC WORKS SOLID WASTE DEPARTMENT HAS A COMMERCIAL DRIVER'S SIDE LOADER WITH SPACE REQUIREMENTS OF 14' CLEARANCE TO THE FRONT OF THE PAD AND 20' CLEARANCE TO THE REAR OF THE PAD. IF OUTWARD OPENING DOORS ARE INSTALLED, DOORS WILL HAVE TO ALLOW 180 DEGREE OPENING FOR COMMERCIAL SIDE LOADER TRUCK TO BE ABLE TO REACH THE CONTAINER.



D/F MONUMENT SIGN

MONUMENT SIGN & PYLON SIGN ELEVATION
1/8" = 1'-0"

GENERAL NOTES - SITE PLAN

- A. BLDG. LIMITATIONS, AREA REQUIREMENTS, & SETBACKS ARE TO CONFORM TO APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION.
- B. PROVIDE FIRE ACCESS LANE AS REQUIRED BY APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION
- C. PROVIDE APPROPRIATE NUMBER OF CURB CUTS AND DRIVEWAY ACCESS WIDTHS TO SITE AS REQUIRED BY APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION.
- D. TYP. PARKING SPACES SHALL BE REQUIRED BY APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION.
- E. COORDINATE LIGHTING LOCATIONS WITH LANDSCAPE PLANTINGS - PROVIDE PHOTOMETRIC ANALYSIS AS REQUIRED BY APPLICABLE CODES.
- F. REFER TO BRAND'S STANDARDS FOR ADDITIONAL INFORMATION AND PRECISE SIGNAGE REQUIREMENTS
- G. IRRIGATE ALL LANDSCAPED AREAS WITH AUTOMATIC UNDERGROUND SPRINKLER SYSTEM EXCEPT THOSE IMMEDIATELY ADJACENT TO EXTERIOR WALL OF THE HOTEL.
- H. ALL AREAS NOT WITHIN PLANTING BEDS TO BE XERISCAPE.
- I. ALL EQUIPMENT MUST BE SCREENED WITH LANDSCAPING OR OTHER MEANS.
- J. ALL SITE DIMENSIONS ARE MINIMUM REQUIREMENTS. COMPLY WITH APPLICABLE CODES AS DETERMINED BY LOCAL JURISDICTION.
- K. PROVIDE HOSE BIBS AROUND MAIN BUILDING PERIMETER AND AT DUMPSTER ENCLOSURE.
- L. REFER TO HOME 2 SUITES BY HILTON STANDARDS MANUAL FOR ADDITIONAL REQUIREMENTS.
- M. PROVIDE AN ACCESSIBLE MEANS OF TRAVEL TO SITE PROPERTY LINE THAT MEETS ALL ACCESSIBILITY REQUIREMENTS
- N. CATCH BASINS ARE TO BE PLACED SO AS NOT TO INTERFERE WITH DESIGNATED ACCESSIBLE ROUTES, THEIR CLEARANCES & MAX. SLOPES
- O. PARKING LOT STRIPES MUST BE WHITE, EXCEPT WHERE OTHER COLORS ARE REQUIRED FOR FIRE LANES & NO PARKING ZONES.
- P. AVOID DEAD-END PARKING.

SITE DATA
B1 - Neighborhood Business District
Setbacks :
Front = 20'
Side = 5'
Rear = 0'

LOT SIZE: ± 132,858 SQFT
ACREAGE ± 3.05 ACRE

BUILDINGS SIZE
Hotel ± 17,699 SQFT
Restaurant ± 7,000 SQFT

PROPOSED BUILDING HEIGHT:
Hotel 48' - 8 1/4"
Restaurant 1 story

NUMBER OF ROOMS
Accessible Units 7 keys
Non-Accessible Unit 108 keys
Total Provided 115 keys

PARKING REQUIREMENTS
Hotel (115 spaces)
Peak Hour Employees (4 spaces)
Restaurant (23 spaces, 1 space per 300 SQFT)
Total Required 142 spaces

PARKING PROVIDED
Standard car 133 cars
Compact car 3 cars
HC car 6 cars
HC - EV car (Van) 1 car
Electric vehicle (EV) 4 cars
Total Provided 145 cars

Standard car parking stall are 9' x 20' and 9' x 18'
Parallel parking stall is 9' x 22'
Compact parking stall is 9' x 16'

GREEN SPACE AREA CALCULATION
LANDSCAPE SQ. AND % 26,666 SF (20.07%)

NOTE:
ALL LAWN TO BE XERISCAPE

LEGEND - SITE PLAN

- CONCRETE PAVING
- PAVED WALKWAY
- PAVING #1: CONCRETE
- PAVING #2: COLORED CONCRETE WITH EXPOSED AGGREGATE OR SAND FINISH
- PAVING #3: DECORATIVE NON-SLIP TILE PAVERS
- PARKING AND DRIVE STRIPING
- GRAVEL - SEE LANDSCAPE
- GROUND COVER - SEE LANDSCAPE
- PROPERTY LINE
- SETBACK LINE
- STREET LIGHT (P-1)
- IN-GROUND UPLIGHT (P-3)
- FLAG POLE



3827 BILLO ROAD
ALDEN, NY, 14004
716-631-0600
ARCHITECT OF RECORD

DONALD M. EDWARD
LICENSE # 20212
10800 ALABASTER DR.
DAVIDSON, NC 28036
donedwardarchitect@gmail.com



04/20/2023

WARNING
IT IS A VIOLATION OF THE LAW FOR ANY PERSON, UNLESS ACTING UNDER THE DIRECTION OF THE ARCHITECT OR ENGINEER, TO ALTER OR REPRODUCE THESE DRAWINGS IN ANY WAY.

DRAWING QUESTIONS
CA@MWTUSA.COM
1-800-717-5816

ISSUED FOR :

CONSTRUCTION AND BID SET



EAGLE PASS, TX 78852
PROTOTYPE VERSION: 3.0

REVISIONS

NO.	DESCRIPTION	DATE	BY

PROJECT NO.: 22-014

DATE: 06/09/23

DRAWN BY: RH/AA

CHKD. BY: AS/FS

SITE PLAN

SHEET

AS100

22-014 AS100 SITE PLAN.dwg

IMPORTANT NOTICE TO ALL CONTRACTORS AND OR SUBCONTRACTORS: (COMPLETE BUILDING SYSTEMS AND OR INSTALLATIONS)

- IF AWARDED A CONTRACT FOR ANY PORTION OF WORK NEEDED TO COMPLETE THIS PROJECT YOU ARE AGREEING TO THE FOLLOWING TERMS:
- YOU ARE A QUALIFIED CONTRACTOR AND/OR SUBCONTRACTOR SPECIFICALLY IN PROVIDING A COMPLETE TURNKEY SERVICE TO YOUR TRADE OR PROFESSION FOR THE TYPE OF WORK AND SCOPE FOR THIS PROJECT.
 - YOU AGREE TO PROVIDE A COMPLETE DESIGN BUILD SOLUTION BASED ON THE ARCHITECT'S INTENDED DESIGN FOR THIS PROJECT.
 - YOUR BID INCLUDES ALL THE STEPS, PROCESSES, MATERIALS, PRODUCTS, GOVERNING PERMITS AND APPROVALS NECESSARY TO PROVIDE A COMPLETED AND WARRANTED SYSTEM OR INSTALLATION THAT DOES NOT REQUIRE ANOTHER CONTRACTOR OR PRODUCT TO COMPLETE YOUR SCOPE OF WORK.
 - YOUR BID MUST HAVE INCLUDED ANY DESIGN INFORMATION REFERENCED WITHIN ANY CIVIL, ARCHITECTURAL, STRUCTURAL, MECHANICAL, ELECTRICAL AND OR PLUMBING DRAWINGS; ALSO NOTE THESE DRAWINGS ARE SCHEMATIC AND ARE INTENDED TO SHOW ONLY BASIC CONCEPTS AND GENERAL INFORMATION. THE COMPLETION OF YOUR WORK MAY INCLUDE OTHER STEPS, PROCESSES, MATERIALS, PRODUCTS, LABOR, GOVERNING PERMITS AND OR APPROVALS NECESSARY TO PROVIDE A COMPLETE SYSTEM INSTALLATION WHETHER SUGGESTED ON THE DRAWINGS OR NOT.
 - AS AN EXAMPLE: ITEMS AND OR TASKS LIKE: FIRE CAULK, DRAFT STOPS, FASTENERS, ANCHORS, EMBLEMENTS, DUMPSTERS, DEBRIS CLEAN UP, ETC. ARE YOUR RESPONSIBILITY. ANY WORK NOT COMPLETED IN A TIMELY MANNER, OR INCOMPLETE WORK WILL BE BILLED BACK TO THE CONTRACTOR AND OR SUBCONTRACTOR, AT THE OWNERS DISCRETION.