

ISOuncoated175bb.icc

Das ECI-Offsetprofil **ISOuncoated175bb.icc** basiert auf der Offset Charakterisierungsdatei „**FOGRA21L.txt**“ und gilt für die folgenden Druckbedingungen gemäß internationalem Standard ISO/CD 12647-2:2002+:

Akzidenz Offsetdruck, Papiertyp 4, ungestrichen weiß Offset, 120 g/m2, Positivkopie, **Rasterweite 70/cm (175 lpi), schwarze Messunterlage (bb)**.

Die Profilberechnung erfolgte in Heidelberg Printopen 4.0.5.2 mit den folgenden Einstellungen:

Schwarz-Länge	9
Schwarz-Breite	5
max. Flächendeckung	320%
max. Schwarz	100 %

Die „Gamut-Mapping“-Option „mehr Kontrast in dunklen Farben“ war ausgeschaltet.

*The ECI offset profile **ISOuncoated175bb.icc** is based on the offset characterization table “**FOGRA21L.txt**” valid for the following reference printing conditions relating to the international standard ISO/CD 12647-2:2002+:*

*Commercial and specialty offset, paper type 4, uncoated white offset paper, 120 g/m2, positive plates, **screen frequency 70/cm (175 lpi), black backing (bb)**.*

The profile was generated using Heidelberg Printopen 4.0.5.2 with the following settings:

<i>Black length</i>	<i>9</i>
<i>Black width</i>	<i>5</i>
<i>Total dot area</i>	<i>320%</i>
<i>Maximum Black</i>	<i>100 %</i>

The “Gamut-Mapping” option “More contrast in dark colors” was switched off.