

ISOuncoatedbb.icc

Das ECI-Offsetprofil **ISOuncoatedbb.icc** basiert auf der Offset Charakterisierungsdatei „**FOGRA13L.txt**“ und gilt für die folgenden Druckbedingungen gemäß internationalem Standard ISO/CD 12647-2:2002+:

Akzidenz Offsetdruck, Papiertyp 4, ungestrichen weiß Offset, 120 g/m2, Positivkopie, **Rasterweite 60/cm (150 lpi), schwarze Messunterlage (bb)**.

Die Profilberechnung erfolgte in Heidelberg Printopen 4.0.5.2 mit den folgenden Einstellungen:

| | |
|---------------------|-------|
| Schwarz-Länge | 9 |
| Schwarz-Breite | 5 |
| max. Flächendeckung | 320% |
| max. Schwarz | 100 % |

Die „Gamut-Mapping“-Option „mehr Kontrast in dunklen Farben“ war ausgeschaltet. .

*The ECI offset profile **ISOuncoatedbb.icc** is based on the offset characterization table “**FOGRA13L.txt**” valid for the following reference printing conditions relating to the international standard ISO/CD 12647-2:2002+:*

*Commercial and specialty offset, paper type 4, uncoated white offset paper, 120 g/m2, positive plates, **screen frequency 60/cm (150 lpi), black backing (bb)**.*

The profile was generated using Heidelberg Printopen 4.0.5.2 with the following settings:

| | |
|-----------------------|--------------|
| <i>Black length</i> | <i>9</i> |
| <i>Black width</i> | <i>5</i> |
| <i>Total dot area</i> | <i>320%</i> |
| <i>Maximum Black</i> | <i>100 %</i> |

The “Gamut-Mapping” option “More contrast in dark colors” was switched off.