

ISOcoatedbb.icc

Das ECI-Offsetprofil **ISOcoatedbb.icc** basiert auf der Offset Charakterisierungsdatei „**FOGRA11L.txt**“ und gilt für die folgenden Druckbedingungen gemäß internationalem Standard ISO/CD 12647-2:2002+:

Akzidenz Offsetdruck, Papiertyp 1 und 2, glänzend oder matt gestrichen Bilderdruck, 115 g/m2, Positivkopie, **Rasterweite 60/cm (150 lpi)**, **schwarze Messunterlage (bb)**.

Die Profilberechnung erfolgte in Heidelberg Printopen 4.0.5.2 mit den folgenden Einstellungen:

Schwarz-Länge	9
Schwarz-Breite	5
max. Flächendeckung	350%
max. Schwarz	100 %

Die „Gamut-Mapping“-Option „mehr Kontrast in dunklen Farben“ war ausgeschaltet. .

*The ECI offset profile **ISOcoatedbb.icc** is based on the offset characterization table “**FOGRA11L.txt**” valid for the following reference printing conditions relating to the international standard ISO/CD 12647-2:2002+:*

*Commercial and specialty offset, paper type 1 and 2, gloss or matt coated paper, 115 g/m2, positive plates, **screen frequency 60/cm (150 lpi)**, **black backing (bb)**.*

The profile was generated using Heidelberg Printopen 4.0.5.2 with the following settings:

<i>Black length</i>	<i>9</i>
<i>Black width</i>	<i>5</i>
<i>Total dot area</i>	<i>350%</i>
<i>Maximum Black</i>	<i>100 %</i>

The “Gamut-Mapping” option “More contrast in dark colors” was switched off.