Model Free Control Generalized Policy Iteration

Marius Lindauer



102

Leibniz Universität Hannover



Recall Policy Iteration

- Initialize policy π
- Repeat:
 - Policy evaluation: compute V^{π}
 - Policy improvement: update π

$$\pi'(s) \in \operatorname*{arg\,max}_{a \in A} R(s,a) + \gamma \sum_{s' \in S} P(s' \mid s,a) V^{\pi}(s') = \operatorname*{arg\,max}_{a \in A} Q^{\pi}(s,a)$$

- Now want to do the above two steps without access to the true dynamics and reward models
- Before we introduced methods for model-free policy evaluation



Model Free Policy Iteration

- ullet Initialize policy π
- Repeat:
 - lacktriangle Policy evaluation: compute Q^π
 - ▶ Policy improvement: update π



MC for On-Policy Q-Evaluation

- Initialize $\forall s \in S, a \in A$:
 - N(s,a) = 0
 - G(s,a) = 0
 - $Q^{\pi}(s,a) = 0$
- Loop
 - Using policy π sample episode $i=s_{i,1},a_{i,1},r_{i,1},s_{i,2},a_{i,2},r_{i,2},\ldots,s_{i,T_i}$
 - $G_{i,t} = r_{i,t} + \gamma r_{i,t+1}, \gamma^2 r_{i,t+2} + \dots \gamma^{T_i 1} r_{i,T_i}$
 - For each pair (s, a) visited in episode i
 - ***** For first (or every) time t that (s, a) is visited in episode i:
 - \star N(s,a) = N(s,a) + 1
 - \star $G(s,a) = G(s,a) + G_{i,t}$
 - ★ Update estimate $Q^{\pi}(s, a) = G(s, a)/N(s, a)$



Model-free Generalized Policy Improvement

- Given an estimate $Q^{\pi_i}(s,a) \forall s \in S, a \in A$
- Update new policy

$$\pi_{i+1}(s) \in \operatorname*{arg\,max}_{a \in A} Q^{\pi_i}(s, a)$$

