

Model Free Control

SARSA and Q-Learning

Marius Lindauer



Winter Term 2021

Model-free Policy Iteration with TD Methods

- ▶ Use temporal difference methods for policy evaluation step
- ▶ Initialize policy π
- ▶ Repeat:
 - ▶ Policy evaluation: compute Q^π using temporal difference updating with Q -greedy policy
 - ▶ Policy improvement: Same as Monte Carlo policy improvement, set π to ϵ -greedy (Q^π)
- ▶ First consider SARSA, which is an on-policy algorithm

General Form of SARSA Algorithm

► Initialization:

- ϵ -greedy policy
- $t = 0$
- initial state $s_t = s_0$

► Loop

- Take action $a_t \sim \pi(s_t)$
- Observe (r_t, s_{t+1}) , $a_{t+1} \sim \pi(s_{t+1})$
- Update Q given $(s_t, a_t, r_t, s_{t+1}, a_{t+1})$:

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha(r_t + \gamma Q(s_{t+1}, a_{t+1}) - Q(s_t, a_t))$$

- $\pi(s_t) \in \arg \max_{a \in A} Q(s_t, a)$ with probability $1 - \epsilon$, else random
- $t = t + 1$

Convergence Properties of SARSA

► Theorem:

SARSA for finite-state and finite-action MDPs converges to the optimal action-value, $Q(s, a) \rightarrow Q^*(s, a)$, under the following conditions:

1. The policy sequence $\pi_t(a | s)$ satisfies the condition of GLIE
2. The step-sizes α_t satisfy the **Robbins-Munro sequence** such that

$$\sum_{t=1}^{\infty} \alpha_t = \infty$$

$$\sum_{t=1}^{\infty} \alpha_t^2 < \infty$$

- For example $\alpha_t = \frac{1}{t}$ satisfies the above condition
- Would one want to use a step size choice that satisfies the above in practice? Likely not.

Q-Learning: Learning the Optimal State-Action Value

- ▶ SARSA is an on-policy learning algorithm
- ▶ SARSA estimates the value of the current behavior policy (policy using to take actions in the world)
- ▶ And then updates the policy trying to estimate
- ▶ Alternatively, can we directly estimate the value of π^* while acting with another behavior policy π_b ?
- ▶ Yes! Q-learning, an off-policy RL algorithm
- ▶ Key idea: Maintain state-action Q estimates and use to bootstrap– use the value of the best future action
- ▶ Recall SARSA:

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha((r_t + \gamma Q(s_{t+1}, a_{t+1})) - Q(s_t, a_t))$$

- ▶ Q-Learning:

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha((r_t + \gamma \max_{a' \in A} Q(s_{t+1}, a')) - Q(s_t, a_t))$$

Q-Learning with ϵ -greedy Exploration

► Initialization:

- $Q(s, a) = 0. \forall s \in S, a \in A$
- $t = 0$
- initial state $s_t = s_0$

► Loop

- Take action $a_t \sim \pi_b(s_t)$
- Observe (r_t, s_{t+1})
- Update Q

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha(r_t + \gamma \max_{a \in A} Q(s_{t+1}, a) - Q(s_t, a_t))$$

- $\pi(s_t) \in \arg \max_{a \in A} Q(s_t, a)$ with probability $1 - \epsilon$, else random
- $t = t + 1$

Q-Learning with ϵ -greedy Exploration

- ▶ Conditions for convergence to Q^* ?
 - ▶ Visit all (s, a) pairs infinitely often
 - ▶ the step-sizes α_t satisfy the Robbins-Munro sequence
 - ▶ Note: the algorithm does not have to be greedy in the limit of infinite exploration (GLIE) to satisfy this
- ▶ Conditions for convergence to optimal π^*
 - ▶ The above requirements to converge to optimal Q^*
 - ▶ The algorithm is GLIE