

Machine Learning and Data Analytics

ME 5013- Fall 2019

Lectures 18

- Neural networks basics




The University of Texas at San Antonio™

Adel Alaeddini, PhD

Associate Professor of Mechanical Engineering

Advanced Data Engineering Lab

adel.alaeddini@utsa.edu



$$g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1 x_2 + \theta_4 x_1^2 x_2 + \theta_5 x_1^3 x_2 + \theta_6 x_1 x_2^2 + \dots)$$

x_1 = size

x_2 = # bedrooms

x_3 = # floors


x_4 = age

...

x_{100}

What is this?

You see this:



But the camera sees this:

194	210	201	212	199	213	215	195	178	158	182	209
180	189	190	221	209	205	191	167	147	115	129	163
114	126	140	188	176	165	152	140	170	106	78	88
87	103	115	154	143	142	149	153	173	101	57	57
102	112	106	131	122	138	152	147	128	84	58	66
94	95	79	104	105	124	129	113	107	87	69	67
68	71	69	98	89	92	98	95	89	88	76	67
41	56	68	99	63	45	60	82	58	76	75	65
20	43	69	75	56	41	51	73	55	70	63	44
50	50	57	69	75	75	73	74	53	68	59	37
72	59	53	66	84	92	84	74	57	72	63	42
67	61	58	65	75	78	76	73	59	75	69	50



Cars




Not a car


Testing:



What is this?



Learning
Algorithm



+ Cars
- "Non"-Cars

50 x 50 pixel images → 2500 pixels
 $n = 2500$ (7500 if RGB)

$$x = \begin{bmatrix} \text{pixel 1 intensity} \\ \text{pixel 2 intensity} \\ \vdots \\ \text{pixel 2500 intensity} \end{bmatrix}$$


Quadratic features ($x_i \times x_j$): ≈3 million features

Neural Networks

Origins: Algorithms that try to mimic the brain.

Was very widely used in 80s and early 90s; popularity diminished in late 90s.

Recent resurgence: State-of-the-art technique for many applications



Auditory cortex learns to see


[Roe et al., 1992]



Seeing with your tongue



Human echolocation (sonar)





Haptic belt: Direction sense



Implanting a 3rd eye


[BrainPort; Welsh & Blasch, 1997; Nagel et al., 2005; Constantine-Paton & Law, 2009]






Sigmoid (logistic) activation function.

$$g(z) = \frac{1}{1 + e^{-z}}$$





$a_i^{(j)}$ = “activation” of unit i in layer j

$\Theta^{(j)}$ = matrix of weights controlling function mapping from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$


$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$

$$h_{\Theta}(x) = a_1^{(3)} = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

If network has s_j units in layer j , s_{j+1} units in layer $j + 1$, then $\Theta^{(j)}$ will be of dimension $s_{j+1} \times (s_j + 1)$.

Forward propagation: Vectorized implementation



$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$

$$h_{\Theta}(x) = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

$$x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad z^{(2)} = \begin{bmatrix} z_1^{(2)} \\ z_2^{(2)} \\ z_3^{(2)} \end{bmatrix}$$

$$z^{(2)} = \Theta^{(1)} x$$


$$a^{(2)} = g(z^{(2)})$$

Add $a_0^{(2)} = 1.$

$$z^{(3)} = \Theta^{(2)} a^{(2)}$$

$$h_{\Theta}(x) = a^{(3)} = g(z^{(3)})$$

Forward propagation: Vectorized implementation



$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$

$$h_{\Theta}(x) = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

$$x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad z^{(2)} = \begin{bmatrix} z_1^{(2)} \\ z_2^{(2)} \\ z_3^{(2)} \end{bmatrix}$$


$$z^{(2)} = \Theta^{(1)} x$$

$$a^{(2)} = g(z^{(2)})$$


Add $a_0^{(2)} = 1$.

$$z^{(3)} = \Theta^{(2)} a^{(2)}$$


$$h_{\Theta}(x) = a^{(3)} = g(z^{(3)})$$



Other network architectures




x_1 x_2 are binary (0 or 1)



$$y = x_1 \text{ XOR } x_2$$


$$x_1 \text{ XNOR } x_2$$

$$\text{NOT } (x_1 \text{ XOR } x_2)$$




$$x_1, x_2 \in \{0, 1\}$$


$$y = x_1 \text{ AND } x_2$$




$$h_{\theta}(x) = g(-30 + 20 x_1 + 20 x_2)$$

$$\theta_{10}^{(1)} \quad \theta_{11}^{(1)} \quad \theta_{12}^{(1)}$$





x_1	x_2	$h_{\Theta}(x)$
0	0	
0	1	
1	0	
1	1	







x_1	$h_{\Theta}(x)$
0	
1	

$$h_{\Theta}(x) = g(10 - 20x_1)$$


(NOT x_1) AND (NOT x_2)


?

Putting it together: x_1 XNOR x_2




x_1	x_2	$a_1^{(2)}$	$a_2^{(2)}$	$h_{\Theta}(x)$
0	0			
0	1			
1	0			
1	1			





[Courtesy of Yann LeCun]



[Courtesy of Yann LeCun]



Pedestrian




Car



Motorcycle




Truck



$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, etc.
 when pedestrian when car when motorcycle

Multiple output units: One-vs-all.



$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, etc.
 when pedestrian when car when motorcycle

Training set: $(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})$

$y^{(i)}$ one of $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$
 pedestrian car motorcycle truck