

SCHEDULE OF RCC SLABS

|    | TYPE        | THICKNESS | STEEL ALONG SHORT SPAN                                                  | STEEL ACROSS SHORT SPAN   | REMARKS                                                          |
|----|-------------|-----------|-------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------|
|    | S1          | 125       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 150 C/C ALT. BENT UP | –                                                                |
|    | S2          | 125       | T8 @ 125 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S3          | 125       | T8 @ 175 C/C ALT. BENT UP                                               | T8 @ 175 C/C ALT. BENT UP | –                                                                |
|    | S3A         | 125       | T8 @ 100 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
| R1 | S4          | 165       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 200C/C DIST.         | –                                                                |
|    | S5          | 125       | T8 @ 125 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | PROVIDE EOS AS SHOWN                                             |
|    | S6          | 125       | T8 @ 200 C/C ALT. BENT UP                                               | T8 @ 200 C/C ALT. BENT UP | –                                                                |
|    | S7          | 125       | T8 @ 200 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S8          | 125       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 150 C/C ALT. BENT UP | –                                                                |
|    | S9          | 125       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S10         | 125       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S11         | 125       | T8 @ 150 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S12         | 200       | T8 @ 175 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S12A        | 150       | T8 @ 175 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S13         | 125       | T8 @ 200 C/C ALL STR.                                                   | T8 @ 200 C/C DIST.        | –                                                                |
| R1 | S14         | 125       | T8 @ 200 C/C ALT. BENT UP                                               | T8 @ 250 C/C DIST.        | @ MIDLANDING                                                     |
|    | S15         | 125       | T8 @ 200 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | SUNK SLAB–400MM                                                  |
| R2 | S16         | 125       | T8 @ 200 C/C ALL STR.                                                   | T8 @ 200 C/C DIST.        | SERVICE SLAB<br>SUPPORT S16A                                     |
|    | S17         | 125       | T8 @ 175 C/C ALT. BENT UP                                               | T8 @ 200 C/C DIST.        | –                                                                |
|    | S18         | 125       | T8 @ 200 C/C ALL STR.                                                   | T8 @ 200 C/C DIST.        |                                                                  |
|    | CH          | 125       | T8 @ 150 C/C ALL STR AT TOP ;EVERY<br>ALTERNATE BAR BENT BACK ALONG BTM | T8 @ 150 C/C AT TOP & BTM | CANTILEVER SLAB                                                  |
|    | AST9,AST11  | 200       | T12 @ 100 C/C ALT. BAR BENT UP                                          | T8 @ 200 C/C DIST.        | SCISSOR JOINT WITH RESP.UPPER LANDING<br>SUPPORTS AST10 & AST12  |
|    | AST10,AST12 | 200       | T12 @ 100 C/C ALT. BAR BENT UP                                          | T8 @ 200 C/C DIST.        | SCISSOR JOINT WITH RESP.UPPER LANDING<br>RESTING ON AST9 & AST11 |
|    | BST9,BST11  | 200       | T12 @ 100 C/C ALT. BAR BENT UP                                          | T8 @ 200 C/C DIST.        | SCISSOR JOINT WITH RESP.UPPER LANDING<br>SUPPORTS BST10 & BST12  |
|    | BST10,BST12 | 200       | T12 @ 100 C/C ALT. BAR BENT UP                                          | T8 @ 200 C/C DIST.        | SCISSOR JOINT WITH RESP.UPPER LANDING<br>RESTING ON BST9 & BST11 |
| R2 | S16A        | 125       | DIST. STEEL OF S16                                                      | T8 @ 200 C/C DIST.        | SERVICE SLAB<br>RESTING ON S16                                   |
| R2 | S16B        | 125       | DIST. STEEL OF S16A                                                     | T8 @ 200 C/C DIST.        | SERVICE SLAB<br>RESTING ON S16A                                  |