laces. WK1

range(2,10,2) → 2,4,6,8

for index, fruit in enumerate(fruit
print(index, fruit)

answer =
print(a

icable. Lists are
arts at 0. Slicing
tem to the end.
m. List
e a list using
les store multip
tion use ( ) to
as key-value
d["key"] =
ys() ; .values()
ues only. It
ead or write
file. If a
e. split(",")
se try and
ing your
ap to store
by a dictionary.
2,4,4,6}
ne) → {2,4,6}
ds.txt") as f:
ad
:
age = int("abc")
pt ValueError:
rint("Please enter
a number")

WK2

A class is a blueprint for creating objects. __init__ () runs when a new object is created. self refers to the particular object being worked on. self.name = name saves the name inside that object. Attributes are variables belonging to an object. Each object has its own instance attributes. Changing one object's attribute does not automatically change another's. A method is a function defined inside a class. Call it using the object and a dot. One method can call another method using self. A method can update an object's attributes using self. Class level attributes shared by all objects of the class unless an object has its own separate attribute with that name. You can store objects in a list and loop through them to call a method on each one.

```
class Dog:
    pass
    def __init__(self, name):
        self.name = name

dog1 = Dog("Luna")
print(dog1.name) → Luna
class Animal:
    def speak(self):
        print("Hello")
```

```
class Cat:
    def speak(self):
        print("Meow")

cat = Cat()
cat.speak() → Meow

animals = [Animal(), Animal()]

for animal in animals:
    animal.speak()
```

WK5