

# ML: Research and Applications

## Insys Project

Dr. Mariela De Lucas Alvarez

DFKI - Robotics Innovation Center  
Interaction and Learning

Director: Prof. Dr. Frank Kirchner

*<https://robotik.dfki-bremen.de/>  
[robotik@dfki.de](mailto:robotik@dfki.de)*

January 23, 2024


- 1 Introduction
- 2 Multimodal Data Acquisition and Processing
- 3 Architecture Design and Tuning
- 4 XAI Methods
- 5 Evaluation
- 6 Conclusions




The goal of INSYS is to develop Explainable Artificial Intelligence (XAI) methods for multi modal robotic systems in the context of space applications.

**XAI is the research field concerned with ([Langer2021, Gilpin2019]):**

- Development of approaches that make AI understandable to humans.
- Providing insights into behaviour and processes of complex systems.
- Allowing part of the internal system to be more transparent.







- DFKI-RIC Lunar Cave Analog
  - ▶ Recordings of mobility hazards
  - ▶ Rock terrain with 30° slopes
- Entern Trials: Canary Islands
  - ▶ Lava tubes - Hard rocky terrain
- DFKI-RIC Test Field
  - ▶ Compact and loose sand terrain, Concrete and Grass
  - ▶ Mostly flat with some slopes

- Binary Terrain



Uneven rocky



Rocky plateau



Rocky incline (lunar analog)



Coarse-grained loose sand



Compact sand

- Multi-Category Terrain (6 classes)



Rocky



Flat concrete



Compact sand




Grass




Dirt




Gravel





## Feature Mapping: t-SNE




Location categories




Terrain categories

## UQ Model Training



- Various combinations of CNNs and Optimized tuning with BOHB (Bayesian Optimization and Hyperband) method [Falkner2018]
- Also include SOTA benchmark models: Residual Network (ResNet) [Wang 2017], Fully Convolutional Network (FCN) [Wang 2017], Encoder [Fawaz 2019]
- 3 Uncertainty Quantification methods were applied on those models: Monte Carlo Dropout [Gal 2016], Monte Carlo DropConnect [Mobiny 2021], Flipout [Wen 2018]
- In total, 480 BOHB models + 48 benchmark models with their variants = 528 models

## Evaluation



Grad-CAM

$$H(\mathbb{P}) = - \sum_{c \in C} \mathbb{P}(c) \log \mathbb{P}(c)$$


Predictive Entropy

$$ECE = \sum_{i=1}^K P(i) \cdot |o_i - e_i|$$

Expected Calibration Error

- Grad-CAM, a back-propagation-based XAI method, locates contributing regions in the raw data for predicting specific labels.
- Predictive Entropy to measure the uncertainty associated with a models predictions.
- Expected Calibration Error (ECE) assesses the calibration of the probabilistic model. Helps determine if the predictions align with the actual outcomes.
- Metrics and Grad-CAM used in conjunction to better understand the outputs of our classifiers with high confidence.

## Evaluation



Grad-CAM

$$H(\mathbb{P}) = - \sum_{c \in C} \mathbb{P}(c) \log \mathbb{P}(c)$$

Predictive Entropy



$$ECE = \sum_{i=1}^K P(i) \cdot |o_i - e_i|$$

Expected Calibration Error



- Grad-CAM, a back-propagation-based XAI method, locates contributing regions in the raw data for predicting specific labels.
- Predictive Entropy to measure the uncertainty associated with a models predictions.
- Expected Calibration Error (ECE) assesses the calibration of the probabilistic model. Helps determine if the predictions align with the actual outcomes.
- Metrics and Grad-CAM used in conjunction to better understand the outputs of our classifiers with high confidence.

# Evaluation



## Weighted F1-score for all trained models (AP3200)



## Detection of Inconsistencies - Binary Terrain (AP3400)





## Detection of Inconsistencies - Multi-Class Terrain (AP3400)





# Evaluation

## Grad-CAM Visualization [Selvaraju et al 2017]



### ● Rock:



### ● Sand:





### ● Concrete:





## Grad-CAM Visualization


● Dirt:



● Gravel:



● Grass:



Advantages of using XAI and UQ methods in ML applications:

### Interpretability and Trust:

- **Grad-CAM:** Visualize and interpret model decisions by highlighting influential regions in input data.
- **Uncertainty Methods:** Provide insights into prediction reliability, promoting trust and cautious reliance on model outputs.

### Robustness and Bias Detection:

- **Grad-CAM:** Reveals model biases through visualizing influential features, aiding bias detection.
- **Uncertainty Methods:** Assess model robustness by capturing prediction variations and identifying areas of uncertainty.

# Thank you!

*mariela.de\_lucas\_alvarez@dfki.de*



Langer, M. et al (2021)

What Do We Want From Explainable Artificial Intelligence? A Stakeholder Perspective on XAI and a Conceptual Model Guiding Interdisciplinary XAI Research.

<https://doi.org/10.1016/j.artint.2021.103473>



Gilpin, L. et al (2019)

Explaining Explanations: An Overview of Interpretability of Machine Learning

<https://arxiv.org/pdf/1806.00069.pdf>



Ismail, A. A., Gunady, M., Bravo, H. C., & Feizi, S. (2020).

Benchmarking Deep Learning Interpretability in Time Series Predictions.

<http://arxiv.org/abs/2010.13924>



O'Sullivan, Conor (2020)

Interpretable vs Explainable Machine Learning

*Towards Data Science*

<https://towardsdatascience.com/interpretable-vs-explainable-machine-learning-1fa525e12f48>

-  Saveriano, M. et al (2019)  
Symbolic Task Compression in Structured Task Learning  
<https://doi.org/10.1109/IRC.2019.00033>
-  Montavon, G. et al (2017)  
Methods for Interpreting and Understanding Deep Neural Networks  
<https://arxiv.org/abs/1706.07979v1>
-  Falkner, S. et al (2018)  
BOHB: Robust and efficient hyperparameter optimization at scale  
<http://proceedings.mlr.press/v80/falkner18a/falkner18a.pdf>
-  Wang, Z. et al (2017)  
Timeseries classification from scratch with deep neural networks: A strong baseline  
<http://pmo78bb17.pic35.websiteonline.cn/upload/1611.pdf>
-  Fawaz, H.I. et al (2019)  
Deep learning for time series classification: a review  
<https://arxiv.org/pdf/1809.04356.pdf>



Zhou, B. et al (2016)

Learning Deep Features for Discriminative Localization

<https://dspace.mit.edu/handle/1721.1/112986>



Van der Maaten, L. & Hinton, G. (2008)

Visualizing Data using t-SNE

<https://www.jmlr.org/papers/volume9/vandermaaten08a/vandermaaten08a.pdf?fbclid=IwAR1DyJzXWzCgkVjPQHfOOGdLcUoqBZGmMzvYRzJF0>



Fawaz et al (2019)

ResNet model

<https://github.com/hfawaz/dl-4-tsc/blob/master/classifiers/resnet.py>



Fawaz et al (2019)

FCN model

<https://github.com/hfawaz/dl-4-tsc/blob/master/classifiers/fcn.py>



De Lucas Alvarez (2021)

Compact Neural Networks for Autonomous Robots

Dissertation for Doctoral Degree May 2021



Universität Bremen



Abdar et al (2021)

A review of uncertainty quantification in deep learning: Techniques, applications and challenges.

<https://doi.org/10.1016/j.inffus.2021.05.008>



Gal, Y. et al (2016)

Dropout as a bayesian approximation: Representing model uncertainty in deep learning

<http://proceedings.mlr.press/v48/gal16.pdf>



Mobiny, A. et al (2021)

Dropconnect is effective in modeling uncertainty of bayesian deep networks

<https://www.nature.com/articles/s41598-021-84854-x>



Wen W. et al (2018)

Flipout: Efficient pseudo-independent weight perturbations on mini-batches

<https://arxiv.org/pdf/1803.04386.pdf>



-  Selvaraju, Ramprasaath R., et al (2017)  
Grad-cam: Visual explanations from deep networks via gradient-based localization
-  Guo, C et al (2017)  
On calibration of modern neural networks
-  Naeini et al (2017)  
Obtaining well calibrated probabilities using bayesian binning