```java
/*
NOTE: this program doesnot handle every single error case
that is for you to figure out. Here, we only present essential functionality
*/
import java.io.*;

public class question55
{
    public static void main(String args[])throws IOException
    {
        InputStreamReader read=new InputStreamReader(System.in);
        BufferedReader in=new BufferedReader(read);

        int seats[]=new int[200];
        int bill=0;
        int n=0;

        //initializing the array with -1's to signify that a seat hasn't been occupied.
        We will insert 1 whenever a seat gets occupied
        for(int i=0;i<200;i++)
        {
            seats[i]=-1;
        }

        do
        {
            System.out.print("Enter \n1. to book seats\n0. to exit ->");
            n=Integer.parseInt(in.readLine());

            if(n==1)
            {

                System.out.print("Enter the seat type\n1. First class\n2. Business
                class\n3. Economy class ->");
                int seattype=Integer.parseInt(in.readLine());

                System.out.print("Enter the number of seats ->");
                int noofseats=Integer.parseInt(in.readLine());

                int startseatno=0;//this variable stores the starting seat number of the
                seats to assign
                if(seattype==1)
                {
                    for(int i=0;i<50;i++)//50 because the first 50 seats are first class
                    {
                        if(seats[i]==-1)
                        {
                            startseatno=i;
                            break;
                        }
                    }

                    //now reserving the seats
                    for(int i=startseatno;i<=noofseats;i++)
                    {
                        seats[i]=1;//1 means reserving the seats
                    }

                    bill=noofseats*20000;
                    System.out.println("Seats booked! Your bill is="+bill);
                }
                else if(seattype==2)
                {
                    for(int i=50;i<100;i++)
                    {
```

```java
                        if(seats[i]==-1)
                        {
                            startseatno=i;
                            break;
                        }
                    }

                    //now reserving the seats
                    for(int i=startseatno;i<=noofseats;i++)
                    {
                        seats[i]=1;//1 means reserving the seats
                    }

                    bill=noofseats*15000;
                    System.out.println("Seats booked! Your bill is="+bill);
                }
                else
                {
                    for(int i=100;i<200;i++)//50 because the first 50 seats are first
                    class
                    {
                        if(seats[i]==-1)
                        {
                            startseatno=i;
                            break;
                        }
                    }

                    //now reserving the seats
                    for(int i=startseatno;i<=noofseats;i++)
                    {
                        seats[i]=1;//1 means reserving the seats
                    }

                    bill=noofseats*10000;
                    System.out.println("Seats booked! Your bill is="+bill);
                }

            }

        }while(n!=0);

    }
}
```