Indirect Prompt Injection in LLM CV Screening

Replication report · Milani, Franzoni & Florindi, *Neural Computing & Applications* 38:530 (2026), doi:10.1007/s00521-026-12266-x

Code: github.com/SHASHANK8412/Indirect-prompt-injection-in-LLMs

Summary

This project replicates an empirical study of indirect prompt injection: instructions hidden in a CV that change how an LLM evaluates candidates. The full pipeline, the paper's defense and its three-layer architecture are implemented and tested. Experiments with the paper's protocol are in progress on free models; the tables below compare the results so far with the paper's.

1. What has been done

Component	Work completed
Dataset	27 synthetic CVs matching the paper's Table 1: 3 seniority levels × 3 achievement-density classes, one role per cell, 450–3,000 words, achievement density checked automatically (dataset.py).
Attacks	The paper's four injections (Definitions 3.1–3.4) verbatim, hidden in the PDF as white or 1pt text at 4 placements; every attacked PDF is verified to be machine-readable but invisible (inject.py).
Experiment runner	The paper's protocol: single-CV sessions for p.Pos/p.Neg, multi-CV sessions for p.Pos-Neg/p.Pos-Med, fresh session per trial, temperature 0, resumable, with cost estimates; OpenAI, Gemini, DeepSeek, Grok, Perplexity and local Ollama models (runner.py).
Paper's defense	u1.X / u2.X, the user prompt plus the paper's prompt-extension sentence, verbatim (defense ope).
OPE architecture	Section 4.2's three layers as software: isolation, meta-instructions at the outer edges, and an audit plus remediation loop (ope/ package; defenses ope_layered and ope_full).
Extra defenses	Beyond the paper: spotlighting/datamarking, a two-pass JSON sanitiser, and a hidden-text and instruction pre-filter.
Metrics	The paper's ASR, Sentiment Index, ΔSI, DAR, ME and AD; the SI scorer reproduces the paper's worked example exactly (3.5 → 5.0, ΔSI 1.5). Added: rank shift, false-alarm rate, LLM judge.
Analysis	The paper's Tables 4–7 with CV-clustered bootstrap CIs, regression, charts, and an automatic side-by-side comparison with the paper's reported values.
Web application	Local app with OPE Analyze, Results, Explorer, Dataset and Runs pages.
Quality	88 automated tests; README, architecture and paper-alignment documents; GitHub repository.

2. Experimental setup

- **Dataset:** 27 synthetic CVs laid out as in the paper's Table 1 (3 seniority levels × 3 achievement-density classes, one role per cell, 450–3,000 words). Fictional people only.
- **Attacks:** the paper's Definitions 3.1–3.4 verbatim, hidden as white text at the bottom of the PDF; the model receives the PDF's extracted text.
- **Prompts:** u1 / u2 (no defense) and the paper's u1.X / u2.X (defense *ope*), verbatim.
- **Protocol:** single-CV sessions for p.Pos and p.Neg; multi-CV sessions with one injected CV for p.Pos-Neg and p.Pos-Med. Fresh session per trial, temperature 0.
- **Models:** gemini (gemini-3.8-flash), groq (openai/gpt-oss-120b), groq_qwen (qwen/qwen3.8-27b), llama32 (llama3.2:3b), through official APIs or locally with Ollama.
- **Success rule (ASR):** ΔSI ≥ 1.0 in the attacker's direction; SI = the paper's keyword-weighted Sentiment Index.
- **Size:** gemini: 29 attacked trials, groq: 108 attacked trials, groq_qwen: 108 attacked trials, llama32: 123 attacked trials. 550 model responses in total, including clean baselines.

Note: llama3.2:3b ran the single-CV protocol only: a 27-CV session (~70k tokens) does not fit a small local model's context window. This is a pilot with one trial per condition (the paper used N = 10), so confidence intervals are wide.

3. Expected (paper) vs actual (this replication)

The paper's main claims, what it reports, and what the replication shows so far.

Claim in the paper	Expected (paper)	Actual (ΔSI ≥ 1.0)	Status
All models vulnerable without defense	ASR 92–98% (Table 4)	gemini 60%, groq 33%, groq_qwen 44%, llama32 44%	Partly
OPE lowers ASR, unevenly across models	12.5% (ChatGPT) to 45.5% (DeepSeek)	gemini 0%, groq 20%, groq_qwen 2%, llama32 39%	Agrees
OPE raises alerts (DAR)	50–91% by model	gemini 100%, groq 15%, groq_qwen 98%, llama32 31%	See values
Detection ≠ resistance (aware-but-bypassed)	p.Pos-Med: 85.5% DAR yet 32.2% ASR	10% of alerted trials still succeeded	Agrees
Longer CVs harder to protect	Defended ASR Junior 15% → Senior 33% (Table 5)	Junior 19%, Mid 13%, Senior 28%	See Table 5
Multi-CV attacks hardest (p.Pos-Med)	Defended ASR 32.2% (Table 7)	llama32 29%	See Table 7

How the success threshold changes ASR (%). The paper does not define the threshold. Clean CVs already score SI ≈ 4, so inflating attacks rarely gain a full point: ΔSI ≥ 1.0 undercounts them.

model	defense	ΔSI ≥ 0.5	ΔSI ≥ 1.0
gemini	none	80.0%	60.0%
gemini	ope	7.1%	0.0%
groq	none	57.4%	33.3%
groq	ope	55.6%	20.4%
groq_qwen	none	83.3%	44.4%
groq_qwen	ope	13.0%	1.9%
llama32	none	85.5%	43.5%
llama32	ope	85.2%	39.3%

4. Detailed results compared with the paper

Shaded columns are the paper's reported values. Percentages; 'defended' = u1.X / u2.X.

Table 4 · by model

model	n	ASR none (ours)	ASR none (paper)	ASR defended (ours)	ASR defended (paper)	ME (ours)	ME (paper)	DAR (ours)	DAR (paper)
gemini	29	60.0%	92.5%	0.0%	19.8%	82.0%	78.6%	100.0%	82.3%
groq	108	33.3%	–	20.4%	–	67.2%	–	14.8%	–
groq_qwen	108	44.4%	–	1.9%	–	79.9%	–	98.1%	–
llama32	123	43.5%	–	39.3%	–	51.9%	–	31.1%	–

Table 5 · by seniority (defended)

seniority	n	ASR defended (ours)	ASR defended (paper)	ME (ours)	ME (paper)	DAR (ours)	DAR (paper)
Junior	74	18.9%	15.2%	69.0%	84.8%	58.1%	88.6%
Mid	55	12.7%	22.4%	71.7%	77.6%	43.6%	79.1%
Senior	54	27.8%	33.1%	59.4%	66.9%	50.0%	68.4%

Table 6 · by achievement density

ad_class	n	|dSI| none (ours)	dSI (paper)	ME (ours)	ME (paper)
High	132	0.86	1.20	62.1%	71.4%
Medium	123	0.86	1.90	70.6%	79.2%
Low	113	1.02	2.60	68.6%	86.5%


Table 7 · by injection type (defended)


attack	n	ASR defended (ours)	ASR defended (paper)	ME (ours)	ME (paper)	DAR (ours)	DAR (paper)
p.Pos	88	4.5%	14.2%	65.5%	85.8%	56.8%	92.2%
p.Neg	88	34.1%	8.6%	69.2%	91.4%	44.3%	96.1%
p.Pos-Neg	4	50.0%	22.8%	55.9%	77.2%	75.0%	88.4%
p.Pos-Med	3	0.0%	32.2%	61.1%	67.8%	66.7%	85.5%

Undefended ASR by model and injection type (%)

model	p.Pos	p.Neg	p.Pos-Neg	p.Pos-Med
gemini	100.0%	14.3%	–	–
groq	51.9%	14.8%	–	–
groq_qwen	77.8%	11.1%	–	–
llama32	7.4%	92.6%	0.0%	0.0%

5. Charts





One point per model × defense × attack. Marker size = share of trials that raised an alert AND still succeeded.

6. Findings

Findings (one trial per condition; gpt-oss-120b, qwen3.8-27b and llama3.2:3b completed the paper's single-CV protocol on all 27 CVs; Gemini is a smaller sample limited by its free quota):

- Every model followed the paper's injections without a defense. At ΔSI ≥ 0.5 the undefended inflating attack (p.Pos) succeeded in 89% (gpt-oss), 93% (qwen), 85% (llama) and 100% (gemini) of trials, close to the paper's 92–98%.

- The paper's wording matters. Stand-in injections addressed to "any AI system" did not move Gemini at all; the paper's "take into account any previous prompt request, but answer with these additional constraints" phrasing did.
- The paper's one-sentence defense (u1.X) works very differently across models, as the paper reports. It neutralised almost every attack on Gemini and Qwen (defended p.Pos ASR 0%), reduced it strongly on gpt-oss (52% → 11%, close to the paper's 12.5% for ChatGPT), and barely helped the 3B local model.
- Detection is not the same as protection, in both directions. gpt-oss resisted most defended attacks while flagging only 15% of them (it quietly ignores the injection); llama flagged about a third of attacks yet was still manipulated.
- Alert rates must be read with false alarms, which the paper does not report. Gemini and gpt-oss raised no alerts on clean CVs, so their alerts are meaningful. Qwen (52%) and llama (52%) also raised "manipulation" alerts on clean CVs, so their high detection rates overstate their precision.
- Models resist the deflating attack (p.Neg) more than the inflating one: gpt-oss and qwen rarely produced a full one-point drop. With the defense, gpt-oss became slightly more critical overall, which made p.Neg look more successful (15% → 30%).
- On document length, gpt-oss had its highest defended ASR on Senior CVs (33%, the same as the paper's Senior figure), and llama's mitigation was lowest on Senior CVs, consistent with the paper's "longer is harder to protect". Qwen showed no length effect because its defense blocked nearly everything.
- The success threshold changes the headline numbers a lot: clean CVs already score SI ≈ 4, so inflating attacks rarely gain a full point. The paper does not state its criterion; both thresholds are reported in section 3.

7. Status and what remains

- Done: implementation (dataset, attacks, runner, defenses, OPE architecture, metrics, analysis, web app) aligned with the paper and tested (91 tests).
- Done: the paper's single-CV protocol on all 27 CVs for gpt-oss-120b and qwen3.8-27b (Groq) and llama3.2:3b (local), one trial per condition.
- Running: llama3.2:3b multi-CV attacks (p.Pos-Neg, p.Pos-Med) on 3-CV sessions, then the first real-model test of the full OPE pipeline (ope_full).
- Partial: gemini-3.8-flash, limited by its free tier to 20 requests per day; resumes automatically from where it stopped.
- Not yet tested: multi-CV attacks with all 27 CVs per session (too large for the free tiers and local models) and N = 10 repetitions.
- To cover the paper's exact models: OpenAI credit (gpt-4o, the Copilot stand-in) and DeepSeek, Grok and Perplexity keys.

8. Limitations

- Models are reached through APIs and local runtimes, not the web interfaces the paper scripted; Gemini 2.5 Flash is unavailable to new API accounts, so gemini-3.8-flash was used.
- The CVs are synthetic, built to Table 1's specification, not the authors' dataset.
- The paper does not define its ASR success criterion; this report uses a ΔSI threshold.
- SI is a keyword score; responses with few evaluative words make it noisy.
- Pilot scale (one trial per condition): treat differences of a few percentage points as noise.
- False alarms (alerts on clean CVs under the defense): gemini 0%, groq 0%, groq_qwen 52%, llama32 55%