

附件 5:

逆变器参数及价格表

序号	型号	直流输入			交流输出			逆变效率 (80%阻性负载)	使用环境温度 (℃)	外观尺寸 (mm) 宽×高×深	参考价格 (元/台)
		额定电压 (V)	额定电流 (A)	允许输入电压范围 (V)	额定电压/频率 (V/Hz)	额定电流 (A)	额定功率 (kW)				
1	SN1	DC24	25	21~32	AC220/50	2.2	0.4	84%	-20~50	200×365×395	2900
2	SN2	DC24	50	21~32	AC220/50	4.5	0.8	84%	-20~50	200×365×395	4500
3	SN3	DC48	24	42~64	AC220/50	4.5	0.8	86%	-20~50	200×365×395	4500
4	SN4	DC48	48	42~64	AC220/50	9.0	1.6	86%	-20~50	200×365×395	6900
5	SN5	DC48	73	42~64	AC220/50	13.6	2.4	86%	-20~50	400×750×470	10200
6	SN6	DC48	115	42~64	AC220/50	22.7	4	90%	-20~50	400×750×47	15000
7	SN7	DC110	30	99~150	AC220/50	13.6	2.4	90%	-20~50	458×400×470	10200
8	SN8	DC110	51	99~150	AC220/50	22.7	4	90%	-20~50	400×750×470	15300
9	SN9	DC110	101	99~150	AC220/50	45.5	8	92%	-20~50	800×1800×600	35000
10	SN10	DC110	202	99~150	AC220/50	91	16	92%	-20~50	800×2260×600	63800
11	SN11	DC220	5	180~300	AC220/50	4.5	0.8	94%	-20~50	205×365×425	4500
12	SN12	DC220	10	180~300	AC220/50	9.1	1.6	94%	-20~50	205×365×425	6900
13	SN13	DC220	15.2	180~300	AC220/50	13.6	2.4	94%	-20~50	205×365×425	10300
14	SN14	DC220	25.3	180~300	AC220/50	22.7	4.0	94%	-20~50	400×740×470	15300
15	SN15	DC220	37.9	180~300	AC220/50	34.1	6.0	94%	-20~50	400×740×470	22000
16	SN16	DC220	48.4	180~300	AC220/50	45.5	8	94%	-20~50	400×750×470	35000
17	SN17	DC650	40	250~800	AC230/50	15	10	97.3%	-25~60	550×650×250	43750
18	SN18	DC650	40	330~800	AC230/50	18	12	97.3%	-25~60	550×650×250	54700