

ITEM NO.	RATING	А
1	4000 AMP.	20
2	5000 AMP.	25

ELECTRICAL SPECIFICATION IEC: 60137:2017

- 1) Rated Voltage......1.1kV.
- 2) Dry Power Frequency Withstand Voltage Test (One Minute)......10kV.

OTHER:-

- 1) End Copper Palm Will be Electrotinned 12 to 15 Microns.
- 2) Electroytic Copper With High Electrical Conductivity.
- 3) Colour brick red.

THE COPYRIGHT OF THESE DRAWINGS AND OF ALL ANNEXES WHITCH ARE ENTRUSTED TO A PERSON'S CARE ALWAYS REMAIN THE PROPERTY OF OUR FIRM. THEY MUST NOT BE COPIED OR DUPLICATED.NOT SHOWN TO OR PLACED AT THE DISPOSAL OF THIRD PERSONS WITHOUT OUR WRITTEN CONSENT.

1
_

1.1kV Epoxy Bushing

MANUFACTURER SUNSHINE ENGINEERING

Email :- sunshineengineering23@gmail.com Mob. :- +91 7499544230

All dimensions are in mm						
SCALE	NTS	REF.				
DRG	UKN	PROJECTION				
CHD	Pitale	· 🖃 🕀				
APPD	Pitale	Drawing No.	Rev.			
DATE	18/08/22	SE/EB01/004				

		120±1 96±0.5	-	6, HOLES	2
1	-	•			
		=======================================	100		
190	+	=====		230±1	
		=======================================	100		
		<u>A</u> 60			0
				0	0
		0	0	0	
		0	0		