

Jubilee

INSURANCE

IPRS/LEXISNEXIS/KRA

APPLICATION PROGRAMMING INTERFACE DOCUMENTATION

(API v1.1)

Date	Version	Description of change	Revised By
24 th January 2025	1.0	Initial Draft	Joseph Kaigai
29 th January 2025	1.0	Initial Draft	Samuel Murani
27 th March 2025	1.1	Official Release	Samuel Murani Joseph Kaigai

Confidentiality Disclaimer

This document and the information in it are provided in confidence, and may not be disclosed to any third party or used for any other purpose without the express written permission of jubilee insurance ltd. Any form of reproduction, dissemination, copying, disclosure, modification, distribution and or publication of this material is strictly prohibited.

Table of Contents

Introduction	4
IPRS	4
Scope	4
Integration Requirements.....	4
API Details.....	4
Search IPRS Interface	5
Ping IPRS Interface.....	7
Search by Alien ID Interface	9
Search by Passport Number Interface	10
Search by Birth Certificate Number Interface	12
Search by Death Certificate Number Interface	13
Bulk IPRS Search Interface	15
LEXISNEXIS	16
Scope	16
Integration Requirements.....	16
API Details.....	16
Search Record Interface	17
KRA	20
Scope	20
Integration Requirements.....	20
API Details.....	20
Validate ID Number Interface	21

Introduction

This document provides a comprehensive guide to the APIs within the Jubilee Insurance Enterprise Service Bus (ESB) that facilitate access to services from the Integrated Population Registration System (IPRS), LexisNexis, and the Kenya Revenue Authority (KRA). It is designed to assist both internal teams and third-party businesses in integrating and utilizing these APIs effectively.

The guide outlines the technical specifications, integration steps, and best practices to ensure seamless, secure, and reliable interaction with IPRS, LexisNexis, and KRA data and services through the ESB.

IPRS

Scope

The scope of this document is an API specification for:

- ❖ Search IPRS API (REST)
- ❖ Ping IPRS API (REST)
- ❖ Search by Alien ID API (REST)
- ❖ Search by Passport Number API (REST)
- ❖ Search by Birth Certificate Number API (REST)
- ❖ Search by Death Certificate Number API (REST)
- ❖ Bulk IPRS Search API (REST)
- ❖ Bulk KRA Search API (REST)
- ❖ KRA Search API (REST)
- ❖ Search IPRS V1 Pin & ID API (REST)

Integration Requirements

- Communication protocol will be HTTPS.
- REST integration will be as per the guidelines.

API Details

This contains the following interfaces:

- ❖ Search IPRS Interface
- ❖ Ping IPRS Interface
- ❖ Search by Alien ID Interface

- ❖ Search by Passport Number Interface
- ❖ Search by Birth Certificate Number Interface
- ❖ Search by Death Certificate Number Interface
- ❖ Bulk IPRS Search Interface
- ❖ Bulk KRA Search Interface
- ❖ KRA Search Interface
- ❖ Search IPRS V1 Pin & ID Interface

Expected response statuses

These are responses that the API might return depending on specific circumstance.

Status Code	Description	Details
200 OK	Success	The request was sent successfully. Returns a success message.
400 Bad Request	Invalid Request	The request contained invalid parameters.
401 Unauthorized	Authentication Failed	The JWT token is missing, invalid, or expired.
404 Not Found	Not Found	No matching records were found.
500 Internal Server Error	Server Error	An unexpected error occurred on the server.

Search IPRS Interface

- ❖ This interface searches for an individual in the system.
- ❖ Full URL: `{{BASE_URL}}/iprs/searchV2/{{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_SEARCH_USER
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for an individual.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/searchV2/{Business}}

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
BUSINESS	YES	String	The business name.

Request Body

Body Requirements (Form Data)

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
{
  "identifier":"ID_NUMBER",
```

```
"value": "32996206"
}
```

Response Details

The response will contain details of the individual.

Sample Response

```
{
  "success": true,
  "status": {
    "code": 200,
    "message": "OK"
  },
  "details": "Request was successful",
  "data": {
    "errorOccurred": false,
    "isFingerprintNil": null,
    "isPhotoNil": null,
    "isSignatureNil": null,
    "dateOfDeath": null,
    "otherName": null,
    "surname": null,
    "occupation": "NA",
    "ethnicGroup": null,
    "dateOfBirth": "06/05/1995",
    "placeOfLive": null,
    "pin": null,
    "placeOfDeath": null,
    "placeOfBirth": null,
    "serialNumber": null,
    "clan": null,
    "firstName": null,
    "idNumber": "12345678",
    "citizenship": "Kenyan",
    "gender": "Female",
    "dateOfIssue": null,
    "regOffice": null
  },
  "pagination": null,
  "error": null
}
```

Ping IPRS Interface

- ❖ This interface searches for an individual in the system.
- ❖ Full URL: `{{BASE_URL}}/iprs/pingIprs/{{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_PING_SEARCH
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Pings the system.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/searchV2/{Business}}

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
Business	YES	String	The business name.

Request Body

Body Requirements (Form Data)

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
{
  "identifier":"ID_NUMBER",
  "value":"30183275"
}
```

Response Details

The response will contain details of the individual.

Search by Alien ID Interface

- ❖ This interface searches for an individual in the system based on the alien id.
- ❖ Full URL: `{{BASE_URL}}/iprs/searchUsingAlienId /{{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_SEARCH_USER_BY_ALIENID
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for an individual.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/searchUsingAlienId /{{Business}}

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes

Content-Type	Set to application/json.	String	Yes
--------------	--------------------------	--------	-----

Path Parameters

Parameter	Required	Data Types	Description
Business	YES	String	The business name.

Request Body

Body Requirements (Form Data)

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
{
  "identifier":"ALIEN_ID",
  "value":"12345678"
}
```

Response Details

The response will contain details of the individual.

Search by Passport Number Interface

- ❖ This interface searches for an individual in the system based on the policy number.
- ❖ Full URL: `{{BASE_URL}}/iprs/searchUsingPassportNumber / {{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_SEARCH_USER_BY_POLICYNO
--------------	------------------------------

Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for an individual.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/searchUsingPassportNumber /{{Business}}

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
Business	YES	String	The business name.

Request Body

Body Requirements

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.
idNumber	YES	String	The id number.

Sample Request

```
{
  "identifier":"PASSPORT",
```

```
"value": "12345678",  
"idNumber": "12345678"  
}
```

Response Details

The response will contain details of the individual.

Search by Birth Certificate Number Interface

- ❖ This interface searches for an individual in the system based on the birth certificate number.
- ❖ Full URL: `{{BASE_URL}}/iprs/searchUsingBirthCertificateNumber/{{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_SEARCH_USER_BY_BIRTHCERT
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for an individual.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	<code>/iprs/searchUsingBirthCertificateNumber/{{Business}}</code>

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
Business	YES	String	The business name.

Request Body

Body Requirements

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
{
  "identifier":"BIRTH_CERTIFICATE",
  "value":"12345678"
}
```

Response Details

The response will contain details of the individual.

Search by Death Certificate Number Interface

- ❖ This interface searches for an individual in the system based on the death certificate number.
- ❖ Full URL: `{{BASE_URL}}/ iprs/searchUsingDeathCertificateNumber /{{Business}}`
- ❖ Method: POST

Description

Interface ID	IPRS_SEARCH_USER_BY_DEATHCERT
Version	1.1
Interface Type	REST

Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for an individual.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/searchUsingDeathCertificateNumber / {{Business}}

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
Business	YES	String	The business name.

Request Body

Body Requirements

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
{
  "identifier":"DEATH_CERTIFICATE",
  "value":"12345678"
}
```

Response Details

The response will contain details of the individual.

Bulk IPRS Search Interface

- ❖ This interface searches for individuals in the system in bulk based on the id numbers.
- ❖ Full URL: `{{BASE_URL}}/iprs/bulk-search`
- ❖ Method: POST

Description

Interface ID	IPRS_BULK_SEARCH
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Bulk searches individuals.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST
Endpoint	/iprs/bulk-search

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Request Body

Body Requirements

Parameter	Required	Data Types	Description
identifier	YES	String	The search identifier.
value	YES	String	The value of the identifier.

Sample Request

```
[
  {
    "identifier":"ID_NUMBER",
    "value":"12345678"
  },
  {
    "identifier":"ID_NUMBER",
    "value":"13579246"
  },
  {
    "identifier":"ID_NUMBER",
    "value":"87654321"
  }
]
```

Response Details

The response will contain details of the individuals.

LEXISNEXIS

Scope

The scope of this document is an API specification for:

- ❖ Search Record API (REST)

Integration Requirements

- Communication protocol will be HTTPS.
- REST integration will be as per the guidelines.

API Details

This contains the following interfaces:

❖ Search Record Interface

Expected response statuses

These are responses that the API might return depending on specific circumstance.

Status Code	Description	Details
200 OK	Success	The request was sent successfully. Returns a success message.
400 Bad Request	Invalid Request	The request contained invalid parameters.
401 Unauthorized	Authentication Failed	The JWT token is missing, invalid, or expired.
404 Not Found	Not Found	No matching records were found.
500 Internal Server Error	Server Error	An unexpected error occurred on the server.

Search Record Interface

- ❖ This interface searches for a user in the system.
- ❖ Full URL: `{{BASE_URL}}/lexis/search/{{BUSINESS}}`
- ❖ Method: POST

Description

Interface ID	LEXIS_SEARCH_USER
Version	1.1
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Searches for a user.
Rules	Requires a valid JWT token in the Authorization header. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	POST

Endpoint	/lexis/search/{{BUSINESS}}
----------	----------------------------

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes
Content-Type	Set to application/json.	String	Yes

Path Parameters

Parameter	Required	Data Types	Description
BUSINESS	YES	String	The business name.

Request Body

Body Requirements (Form Data)

Parameter	Required	Data Types	Description
firstName	YES	String	The user's first name.
middleName	NO	String	The user's middle name.
lastName	YES	String	The user's last name.
gender	YES	String	The user's gender.
dob	YES	String	The user's date of birth in YYYY-MM-DD format.
nationalIdentificationNumber	NO	String	The user's national ID NUMBER.
countryCode	YES	String	The country code.
entityType	YES	String	The entity type.

sourceName	YES	String	The source.

Sample Request

```
{
  "firstName": "joseph",
  "middleName": "",
  "lastName": "Karanja",
  "gender": "Male",
  "dob": "1992-01-01",
  "nationalIdentificationNumber": "",
  "countryCode": "KEN",
  "entityType": "Individual",
  "sourceName": "Portals"
}
```

Response Details

The response will contain details of the individual.

Sample Response

```
{
  "success": true,
  "status": {
    "code": 200,
    "message": "OK"
  },
  "details": "Request was successful",
  "data": {
    "BestCountryScore": -1.0,
    "BestNameScore": 96.0,
    "EntityScore": 96.0,
    "ReasonListed": "National:PEP:Courts",
    "entityDetails": [
      {
        "Comments": "Starting 2007",
        "ID": 0,
        "Type": "Occupation",
        "Value": "Judge of the High Court of Kenya, appointed December 24, 2007."
      },
      {
        "Comments": "Karanja, Joseph Raphael | https://members.worldcompliance.com/metawatch2.aspx?id=788c9bd4-070b-417b-80ef-9c5722e1e27f",
        "ID": 0,

```

```

      "Type": "Other",
      "Value": "Link to WorldCompliance Online Database"
    },
    {
      "Comments": "https://web.archive.org/web/20240613063908/https://judiciary.go.ke/team_member/hon-justice-joseph-r-karanja/ | https://archive.gazettes.africa/archive/ke/2013/ke-government-gazette-dated-2013-10-04-no-145.pdf | https://www.the-star.co.ke/news/2023-03-16-man-in-court-on-suspicion-of-murdering-wife",
      "ID": 0,
      "Type": "Other",
      "Value": "Sources of Record Information"
    },
    {
      "Comments": null,
      "ID": 0,
      "Type": "PlaceOfBirth",
      "Value": "Nairobi County, Kenya"
    }
  ]
},
"pagination": null,
"error": null
}

```

KRA

Scope

The scope of this document is an API specification for:

- ❖ Validate ID Number API(REST)

Integration Requirements

- Communication protocol will be HTTPS.
- REST integration will be as per the guidelines.

API Details

This contains the following interfaces:

- ❖ Validate ID Number Interface

Expected response statuses

These are responses that the API might return depending on specific circumstance.

Status Code	Description	Details
200 OK	Success	The request was sent successfully. Returns a success message.
400 Bad Request	Invalid Request	The request contained invalid parameters.
401 Unauthorized	Authentication Failed	The JWT token is missing, invalid, or expired.
417 Invalid Id	Not Found	No matching records were found.
500 Internal Server Error	Server Error	An unexpected error occurred on the server.

Validate ID Number Interface

- ❖ This interface validates an id number.
- ❖ Full URL: `{{BASE_URL}} /api/v1/kra/validate-id?typeOfTaxpayer={country}&taxpayerID={{idNo}}`
- ❖ Method: Get

Description

Interface ID	KRA_VALIDATE_ID
Version	1.0
Interface Type	REST
Target Applications	ESB (Enterprise Service Bus), Third-Party Applications
Description	Validates an id number.
Rules	Requires a valid JWT token in the Authorization header. Requires the query parameters. All required fields in the request body must be provided.
REST Message Format	JSON
REST Method	GET
Endpoint	/api/v1/kra/validate-id

Request Details

Header Requirements

Header Name	Description	Data Type	Required
Authorization	Bearer Token for auth (JWT).	String	Yes

Query Parameters

Parameter	Required	Data Types	Description
typeOfTaxpayer	YES	String	The country the individual belongs i.e. KE
taxpayerID	YES	String	The id number.

Notes

Following are the options for the typeOfTaxpayer parameter:

- COMP: Non-Individual – Company
- KE: Individual - Kenyan Citizen
- NKE: Individual – Non-Kenyan Resident
- NKENR: Individual – Non-Kenyan Non-Resident

The error codes from the KRA platform:

Response Code	Status	Message
30000	OK	Valid ID
30001	NOK	Invalid User ID or Password
30002	NOK	Invalid ID
30003	NOK	iPage not Done

Response Details

The response contains the status of the request.

Sample Response

```
{  
  "success": true,
```

```
"status": {  
  "code": 200,  
  "message": "OK"  
},  
"details": "Request was successful",  
"data": {  
  "responseCode": "30000",  
  "message": "Valid ID",  
  "status": "OK",  
  "pin": "A009123456X",  
  "taxpayerName": "John Doe"  
},  
"pagination": null,  
"error": null  
}
```

Live Free!