Housing API (2.0)

Download OpenAPI specification: Download

areas

Api List Areas

List areas, with optional fuzzy search and pagination.

QUERY PARAMETERS

`q` >	Q (string) or Q (null) (Q) Fuzzy search by area name
`limit`	integer (Limit) [1 .. 200] Default: `50`

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /areas

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "area_code": "string",
      "area_name": "string"
   }
]
```

Api Get Area

Retrieve a single area by area_code.

PATH PARAMETERS

area_code required	string (Area Code)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /areas/{area_code}

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "area_code": "string",
    "area_name": "string"
}
```

Api Postcode

List postcodes belonging to the specified area_code.

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

limit	integer (Limit) [1 .. 200] Default: 50

Responses

> 200 Successful Response

> 400 Invalid input.

> 404 Resource not found.

> 422 Validation Error

GET /areas/{area_code}/postcodes

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "postcode": "string",
      "area_code": "string",
      "area_name": "string"
   }
]
```


---

postcode_map

Get Postcode Areas

PATH PARAMETERS

postcode required	string (Postcode)

Responses

> 200 Successful Response

> 400 Invalid input.

> 404 Resource not found.

> **422** Validation Error

GET /postcode_map/{postcode}

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "area_name": "string"
}
```

Get Postcode Fuzzy

QUERY PARAMETERS

q >	Q (string) or Q (null) (Q) Fuzzy search by postcode
limit	integer (Limit) [1 .. 200] Default: 50

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /postcode_map

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "postcode": "string",
      "area_code": "string",
      "area_name": "string"
   }
]
```


---

rent_stats_official

Api Get Rent Stats

QUERY PARAMETERS

area_code required	string (Area Code)
time_period required	string (Time Period)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /rent_stats_official/rent-stats

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "time_period": "string",
    "area_code": "string",
    "region_or_country_name": "string",
  - "overall": {
        "index": 0,
        "rental_price": 0,
        "annual_change": 0
    },
  - "one_bed": {
        "index": 0,
        "rental_price": 0
    },
  - "two_bed": {
        "index": 0,
        "rental_price": 0
    },
  - "three_bed": {
        "index": 0,
        "rental_price": 0
    },
```

```
  - "property_prices": {
        "detached": 0,
        "semidetached": 0,
        "terraced": 0,
        "flat_maisonette": 0
    }
}
```

Api Get Rent Stats Series

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

from >	From (string) or From (null) (From) Start time period (YYYY-MM)
to >	To (string) or To (null) (To) End time period (YYYY-MM)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /rent_stats_official/areas/{area_code}/rent-stats

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "time_period": "string",
      "area_code": "string",
      "region_or_country_name": "string",
    + "overall": { … },
    + "one_bed": { … },
    + "two_bed": { … },
    + "three_bed": { … },
    + "property_prices": { … }
   }
]
```

Api Get Rent Stats Latest

PATH PARAMETERS

area_code required	string (Area Code)

Responses

- **200** Successful Response
- **400** Invalid input.
- **404** Area not found, or no rent stats available.
- **422** Validation Error

GET /rent_stats_official/areas/{area_code}/rent-stats/latest

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "time_period": "string",
    "area_code": "string",
    "region_or_country_name": "string",
  - "overall": {
        "index": 0,
        "rental_price": 0,
        "annual_change": 0
    },
  - "one_bed": {
        "index": 0,
        "rental_price": 0
    },
  - "two_bed": {
        "index": 0,
        "rental_price": 0
    },
  - "three_bed": {
        "index": 0,
        "rental_price": 0
    },
  - "property_prices": {
        "detached": 0,
        "semidetached": 0,
        "terraced": 0,
        "flat_maisonette": 0
    }
}
```

Api Get Rent Stats Availability

PATH PARAMETERS

area_code required	string (Area Code)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Area not found.

> **422** Validation Error

GET /rent_stats_official/areas/{area_code}/rent-stats/availability

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "area_code": "string",
    "min_time_period": "string",
    "max_time_period": "string",
    "count": 0
}
```

Api Get Rent Trend Plot

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

from >	From (string) or From (null) (From) Start time period (YYYY-MM)
to >	To (string) or To (null) (To) End time period (YYYY-MM)
metric	string (Metric) Default: `"rental_price"` Enum: `"rental_price"` `"index_value"` `"annual_change"`
bedrooms	string (Bedrooms) Default: `"overall"` Enum: `"overall"` `"1"` `"2"` `"3"`

Responses

— **200** PNG image

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /rent_stats_official/areas/{area_code}/rent-trend.png

Response samples

400 404 422

Content type
application/json

Copy

```
{
  "detail": "string"
```

```
}
```

Api Rent Trend By Name

QUERY PARAMETERS

`area` required	string (Area) Area name, e.g. Leeds
`from` >	From (string) or From (null) (From) Start time period (YYYY-MM)
`to` >	To (string) or To (null) (To) End time period (YYYY-MM)
`metric`	string (Metric) Default: `"rental_price"` Enum: `"rental_price"` `"index_value"` `"annual_change"`
`bedrooms`	string (Bedrooms) Default: `"overall"` Enum: `"overall"` `"1"` `"2"` `"3"`

Responses

— **200** PNG image

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET `/rent_stats_official/areas/rent-trend.png`

Response samples

400 404 422

Content type
application/json

Copy

```
{
    "detail": "string"
}
```

sales_official

List official sales transactions (supports search/filtering)

QUERY PARAMETERS

postcode_like >	Postcode Like (string) or Postcode Like (null) (Postcode Like) Fuzzy postcode (ignores spaces)
uuid_prefix >	Uuid Prefix (string) or Uuid Prefix (null) (Uuid Prefix) UUID prefix
date_from >	Date From (string) or Date From (null) (Date From)
date_to >	Date To (string) or Date To (null) (Date To)
min_price >	Min Price (integer) or Min Price (null) (Min Price)
max_price >	Max Price (integer) or Max Price (null) (Max Price)
property_type >	Property Type (string) or Property Type (null) (Property Type)
new_build >	New Build (boolean) or New Build (null) (New Build)
tenure >	Tenure (string) or Tenure (null) (Tenure)
limit	integer (Limit) [1 .. 200] Default: 50

`offset`	integer (Offset) `>= 0` Default: `0`
`sort_by`	string (Sort By) Default: `"transaction_date"` Enum: `"transaction_date"` `"price"`
`order`	string (Order) Default: `"desc"` Enum: `"asc"` `"desc"`
`include_total`	boolean (Include Total) Default: `false`

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ],
```

```
  - "meta": {
        "limit": 0,
        "offset": 0,
        "count": 0,
        "total": 0
    },
  - "links": {
        "self": "string",
        "next": "string",
        "prev": "string"
    }
}
```

Get a specific sales transaction

PATH PARAMETERS

`transaction_uuid` required	string <uuid> (Transaction Uuid)

Responses

- **200** Successful Response
- **400** Invalid input.
- **404** Resource not found.
- **422** Validation Error

GET `/sales_official/transactions/{transaction_uuid}`

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "transaction_uuid": "string",
    "price": 0,
    "transaction_date": "2019-08-24",
    "postcode": "string",
    "area_code": "string",
    "property_type": "D",
    "new_build": true,
    "tenure": "F",
    "paon": "string",
    "saon": "string",
  - "links": {
        "self": "sales_official/44F406B7-3032-1095-E063-4704A8C048D4"
    }
}
```


List official sales transactions for a given area (supports filtering)

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

date_from >	Date From (string) or Date From (null) (Date From)
date_to >	Date To (string) or Date To (null) (Date To)
min_price >	Min Price (integer) or Min Price (null) (Min Price)
max_price >	Max Price (integer) or Max Price (null) (Max Price)
property_type >	Property Type (string) or Property Type (null) (Property Type)
new_build >	New Build (boolean) or New Build (null) (New Build)

tenure >	Tenure (string) or Tenure (null) (Tenure)
limit	integer (Limit) [1 .. 200] Default: 50
offset	integer (Offset) >= 0 Default: 0
sort_by	string (Sort By) Default: "transaction_date" Enum: "transaction_date" "price"
order	string (Order) Default: "desc" Enum: "asc" "desc"
include_total	boolean (Include Total) Default: false

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official/areas/{area_code}

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ],
  - "meta": {
        "limit": 0,
        "offset": 0,
        "count": 0,
        "total": 0
    },
  - "links": {
        "self": "string",
        "next": "string",
        "prev": "string"
    }
}
```

List official sales transactions for a given postcode (supports filtering)

PATH PARAMETERS

postcode required	string (Postcode)

QUERY PARAMETERS

date_from >	Date From (string) or Date From (null) (Date From)
date_to >	Date To (string) or Date To (null) (Date To)
min_price >	Min Price (integer) or Min Price (null) (Min Price)
max_price >	Max Price (integer) or Max Price (null) (Max Price)
property_type >	Property Type (string) or Property Type (null) (Property Type)
new_build >	New Build (boolean) or New Build (null) (New Build)
tenure >	Tenure (string) or Tenure (null) (Tenure)
limit	integer (Limit) [1 .. 200] Default: 50

offset	integer (Offset) >= 0 Default: 0
sort_by	string (Sort By) Default: "transaction_date" Enum: "transaction_date" "price"
order	string (Order) Default: "desc" Enum: "asc" "desc"
include_total	boolean (Include Total) Default: false

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official/postcodes/{postcode}

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ],
```

```
  - "meta": {
        "limit": 0,
        "offset": 0,
        "count": 0,
        "total": 0
    },
  - "links": {
        "self": "string",
        "next": "string",
        "prev": "string"
    }
}
```


Get aggregated official sales stats for an area and month

QUERY PARAMETERS

`area_code` required	string (Area Code)
`time_period` required	string (Time Period)
`min_price` >	Min Price (number) or Min Price (null) (Min Price)
`max_price` >	Max Price (number) or Max Price (null) (Max Price)
`property_type` >	Property Type (string) or Property Type (null) (Property Type)
`new_build` >	New Build (boolean) or New Build (null) (New Build)
`tenure` >	Tenure (string) or Tenure (null) (Tenure)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official/sales-stats

Response samples

200 400 404 422

Content type
application/json

Copy


```
{
    "area_code": "string",
    "time_period": "string",
    "count": 0,
    "avg_price": 0,
    "min_price": 0,
    "max_price": 0,
    "total_value": 0,
    "property_type": "D",
    "new_build": true,
    "tenure": "F"
}
```


Get time-series of aggregated official sales stats for an area

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

date_from >	Date From (string) or Date From (null) (Date From)
date_to >	Date To (string) or Date To (null) (Date To)
min_price >	Min Price (number) or Min Price (null) (Min Price)

max_price >	Max Price (number) or Max Price (null) (Max Price)
property_type >	Property Type (string) or Property Type (null) (Property Type)
new_build >	New Build (boolean) or New Build (null) (New Build)
tenure >	Tenure (string) or Tenure (null) (Tenure)
limit	integer (Limit) [1 .. 500] Default: 240
offset	integer (Offset) >= 0 Default: 0

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official/areas/{area_code}/sales-stats

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "area_code": "string",
- "items": [
   + { … }
  ]
}
```

Get latest available aggregated official sales stats for an area

PATH PARAMETERS

area_code required	string (Area Code)

QUERY PARAMETERS

min_price >	Min Price (number) or Min Price (null) (Min Price)
max_price >	Max Price (number) or Max Price (null) (Max Price)
property_type >	Property Type (string) or Property Type (null) (Property Type)
new_build >	New Build (boolean) or New Build (null) (New Build)
tenure >	Tenure (string) or Tenure (null) (Tenure)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /sales_official/areas/{area_code}/sales-stats/latest

Response samples

200 400 404 422

Content type
application/json

Copy


```
{
    "area_code": "string",
    "time_period": "string",
    "count": 0,
    "avg_price": 0,
    "min_price": 0,
    "max_price": 0,
    "total_value": 0,
    "property_type": "D",
    "new_build": true,
    "tenure": "F"
}
```

Get min/max months available for official sales stats in an area

PATH PARAMETERS

area_code required	string (Area Code)

Responses

- **200** Successful Response
- **400** Invalid input.
- **404** Resource not found.
- **422** Validation Error

GET /sales_official/areas/{area_code}/sales-stats/availability

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "area_code": "string",
    "min_time_period": "string",
    "max_time_period": "string",
    "months": 0
}
```

---

rent_user

Api Create Rental Record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

postcode required	string (Postcode) [2 .. 12] characters UK postcode (normalized in service).
area_code >	Area Code (string) or Area Code (null) (Area Code) Area code, e.g. E08000035.
time_period required	string (Time Period) YYYY-MM, e.g. 2024-07.
rent required	number (Rent) > 0 Monthly rent in GBP.

`bedrooms` >	Bedrooms (integer) or Bedrooms (null) (Bedrooms) Number of bedrooms.
`property_type` >	Property Type (string) or Property Type (null) (Property Type) Property type category.
`source`	string (Source) Default: `"user"` Enum: `"user"` `"survey"` `"partner"`

Responses

> **201** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

POST `/rent_user`

Request samples

Payload

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "rent": 0,
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user"
}
```

Response samples

201 400 404 422

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "rent": 0,
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string",
    "uploader_id": 0
}
```

Api List Rental Records

QUERY PARAMETERS

`time_period` >	Time Period (string) or Time Period (null) (Time Period)
`area_code` >	Area Code (string) or Area Code (null) (Area Code)
`postcode` >	Postcode (string) or Postcode (null) (Postcode)
`bedrooms` >	Bedrooms (integer) or Bedrooms (null) (Bedrooms)
`property_type` >	Property Type (string) or Property Type (null) (Property Type)
`limit`	integer (Limit) [1 .. 200] Default: 50
`offset`	integer (Offset) >= 0 Default: 0

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /rent_user

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ]
}
```

Api Get Rental Record

PATH PARAMETERS

record_id required	integer (Record Id)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /rent_user/{record_id}

Response samples

200 | 400 | 404 | 422

Content type
application/json

Copy


```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "rent": 0,
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string",
    "uploader_id": 0
}
```

Api Update Rental Record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

record_id required	integer (Record Id)

REQUEST BODY SCHEMA: application/json

required

postcode >	Postcode (string) or Postcode (null) (Postcode)
area_code >	Area Code (string) or Area Code (null) (Area Code)
time_period >	Time Period (string) or Time Period (null) (Time Period)
rent >	Rent (number) or Rent (null) (Rent)
bedrooms >	Bedrooms (integer) or Bedrooms (null) (Bedrooms)
property_type >	Property Type (string) or Property Type (null) (Property Type)
source >	Source (string) or Source (null) (Source)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

PUT /rent_user/{record_id}

Request samples

Payload

Content type
application/json

Copy

```
{
  "postcode": "string",
  "area_code": "string",
  "time_period": "string",
  "rent": 0,
```

```
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user"
}
```

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "rent": 0,
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string",
    "uploader_id": 0
}
```

Api Patch Rental Record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`record_id` required	integer (Record Id)

REQUEST BODY SCHEMA: application/json
required

`postcode` >	Postcode (string) or Postcode (null) (Postcode)
`area_code` >	Area Code (string) or Area Code (null) (Area Code)
`time_period` >	Time Period (string) or Time Period (null) (Time Period)

rent >	Rent (number) or Rent (null) (Rent)
bedrooms >	Bedrooms (integer) or Bedrooms (null) (Bedrooms)
property_type >	Property Type (string) or Property Type (null) (Property Type)
source >	Source (string) or Source (null) (Source)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

PATCH /rent_user/{record_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "rent": 999
}
```

Response samples

200 **400** **404** **422**

Content type
application/json

Copy


```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "rent": 0,
    "bedrooms": 10,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string",
    "uploader_id": 0
}
```

Api Delete Rental Record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`record_id` required	integer (Record Id)

Responses

— **204** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

DELETE `/rent_user/{record_id}`

Response samples

400 404 422

Content type
application/json

Copy

```
{
    "detail": "string"
}
```

user_sales_transactions

Api Create User Sale

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`postcode` required	string (Postcode) [2 .. 12] characters
`area_code` >	Area Code (string) or Area Code (null) (Area Code) Optional. If omitted, will be derived from postcode_map.
`time_period` required	string (Time Period) YYYY-MM
`price` required	number (Price) > 0 Transaction price in GBP.
`property_type` >	Property Type (string) or Property Type (null) (Property Type)
`source`	string (Source) Default: `"user"` Enum: `"user"` `"survey"` `"partner"`

Responses

> **201** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

POST /user-sales-transactions

Request samples

Payload

Content type
application/json

Copy

```
{
  "postcode": "string",
  "area_code": "string",
  "time_period": "string",
  "price": 0,
  "property_type": "flat",
  "source": "user"
}
```

Response samples

201 **400** **404** **422**

Content type
application/json

Copy

```
{
  "postcode": "string",
  "area_code": "string",
  "time_period": "string",
  "price": 0,
  "property_type": "flat",
```

```
    "source": "user",
    "id": 0,
    "created_at": "string"
}
```


Api List User Sales

QUERY PARAMETERS

postcode >	Postcode (string) or Postcode (null) (Postcode)
area_code >	Area Code (string) or Area Code (null) (Area Code)
from_period >	From Period (string) or From Period (null) (From Period)
to_period >	To Period (string) or To Period (null) (To Period)
property_type >	Property Type (string) or Property Type (null) (Property Type)
min_price >	Min Price (number) or Min Price (null) (Min Price)
max_price >	Max Price (number) or Max Price (null) (Max Price)
limit	integer (Limit) [1 .. 200] Default: 50
offset	integer (Offset) >= 0 Default: 0

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

GET /user-sales-transactions

Response samples

200 400 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ]
}
```

Api Get User Sale

PATH PARAMETERS

record_id required	integer (Record Id)

Responses

> 200 Successful Response

> 400 Invalid input.

> 404 Resource not found.

> 422 Validation Error

GET /user-sales-transactions/{record_id}

Response samples

200 400 404 422

Content type
application/json

Copy


```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "price": 0,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string"
}
```

Api Put User Sale

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`record_id` required	integer (Record Id)

REQUEST BODY SCHEMA: application/json
required

`postcode` required	string (Postcode) [2 .. 12] characters
`area_code` >	Area Code (string) or Area Code (null) (Area Code) Optional. If omitted, will be derived from postcode_map.
`time_period` required	string (Time Period) YYYY-MM
`price` required	number (Price) > 0 Transaction price in GBP.
`property_type` >	Property Type (string) or Property Type (null) (Property Type)

`source`	string (Source) Default: `"user"` Enum: `"user"` `"survey"` `"partner"`

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

PUT `/user-sales-transactions/{record_id}`

Request samples

Payload

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "price": 0,
    "property_type": "flat",
    "source": "user"
}
```

Response samples

200 **400** **404** **422**

Content type
application/json

Copy


```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "price": 0,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string"
}
```

Api Patch User Sale

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`record_id` required	integer (Record Id)

REQUEST BODY SCHEMA: application/json
required

`time_period` >	Time Period (string) or Time Period (null) (Time Period)
`price` >	Price (number) or Price (null) (Price)
`property_type` >	Property Type (string) or Property Type (null) (Property Type)

Responses

> **200** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

PATCH /user-sales-transactions/{record_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "price": 300000
}
```

Response samples

200 400 404 422

Content type
application/json

Copy

```
{
    "postcode": "string",
    "area_code": "string",
    "time_period": "string",
    "price": 0,
    "property_type": "flat",
    "source": "user",
    "id": 0,
    "created_at": "string"
}
```

Api Delete User Sale

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

record_id required	integer (Record Id)

Responses

— **204** Successful Response

> **400** Invalid input.

> **404** Resource not found.

> **422** Validation Error

DELETE /user-sales-transactions/{record_id}

Response samples

400 | 404 | 422

Content type
application/json

Copy

```
{
    "detail": "string"
}
```

authority

Register a new user

Create a user account.

- Stores password as a secure hash (never stores plaintext password)
- Enforces unique username/email via service layer

REQUEST BODY SCHEMA: application/json
required

`username` required	string (Username) [3 .. 30] characters Unique username (letters, numbers, underscore).
`email` required	string <email> (Email) [5 .. 254] characters Unique email address.
`password` required	string (Password) [8 .. 128] characters Plain password (will be hashed and never stored in plain text).

Responses

> **200** Successful Response

> **422** Validation Error

POST `/auth/register`

Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "shirui_zh",
    "email": "s.zhao@example.com",
    "password": "Str0ngPassw0rd!"
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
{
    "username": "shirui_zh",
    "email": "s.zhao@example.com",
    "id": 0,
    "created_at": "string"
}
```

Login and get access token

Login with username OR email (form.username field can be either). Returns JWT bearer token.

REQUEST BODY SCHEMA: application/x-www-form-urlencoded
required

grant_type >	Grant Type (string) or Grant Type (null) (Grant Type)
username required	string (Username)
password required	string <password> (Password)
scope	string (Scope) Default: `""`
client_id >	Client Id (string) or Client Id (null) (Client Id)
client_secret >	Client Secret (string) or Client Secret (null) <password> (Client Secret)

Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/login

Response samples

200 422

Content type
application/json

Copy

```
{
    "access_token": "string",
    "token_type": "bearer"
}
```