

PACKAGED AIR HANDLING UNIT SCHEDULE																								
UNIT MARK	LOCATION	SERVICE	QTY	FAN					COOLING COIL									MOTOR			REMARKS			
				TYPE	CMH	ESP(pa)	DRIVE TYPE	RPM	CAP (KW)		EAT°C		AIR Δ P Pa	EWT °C	LWT °C	WTR Δ P KPa	L/S	HP	VOLTAGE	TYPE				
									TOTAL	SENSIBLE	DB	WB												
F1-C3-PAH-1001	CUB3 L10	CHILLER ROOM	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1002	CUB3 L10	CHILLER ROOM	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1003	CUB3 L10	CHILLER ROOM	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1004	CUB3 L10	UPS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1005	CUB3 L10	UPS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1006	CUB3 L10	BATTERY	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1007	CUB3 L10	BATTERY	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1008	CUB3 L20	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1009	CUB3 L20	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1010	CUB3 L20	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1011	CUB3 L20	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1012	CUB3 L20	SMS HV ROOM	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1013	CUB3 L20	SMS HV ROOM	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1014	CUB3 L20	NETWORK RM.	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1015	CUB3 L20	NETWORK RM.	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1016	CUB3 L20	FMCS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1017	CUB3 L20	FMCS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1018	CUB3 L20	6.6kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1019	CUB3 L20	6.6kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1020	CUB3 L30	6.6kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1021	CUB3 L30	6.6kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1022	CUB3 L30	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1023	CUB3 L30	22.8kV SWG	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1024	CUB3 L30	480V SUBS	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1025	CUB3 L30	480V SUBS	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1026	CUB3 L30	480V SUBS	1	FORWARD CURVED	27600	250	BELT	—	192	128	29.0	22.0	—	12	20	<50	5.6	15	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1027	CUB3 L30	GEN CONTROL	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1028	CUB3 L30	GEN CONTROL	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1029	CUB3 L30	UPS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1030	CUB3 L30	UPS	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1031	CUB3 L30	BATTERY	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1032	CUB3 L30	BATTERY	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	
F1-C3-PAH-1033	CUB3 L30	VFD	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	使用自壓排水器		
F1-C3-PAH-1034	CUB3 L30	VFD	1	FORWARD CURVED	6000	250	BELT	—	36	25.4	29.0	22.0	—	12	20	<50	1.0	3	3/460/60	ODP	IE: 4	(STANDBY)	使用自壓排水器	

ROW COOLER EQUIPERNT SCHDULE														
UNIT NO.	LOCATION	Room Name	Q'TY	AIR VOLUME (CMH)	冷卻盤管 COOLING COIL DATA					輸入功率 INPUT POWER		加濕量 CAPACITY	再熱器 容量 CAPACITY	REMARK
					能量 COILING CAPACITY (Kw)	水 流 量 WATER FLOW (LPM)	進水溫度 ENTERING WATER TEMP (°C)	出水溫度 LEAVING WATER TEMP (°C)	入風溫度 ENTERING AIR TEMP (°CDB)	KW	PH/VOLT/Hz			
DC1-RC-01	CUB3 L20	TNDC1A	1	14050	95	150	12	22.5	37.5	15.8	3Φ-380/220V-60HZ	3kg/hr	8.1 KW	(恆溫恆濕)
DC1-RC-02	CUB3 L20	TNDC1A	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-03	CUB3 L20	TNDC1A	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-04	CUB3 L20	TNDC1A	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-05	CUB3 L20	TNDC1A	1	14050	95	150	12	22.5	37.5	15.8	3Φ-380/220V-60HZ	3kg/hr	8.1 KW	(恆溫恆濕)
DC1-RC-06	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-07	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-08	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-09	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-10	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-11	CUB3 L20	TNDC1A	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-12	CUB3 L20	TNDC1C	1	14050	95	150	12	22.5	37.5	15.8	3Φ-380/220V-60HZ	3kg/hr	8.1 KW	(恆溫恆濕)
DC1-RC-13	CUB3 L20	TNDC1C	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-14	CUB3 L20	TNDC1C	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-15	CUB3 L20	TNDC1C	1	14050	95	150	12	22.5	37.5	4.8	3Φ-380/220V-60HZ	-	-	(單冷)
DC1-RC-16	CUB3 L20	TNDC1C	1	14050	95	150	12	22.5	37.5	15.8	3Φ-380/220V-60HZ	3kg/hr	8.1 KW	(恆溫恆濕)
DC1-RC-17	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-18	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-19	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-20	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-21	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-22	CUB3 L20	TNDC1C	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-23	CUB3 L20	VENDER AREA	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-24	CUB3 L20	VENDER AREA	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)
DC1-RC-25	CUB3 L20	VENDER AREA	1	7475	43	100	12	22.5	37.5	2	1Φ-220V-60HZ	-	-	(單冷)