room-15

ESP8266 - AT Command Reference

26 Mar 2015 | by fuho

ESP8266, in it's default configuration, boots up into the serial modem mode. In this mode you can communicate with it using a set of **AT commands**. I will present to you a reference of all known AT commands that ESP8266 supports, explain what they do and how to use them.

Historically AT commands are based on the Hayes Command Set and these are no different.

AT Commands

Index of all known AT commands

Basic	WiFI layer	TCPIP Layer
AT	AT+CWMODE	AT+CIPSTATUS
AT+RST	AT+CWJAP	AT+CIPSTART
AT+GMR	AT+CWLAP	AT+CIPSEND
AT+GSLP	AT+CWQAP	AT+CIPCLOSE
ATE	AT+CWSAP	AT+CIFSR
	AT+CWLIF	AT+CIPMUX
	AT+CWDHCP	AT+CIPSERVER
	AT+CIPSTAMAC	AT+CIPMODE

	AT+CIPAPMAC	AT+CIPSTO
	AT+CIPSTA	AT+CIUPDATE
	AT+CIPAP	+IPD

Line termination

ESP8266 expects `<CR><LF>` or *CarriageReturn* and *LineFeed* at the end of each command, but just `<CR` > seems to work too.

Command variants

Each command can have up to 4 variants changing the *function* of it. You can chose between them by appending one of four possible values to the end of the root command itself. These four appendices can have the following values `""` , `= <parameter|[parameters]>` , `"?"` , `=?`

Type	Example	Description
Test	AT+CIPSTART=?	Query the range of values (So far only AT+CWMODE=? uses it)
Query	AT+CMD?	Returns the current value of the parameter.
Set	AT+CMD=Parameter	Set the value of user-defined parameters in commands and run.
Execute	AT+CMD	Runs commands with no user-defined parameters.

Note:

- Not all AT commands support all 4 variants.
- [] = default value, not required or may not appear.
- String values require double quotation marks, for example: `AT+CWSAP="ESP756190","21030826",1,4` .
- Baud rate = 115200
- AT instruction ends with “\r\n”

Commands

`AT` - Test AT startup

Variant	Command	Response	Function
Execute	AT	OK	Test if AT system works correctly

Back to Index

`AT+RST` - Restart module

Variant	Command	Response	Function
Execute	AT+RST	OK	Reset the module

ESP-01 Output after reset:

```
 ets Jan  8 2013,rst cause:4, boot mode:(3,7)

wdt reset
load 0x40100000, len 24444, room 16
tail 12
chksum 0xe0
ho 0 tail 12 room 4
load 0x3ffe8000, len 3168, room 12
tail 4
chksum 0x93
load 0x3ffe8c60, len 4956, room 4
tail 8
chksum 0xbd
csum 0xbd

ready
```

ESP-12 Output after reset:

```
\0x04B1\0x85 \0xff\0x13:'\0xe0;\0xcc;!G\0xfa\0x11\0xa9R\0xc6\0x83\0x01
[Vendor:www.ai-thinker.com Version:0.9.2.4]

ready
```

Back to Index

`AT+GMR` - View version info

Variant	Command	Response	Function
Execute	AT+GMR	`version` , OK	Print firmware version

Parameters:

- `version` : firmware version number

ESP-01 output:

```
00160901
```

ESP-12 output:

```
0018000902-AI03
```

Back to Index

`AT+GSLP` - Enter deep-sleep mode

Variant	Command	Response	Function
set	AT+GSLP= `time`	`time` OK	Enter deep sleep mode for `time` milliseconds

parameters:

- `time` : Time to sleep in milliseconds

Example：

`AT+GSLP=1500`

Note:

Hardware has to support deep-sleep wake up (Reset pin has to be High).

Back to Index

`ATE` - Enable / Disable echo

Variant	Command	Response	Function
Execute	ATE0	OK	Disable echo (Doesn't send back received command)
Execute	ATE1	OK	Enable echo (Sends back received command before response)

Note:

I haven't had any luck with this command yet. Both `ATE0` and `ATE1` return `no this fun` .
`ATE` returns `OK`
This changed with `ESP-12` where the command functions exactly as expected!

Back to Index

`AT+CWMODE` - WIFI mode（station, AP, station + AP）

Variant	Command	Response	Function
Test	AT+CWMODE=?	+CWMODE:(1-3) OK	List valid modes
Query	AT+CWMODE?	+CWMODE: `mode` OK	Query AP's info which is connect by ESP8266.
Execute	AT+CWMODE= `mode`	OK	Set AP's info which will be connect by ESP8266.

Parameters:

- `mode` : An integer designating the mode of operation either 1, 2, or 3.
  1 = Station mode (client)
  2 = AP mode (host)
  3 = AP + Station mode (Yes, ESP8266 has a dual mode!)

Notes:

ESP-12 came configured as **host** with ssid set to *ESP_A0A3F2*, no password, channel *1* You can use AT+CWSAP? to find the current settings.

Back to Index

`AT+CWJAP` - Connect to AP

Variant	Command	Response	Function
Query	AT+CWJAP?	+ CWJAP: `ssid` OK	Prints the SSID of Access Point ESP8266 is connected to.
Execute	AT+CWJAP= `ssid` , `pwd`	OK	Commands ESP8266 to connect a SSID with supplied password.

Parameters:

- `ssid` : String, AP's SSID
- `pwd` : String, not longer than 64 characters

Example :

```
AT+CWJAP="my-test-wifi","1234test"
```

Example `AT+CWJAP?` :

```
+CWJAP:"my-test-wifi"
```

Back to Index

`AT+CWLAP` - Lists available APs

Variant	Command	Response	Function
Set	AT+CWLAP= `ssid` , `mac` , `ch`	+CWLAP: `ecn` , `ssid` , `rssi` , `mac` OK	Search available APs with specific conditions.
			Lists

Execute	AT+CWLAP	AT+CWLAP: `ecn` , `ssid` , `rssi` , `mac` OK	available Access Points.

Parameters:

- `ecn` :
  - **0** = OPEN
  - **1** = WEP
  - **2** = WPA_PSK
  - **3** = WPA2_PSK
  - **4** = WPA_WPA2_PSK
- `ssid` : String, SSID of AP
- `rssi` : signal strength
- `mac` : String, MAC address

Note:

On **ESP-01** I have had no luck with the set version of this command (`AT+CWLAP=...`). If you know what it does please let me know.
On **ESP-12**, the *Set* version of the command allows to see if a certain SSID, with certain MAC on certain channel exists. If it doesit is returned as one line of the *Execute* version of this command.

Example `AT+CWLAP` :

```
+CWLAP:(3,"CVBJB",-71,"f8:e4:fb:5b:a9:5a",1)
+CWLAP:(3,"HT_00d02d638ac3",-90,"04:f0:21:0f:1f:61",1)
+CWLAP:(3,"CLDRM",-69,"22:c9:d0:1a:f6:54",1)
+CWLAP:(2,"AllSaints",-88,"c4:01:7c:3b:08:48",1)
+CWLAP:(0,"AllSaints-Guest",-83,"c4:01:7c:7b:08:48",1)
+CWLAP:(0,"AllSaints-Guest",-83,"c4:01:7c:7b:05:08",6)
+CWLAP:(4,"C7FU24",-27,"e8:94:f6:90:f9:d7",6)
+CWLAP:(2,"AllSaints",-82,"c4:01:7c:3b:05:08",6)
+CWLAP:(3,"QGJTL",-87,"f8:e4:fb:b5:6b:b4",6)
+CWLAP:(4,"50EFA8",-78,"74:44:01:50:ef:a7",6)
+CWLAP:(0,"optimumwifi",-78,"76:44:01:50:ef:a8",6)
+CWLAP:(3,"BHQH4",-95,"18:1b:eb:1a:af:5b",6)
+CWLAP:(3,"NETGEAR49",-86,"84:1b:5e:e0:28:03",7)
+CWLAP:(3,"ngHub_319332NW00047",-56,"20:e5:2a:79:b1:2f",11)
+CWLAP:(3,"BFZR4",-73,"18:1b:eb:1d:c3:91",11)
+CWLAP:(1,"5FFVL",-82,"00:26:b8:b5:c0:f2",11)
+CWLAP:(3,"59G6D",-77,"00:7f:28:6d:91:7b",11)
+CWLAP:(3,"N16FU",-53,"20:cf:30:ce:60:fe",11)
+CWLAP:(3,"ITS",-82,"90:72:40:21:5f:76",11)
+CWLAP:(3,"ITS",-79,"24:a2:e1:f0:04:e4",11)
```

Example `AT+CWLAP="N16FU","20:cf:30:ce:60:fe",11` :

```
+CWLAP:(3,"N16FU",-53,"20:cf:30:ce:60:fe",11)
```

Back to Index

`AT+CWQAP` - Disconnect from AP

Variant	Command	Response	Function
Execute	AT+CWQAP	OK	Disconnect ESP8266 from the AP is currently connected to.

Note:

After running this command, if you run `AT+CWJAP?` it still shows the AP you were connected to before. Back to Index

`AT+CWSAP` - Configuration of softAP mode

Variant	Command	Response	Function
Query	AT+CWSAP?	+CWSAP: `ssid` , `pwd` , `ch` , `ecn` OK	Query configurati of ESP826 softAP moc
Set	AT+CWSAP= `ssid` , `pwd` , `ch` , `ecn`	OK	Set configurati of softAP mode.

Parameters:

- `ssid` : String, ESP8266's softAP SSID
- `pwd` : String, Password, no longer than 64 characters
- `ch` : channel id
- `ecn` :
  - **0** = OPEN
  - **2** = WPA_PSK
  - **3** = WPA2_PSK
  - **4** = WPA_WPA2_PSK

Example

`AT+CWSAP="esp_123","1234test",5,3`

`AT+CWSAP?` => `+CWSAP:"esp_123","1234test",5,3`

Back to Index

`AT+CWLIF` - List clients connected to ESP8266 softAP

Variant	Command	Response	Function
Execute	AT+CWLIF	[`ip` , `other`]	List information on of connected

		OK	clients.

Parameters:

`ip` : IP address of a client connected to the ESP8266 softAP `other` : Other info, look at example. I don't know what it means yet.

Example (ESP-01):

```
AT+CWLIF

192.168.4.100,3fff50b4:3fff50ba:3fff50c0:3fff50c6:3fff50cc:3fff50d2

OK
```

Example (ESP-12):

```
AT+CWLIF

192.168.4.100,c0:ee:fb:25:33:ec

OK
```

I ran the command after connecting to the ESP8266 with my cellphone.

Back to Index

`AT+CWDHCP` - Enable/Disable DHCP

Variant	Command	Response	Function
Set	AT+CWDHCP= `mode` , `en`	OK	Enable or disable DHCP for selected mode

Parameters:

- `mode` :
  - **0** : set ESP8266 as a softAP
  - **1** : set ESP8266 as a station
  - **2** : set both ESP8266 to both softAP and a station

- `en` :
  - **0** : Enable DHCP
  - **1** : Disable DHCP

Note:

This command doesn't seem to work on firmware *00160901* (ESP-01) nor *0018000902-AI03* (ESP-12).

Back to Index

`AT+CIPSTAMAC` - Set MAC address of ESP8266 station

Variant	Command	Response	Function
Query	AT+CIPSTAMAC?	+CIPSTAMAC: `mac` OK	Print current MAC ESP8266's address.
Execute	AT+CIPSTAMAC= `mac`	OK	Set ESP8266's MAC address.

Parameters:

- `mac` : String, MAC address of the ESP8266 station.

Example:

```
AT+CIPSTAMAC="18:aa:35:97:d4:7b"
```

Note:

This command doesn't seem to work on firmware 00160901

Back to Index

`AT+CIPAPMAC` - Set MAC address of ESP8266 softAP

Variant	Command	Response	Function
Query	AT+CIPAPMAC?	+CIPAPMAC: `mac` OK	Get MAC address of ESP8266 softAP.
Execute	AT+CIPAPMAC= `mac`	OK	Set mac of ESP8266 softAP.

Parameters:

- `mac` : String, MAC address of the ESP8266 softAP.

Example:

AT+CIPAPMAC="2c:aa:35:97:d4:7b"

Note:

This command doesn't seem to work on firmware 00160901

Back to Index

`AT+CIPSTA` - Set IP address of ESP8266 station

Variant	Command	Response	Function
Query	AT+CIPSTA?	+CIPSTA: `ip` OK	Get IP address of ESP8266 station.
Execute	AT+CIPSTA= `ip`	OK	Set ip addr of ESP8266 station.

Parameters:

- `ip` : String, ip address of the ESP8266 station.

Example:

AT+CIPSTA=”192.168.101.108”

Note:

This command doesn’t seem to work on firmware 00160901

Back to Index

`AT+CIPAP` - Set ip address of ESP8266 softAP

Variant	Command	Response	Function
Query	AT+CIPAP?	+CIPAP: `ip` OK	Get ip address of ESP8266 softAP.
Execute	AT+CIPAP= `ip`	OK	Set ip addr of ESP8266 softAP.

Parameters:

- `ip` : String, ip address of ESP8266 softAP.

Example:

```
AT+CIPAP="192.168.5.1"
```

Note:

This command doesn’t seem to work on firmware 00160901

Back to Index

`AT+CIPSTATUS` - Information about connection

Variant	Command	Response	Function
Test	AT+CIPSTATUS=?	OK	
Execute	AT+CIPSTATUS	STATUS: `status` +CIPSTATUS: `id` , `type` , `addr` , `port` , `tetype` OK	Get information about connection.

Parameters:

- `status` :
  - **2**: Got IP
  - **3**: Connected
  - **4**: Disconnected

- `id` : id of the connection (0~4), for multi-connect
- `type` : String, "TCP" or "UDP"
- `addr` : String, IP address.
- `port` : port number
- `tetype` :
  - **0** = ESP8266 runs as a client
  - **1** = ESP8266 runs as a server

Note:

On **ESP-01** this command returns `STATUS:1` instead (no extra info, but status changes) On **0018000902-AI03** this command returns `STATUS:2` instead (no extra info, but status changes)

Back to Index

`AT+CIPSTART` - Establish TCP connection or register UDP port and start a connection

Variant	Command	Response	Function
Set	AT+CIPSTART= `type` , `addr` , `port`	OK	Start a connection as client. (Single connection mode)
Set	AT+CIPSTART= `id` , `type` , `addr` , `port`	OK	Start a connection as client. (Multiple connection mode)
Test	AT+CIPSTART=?	[+CIPSTART:(id)("type"),("ip address"),(port)] OK	List possible command variations)

Parameters:

- `id` : 0-4, id of connection
- `type` : String, "TCP" or "UDP"
- `addr` : String, remote IP
- `port` : String, remote port

Back to Index

`AT+CIPSEND` - Send data

Variant	Command	Response	Function
Test	AT+CIPSEND=?	OK	
Set	AT+CIPSEND= `length`	SEND OK	Set length of the data that will be sent. For normal send (single connection).
Set	AT+CIPSEND= `id` , `length`	SEND OK	Set length of the data that will be sent. For normal send (multiple connection).
Execute	AT+CIPSEND		Send data. For unvarnished transmission mode.

Normal Mode

Parameters:

- `id` : ID no. of transmit connection
- `length` : data length, MAX 2048 bytes

Unvarnished Transmission Mode

Wrap return “**>**” after execute command. Enters unvarnished transmission, 20ms interval between each packet, maximum 2048 bytes per packet. When single packet containing “+++” is received, it returns to command mode.

Back to Index

`AT+CIPCLOSE` - Close TCP or UDP connection

Variant	Command	Response	Function
Test	AT+CIPCLOSE=?	OK	
Set	AT+CIPCLOSE= `id`	OK	Close TCP or UDP connection.For multiply connection mode
Execute	AT+CIPCLOSE	OK	Close TCP or UDP connection.For single connection mode

Parameters:

- `id` : ID no. of connection to close, when id=5, all connections will be closed.

Note:

In server mode, id = 5 has no effect!

Back to Index

`AT+CIFSR` - Get local IP address

Variant	Command	Response	Function
Test	AT+CIFSR=?	OK	
Execute	AT+CIFSR	+CIFSR: `ip` OK	Get local IP address.

Parameters:

- `ip` : IP address of the ESP8266 as an client.

Example `AT+CIFSR` :

```
10.101.10.134
```

Back to Index

`AT+CIPMUX` - Enable multiple connections or not

Variant	Command	Response	Function
Set	AT+CIPMUX= `mode`	OK	Enable / disable multiplex mode (up to 4 conenctions)
Query	AT+CIPMUX?	+CIPMUX: `mode` OK	Print current multiplex mode.

Parameters:

- `mode` :
  - **0**: Single connection
  - **1**: Multiple connections (MAX 4)

NOTE:

This mode can only be changed after all connections are disconnected. If server is started, reboot is required.

Back to Index

`AT+CIPSERVER` - Configure as server

Variant	Command	Response	Function
Set	AT+CIPSERVER= `mode` [, `port`]	OK	Configure ESP8266 as server

Parameters:

- `mode` :
- 0: Delete server (need to follow by restart)
- 1: Create server

- `port` : port number, default is 333

NOTE:

1. Server can only be created when AT+CIPMUX=1
2. Server monitor will automatically be created when Server is created.
3. When a client is connected to the server, it will take up one connection，be gave an id.

Back to Index

`AT+CIPMODE` - Set transfer mode

Variant	Command	Response	Function
Query	AT+CIPMODE?	+CIPMODE: `mode` OK	Set transfer mode,normal or transparent transmission.
Set	AT+CIPMODE= `mode`	OK	Set transfer mode,normal or transparent transmission.

Parameters:

- `mode` :
- 0: normal mode
- 1: unvarnished transmission mode

Back to Index

`AT+CIPSTO` - Set server timeout

Variant	Command	Response	Function
Query	AT+CIPSTO?	+CIPSTO: `time`	Query server timeout.
Set	AT+CIPSTO= `time`	OK	Set server timeout.

Parameters:

- `time` : server timeout, range 0~7200 seconds

Back to Index

`AT+CIUPDATE` - update through network

!!! Don’t run this unless you know what you’re doing !!!

!!! It will likely brick your device !!! Attempts to self-update from the internet.

Variant	Command	Response	Function

Execute	AT+CIUPDATE	+CIPUPDATE: `n` OK	Start update through network

Parameters:

- `n` :
- 1: found server
- 2: connect server
- 3: got edition
- 4: start update

Example:

```
AT+CIUPDATE

+CIUPDATE: 1
+CIUPDATE: 2
+CIUPDATE: 3
+CIUPDATE: 4

\0x02\0x8cl\0x8el\0x8e\0x1cp\0x0c\0x8c\0xf2nn\0xee\0x00l\0x8c\0x8el`
\0x02\0x90\0x12\0x12nnl\0x8cl`\0x02\0x0e\0x02nr\0x8e\0x92\0x92n\0x0c\0
\0x02\0x8c\0x92`\0x02`
\0xf2n\0x0c\0x0c\0x0c\0x9e\0xe0b\0x82nl\0x8c\0x0c\0x8c
\0xf2nn\0xee\0x00\0x0c\0x8e\0x0elp\0xf2n\0xe0\0x10\0x02\0x0c
\0x0cr\0x8c\0x9c\0x9c\0xe2\0xe0\0x0c\0x0c\0x0c
\0x0cb\0x0cn\0xe2|\0x02\0xec\0xecl\0x8c\0x0cb\0x8c\0xf2nn
...forever
```

Back to Index

`+IPD` - Receive network data

Variant	Command	Response	Function
Execute		+IPD, `len` : `data`	Receive network data from single connection.
Execute		+IPD, `id` , `len` : `data`	Receive network data from multiple connection.

Parameters:

- `id` : id no. of connection
- `len` : data length
- `data` : data received

Note:

I have had no luck with this command so far.

Back to Index

Sources

esp8266 GitHub Wiki

Links

2 Comments room-15 1 Login

Recommend Share Sort by Best

Join the discussion…

Surya Teja Karra • 6 months ago

does any command exists to perform forget AP? the AT+CWQAP disconnects from AP but does not forgets it. So on reset of the chip, it is connecting to this wifi again.

• Reply • Share ›

Áĥmęď Øśmâņ Surya Teja Karra • 4 months ago

I was have the same problem but i solved it by this way
sending the AT+CWJAP with spaces instead of your ssid,pwd like this :
AT+CWJAP=" "," "\r\n
then check the connection
AT+CWJAP?\r\n
the module replay with this :
+CWJAP?
+CWJAP:" "
OK
and you got it ;)

• Reply • Share ›

ALSO ON **ROOM-15**

Keep the "m" prefix
4 comments • a year ago
Carl A — this. is ugly. Like your mom. Case closed.

Navigating Google Street View Using Google Cardboard
1 comment • a year ago
Marc Bretzfelder — You can now navigate Google Street View in Cardboard natively in the new

Beware of Preference Default Values in XML
1 comment • a year ago
Carl A — I like doing layout with XML, but it feels like there are too many things like this, where you're better

Adventures in Espresso and Unit Testing Part 2
4 comments • a year ago
Денис Волынцев — I totally agree with you about lack of documentation. And thank you for

Related Posts

CamelHumps the hidden Android Studio gem 13 May 2016 | by Martin Breuer

Library versioning done right 27 Jan 2016 | by Martin Breuer

Static code quality measurements with SonarQube, JaCoCo and UnitTests 21 Jan 2016 | by Martin Breuer