

A (Project Stage – I) Report

on

Design and Analysis of Spy Robot with advanced surveillance

to be submitted in partial fulfilment of the requirements

for the award of degree of

BACHELOR OF ENGINEERING

(Automation and Robotics)

Submitted by:

BA&R03 : SHRIKANT CHILBULE

BA&R11 : PRATHAMESH CHOUDARY

BA&R28 : AHEMAD RAJA PATHAN

BA&R33 : PUSHKAR BRAHMANKAR

Group ID. 08

Prof. Yashraj Patil

Guide

Assistant Professor

Department of Automation and Robotics



DEPARTMENT OF AUTOMATION AND ROBOTICS

DR. D. Y. PATIL INSTITUTE OF TECHNOLOGY, PIMPRI

(Affiliated to Savitribai Phule Pune University, Pune)

PUNE – 411 018, MAHARASHTRA

2024-2025



Certificate

This is to certify that the following group of bonafide students from the Department of Automation and Robotics have successfully completed the prerequisites as laid down by the Savitribai Phule Pune University, Pune in the form of a report as per the course structure for the Project Stage – I.

Exam Seat No.	Roll No.	Name of the project group students
	BA&R03	: SHRIKANT CHILBULE
	BA&R11	: PRATHAMESH CHOUDARY
	BA&R28	: AHEMAD RAJA PATHAN
	BA&R33	: PUSHKAR BRAHMANKAR

It is herewith certified that this project work has not been submitted for award of any degree/diploma to any other university in India or abroad.

Prof. Yashraj Patil
Guide
Assistant Professor
Department of Automation and
Robotics, DIT, Pimpri

Dr. Vikas S. Panwar
Project Coordinator
Department of Automation and
Robotics
DIT, Pimpri

Dr. Niyaj D. Shikalgar
Head,
Department of Automation and
Robotics
DIT, Pimpri

Dr. L. K. Wadhwa
Principal,
DIT, Pimpri

External Examiner
(Name and Signature)

Date: Friday, 08 November 2024
Place: DIT, Pimpri

Declaration by the candidates

With this, I certify that the report entitled “**Design and Analysis of Spy Robot with advanced surveillance**” was submitted in partial fulfilment of the requirements for the award of the degree of Bachelor of Engineering in Automation and Robotics to Savitribai Phule Pune University, Pune is an authentic record of project work carried out by us under the supervision and guidance of **Prof. Yashraj Patil**.

The work incorporated in this report has not been submitted elsewhere for the award of any degree/diploma in India or abroad.

Exam Seat No.	Roll No.	Name of the project group students	Signature
	BA&R03	: SHRIKANT CHILBULE	
	BA&R11	: PRATHAMESH CHOUDARY	
	BA&R28	: AHEMAD RAJA PATHAN	
	BA&R33	: PUSHKAR BRAHMANKAR	

Undergraduate students,
Department of Automation and Robotics,
DIT, Pimpri, Pune – 411018 (Maharashtra), INDIA

Place: DIT, Pimpri
Date: Friday, 08 November 2024

Acknowledgement

We would like to express our sincere gratitude to all those who have contributed to the successful completion of this project. First and foremost, we extend our heartfelt thanks to our guide, **Prof.Yashraj Patil** Assistant Professor in the Department of Automation and Robotics at Dr. D.Y. Patil Institute of Technology, for his invaluable mentorship, constructive feedback, and unwavering support throughout the project. His insights and expertise have been instrumental in helping us refine our ideas and achieve our project goals.

We are also deeply appreciative of **Dr. Vikas S. Panwar**, Project Coordinator, and **Dr. Niyaj D. Shikalgar**, Head of the Department, for their encouragement and the resources they have made available to us. Their dedication to providing a supportive academic environment has been essential in enabling us to carry out our research effectively.

ABSTRACT

The **Spy Robot Tank with Live Video Streaming and Landmine Detection** is an advanced robotics solution designed for remote surveillance, landmine detection, and secure operation using biometric authentication. This robot integrates **ESP32** microcontroller capabilities, offering both **Wi-Fi** and **Bluetooth** connectivity for real-time control and monitoring. It is equipped with a **biometric fingerprint sensor** to ensure only authorized personnel can operate the robot, enhancing security for sensitive missions in hazardous environments. The primary function of this robot is to navigate potentially dangerous terrains, detect landmines using specialized sensors, and provide live video feed to a remote operator. The robot is equipped with **metal detectors** to detect landmines, while a **camera** captures real-time video footage, enabling the operator to visualize the environment. The system features **biometric authentication**, ensuring the tank can only be started and operated by authorized personnel, preventing misuse or unauthorized access. This robot offers a versatile platform for applications in **post-conflict demining**, **security surveillance**, and **disaster recovery**. The integration of live video streaming and the biometric authentication system enhances its usability and security, making it an ideal solution for hazardous operations.

TABLE OF CONTENT

Sr. No.	Content	Page No.
	Abstract	III
	Table of content	IV
	List of figures	V
	List of tables	VI
	Chapter 1 Introduction	1
	Chapter 2 Literature Review	3-45
2.1	Introduction to Surveillance Robots	5
2.2	360-Degree Camera for Wide-Area Coverage	5
2.3	Real-Time Live Streaming Technologies	5
2.4	Wireless Control Mechanism	6
2.5	Fire Detection Sensors in Robotics	6
2.6	Toxic Gas Detection Integration	6
2.7	Metal Detection in Hazardous Environment	6
2.7.1	Electromagnetic Coil Metal Detection	6
2.7.2	GPS and Autonomy	7
2.8	Renewable Power via Solar Panels	7
2.9	GPS for Location Tracking	7
2.9.1	Biometric Security Features	7
	Chapter 3 Methodology	
3.1	Introduction	8
3.2	Working Principle	8
3.3	Block diagram	8
3.4	Working	8
3.5	Circuit Diagram	11

3.6	Method of Procedure(mop) – Steps Include	12
3.8	Hardware Description	15

Chapter 4: System Implementation

4.1	Introduction	23
4.2	System Architecture	23
4.3	Data Flow and Integration	23
4.4	Component Integration and Interfacing	24
4.5	Operation Sequence	24
4.6	Communication and Control Interface	25
4.7	Error Handling and Safety Protocols	25
4.8	Software Implementation	26

Chapter 5 Result, Conclusion

5.1	Project Design	27
5.2	Project Analysis	28
5.3	Conclusion	29
5.4	Reference	30

LIST OF FIGURES

Figure No	Description	Page No.
3.5	Circuit Diagram	11
3.8.1	Metal Tank-1	15
3.8.2	!2v 10 rpm Johnson Motor	16
3.8.3	Track Belt-2	16
3.8.3	Pully-8	16
3.8.4	Node mcu esp 8266-4	17
3.8.5	Gps module neo 6m-1	17
3.8.6	Metal detector sensor-1	17
3.8.7	Camera-1	18
3.8.8	Finger Print sensor R307-1	18
3.8.9	Fire sensor-1	19
3.8.10	Solar panel-1	19
3.8.11	12v battery-1	20
3.8.12	L298n motor driver-1	20
3.8.13	Header pins-2	20
3.8.14	Wires-5mtr	21
3.8.15	Jumper wires	21
3.8.16	Switch -1	22

5.1.1	Top View	27
5.1.2	Isometric view	27
5.2.1	Static Displacement	28
5.2.2	Static Strain	29
5.2.3	Mesh Quality	30

LIST OF TABLES

Table No	Description	Page No.
1.5	Proposed detailed activity and sub activity plan	4

CHAPTER 1

INTRODUCTION

The presence of landmines in post-conflict regions and hazardous areas continues to pose a serious threat to human life, hindering reconstruction, rehabilitation, and relief operations. While conventional methods of landmine detection, such as manual surveying and metal detectors, are still widely used, they are time-consuming, dangerous, and often impractical in regions plagued by unexploded ordnance. The risk of human casualties due to accidental detonation remains a significant issue, making it imperative to develop more efficient, safer, and smarter systems for landmine detection and surveillance.

In parallel, the security and control of sensitive operations in hazardous areas also require heightened safety measures. Surveillance and reconnaissance tasks often need to be performed without putting human lives at risk, especially in environments where landmines or other explosive hazards may exist. Additionally, ensuring that only authorized personnel are allowed to operate potentially dangerous equipment, like a robot designed for landmine detection, is critical to preventing misuse and enhancing operational security.

To address these challenges, the **Spy Robot Tank with Live Video Streaming, Landmine Detection, and Biometric Authentication for Safe Operation** project presents an innovative solution. This project integrates a **biometric fingerprint authentication system**, an advanced **landmine detection system**, and **live video streaming** capabilities into a single robotic platform. The result is a **secure, efficient, and autonomous robot** capable of detecting landmines while providing real-time video feedback to an operator—without endangering human lives in potentially perilous areas.

The **ESP32** microcontroller serves as the heart of this robot, providing Wi-Fi and Bluetooth connectivity for both remote control and live video streaming. The integration of a **biometric fingerprint sensor** ensures that only authorized users can activate and control the robot, thus enhancing the security of the system and reducing the risk of unauthorized access or tampering. The robot's landmine detection capability relies on **metal detectors** or **ground-penetrating radar (GPR)**, enabling it to detect buried explosives in real time.

1.1 Problem Statement

Military operations in hazardous environments demand advanced, autonomous surveillance systems capable of real-time intelligence and comprehensive threat detection, which current systems lack. The proposed spy robot will fill current gaps by incorporating an IoT-based system for remote control, a 360-degree camera for live streaming, and a GPS module for precise navigation. It will include landmine, toxic gas, and fire detection sensors, along with a biometric sensor for authorized operation, and a self-charging solar panel for extended missions. This comprehensive integration is designed to improve situational awareness, safety, and operational efficiency in military operations.

1.2 Objective

1. **Landmine Detection:** Develop a robotic system capable of detecting buried landmines using **metal detectors** or **ground-penetrating radar (GPR)**.
2. **Biometric Authentication:** Integrate a **biometric fingerprint sensor** for secure and authenticated operation, ensuring that only authorized users can activate and control the robot.
3. **Live Video Streaming:** Stream real-time video from the robot's camera to a mobile app or web interface, allowing operators to visually assess the environment and make informed decisions.
4. **Remote Control and Navigation:** Enable **remote control** of the robot through **Wi-Fi or Bluetooth**, allowing the operator to navigate the robot in hazardous environments without direct human involvement.
5. **Safety and Security:** Ensure the system is tamper-proof, offering enhanced security through biometric authentication and real-time alerts for landmine detection and system malfunctions.
6. **Usability and Efficiency:** Provide an easy-to-use control interface, ensuring smooth interaction between the operator and the robot during operations.

1.3 Scope

The Spy Robot System's future development focuses on advanced AI-driven autonomous navigation, IoT-based remote monitoring, and secure communication for enhanced surveillance and operational security in military environments. Innovations include AI-powered object recognition, improved energy efficiency with self-charging, self-diagnostic and repair capabilities, and advanced cybersecurity to prevent tampering. Real-time threat analysis and predictive analytics further strengthen mission success. Ethical and legal frameworks will guide responsible deployment, ensuring enhanced effectiveness in high-risk, complex environments.

1.4 Application

- **Demining Operations:** Safely detect and mark landmines in post-conflict regions, allowing for the safe clearance of minefields.
- **Security Surveillance:** Perform reconnaissance and surveillance in hazardous or restricted areas, such as military bases, disaster zones, or conflict regions.
- **Disaster Response:** Used in search and rescue operations where unexploded ordnance or landmines may be present, the robot can assist in clearing a safe path for rescue teams.
- **Military and Defense:** The robot can be deployed for reconnaissance and threat detection in military operations, providing critical information to commanders without putting human soldiers at risk.
- **Chemical and Biological Threat Assessment:** In environments where there is a risk of chemical or biological warfare, the robot's toxic gas detection sensors provide crucial information about hazardous conditions. This allows for timely evacuation, decontamination efforts, and strategic adjustments to avoid exposure.
- **Perimeter Security and Base Protection:** The Spy Robot can patrol the perimeter of a base or secure area, using its 360-degree camera to monitor for any unusual activity or unauthorized personnel. The robot's biometric authentication ensures that it cannot be easily compromised or redirected by intruders. Additionally, its landmine and fire detection capabilities help to identify and address potential threats to base security, while its self-charging solar panel ensures continuous operation.

1.5 Project plan with timeline

Table 1: Proposed detailed activity and sub activity plan

Year 		2023						2024					
Activity	Sub Activity	M1	M2	M3	M4	M5	M6	M7	M8	M9	M10	M11	M12
Data acquisition and Processing	Literature review												
	Data acquisition												
	Data Processing												
	Feature extraction												
Model training	Model training												
	Model assessment												
	Predictions and presentation												
Application development	Decision support												
	Preparing framework and writing research article												
	Communication of research article to journal												
Writing and finalization of Report													

CHAPTER 2

LITERATURE REVIEW

This literature review examines the current advancements in robotic technology relevant to developing a multifunctional spy robot equipped with features such as 360-degree live-streaming cameras, toxic gas detection, wireless controls, metal and fire detection, GPS tracking, and a solar-powered self-charging system.

2.1 Introduction to surveillance system

Spy robots with 360-degree live-streaming cameras are widely used for real-time surveillance, especially in military and hazardous areas. Advanced camera modules, like those used in mobile robots, offer high-resolution video feeds and reliable streaming through Wi-Fi, supporting real-time monitoring over the internet. Research highlights the effectiveness of these systems in providing consistent surveillance with minimal human intervention, thus enhancing security in inaccessible zones (IEEE, 2024; IJARC).

2.2 360-Degree Camera for Wide Area Coverage

Literature on surveillance systems emphasizes the importance of continuous live streaming and the ability to monitor environments remotely in real time, often using Wi-Fi or IoT-based communication setups. Research on streaming functionality highlights the need for robust image processing and network stability, which can be achieved using ESP32-CAM modules or Raspberry Pi-based systems (IARJSET 2023)

2.3 Real-Time Live Streaming Technologies

The role of real-time streaming in surveillance, focusing on protocols like WebRTC and platforms such as ESP32-CAM for secure and high-quality video transmission. Research demonstrates that low-latency streaming enables faster response in dynamic settings, providing significant operational benefits in emergency situations

2.4 Wireless Control Mechanism

The wireless control systems for spy robots leverage Bluetooth and ZigBee for short-range operations and Wi-Fi for longer distances. Wireless technology enables the operator to control the robot remotely, which is essential in situations requiring flexibility and real-time response, such as hazardous areas where human presence is risky (IJERT, 2023).

2.5 Fire Detection Sensor in Robotics

Fire sensors, primarily using infrared or photoelectric detection methods, enable early fire detection and alert generation. Studies also discuss the potential of integrating machine learning with these sensors to improve detection accuracy and speed, which is especially beneficial in high-risk zones

2.6 Toxic Gas Detection Integration

Toxic gas detection typically involves the use of MQ gas sensors, which are capable of identifying gases such as CO and methane. Literature points out the importance of immediate detection and response in closed spaces, where toxic exposure risks are high. Integrating these sensors with real-time alerts is vital for mission-critical surveillance robots (IRJET, 2022)

2.7 Metal Detection in Hazardous Detection

Metal detection is critical in robots intended for exploration in hazardous areas or combat zones. Robots equipped with coils for metal detection are capable of alerting operators and stopping automatically upon detection of metals, which prevents potential safety risks (IJERT, 2023).

2.7.1 Electromagnetic Coil Metal Detection

Incorporating metal detection systems has proven essential for applications like landmine detection and unexploded ordnance identification. Research shows that integrating a metal detector within a robot significantly enhances its ability to locate hazardous metallic objects in dangerous areas. The metal detectors work efficiently with remote control mechanisms to provide real-time alerts, further enhancing the robot's surveillance capabilities (IJERT, 2020; IEEE, 2024).

2.7.2 GPS and Anatomy

GPS data can be used with autonomous control algorithms to enable area-based navigation and restricted zone alerts. This section discusses GPS in conjunction with autonomous features for improved surveillance coverage

2.8 Renewable Power via Solar Panels

A crucial innovation in robotics for extended operations is the use of renewable energy sources like solar panels. Solar charging systems are particularly beneficial for remote, high-risk areas where regular recharging may not be feasible. Studies on solar-powered robots emphasize their importance in sustainable operations, reducing dependency on traditional battery charging methods. Implementing a solar-powered charging module ensures continuous operation and power reliability, crucial for long-term surveillance missions (IJARC, 2024).

2.9 GPS for Location Tracking

A crucial innovation in robotics for extended operations is the use of renewable energy sources like solar panels. Solar charging systems are particularly beneficial for remote, high-risk areas where regular recharging may not be feasible. Studies on solar-powered robots emphasize their importance in sustainable operations, reducing dependency on traditional battery charging methods. Implementing a solar-powered charging module ensures continuous operation and power reliability, crucial for long-term surveillance missions (IJARC, 2024).

2.9.1 Biometric Security Feature

Biometric sensors, especially fingerprint or facial recognition, enhance the security features of the robot, allowing controlled access and monitoring. Research underscores the value of integrating these sensors with image processing and AI algorithms to authenticate operators and provide alerts in case of unauthorized access attempts.

Overall, these advancements reinforce the feasibility and robustness of the design choices for your spy robot project, ensuring comprehensive situational awareness, enhanced detection accuracy, and seamless data integration for mission-critical tasks. These studies and technologies continue to push the boundaries of robot-assisted surveillance, providing safer and more efficient responses in hazardous environments.

CHAPTER 3 Methodology

3.1 Introduction

The development of the Spy Robot was divided into systematic stages to ensure the integration and functionality of each feature effectively. The following steps were undertaken in the design and development process:

1. Requirements Analysis and Specification

- A detailed requirements analysis was conducted to identify essential features, operational environments, and performance expectations. This included features like a 360-degree camera, live streaming, wireless control, fire and toxic gas sensors, metal detection, solar panel for self-charging, GPS tracking, and biometric sensing.

- Functional and technical specifications were established for each component to align with the mission-critical requirements of military applications.

2. System Design and Architecture Development

- A modular design approach was adopted, allowing each component to be independently developed and tested before full integration.

- The architecture was designed to support seamless communication between sensors and controllers, with a focus on wireless data transmission to allow real-time monitoring and control.

3. Component Selection and Procurement

- Appropriate components were chosen based on technical requirements, compatibility, power efficiency, and durability in military settings.

- Key components included high-resolution cameras for 360-degree coverage, wireless modules for remote control, specialised sensors for fire, toxic gases, and metal detection, a GPS module, and a solar panel optimised for efficient energy capture.

4. Hardware and Software Integration

- The selected components were integrated onto a single platform with a microcontroller as the primary control unit.
- Software algorithms were developed to interpret sensor data, control robotic movement, enable live streaming, and manage the autonomous self-charging mechanism.
- A custom software interface was created for wireless remote control and live-stream monitoring.

5. Sensor Calibration and Testing

- Each sensor was calibrated individually to ensure precise detection and response. Testing environments were set up to evaluate sensor performance under varied conditions, including smoke for fire detection and sample toxic gases.
- The metal detector was tested for accuracy in detecting different types of metals within its range.

6. Field Testing and Validation

- The robot underwent field trials to assess its performance, mobility, data transmission stability, and real-time response. GPS accuracy, battery life under solar charging, and wireless range were thoroughly tested.
- Feedback from field tests was used to make iterative improvements, fine-tuning the system for operational robustness.

7. Report and Documentation


- A comprehensive report documenting the methodology, component specifications, integration process, and test results was compiled.
- Each development stage and test outcome were documented to provide a detailed overview of the project's scope, challenges, and solutions implemented.

This methodology should clearly convey the structured approach you used to develop and test the Spy Robot, reflecting both your project's technical depth and practical applications.

Working Principle: -

1. **Biometric Authentication:** The operator places their finger on the fingerprint sensor. The system matches the fingerprint to the stored template in the database. If authenticated, the robot can be activated.
2. **Landmine Detection:** Once activated, the robot starts moving through the terrain. It uses the **metal detector** to detect landmines underground, sending real-time feedback to the operator about the presence of potential threats.
3. **Live Video Streaming:** The ESP32-CAM module streams live video footage to the operator's mobile device or web interface, allowing for remote visual inspection.
4. **Remote Control:** The operator controls the robot's movements via a mobile app or web interface, guiding the tank through dangerous areas while monitoring both the live video feed and sensor data.
5. **Alert System:** If a landmine is detected, the robot sends an msg to the operator for further analysis and action. Additionally, if unauthorised access is attempted, the system prevents operation.

3.5 Circuit diagram: -



3.6 Method of Procedure (MOP) - steps included

Step 1: Planning and Design

- Review the project requirements to ensure the inclusion of all desired features: 360-degree camera, live streaming, wireless control, fire sensor, toxic gas detection, metal detector, self-charging solar panel, GPS location tracking, and biometric sensor.
- Create a detailed block diagram of the system architecture to plan component placement, wiring, and integration points.
- Finalise the hardware layout for the robot, taking into account weight distribution and component accessibility for easy maintenance and adjustments.

Step 2: Chassis and Motor Assembly

1. Assemble the Metal Tank Chassis

- Construct the robot body using the metal tank as the base, ensuring structural stability.

2. Install Track Belts and Motors

- Attach the two 12V, 10 RPM Johnson motors to the chassis and secure the track belts around the pulleys.

- Position four pulleys on each side to hold the track belts in place, ensuring smooth movement and proper tension.

3. Motor Driver Setup

- Connect the motors to the L298N motor driver, which will control the motor speed and direction based on commands from the microcontroller.

Step 3: Power System Setup

1. Battery Installation

- Secure the 12V battery on the chassis, ensuring it is centrally located to maintain balance.

2. Buck Converter Connection

- Use the buck converter module to step down the 12V battery output to 5V for components that require lower voltage, such as the NodeMCU ESP8266 boards.

3. Solar Panel Installation

- Mount the solar panel in a location with maximum sun exposure, ensuring it is connected to the battery charging circuit to support self-charging functionality.

Step 4: Microcontroller and Module Integration

1. NodeMCU ESP8266 Configuration

- Install the four NodeMCU ESP8266 modules for wireless control, camera streaming, sensor data processing, and GPS tracking.

- Configure each NodeMCU for specific tasks, ensuring proper communication and synchronisation across modules.

2. GPS Module Setup

- Connect the Neo 6M GPS module to one of the NodeMCU boards for real-time location tracking.

- Calibrate and test the GPS module's accuracy in providing location coordinates.

Step 5: Sensor and Camera Installation

1. Install Metal Detector Sensor

- Secure the metal detector sensor in an accessible location, ensuring it has a clear field for metal detection.

2. Camera Mounting

- Mount the camera in a 360-degree position, ensuring it captures a complete view for live streaming.

3. Biometric (Fingerprint) Sensor Installation

- Attach the R307 fingerprint sensor in a location where fingerprints can be easily scanned, and test its accuracy for data authentication.

4. Fire Sensor and Toxic Gas Detection Setup

- Place the fire sensor in an exposed location for optimal fire detection range. Test the sensor by exposing it to small heat sources to verify responsiveness.

5. Wiring and Jumper Connection

- Connect the sensors and modules with header pins and jumper wires to the NodeMCU boards, organising the wires to prevent tangling.

Step 6: Programming and Software Configuration

1. Program the NodeMCU ESP8266 Modules

- Write and upload code to each NodeMCU module, programming the following functions:
 - Control Module: Receives wireless control commands and controls motor functions.
 - Camera Module: Streams live video feed and processes 360-degree visuals.
 - GPS Module: Sends location coordinates in real-time.

- Sensor Module: Collects data from fire, metal, gas, and biometric sensors.

2. Wireless Interface Setup

- Establish a remote-control interface for real-time robot control, enabling live monitoring and command input.

Step 7: Calibration and Testing

1. Sensor Calibration

- Test each sensor individually by exposing them to relevant conditions (e.g., flame for the fire sensor, metal for the metal detector) and adjust sensitivity settings as needed.

2. Motor and Mobility Testing

- Test the track belt system by moving the robot forward, backward, and in circular patterns. Verify smooth motion and stability on different terrains.

3. Camera Streaming Test

- Activate the 360-degree camera and confirm that the live streaming quality meets expectations with minimal lag.

4. Wireless Control Range Testing

- Measure the effective wireless control range of the NodeMCU ESP8266 modules to ensure the robot remains responsive within the operational distance.

5. Solar Charging Test

- Place the robot in sunlight and monitor the battery charging rate via the solar panel to verify it supports sustainable self-charging.

Step 8: Field Testing and Validation

1. Integration Testing

- Verify that all components (motors, sensors, camera, GPS, and control modules) work seamlessly together without interference.

2. Outdoor Field Trials

- Conduct field trials in an outdoor setting, testing all functionalities under operational conditions, including live streaming, sensor response, and GPS tracking.

3. Stress Testing

- Test the robot in various environmental conditions (temperature, dust, and humidity) to assess durability and reliability in real-world applications.

Step 9: Documentation and Reporting

- Document all observations from the field tests, including performance data, issues encountered, and improvements made.
- Compile a final report detailing the MOP, test results, and overall project achievements, including images and data to demonstrate the robot's capabilities.

3.8 Hardware Description

The hardware configuration of the spy robot incorporates various components to achieve remote surveillance, landmine detection, and biometric security. Each component plays a specific role in the system, ensuring reliability and operational efficiency in hazardous environments.

- A. Metal Tank Chassis: Provides a sturdy base to house and protect all sensitive components. The metal construction ensures durability, especially in rough terrains.



Fig.No.3.8.1 Metal Tank Chassis

- B. Track Belt (2): Enables enhanced maneuverability across different surfaces, allowing the robot to navigate challenging terrains, including sand, gravel, and debris.



Fig.No.3.8.2 Track Belt

- C. 12V 10 RPM Johnson Motors (2): Powers the track belts, providing the required torque for smooth movement. The low RPM ensures steady and controlled navigation.



Fig.No.3.8.3 Johnson Motors

- D. Pulleys (8): Serves as guides for the track belts, reducing slippage and ensuring stable movement.



Fig.No.3.8.4 Pulleys

- E. NodeMCU ESP8266 (4): Functions as the primary microcontroller, handling both data processing and communication. It enables Wi-Fi connectivity, allowing remote monitoring and control.



Fig. No.3.8.5 NodeMCU ESP8266

- F. GPS Module (Neo 6M): Tracks the robot's location, providing real-time position data to the operator, which is essential for precise navigation in unknown or hazardous territories.



Fig.No.3.8.6 GPS Module (Neo 6m)

- G. Metal Detector Sensor: Detects buried metal objects, such as landmines, alerting the operator about potential hazards.



Fig.No.3.8.7 Metal Detector Sensor

- H. Camera: Captures live video, streaming real-time footage to the operator's control interface. This feature enhances the operator's situational awareness and aids in decision-making.



Fig.No.3.8.8 Camera

- I. Finger print sensor R307 – 1: The fingerprint sensor (R307) is integrated with the ESP8266, requiring the operator's fingerprint for activation. A verification function compares the input with stored fingerprint templates, allowing only authorized users to operate the robot.



Fig.No.3.8.9. Finger Print Sensor

- J. Fire Sensor: Monitors the environment for signs of fire, alerting the operator to potential threats in the operational area.




Fig. No.3.8.10. Fire Sensor

- K. Solar Panel (1): Extends the robot's operational time by charging the 12V battery, enabling continuous operation in remote areas without frequent recharging.



Fig.No.3.8.11 Solar Panel

- L. 12V Battery: Supplies power to the robot's main components, supporting both the motors and the microcontroller units



Fig.No.3.8.12 12V Battery

- M. L298N Motor Driver: Controls the movement of the motors by handling the bidirectional movement and speed control.




Fig.No.3.8.13 L298N Motor Driver

- N. Header Pins-2: Header pins make it easy to connect and disconnect these sensors from the main circuit board, allowing for straightforward installation and troubleshooting. For example, a fire detection sensor module can be attached using header pins, ensuring a solid connection while also being easily replaceable if needed.



Fig.No.3.8.14 Header Pins

- O. Wires-5mtr: Wires are essential for delivering power from the battery or power source to all components of the spy robot, including motors, sensors, and control boards. Properly gauged power wires ensure that components receive consistent voltage and current levels, which is essential for stable operation.



Fig.No.3.8.15 Wires-5mtr

- P. Jumper Wires – 50 to 100: Facilitate secure connections between components, ensuring stable data flow and power distribution.



Fig.No.3.8.16Jumper Wires

- Q. Switch – 1: Provides a manual power on/off control for the entire system, allowing the operator to conserve power when the robot is inactive.



Fig No.3.8.17 Switch

- R. Buck Converter Module (12V to 5V): Converts 12V from the battery to 5V, ensuring compatibility with lower-voltage components like the ESP8266 modules and sensors.



Fig.No.3.8.18 Buck Converter Module

Chapter 4 System Implementation

4.1 Introduction

The system implementation of the spy robot integrates hardware components with software algorithms to achieve seamless functionality for remote surveillance, hazard detection, and secure access control. This section provides an overview of the system architecture, component integration, data flow, and operational sequences that allow the robot to perform in hazardous and remote environments.

4.2. System Architecture

The spy robot's architecture is divided into three primary modules:

Control Module: Includes the microcontroller (NodeMCU ESP8266) responsible for processing commands, controlling motors, and managing sensor inputs.

Sensing and Detection Module: Comprises sensors for detecting landmines (metal detector), fire, and authentication (fingerprint sensor). These sensors provide critical data used for operational decisions.

Communication and Power Module: Manages communication (Wi-Fi) for remote control and live streaming, GPS for location tracking, and power management using a battery and solar panel for continuous operation.

The NodeMCU ESP8266 microcontroller acts as the central processing unit, coordinating communication between modules, handling data, and executing commands received from the operator interface.

4.3 Data Flow and Integration

Sensor Data Collection: Each sensor (metal detector, fire sensor, fingerprint sensor, GPS) provides data that is collected and processed by the ESP8266 microcontroller. For instance, the metal detector sends a signal when it detects metal, which is then processed by the ESP8266 to trigger an alert.

Data Transmission: Real-time data from the sensors, GPS coordinates, and video feed from the camera are transmitted to the operator's control interface over Wi-Fi. This enables remote monitoring and control of the robot.

Operator Commands: Commands sent by the operator—such as movement, speed adjustments, and sensor status checks—are received by the ESP8266, which then

interprets these commands and executes the appropriate actions (e.g., motor control for navigation).

4.4 Component Integration and Interfacing

Microcontroller and Sensors: The ESP8266 microcontroller interfaces with each sensor to gather data. Libraries specific to each sensor, such as Adafruit_Fingerprint for the fingerprint sensor and TinyGPS++ for GPS data parsing, are used to streamline sensor integration and ensure accurate data collection.

Motor Control via L298N: The motor driver (L298N) is connected to the ESP8266 to control the movement of the robot. The ESP8266 sends PWM signals to the motor driver, allowing control over speed and direction based on the operator's commands.

Camera and Video Streaming: The ESP8266, in conjunction with the camera module, handles video streaming via Wi-Fi. The camera captures live footage and transmits it using protocols like MJPEG, enabling low-latency streaming to the operator's device.

Power Management: The 12V battery provides the primary power source, with a buck converter used to step down the voltage for 5V components. The solar panel supplements the battery, extending operational time. Power management routines in the software monitor battery health and switch to solar power when available.

4.5 Operational Sequence

The system operates in a series of sequential stages to ensure that all functions are performed smoothly and accurately:

Startup and Authentication: Upon powering on, the robot initiates a fingerprint authentication sequence via the R307 fingerprint sensor. The robot remains inactive until an authorized fingerprint is detected. This ensures secure access and prevents unauthorized operation.

Sensor and Component Initialization: After successful authentication, the ESP8266 initializes all sensors and components. It performs checks to verify sensor connectivity and functionality.

Remote Connection Setup: The ESP8266 establishes a Wi-Fi connection and links to the operator's mobile app or web interface, allowing real-time monitoring and control.

Real-Time Operation:

Surveillance: The camera begins streaming live footage, allowing the operator to view the robot's surroundings remotely.

Navigation and Control: The operator sends movement commands, which are translated by the ESP8266 into motor control signals, enabling precise movement across the operational field.

Detection and Alerts: The sensors continuously monitor for hazards. Upon detecting metal or fire, the system immediately alerts the operator through the interface, allowing for informed decision-making.

GPS Tracking: The GPS module sends location data to the operator in real time, providing precise tracking and facilitating navigation through the designated area.

Power Monitoring: Battery levels are checked continuously. If low power is detected, the system switches to solar charging if sunlight is available, ensuring uninterrupted operation.

4.6 Communication and Control Interface

The operator's interface, accessible via a mobile app or web application, displays all relevant data and controls:

Live Video Feed: Shows the camera's live stream, enabling the operator to visually monitor the robot's surroundings.

Sensor Alerts and Status: Displays the status of each sensor, including alerts for detected hazards (e.g., metal or fire).

Navigation Controls: Provides directional buttons or joystick for controlling the robot's movements.

GPS and Battery Information: Shows real-time GPS coordinates and battery level, enabling the operator to manage power and locate the robot easily.

4.7 Error Handling and Safety Protocols

Error Detection: The system is programmed to detect sensor malfunctions or connectivity issues. If a sensor fails to respond or returns an error, the system logs the issue and notifies the operator.

Safety Protocols: The robot includes fail-safes to halt operation in the event of critical errors. Unauthorized access attempts are logged, and the robot can lock itself if tampering is detected, ensuring security in sensitive environments.

This system implementation details how hardware and software elements integrate to create a secure, functional, and efficient surveillance robot, supporting high-risk operational tasks in challenging environments.

4.8 Software Implementation

The software for the spy robot integrates several key functionalities: remote control, sensor data processing, video streaming, and security access. Each feature is implemented to ensure that the robot operates effectively in dynamic environments.

Microcontroller Programming (NodeMCU ESP8266)

The ESP8266 modules are programmed using Arduino IDE or a similar environment. Each module handles different functions, such as motor control, sensor data acquisition, GPS tracking, and communication.

Motor Control: The motor driver (L298N) is controlled through PWM signals from the ESP8266, enabling precise speed and directional control.

GPS Data Handling: The GPS module communicates with the ESP8266, transmitting location coordinates. This data is processed and relayed to the operator interface for real-time position tracking.

Biometric Access Control

Sensor Data Processing and Alerts

Metal and Fire Detection: Data from the metal detector and fire sensor are continuously monitored. When metal is detected or if a fire is sensed, an alert is generated and transmitted to the operator's interface, notifying them of potential hazards.

Real-time alerts are configured to be sent over Wi-Fi, allowing for prompt operator response to critical situations.

Real-Time Video Streaming

The camera module is connected to the ESP8266 and transmits live video feed to a mobile app or web interface via Wi-Fi. This video feed gives the operator a visual of the robot's surroundings, enhancing decision-making capabilities in real-time.

Remote Control Interface

Chapter 5 Result

5.1 Project Design




Fig.5.1.1 Top view

A top-down view of a compact, tracked spy robot designed for covert surveillance and reconnaissance. Its durable chassis, equipped with a tracked system, enables navigation across various terrains, including uneven surfaces and obstacles. The robot's core components include a microcontroller for processing sensor data and controlling actuators, a camera for capturing visual information, and a battery pack for power supply. Additionally, motor drivers and motors ensure the robot's mobility. Potential applications of this spy robot encompass surveillance, search and rescue, security, and exploration.




Fig.No.5.1.2 Isometric View

A 3D rendering of a tracked spy robot designed for reconnaissance and surveillance missions. The robot features a robust, transparent chassis that allows for easy visibility of its internal components. A prominent feature is the 360-degree rotating camera mounted on a swivel base, enabling comprehensive surveillance capabilities. The tracked system provides excellent traction and manoeuvrability across various terrains, including uneven surfaces and obstacles. The robot's power source, likely a battery pack, is visible within the chassis, along with the electronic components responsible for controlling the robot's movement and sensor systems. This versatile spy robot is capable of autonomous operation, making it a valuable tool for a range of applications, such as security, exploration, and search and rescue.

5.2 Project Analysis




Fig.No.5.2.1 Static Displacement

A 3D finite element analysis (FEA) simulation of a tracked spy robot chassis. The simulation likely aims to assess the structural integrity and deformation under various loading conditions. The color contours on the chassis represent the magnitude of displacement, with red indicating higher deformation and blue indicating lower deformation. The presence of green dots suggests the application of external forces or constraints to the model. This analysis can help identify potential weak points in the design and optimize the chassis for improved strength and durability.




Fig.No.5.2.2 Static Strain

A 3D finite element analysis (FEA) simulation of a tracked robot chassis. The simulation likely aims to assess the structural integrity and stress distribution under various loading conditions. The color contours on the chassis represent the magnitude of strain, with red indicating higher strain and blue indicating lower strain. The presence of green dots suggests the application of external forces or constraints to the model. This analysis can help identify potential stress concentration areas and optimize the chassis design for improved strength and durability.




Fig.No.5.2.3 Mesh Quality

A 3D finite element analysis (FEA) mesh of a tracked robot chassis. The mesh consists of numerous elements, which are used to discretize the continuous geometry of the chassis. This mesh is essential for performing numerical simulations to analyze the structural behaviour of the chassis under various loading conditions. The quality of the mesh, in terms of element size and shape, significantly impacts the accuracy of the simulation results.

CONCLUSION

The **Spy Robot Tank with Live Video Streaming, Landmine Detection, and Biometric Authentication** addresses a critical need for safe, secure, and efficient operations in hazardous environments, such as landmine detection zones. By integrating biometric authentication, advanced sensor systems, and real-time video feedback, this project offers a comprehensive solution that enhances both the safety and effectiveness of demining operations.

REFERENCES

- [1] Abdalla, Ghanem Osman Elhaj, and T. Veeramanikandasamy. "Implementation of spy robot for a surveillance system using Internet protocol of Raspberry Pi." 2017 2nd IEEE International Conference on Recent Trends in Electronics, Information & Communication Technology (RTEICT). IEEE, 2017.
- [2] Patel, Dhiraj Singh, et al. "Mobile operated spy robot." International journal of emerging technology and advanced engineering (IJETAEE) (2013).
- [3] Rangapur, Irfan, BK Swathi Prasad, and R. Suresh. "Design and development of spherical spy robot for surveillance operation." Procedia Computer Science 171 (2020): 1212-1220.
- [4] Singh, Akash, Tanisha Gupta, and Manish Korde. "Bluetooth controlled spy robot." 2017 International Conference on Information, Communication, Instrumentation and Control (ICICIC). IEEE, 2017.
- [5] Khaing, Wai Mo Mo, and Kyaw Thiha. "Design and implementation of remote operated spy robot control system." International Journal of Science, Engineering and Technology Research (IJSETR) 3.7 (2014): 1952-1959.
- [6] Balakrishnan, M., et al. "A smart spy robot charged and controlled by wireless systems." 2015 International Conference on Innovations in Information, Embedded and Communication Systems (ICIIECS). IEEE, 2015.
- [7] Patil, Swati, et al. "Military spying robot." AIP Conference Proceedings. Vol. 3209. No. 1. AIP Publishing, 2024.
- [8] Prabhu, L., et al. "Design and fabrication of mobile spy robot." AIP Conference Proceedings. Vol. 2523. No. 1. AIP Publishing, 2023.
- [9] Suhendar, Benny, and Yul Hendra. "Spy robot that is controlled by bluetooth android mobile." 1st International Multidisciplinary Conference on Education, Technology, and Engineering (IMCETE 2019). Atlantis Press, 2020.
- [10] Sathyaprakash, B. P. "Surveillance Spy Robot with Wireless Night Vision Camera and Metal Detection." Turkish Journal of Computer and Mathematics Education (TURCOMAT) 12.12 (2021): 2397-2402.

-
- [11] Kumar, Abhishek. "IoT-Enhanced Spy Robotics Bridging Security Gaps." *Shaping the Future of Automation With Cloud-Enhanced Robotics*. IGI Global, 2024. 343-358.
 - [12] Akthar, Md Shoaib, et al. "Long Range Spy Robot Using Internet of Things."
 - [13] Latha, N., et al. "Spying Robot With Camera Rotation For War Fields." *International Journal For Recent Developments In Science & Technology*, Issn: 2581-4575
 - [14] Pooja Konde, Pooja Konde, et al. "Spying Robot." *4th International Conference on Communication & Information Processing (ICCIP)*. 2022.
 - [15] Chiwande, Sujata S., et al. "War Field Spy Robot with Metal Detection and Live Streaming." *2023 7th International Conference on Intelligent Computing and Control Systems (ICICCS)*. IEEE, 2023.
 - [16] Venu, D. N. "IOT Surveillance Robot Using ESP-32 Wi-Fi CAM & Arduino." *IJFANS International Journal of Food and Nutritional Sciences* 11.5 (2022): 198-205.
 - [17] Rajeshwaran, K., et al. "Sensor Assisted War Field Spying Robot using Internet of Things (IoT)." *2023 4th International Conference on Electronics and Sustainable Communication Systems (ICESC)*. IEEE, 2023.
 - [18] Minu, M. S., et al. "Arduino controlled multipurpose war field spy robot for military surveillance." *International Journal of Advanced Science and Technology* 29.3 (2020): 5485-5494.
 - [19] Akilan, T., et al. "Surveillance robot in hazardous place using IoT technology." *2020 2nd International conference on advances in computing, communication control and networking (ICACCCN)*. IEEE, 2020.
 - [20] Mudda, Mallikarjun, et al. "War Field Spying Robot with Wireless Camera."

