

## DP on trees

We define functions for nodes of trees, which we recursively calculate based on children of a node.

One of the states in the DP is node  $i$ , denoting we are solving for subtree of node  $i$ .


Lets see some examples

Q1 Given a tree,  $N$  nodes  $1-N$ .

Each node has  $C_i$  coins. Choose a set of nodes such that

- 1) No 2 nodes are adjacent
- 2) Sum of coins is **max**

Return this max sum of coins.




If parent is taken  $\Rightarrow$   
cannot take a child

Have we seen something like this before



House Robber

$$dp(i) \Rightarrow \max(dp(i-1), \text{coins}[i] + dp(i-2))$$



$dp[\text{node}][\text{can\_this\_be\_taken}]$

2 scenarios

you take 1

you don't take 1

$\sum dp[child][true]$


$coins[1]$

$+ \sum dp[child][false]$

Generalise

$dp(node, true) \rightarrow$   
 $\begin{cases} coins[i] + \sum dp[child][false] \\ \sum dp[child][true] \end{cases}$

$dp(node, false) \rightarrow \sum dp[child][true]$



```

int maxCoins (vector <int> adj [N], int coins[]) {
    int dp [N][2]
    // i, 0 → false      i, 1 → true
    ans = dfs (1, 1)
    return ans.
}

```

```

int dfs (int node, par, int can_take) {
    if ( dp[node][can_take] in cache )
        return dp[node][can_take]
}

```

ans = 0

```

if ( can_take == 0 ) {
}

```

```

    for ( j = 0; j < adj[i].size; j++ ) {

```

```

        cur-child = adj[i][j]

```

```

        if ( cur-child != par )

```

```

            ans += dfs ( cur-child, 1 )
        }
    }
}

```

```


- else {
    ans1 = coins [node]
    for (j = 0; j < adj [i].size; j++) {
        wr-child = adj [i] [j]
        ans1 += dfs (wr-child, 0)
    }

    ans2 = 0
    for (j = 0; j < adj [i].size; j++) {
        wr-child = adj [i] [j]
        ans2 += dfs (wr-child, 1)
    }

    ans = max (ans1, ans2)
}


dp (node) (can-take) = ans
return ans
}

```




$adj(1)$       2  
 $adj(2)$       1 3  
 $adj(3)$       2

Q2 Given a tree, find the diameter  
 Diameter  $\Rightarrow$  Longest path b/w any 2 nodes.



When standing at node  $i \Rightarrow$



- Longest path starts at  $i$  & goes into subtree  $f(i)$
- Longest path passing through  $i$   
 $g(i)$



$$f(i) = 1 + \max(f(\text{child}))$$

$$g(i) = 1 + \text{sum of 2 biggest in } \{f_1, f_2, f_3, \dots\}$$

$f(i) \Rightarrow$  One arm maximum  
 $g(i) \Rightarrow$  Two arm maximum.



Diameter  $\Rightarrow$  max( all f values  $\cup$  all g values )

node


2 biggest f values.

f-values in a arraylist  
sort this arraylist  
get the last & second last



Q3 Given a tree, find no of diff subtrees


$S(\text{node}) \Rightarrow$  subtree rooted at node  
 $f(\text{node}) \Rightarrow$  no of subtrees of  $S(\text{node})$  which includes node



$$f(\text{node}) = \prod_{\text{child}} (1 + f(\text{child}))$$

$\downarrow$   
mult

$g(\text{node}) =$  no of subtrees not rooted at node



$$g(i) = \sum f(\text{child}) + g(\text{child})$$

$$\text{ans} = f(1) + g(1)$$

Edone y



—

—



—

—

