

```
mysql> create database airline;
```

Query OK, 1 row affected (0.26 sec)

```
mysql> use airline;
```

Database changed

```
mysql> CREATE TABLE customer(id INT);
```

Query OK, 0 rows affected (1.63 sec)

```
mysql> CREATE TABLE airline(id INT,name VARCHAR(255),password INT,address
VARCHAR(255),phone no INT);
```

Query OK, 0 rows affected (0.53 sec)

```
mysql> DESC airline;
```

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(255)	YES		NULL	
password	int	YES		NULL	
address	varchar(255)	YES		NULL	
phone_no	int	YES		NULL	

5 rows in set (0.28 sec)

```
mysql> CREATE TABLE airline_1(id INT,name VARCHAR(255),password INT,address
VARCHAR(255),phone_no INT(10));
```

Query OK, 0 rows affected, 1 warning (0.63 sec)

```
mysql> DESC airline_1;
```

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(255)	YES		NULL	
password	int	YES		NULL	

address	varchar(255)	YES		NULL	
phone_no	int	YES		NULL	

5 rows in set (0.00 sec)

```
mysql> INSERT INTO airline_1
VALUES(1,'MANSI',123,'MUMBAI',989565452),(2,'KIRTI',345,'PUNE',932289771),(3,'SWARA',
678,'NASHIK',546789125),(4,'SHREYA',590,'THANE',56894123);
```

Query OK, 4 rows affected (0.16 sec)

Records: 4 Duplicates: 0 Warnings: 0

```
mysql> Select *From airline_1;
```

id	name	password	address	phone_no
1	MANSI	123	MUMBAI	989565452
2	KIRTI	345	PUNE	932289771
3	SWARA	678	NASHIK	546789125
4	SHREYA	590	THANE	56894123

4 rows in set (0.00 sec)

```
mysql> CREATE TABLE ticket_status_2 (ticket_status VARCHAR(255), ticket_id INT(245));
```

Query OK, 0 rows affected, 1 warning (0.66 sec)

```
mysql> DESC ticket_status_2;
```

Field	Type	Null	Key	Default	Extra
ticket_status	varchar(255)	YES		NULL	
ticket_id	int	YES		NULL	

2 rows in set (0.00 sec)

```
mysql> INSERT INTO ticket_status_2 VALUES('reserved',4235);
```

Query OK, 1 row affected (0.12 sec)

```
mysql> DESC ticket_status_2;
```

Field	Type	Null	Key	Default	Extra
ticket_status	varchar(255)	YES		NULL	
ticket_id	int	YES		NULL	

2 rows in set (0.00 sec)

```
mysql> Select *From ticket_status_2;
```

ticket_status	ticket_id
reserved	4235

1 row in set (0.00 sec)

```
mysql> CREATE TABLE administrator_1(username VARCHAR(255),password INT(255));
```

Query OK, 0 rows affected, 1 warning (0.50 sec)

```
mysql> DESC administrator_1;
```

Field	Type	Null	Key	Default	Extra
username	varchar(255)	YES		NULL	
password	int	YES		NULL	

2 rows in set (0.00 sec)

```
mysql> INSERT INTO administrator_1
VALUES('mansi',123),('kirti',345),('shreya',678),('swara',567),('shruti',345);
```

Query OK, 5 rows affected (0.09 sec)

Records: 5 Duplicates: 0 Warnings: 0

```
mysql> Select *From administrator_1;
```

```
+-----+-----+
| username | password |
+-----+-----+
| mansi    | 123      |
| kirti    | 345      |
| shreya   | 678      |
| swara    | 567      |
| shruti   | 345      |
+-----+-----+
```

5 rows in set (0.00 sec)

```
mysql> CREATE TABLE flight(departure_time INT,flight_number INT,price INT,destination
VARCHAR(255),arrival_time INT);
```

Query OK, 0 rows affected (1.73 sec)

```
mysql> DESC flight;
```

```
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| departure_time | int           | YES  |     | NULL    |       |
| flight_number  | int           | YES  |     | NULL    |       |
| price          | int           | YES  |     | NULL    |       |
| destination    | varchar(255) | YES  |     | NULL    |       |
| arrival_time   | int           | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
```

5 rows in set (0.28 sec)

```
mysql> INSERT INTO flight
VALUES(9.00,5656,5000,'DELHI',11.00),(10.00,78844,10000,'KASHMIR',12),(1.00,8569,8900,'
ENGLAND',5),(8.00,8554,45000,'AMERICA',11.00);
```

Query OK, 4 rows affected (0.28 sec)

Records: 4 Duplicates: 0 Warnings: 0

```
mysql> Select *From flight;
```

departure_time	flight_number	price	destination	arrival_time
9	5656	5000	DELHI	11
10	78844	10000	KASHMIR	12
1	8569	8900	ENGLAND	5
8	8554	45000	AMERICA	11

4 rows in set (0.06 sec)

```
mysql> CREATE TABLE customer_1(id INT,name VARCHAR(255),password INT,address
VARCHAR(255),phone_no INT);
```

Query OK, 0 rows affected (2.39 sec)

```
mysql> DESC customer_1;
```

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(255)	YES		NULL	
password	int	YES		NULL	
address	varchar(255)	YES		NULL	
phone_no	int	YES		NULL	

5 rows in set (7.09 sec)

```
mysql> INSERT INTO customer_1
VALUES(1,'MANSI',123,'MUMBAI',45678912),(2,'SAKSHI',589,'DELHI',45645455),(3,'KIRTI',78
9,'PUNE',56546552),(4,'SEJAL',546,'VAI',78945612),(5,'RUTUJA',485,'SATARA',45671454);
```

Query OK, 5 rows affected (0.23 sec)

Records: 5 Duplicates: 0 Warnings: 0

```
mysql> Select *From customer_1;
```

```
+-----+-----+-----+-----+-----+
| id    | name   | password | address | phone_no |
+-----+-----+-----+-----+-----+
| 1     | MANSI  | 123      | MUMBAI  | 45678912 |
| 2     | SAKSHI | 589      | DELHI   | 45645455 |
| 3     | KIRTI  | 789      | PUNE    | 56546552 |
| 4     | SEJAL  | 546      | VAI     | 78945612 |
| 5     | RUTUJA | 485      | SATARA  | 45671454 |
+-----+-----+-----+-----+-----+
```

5 rows in set (0.03 sec)

```
mysql> CREATE TABLE airline_3(air_logo_path VARCHAR(255),airline_staff_name
VARCHAR(25),airline_name VARCHAR(45));
```

Query OK, 0 rows affected (0.98 sec)

```
mysql> DESC airline_3;
```

```
+-----+-----+-----+-----+-----+
| Field                | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| air_logo_path        | varchar(255) | YES  |     | NULL    |       |
| airline_staff_name   | varchar(25)  | YES  |     | NULL    |       |
| airline_name         | varchar(45)  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```

3 rows in set (0.00 sec)

```
mysql> INSERT INTO airline_3 VALUES('XYZ','SAMU','INDIGO'),('ABC','SIDDHU','AIR
INDIA'),('PQR','SAKU','SPICEJET'),('SRE','ASHU','AIRASIA'),('AQW','KIRU','DELTA'),('ASD','MAN
U','HONGKONG_AIRLINE'),('RTY','SEJU','SPIRIT AIRLINE');
```

Query OK, 7 rows affected (0.06 sec)

Records: 7 Duplicates: 0 Warnings: 0

```
mysql> Select *From airline_3;
```

```
+-----+-----+-----+
| air_logo_path | airline_staff_name | airline_name |
+-----+-----+-----+
```

XYZ	SAMU	INDIGO
ABC	SIDDHU	AIR INDIA
PQR	SAKU	SPICEJET
SRE	ASHU	AIRASIA
AQW	KIRU	DELTA
ASD	MANU	HONGKONG_AIRLINE
RTY	SEJU	SPIRIT AIRLINE

7 rows in set (0.00 sec)

mysql> truncate table customer_1;

Query OK, 0 rows affected (1.43 sec)

mysql> Select *From customer_1;

Empty set (0.00 sec)

mysql> DESC customer_1;

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(255)	YES		NULL	
password	int	YES		NULL	
address	varchar(255)	YES		NULL	
phone_no	int	YES		NULL	

5 rows in set (0.00 sec)

mysql> DROP TABLE airline_3;

Query OK, 0 rows affected (0.62 sec)

mysql> DESC airline_3;

ERROR 1146 (42S02): Table 'airline.airline_3' doesn't exist